



A D T

RF EXPOSURE REPORT

REPORT NO.: SA110802C08A

MODEL NO.: TEW-713BR

FCC ID: XU8TEW713BR

RECEIVED: Aug. 2, 2011

TESTED: Aug. 5 ~ 16, 2011

ISSUED: Oct. 4, 2011

APPLICANT: TRENDNET, Inc.

ADDRESS: 20675 Manhattan Place, Torrance, CA 90501,
USA

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan (R.O.C)

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

| | |
|---|---|
| RELEASE CONTROL RECORD | 3 |
| 1. CERTIFICATION..... | 4 |
| 2. RF EXPOSURE LIMIT | 5 |
| 3. MPE CALCULATION FORMULA | 5 |
| 4. CLASSIFICATION | 5 |
| 5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER..... | 6 |



A D T

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|--------------|-------------------|--------------|
| SA110802C08A | Original release | Oct. 4, 2011 |



A D T

1. CERTIFICATION

PRODUCT: 150Mbps Compact Single Port Wireless N Router
BRAND NAME: TRNEDnet
MODEL NO.: TEW-713BR
APPLICANT: TRENDNET, Inc.
TEST ITEM: ENGINEERING SAMPLE
TESTED: Aug. 5 ~ 16, 2011
STANDARDS: FCC Part 2 (Section 2.1091)
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Annie Chang , DATE: Oct. 4, 2011
(Annie Chang / Senior Specialist)

APPROVED BY : Ken Liu , DATE: Oct. 4, 2011
(Ken Liu / Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| FREQUENCY RANGE (MHz) | ELECTRIC FIELD STRENGTH (V/m) | MAGNETIC FIELD STRENGTH (A/m) | POWER DENSITY (mW/cm ²) | AVERAGE TIME (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE | | | | |
| 300-1500 | ... | ... | F/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

| FREQUENCY BAND (MHz) | MAX POWER (dBm) | ANTENNA GAIN (dBi) | DISTANCE (cm) | POWER DENSITY (mW/cm ²) | LIMIT (mW/cm ²) |
|----------------------|-----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 2412-2462 | 26.2 | 2 | 20 | 0.1314 | 1.00 |

--- END ---