

## 15. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 15.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

\* = Plane-wave equipment power density

### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

*\*Please be noted that 2.4G antenna will not transmit together with 5G antenna.*

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

**802.11a Main**

CH	Frequency (MHz)	TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
36	5180	16.75	47.315	23.98	PASS
44	5220	17.76	59.704	23.98	PASS
48	5240	<b>21.54</b>	<b>142.561</b>	23.98	PASS
149	5745	16.52	44.875	30	PASS
157	5785	<b>19.75</b>	<b>94.406</b>	30	PASS
165	5825	18.95	78.524	30	PASS

**MPE Prediction (802.11a 5150~5250)**

Max. output power including tune-up tolerancel:	<b>21.54</b>	(dBm)
Max. output power including tune-up tolerancel:	142.56076	(mW)
Duty cycle:	<b>86.37</b>	(%)
Maximum Pav :	123.12973	(mW)
Peak Antenna gain (Maximum):	<b>9.78</b>	(dBi)
Peak Antenna gain (linear):	9.5060479	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	<b>5240</b>	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.233	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.233 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5240MHz.		

**MPE Prediction (802.11a 5725~5850)**

Max. output power including tune-up tolerancel:	<b>19.75</b>	(dBm)
Max. output power including tune-up tolerancel:	94.406088	(mW)
Duty cycle:	<b>96.37</b>	(%)
Maximum Pav :	90.979147	(mW)
Peak Antenna gain (Maximum):	<b>9.84</b>	(dBi)
Peak Antenna gain (linear):	9.6382902	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	<b>5785</b>	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.175	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.175 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5785MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 802.11ac\_VHT20\_MIMO

CH	Frequency (MHz)	AVERAGE POWER (dBm)			TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
		CHAIN 0	CHAIN 1	CHAIN 2				
36	5180	12.97	9.4	12.18	16.54	45.045	20.2	PASS
44	5220	12.98	9.2	11.75	16.35	43.141	20.2	PASS
48	5240	14.01	9.92	12.24	<b>17.14</b>	51.744	20.2	PASS
149	5745	18.15	17.82	14.72	<b>21.92</b>	155.495	26.16	PASS
157	5785	17.43	17.29	14.45	21.36	136.776	26.16	PASS
165	5825	17.01	16.89	13.38	20.82	120.877	26.16	PASS

**MPE Prediction (802.11ac\_VHT20 5150~5250)**
**MIMO gain=  $G+(10 \log N)= 5.01+4.77= 9.78\text{dBm}$** 

Average output power at antenna input terminal:	<b>17.14</b>	(dBm)
Average output power at antenna input terminal:	51.760683	(mW)
Duty cycle:	<b>59.51</b>	(%)
Maximum Pav :	30.802783	(mW)
Peak Antenna gain (Maximum):	<b>9.78</b>	(dBi)
Peak Antenna gain (linear):	9.5060479	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	<b>5240</b>	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.058	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.058 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5240MHz.		

**MPE Prediction (802.11ac\_VHT20 5725~5850)**
**MIMO gain=  $G+(10 \log N)= 5.07+4.77= 9.84\text{dBm}$** 

Max. output power including tune-up tolerancel:	<b>21.92</b>	(dBm)
Max. output power including tune-up tolerancel:	155.59656	(mW)
Duty cycle:	<b>89.51</b>	(%)
Maximum Pav :	139.27448	(mW)
Peak Antenna gain (Maximum):	<b>9.84</b>	(dBi)
Peak Antenna gain (linear):	9.6382902	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	<b>5745</b>	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.267	(mW/cm <sup>2</sup> )

**Measurement Result**

 The predicted power density level at 20 cm is 0.267 mW/cm<sup>2</sup>.

 This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 5745MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 802.11ac\_VHT40\_MIMO

CH	Frequency (MHz)	AVERAGE POWER (dBm)			TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
		CHAIN 0	CHAIN 1	CHAIN 2				
38	5190	12.65	8.96	11.68	16.13	41.001	20.2	PASS
46	5230	16.62	12.01	15.26	19.79	95.379	20.2	PASS
151	5755	14.21	14.09	10.79	18.06	64.003	26.16	PASS
159	5795	16.62	16.54	13.64	20.57	114.122	26.16	PASS

**MPE Prediction (802.11ac\_VHT40 5150~5250)**
**MIMO gain=  $G+(10 \log N)= 5.01+4.77= 9.78\text{dBm}$** 

Average output power at antenna input terminal:	19.79	(dBm)
Average output power at antenna input terminal:	95.279616	(mW)
Duty cycle:	82.32	(%)
Maximum Pav :	78.43418	(mW)
Peak Antenna gain (Maximum):	9.78	(dBi)
Peak Antenna gain (linear):	9.5060479	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5230	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.148	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.148 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5230MHz.		

**MPE Prediction (802.11ac\_VHT40 5725~5850)**
**MIMO gain=  $G+(10 \log N)= 5.07+4.77= 9.84\text{dBm}$** 

Average output power at antenna input terminal:	20.57	(dBm)
Average output power at antenna input terminal:	114.02498	(mW)
Duty cycle:	82.32	(%)
Maximum Pav :	93.865363	(mW)
Peak Antenna gain (Maximum):	9.84	(dBi)
Peak Antenna gain (linear):	9.6382902	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5795	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.180	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.18 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5795MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## 802.11ac\_VHT80\_MIMO

CH	Frequency (MHz)	AVERAGE POWER (dBm)			TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
		CHAIN 0	CHAIN 1	CHAIN 2				
42	5210	14.3	10.57	13.21	17.73	59.259	20.2	PASS
155	5775	13.48	13.37	10.29	17.38	54.702	26.16	PASS

**MPE Prediction (802.11ac\_VHT80 5150~5250)**
**MIMO gain=  $G+(10 \log N)= 5.01+4.77= 9.78\text{dBm}$** 

Average output power at antenna input terminal:	17.73	(dBm)
Average output power at antenna input terminal:	59.292532	(mW)
Duty cycle:	72.73	(%)
Maximum Pav :	43.123459	(mW)
Peak Antenna gain (Maximum):	9.78	(dBi)
Peak Antenna gain (linear):	9.5060479	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5210	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.082	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.082 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5210MHz.		

**MPE Prediction (802.11ac\_VHT80 5725~5850)**
**MIMO gain=  $G+(10 \log N)= 5.07+4.77= 9.84\text{dBm}$** 

Average output power at antenna input terminal:	17.38	(dBm)
Average output power at antenna input terminal:	54.701596	(mW)
Duty cycle:	72.73	(%)
Maximum Pav :	39.784471	(mW)
Peak Antenna gain (Maximum):	9.84	(dBi)
Peak Antenna gain (linear):	9.6382902	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5775	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.076	(mW/cm <sup>2</sup> )
<b>Measurement Result</b>		
The predicted power density level at 20 cm is 0.076 mW/cm <sup>2</sup> .		
This is below the uncontrolled exposure limit of 1 mW/cm <sup>2</sup> at 5775MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.