

# **FCC Test Report**

FCC ID : XU8TEW814DAP

Equipment : AC1200 Dual Band Wireless Access Point

Model No. : TEW-814DAP

Brand Name : TRENDnet

Applicant : TRENDnet, Inc.

Address : 20675 Manhattan Place, Torrance, CA 90501,

**USA** 

Standard : 47 CFR FCC Part 15.247

Received Date : Jan. 16, 2014

Tested Date : Jan. 22 ~ May 19, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Iac-MRA



Report No.: FR411604AC Report Version: Rev. 01 Page: 1 of 63



## **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	The Equipment List	9
1.5	Test Standards	10
1.6	Measurement Uncertainty	10
2	TEST CONFIGURATION	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	Conducted Emissions	12
3.2	6dB and Occupied Bandwidth	15
3.3	RF Output Power	
3.4	Power Spectral Density	20
3.5	Unwanted Emissions into Restricted Frequency Bands	22
3.6	Emissions in Non-Restricted Frequency Bands	50
4	TEST LABORATORY INFORMATION	63



## **Release Record**

Report No.	Version	Description	Issued Date
FR411604AC	Rev. 01	Initial issue	Aug. 13, 2014

Report No.: FR411604AC Page: 3 of 63



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.154MHz 50.41 (Margin -5.37dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz 53.00 (Margin -1.00dB) - AV	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 11b: 27.39 11g: 25.03 HT20: 25.01 HT40: 20.92	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR411604AC Page: 4 of 63



## 1 General Description

### 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS		
2400-2483.5	b	2412-2462	1-11 [11]	2	1-11 Mbps		
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps		
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15		
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15		

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.

Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

#### 1.1.2 Antenna Details

Ant. No.	Туре	Gain (dBi)	Connector	Remark
1	PCB	2	UFL	

### 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from AC adapter
-------------------	-----------------------

#### 1.1.4 Accessories

	Accessories					
No.	Equipment	Description				
		Brand Name: AMIGO				
		Model Name: AMS9-1201000FU2				
1	AC Adapter	Power Rating: I/P: 100-240Vac, 50-60Hz, 0.5A O/P: 12Vdc, 1.0A				
		Power Line: 1.2m non-shielded cable w/o core				
		Brand Name: FRECOM				
		Model Name: F12W-120100SPAU				
2	AC Adapter	Power Rating: I/P: 100-240Vac, 50-60Hz, 0.3A O/P: 12Vdc, 1.0A				
		Power Line: 1.2m non-shielded cable w/o core				

Report No.: FR411604AC Page: 5 of 63



### 1.1.5 Channel List

Frequency	band (MHz)	2400~	2483.5	
802.11 b /	g / n HT20	802.11n HT40		
Channel	Frequency(MHz)	Channel	Frequency(MHz)	
1	2412	3	2422	
2	2417	4	2427	
3	2422	5	2432	
4	2427	6	2437	
5	2432	7	2442	
6	2437	8	2447	
7	2442	9	2452	
8	2447			
9	2452			
10	2457			
11	2462			

### 1.1.6 Test Tool and Duty Cycle

Test Tool	RTL819x2.3, V. 2013/2/21				
	Mode	Duty cycle (%)	Duty factor (dB)		
	11b	98.84%	0.05		
Duty Cycle and Duty Factor	11g	98.95%	0.05		
	HT20	98.88%	0.05		
	HT40	98.01%	0.09		

Report No.: FR411604AC Page: 6 of 63



## 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	42/44
11b	2437	46/48
11b	2462	41/44
11g	2412	50/52
11g	2437	61/63
11g	2462	53/57
HT20	2412	49/51
HT20	2437	61/63
HT20	2462	51/55
HT40	2422	44/46
HT40	2437	53/55
HT40	2452	48/53

Report No.: FR411604AC Page: 7 of 63




## 1.2 Local Support Equipment List

	Support Equipment List							
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)		
1	Notebook	lenovo	ThinkPad		DoC	RJ45, 10m non-shielded w/o core.		

Note: Support unit was supplied by applicant.

## 1.3 Test Setup Chart



Report No.: FR411604AC Page: 8 of 63



## 1.4 The Equipment List

Test Item	Conducted Emission		Test Site	Conduction room 1 / (CO01-WS)				
Test date	May 16, 2014							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014			
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014			
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015			
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015			

Test Item	Radiated Emission		Test Site	966 chamber 2 / (03CH02-WS)				
Test date	Jan. 22 ~ May 19, 2014							
Instrument	Manufacturer Model No.		Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	Agilent	N9010A	MY52221474	Sep. 26, 2013	Sep. 25, 2014			
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014			
Preamplifier	Burgeon	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014			
Preamplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014			
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014			
Note: Calibration Interval of instruments listed above is one year.								

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014		
Note: Calibration Interval of instruments listed above is two year.							

Test Item	RF Conducted		Test Site	(TH01-WS)				
Test date	May 16, 2014	- Мау 16, 2014						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101486	Nov. 13, 2013	Nov. 12, 2014			
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014			
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014			
Note: Calibration Interval of instruments listed above is one year.								

Report No.: FR411604AC Page: 9 of 63



#### 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r01

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Bandwidth	±34.134 Hz				
Conducted power	±0.808 dB				
Frequency error	±34.134 Hz				
Temperature	±0.6 °C				
Conducted emission	±2.670 dB				
AC conducted emission	±2.92 dB				
Radiated emission ≤ 1GHz	±3.26 dB				
Radiated emission > 1GHz	±4.94 dB				

Report No.: FR411604AC Page: 10 of 63



## 2 Test Configuration

## 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	25°C / 66%	Skys Huang
Radiated Emissions	03CH02-WS	20-23°C / 64-68%	Haru Yang Anderson Hung
RF Conducted	TH01-WS	21°C / 65%	Mark Liao

FCC site registration No.: 657002IC site registration No.: 10807A-2

#### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	11b	2437	1 Mbps	
Radiated Emissions ≤1GHz	11b	2437	1 Mbps	
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	
Fundamental Emission Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	

#### NOTE:

Report No.: FR411604AC Page: 11 of 63

AMIGO Adapter and FRECOM Adapter had been pretested and found that AMIGO Adapter was the worst case and was selected for final testing. (AMIGO Adapter: AMS9-1201000FU2; FRECOM Adapter: F12W-120100SPAU).



### 3 Transmitter Test Results

#### 3.1 Conducted Emissions


#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit						
Frequency Emission (MHz) Quasi-Peak Average						
0.15-0.5	66 - 56 *	56 - 46 *				
0.5-5	56	46				
5-30 60 50						
Note 1: * Decreases with the logarithm of the frequency.						

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR411604AC Page: 12 of 63




#### 3.1.4 Test Result of Conducted Emissions



Report No.: FR411604AC Page: 13 of 63





Report No.: FR411604AC Page: 14 of 63



### 3.2 6dB and Occupied Bandwidth


#### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

#### 3.2.2 Test Procedures

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### 3.2.3 Test Setup



Report No.: FR411604AC Page: 15 of 63



### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation	N	Erog (MUz)			Limit (IrU=)		
Mode	N <sub>TX</sub>	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Limit (kHz)
11b	2	2412	10.07	10.07			500
11b	2	2437	10.07	10.07			500
11b	2	2462	10.07	9.60			500
11g	2	2412	16.33	16.33			500
11g	2	2437	16.07	16.33			500
11g	2	2462	16.33	16.33			500
HT20	2	2412	17.07	17.27			500
HT20	2	2437	16.67	17.13			500
HT20	2	2462	16.93	17.27			500
HT40	2	2422	35.60	35.20			500
HT40	2	2437	35.20	35.33			500
HT40	2	2452	35.33	35.33			500



Report No.: FR411604AC Page: 16 of 63



Modulation	N	Freq.	99% Occupied Bandwidth (MHz)			
Mode	N <sub>TX</sub>	(MHz)	Chain 0	Chain 1	Chain 2	Chain 3
11b	2	2412	15.30	14.87		
11b	2	2437	15.52	14.83		
11b	2	2462	15.16	14.94		
11g	2	2412	16.75	16.75		
11g	2	2437	17.15	16.86		
11g	2	2462	16.79	16.71		
HT20	2	2412	17.95	17.80		
HT20	2	2437	18.16	17.87		
HT20	2	2462	17.95	17.84		
HT40	2	2422	36.01	36.01		
HT40	2	2437	36.34	36.01		
HT40	2	2452	36.08	36.40		



Report No.: FR411604AC Page: 17 of 63



## 3.3 RF Output Power

## 3.3.1 Limit of RF Output Power

Con	duct	ed po	ower shall not exceed 1Watt.							
$\boxtimes$	Ant	enna	gain <= 6dBi, no any corresponding reduction is in output power limit.							
	Ant	tenna gain > 6dBi								
		The	Fixed, point to point operations. conducted output power from the intentional radiator shall be reduced by the amount in dB the directional gain of the antenna exceeds 6 dB							
		Sys Ope	ed, point to point operations tems operations in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-pointerations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 that the directional gain of the antenna exceeds 6 dBi.							
			tems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point rations ,no any corresponding reduction is in transmitter peak output power							
3.3.	2	Test	Procedures							
	Max	ximur	n Peak Conducted Output Power							
		Spe	ectrum analyzer							
		1.	Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.							
		2.	Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.							
		3.	Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.							
		Pov	ver meter							
		1.	A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.							
$\boxtimes$	Max	ximur	n Conducted Output Power							
	$\boxtimes$	Pov	ver meter							
		1.	A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.							
3.3.	3	Test	: Setup							

Report No.: FR411604AC Page: 18 of 63

Power Sensor

Power Meter

Report Version: Rev. 01

EUT



## 3.3.4 Test Result of Maximum Output Power

Modulation Mode	N <sub>TX</sub>	Freq.	Conduc		age) outpu Bm)	t power	Total Power		
Wode		(MHz)	Chain 0	Chain 1	Chain 2	Chain 3	(mW)	(dBm)	(dBm)
11b	2	2412	23.43	23.19			428.742	26.32	30.00
11b	2	2437	24.44	24.32			548.367	27.39	30.00
11b	2	2462	22.55	21.96			336.923	25.28	30.00
11g	2	2412	17.63	17.89			119.461	20.77	30.00
11g	2	2437	21.93	22.11			318.510	25.03	30.00
11g	2	2462	18.11	18.39			133.738	21.26	30.00
HT20	2	2412	16.43	17.18			96.194	19.83	30.00
HT20	2	2437	21.98	22.02			316.982	25.01	30.00
HT20	2	2462	16.83	17.39			103.022	20.13	30.00
HT40	2	2422	13.63	14.18			49.249	16.92	30.00
HT40	2	2437	18.21	17.59			123.633	20.92	30.00
HT40	2	2452	15.83	15.72			75.607	18.79	30.00

Report No.: FR411604AC Page: 19 of 63



### 3.4 Power Spectral Density


#### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

#### 3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - Set the RBW = 30kHz, VBW = 100kHz.
  - Detector = Peak, Sweep time = auto couple.
  - 3. Trace mode = max hold, allow trace to fully stabilize.
  - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - Set the RBW = 30kHz, VBW = 100 kHz.
  - 2. Detector = RMS, Sweep time = auto couple.
  - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
  - 4. Perform the measurement over a single sweep.
  - 5. Use the peak marker function to determine the maximum amplitude level.

#### 3.4.3 Test Setup




Report No.: FR411604AC Page: 20 of 63



### 3.4.4 Test Result of Power Spectral Density

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Total Power Spectral Density (dBm/30kHz)	Limit (dBm/3kHz)
11b	2	2412	3.26	8.00
11b	2	2437	5.13	8.00
11b	2	2462	2.73	8.00
11g	2	2412	-3.82	8.00
11g	2	2437	0.40	8.00
11g	2	2462	-3.50	8.00
HT20	2	2412	-4.67	8.00
HT20	2	2437	0.20	8.00
HT20	2	2462	-4.67	8.00
HT40	2	2422	-10.16	8.00
HT40	2	2437	-5.88	8.00
HT40	2	2452	-8.50	8.00

Note: Test result for HT20 / HT40 is bin-by-bin summing measured value of each TX port.



Report No.: FR411604AC Page: 21 of 63



### 3.5 Unwanted Emissions into Restricted Frequency Bands

#### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit											
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)								
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300								
0.490~1.705	24000/F(kHz)	33.8 - 23	30								
1.705~30.0	30	29	30								
30~88	100	40	3								
88~216	150	43.5	3								
216~960	200	46	3								
Above 960	500	54	3								

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.5.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR411604AC Page: 22 of 63




### 3.5.3 Test Setup



Report No.: FR411604AC Page: 23 of 63



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR411604AC Page: 24 of 63





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR411604AC Page: 25 of 63



### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR411604AC Page: 26 of 63





54.00 -7.77

41.14

46.96

Average

Peak

5.09

5.09

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

4824.00 46.23

4824.00 52.05 74.00 -21.95


Report No.: FR411604AC Page: 27 of 63

Report Version: Rev. 01

5

6





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 28 of 63



Modulation	11b	11b				Test Freq. (MHz)					2437			
Polarization		Vertica	I											
447	Level (d	BuV/m)												
110														



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ü	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2358.00	48.74	54.00	-5.26	51.68	-2.94	Average		
2	2358.00	59.60	74.00	-14.40	62.54	-2.94	Peak		
3	2496.00	49.19	54.00	-4.81	51.52	-2.33	Average		
4	2496.00	61.44	74.00	-12.56	63.77	-2.33	Peak		
5	4874.00	46.41	54.00	-7.59	41.23	5.18	Average		
6	4874.00	51.56	74.00	-22.44	46.38	5.18	Peak		
7	7311.00	40.45	54.00	-13.55	29.71	10.74	Average		
8	7311.00	50.63	74.00	-23.37	39.89	10.74	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 29 of 63



Modulation				11b					Т	Test Freq. (MHz)				2462	2462		
Polarization				Horizontal													
	117	Level	(dBuV	//m)													
	110					_											
	90					$\top$											
														FCC	CLAS	S-B	
	70	2	4														
			Ī	6									500		C D (A		
	50	1	В	- 5		8							FCC	CLAS	2-B (A	VG)	
	30					7											
						11											
	30					+											
	10																
	ام																
	0,	1000	40	00.	6000.	800	0. 1000				00. 180	00. 2	0000. 220	00. 24	000.	26500	
										ncy (MHz)							
			Fr	eq.			Limi	t Ma	rgin	SA		or	Remark		NT	Turn	
					lev		ID 1/	, ,		reading					igh	Table	
			М	Hz	aBuv	/m	dBuV,	/m a	В	dBuV	dB			C	m	deg	
1	ı		238	1.00	52	67	54.00	- <del>- 1</del>	. 33	55.52	-2.	85	Averag				
2					62.		74.00			65.55			Peak	_			
3					52.		54.00			55.15			Averag	e			
4	1				63.		74.00			65.83	-2.		Peak				
9	5		492	4.00	51.	30	54.00	3 -2	.70	46.02	5.	28	Averag	e			
	-		400	1 00		72	74 00	10	27	EQ 4E		20	Doole				

50.45

29.05

5.28

10.84

10.84

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor , cable loss and amplifier gain

4924.00 55.73 74.00 -18.27

7386.00 39.89 54.00 -14.11

7386.00 50.40 74.00 -23.60 39.56


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 30 of 63

Report Version: Rev. 01

7





54.00 -13.12

30.04

40.26

10.84

10.84

Average

Peak

---

---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

7386.00 40.88

7386.00 51.10 74.00 -22.90

Report No.: FR411604AC Page: 31 of 63


Report Version: Rev. 01

7

8



### 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR411604AC Page: 32 of 63






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 33 of 63






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 34 of 63



Modulation	11g	11g				Test Freq. (MHz)					2437			
Polarization		Vertical	Vertical											
117	Level (dB	uV/m)										_		
110														




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV		Remark	ANT High cm	Turn Table deg
1	2377.00	48.14	54.00	-5.86	51.00	-2.86	Average		
2	2377.00	61.95	74.00	-12.05	64.81	-2.86	Peak		
3	2497.00	46.19	54.00	-7.81	48.52	-2.33	Average		
4	2497.00	60.95	74.00	-13.05	63.28	-2.33	Peak		
5	4874.00	36.05	54.00	-17.95	30.87	5.18	Average		
6	4874.00	47.19	74.00	-26.81	42.01	5.18	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 35 of 63





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 36 of 63



1 2

3

4

5

6

Modulation		110	9				Т	est Fr	eq. (M	Hz)		2462	<u> </u>	
Polarization		Ve	rtical											
117	Level (dE	3uV/m)								1		1		$\overline{}$
110				_										+
90														$\perp$
70	4											FCC	CLASS	S-B
70	2													
	<u></u> js										FC	C CLAS	\$-B (A\	/G)
50		6		$\neg$										$\top$
		5												
30				+										+
10				_										$\perp$
0														
·	1000	4000.	6000.	800	0. 100					000. 20	0000. 220	000. 24	000. 2	6500
								cy (MHz)	,					
		Freq.	Emiss		Limi	t Ma	argin		Fact	tor	Remark		NT	Turn
			lev				ı.D	readin					_	Tabl
		MHz	dBu\	//m	dBu√	//m c	1R	dBuV	dl	3		C	m	deg

50.85

63.41

55.14

73.37

28.83

39.95

-3.01

-3.01

-2.39

-2.39

5.28

5.28

Average

Peak Average

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

2342.00 47.84 54.00 -6.16

2342.00 60.40 74.00 -13.60

4924.00 34.11 54.00 -19.89 4924.00 45.23 74.00 -28.77

54.00 -1.25

70.98 74.00 -3.02

2483.50 52.75


2483.50

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 37 of 63



# 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).


Report No.: FR411604AC Page: 38 of 63



30

10

1000




	Freq.	Emission	Limit	Margin	SA	Factor	Kemark	ANI	lurn
		level			reading			High	Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	49.72	54.00	-4.28	52.54	-2.82	Average		
2	2390.00	66.58	74.00	-7.42	69.40	-2.82	Peak		
3	2491.00	46.84	54.00	-7.16	49.19	-2.35	Average		
4	2491.00	59.29	74.00	-14.71	61.64	-2.35	Peak		
5	4824.00	34.02	54.00	-19.98	28.93	5.09	Average		
6	4824.00	45.15	74.00	-28.85	40.06	5.09	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 39 of 63





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 40 of 63

Report Version: Rev. 01

4

5

6

2497.00

4874.00

67.01

39.87

4874.00 52.98 74.00 -21.02

74.00 -6.99

54.00 -14.13

69.34

34.69

47.80

-2.33

5.18


5.18

Peak Average

Peak



Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2377.00	48.58	54.00	-5.42	51.44	-2.86	Average		
2	2377.00	62.32	74.00	-11.68	65.18	-2.86	Peak		
3	2497.00	46.57	54.00	-7.43	48.90	-2.33	Average		
4	2497.00	61.41	74.00	-12.59	63.74	-2.33	Peak		
5	4874.00	35.76	54.00	-18.24	30.58	5.18	Average		
6	4874.00	46.85	74.00	-27.15	41.67	5.18	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 41 of 63






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 42 of 63



Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		
l evel (dBu\	lim).		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		CM	deg
1	2342.00	48.23	54.00	-5.77	51.24	-3.01	Average		
2	2342.00	60.88	74.00	-13.12	63.89	-3.01	Peak		
3	2483.50	52.36	54.00	-1.64	54.75	-2.39	Average		
4	2483.50	72.41	74.00	-1.59	74.80	-2.39	Peak		
5	4924.00	34.27	54.00	-19.73	28.99	5.28	Average		
6	4924.00	45.68	74.00	-28.32	40.40	5.28	Peak		


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 43 of 63



# 3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 44 of 63



Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading		Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2359.00	42.37	54.00	-11.63	45.31	-2.94	Average		
2	2359.00	54.55	74.00	-19.45	57.49	-2.94	Peak		
3	2390.00	48.58	54.00	-5.42	51.40	-2.82	Average		
4	2390.00	68.19	74.00	-5.81	71.01	-2.82	Peak		
5	4804.00	34.23	54.00	-19.77	29.18	5.05	Average		
6	4804.00	45.02	74.00	-28.98	39.97	5.05	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 45 of 63






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB) \*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 46 of 63



Modulation	HT40	Tes	st Freq. (M	Hz)	2437	7		
Polarization	Vertical							
117 Level (dBu	V/m)						7	




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	50.01	54.00	-3.99	52.83	-2.82	Average		
2	2390.00	67.30	74.00	-6.70	70.12	-2.82	Peak		
3	2497.00	50.36	54.00	-3.64	52.69	-2.33	Average		
4	2497.00	67.14	74.00	-6.86	69.47	-2.33	Peak		
5	4874.00	34.98	54.00	-19.02	29.80	5.18	Average		
6	4874.00	45.95	74.00	-28.05	40.77	5.18	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 47 of 63





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR411604AC Page: 48 of 63



30

10

Modulation		HT40		Test Fr	eq. (MHz)		2452	
Polarization		Vertical		•				
117 Le	vel (dBu	V/m)						
110								
90—								
70	4						FCC	CLASS-B
-	2					FC	C CLAS	S-B (AVG)
50		1						

6000.	8000.	10000.	12000.	14000.	16000.	18000.	20000.	22000.	24000.	26500
Frequency (MHz)										

	Freq. 8	mission level	Limit Margin		SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2332.00	44.65	54.00	-9.35	47.69	-3.04	Average		
2	2332.00	55.40	74.00	-18.60	58.44	-3.04	Peak		
3	2483.50	50.02	54.00	-3.98	52.41	-2.39	Average		
4	2483.50	69.05	74.00	-4.95	71.44	-2.39	Peak		
5	4904.00	34.11	54.00	-19.89	28.87	5.24	Average		
6	4904.00	45.27	74.00	-28.73	40.03	5.24	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Page: 49 of 63 Report No.: FR411604AC



# 3.6 Emissions in Non-Restricted Frequency Bands

### 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz

#### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.6.3 Test Procedures


#### Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

#### **Emission level measurement**

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level

#### 3.6.4 Test Setup



# 3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding 10  $log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

Report No.: FR411604AC Page: 50 of 63




# 3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands

#### 802.11b




Report No.: FR411604AC Report Version: Rev. 01






Report No.: FR411604AC Page: 52 of 63






Report No.: FR411604AC Page: 53 of 63






Report No.: FR411604AC Page: 54 of 63





Report No.: FR411604AC Page: 55 of 63






Report No.: FR411604AC Page: 56 of 63




#### 802.11n HT20




Report No.: FR411604AC Page: 57 of 63





Report No.: FR411604AC Page: 58 of 63






Report No.: FR411604AC Page: 59 of 63




#### 802.11n HT40




Report No.: FR411604AC Page: 60 of 63





Report No.: FR411604AC Page: 61 of 63





Report No.: FR411604AC Page: 62 of 63



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR411604AC Page: 63 of 63