



FCC TEST REPORT

(15.407)

REPORT NO.: RF140521C07-1
MODEL NO.: TEW-824DRU (Refer to item 3.1 for more detail)
FCC ID: XU8TEW823824
RECEIVED: May 21, 2014
TESTED: Apr. 15 ~ Jun. 06, 2014
ISSUED: Jun. 13, 2014

APPLICANT: TRENDnet, Inc.

ADDRESS: 20675 Manhattan Place, Torrance, CA 90501

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
3.3 DUTY CYCLE OF TEST SIGNAL	12
3.4 DESCRIPTION OF SUPPORT UNITS	13
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST	14
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
4. TEST TYPES AND RESULTS	16
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT	16
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	16
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS	16
4.1.3 TEST INSTRUMENTS	17
4.1.4 TEST PROCEDURES	18
4.1.5 DEVIATION FROM TEST STANDARD	18
4.1.6 TEST SETUP	19
4.1.7 EUT OPERATING CONDITION	20
4.1.8 TEST RESULTS	21
4.2 CONDUCTED EMISSION MEASUREMENT	41
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	41
4.2.2 TEST INSTRUMENTS	41
4.2.3 TEST PROCEDURES	42
4.2.4 DEVIATION FROM TEST STANDARD	42
4.2.5 TEST SETUP	42
4.2.6 EUT OPERATING CONDITIONS	42
4.2.7 TEST RESULTS	43
4.3 TRANSMIT POWER MEASUREMENT	47
4.3.1 LIMITS OF TRANSMIT POWER MEASUREMENT	47
4.3.2 TEST SETUP	47
4.3.3 TEST INSTRUMENTS	48
4.3.4 TEST PROCEDURE	48
4.3.5 DEVIATION FROM TEST STANDARD	48
4.3.6 EUT OPERATING CONDITIONS	48
4.3.7 TEST RESULTS	49
4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT	53
4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT	53
4.4.2 TEST SETUP	53
4.4.3 TEST INSTRUMENTS	53
4.4.4 TEST PROCEDURES	53
4.4.5 DEVIATION FROM TEST STANDARD	54
4.4.6 EUT OPERATING CONDITIONS	54
4.4.7 TEST RESULTS	55
4.5 FREQUENCY STABILITY	61
4.5.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	61
4.5.2 TEST SETUP	61



A D T

4.5.3	TEST INSTRUMENTS	61
4.5.4	TEST PROCEDURE	62
4.5.5	DEVIATION FROM TEST STANDARD	62
4.5.6	EUT OPERATING CONDITION	62
4.5.7	TEST RESULTS	63
4.6	6dB BANDWIDTH MEASUREMENT	64
4.6.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	64
4.6.2	TEST SETUP	64
4.6.3	TEST INSTRUMENTS	64
4.6.4	TEST PROCEDURE	64
4.6.5	DEVIATION FROM TEST STANDARD	64
4.6.6	EUT OPERATING CONDITIONS	64
4.6.7	TEST RESULTS	65
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	67
6.	INFORMATION ON THE TESTING LABORATORIES	68
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	69



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140521C07-1	Original release	Jun. 13, 2014



1. CERTIFICATION

PRODUCT: AC1750 Dual Band Wireless Router with StreamBoost™
Technology (Refer to item 3.1 for more detail)

MODEL: TEW-824DRU (Refer to item 3.1 for more detail)

BRAND: TRENDnet


APPLICANT: TRENDnet, Inc.

TESTED: Apr. 15 ~ Jun. 06, 2014

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10-2009

The above equipment (model: TEW-824DRU) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE :** Jun. 13, 2014
Pettie Chen / Senior Specialist

APPROVED BY :  , **DATE :** Jun. 13, 2014
Ken Liu / Senior Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.407(b)(6)	AC Power Conducted Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -9.98dB at 0.15000MHz.
15.407(b)(1/2/3/4/6)	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 5150.00MHz.
15.407(b)(1/2/3/4/6)	Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 5150.00MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(1/2/3)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(e)	6dB bandwidth	PASS	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.19 dB
	200MHz ~ 1000MHz	3.21 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	AC1750 Dual Band Wireless Router with StreamBoost™ Technology (Refer to NOTE for more detail)
MODEL NO.	TEW-824DRU (Refer to NOTE for more detail)
POWER SUPPLY	12Vdc (Adapter)
MODULATION TYPE	256QAM, 64QAM, 16QAM, QPSK, BPSK
MODULATION TECHNOLOGY	OFDM
TRANSFER RATE	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 450.0Mbps 802.11ac: up to 1300.0Mbps
OPERATING FREQUENCY	5180 ~ 5240MHz, 5745 ~ 5825MHz
NUMBER OF CHANNEL	5180 ~ 5240MHz: 4 for 802.11a, 802.11n (20MHz), 802.11ac (20MHz) 2 for 802.11n (40MHz), 802.11ac (40MHz) 1 for 802.11ac (80MHz) 5745 ~ 5825MHz: 5 for 802.11a, 802.11n (20MHz) , 802.11ac (20MHz) 2 for 802.11n (40MHz) , 802.11ac (40MHz) 1 for 802.11ac (80MHz)
OUTPUT POWER	466.429mW for 5180 ~ 5240MHz 361.686mW for 5745 ~ 5825MHz
ANTENNA TYPE	Printed antenna with 3dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Adapter

NOTE:

1. The following product names & models are provided to this EUT.

Product Name	Brand	Model	DESCRIPTION
AC1750 Dual Band Wireless Router	TRENDnet	TEW-823DRU	Without StreamBoost function
AC1750 Dual Band Wireless Router with StreamBoost™ Technology	TRENDnet	TEW-824DRU	With StreamBoost function

2. The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 3 receivers.

MODULATION MODE	TX FUNCTION
802.11b	3TX
802.11g	3TX
802.11a	3TX
802.11n (20MHz)	3TX
802.11n (40MHz)	3TX
802.11ac (20MHz)	3TX
802.11ac (40MHz)	3TX
802.11ac (80MHz)	3TX

* The modulation and bandwidth are similar for 802.11n mode for 20MHz / 40MHz and 802.11ac mode for 20MHz / 40MHz, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

3. The EUT consumes power from the following adapters.

ADAPTER 1	
BRAND:	OEM
MODEL:	ADS0271-W 120200
INPUT:	100-240Vac~50-60Hz 0.6A
OUTPUT:	12Vdc / 2.0A
POWER LINE:	1.28m non-shielded cable without core

ADAPTER 2	
BRAND:	AMIGO
MODEL:	AMS3-1202000FU
INPUT:	100-240Vac~50/60Hz 0.8A/65A
OUTPUT:	12Vdc / 2.0A
POWER LINE:	1.2m non-shielded cable without core

4. The 2.4 and 5GHz cannot transmit simultaneously.
5. The above EUT information is declared by manufacturer and for more detailed feature description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (20MHz), 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (40MHz), 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY
42	5210MHz

FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (20MHz), 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz), 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY
155	5775MHz

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
A	√	√	√	√	Tested with adapter 1
B	-	√	√	-	Tested with adapter 2

Where **RE \geq 1G**: Radiated Emission above 1GHz **RE $<$ 1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:
The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
NOTE: “-” means no effect.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6.0
A	802.11n (20MHz)		36 to 48	36, 40, 48	OFDM	BPSK	7.2
A	802.11n (40MHz)		38 to 46	38, 46	OFDM	BPSK	15.0
A	802.11ac (80MHz)		42	42	OFDM	BPSK	97.5
A	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6.0
A	802.11n (20MHz)		149 to 165	149, 157, 165	OFDM	BPSK	7.2
A	802.11n (40MHz)		151 to 159	151, 159	OFDM	BPSK	15.0
A	802.11ac (80MHz)		155	155	OFDM	BPSK	97.5

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11a	5180-5320, 5745-5825	36 to 64, 149 to 165	40	OFDM	BPSK	6.0

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B	802.11a	5180-5320, 5745-5825	36 to 64, 149 to 165	40	OFDM	BPSK	6.0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	BPSK	6.0
A	802.11n (20MHz)		36 to 48	36, 40, 48	OFDM	BPSK	7.2
A	802.11n (40MHz)		38 to 46	38, 46	OFDM	BPSK	15.0
A	802.11ac (80MHz)		42	42	OFDM	BPSK	97.5
A	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	BPSK	6.0
A	802.11n (20MHz)		149 to 165	149, 157, 165	OFDM	BPSK	7.2
A	802.11n (40MHz)		151 to 159	151, 159	OFDM	BPSK	15.0
A	802.11ac (80MHz)		155	155	OFDM	BPSK	97.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 68%RH	120Vac, 60Hz	Sun Lin
RE<1G	25deg. C, 68%RH	120Vac, 60Hz	Sun Lin
PLC	25deg. C, 68%RH	120Vac, 60Hz	Sun Lin
APCM	25deg. C, 60%RH	120Vac, 60Hz	Nick Chen



A D T

3.3 DUTY CYCLE OF TEST SIGNAL


Duty cycle of test signal is > 98 %, duty factor is not required.

802.11a: Duty cycle = $23.8/23.8625 = 0.997$

802.11n (20MHz): Duty cycle = $23.775/23.9 = 0.995$

802.11n (40MHz): Duty cycle = $23.8/23.925 = 0.995$

802.11ac (80MHz): Duty cycle = $23.8125/23.9 = 0.996$



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	E5420	BPQ8MQ1	FCC DoC Approved
2	USB dongle	NA	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	10m RJ45 cable
2	NA

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 1 acted as communication partner to transfer data.
3. Item 2 was provided by client.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST



3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

789033 D02 General UNII Test Procedures New Rules v01

662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO		LIMIT	
	789033 D02 General UNII Test Procedures New Rules v01	FIELD STRENGTH AT 3m	
		PK:74 (dBµV/m)	AV:54 (dBµV/m)
APPLICABLE TO		EIRP LIMIT	EQUIVALENT FIELD STRENGTH AT 3m
√	15.407(b)(1)	PK:-27 (dBm/MHz)	PK:68.3(dBµV/m)
	15.407(b)(2)		
	15.407(b)(3)		
√	15.407(b)(4)	PK:-27 (dBm/MHz) ^{*1} PK:-17 (dBm/MHz) ^{*2}	PK: 68.3(dBµV/m) ^{*1} PK:78.3 (dBµV/m) ^{*2}

NOTE: ^{*1} beyond 10MHz of the band edge ^{*2} within 10 MHz of band edge

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Sep. 09, 2013	Sep. 08, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU 43	100115	Dec. 18, 2013	Dec. 17, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Feb. 26, 2014	Feb. 25, 2015
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2014	Jan. 04, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Preamplifier Agilent	8449B	3008A01961	Oct. 28, 2013	Oct. 27, 2014
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309220/4	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250724/4	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295012/4	Aug. 26, 2013	Aug. 25, 2014
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA	NA
Turn Table BV ADT	TT100.	TT93021704	NA	NA
Turn Table Controller BV ADT	SC100.	SC93021704	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 18, 2013	Oct. 17, 2014
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 10, 2013	Jun. 09, 2014

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 4.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 460141.
 5. The IC Site Registration No. is IC7450F-4.

4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.5 DEVIATION FROM TEST STANDARD


No deviation.

4.1.6 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.7 EUT OPERATING CONDITION

- a. Placed the EUT on the testing table.
- b. Prepared a notebook to act as a communication partner and placed it outside of testing area.
- c. The communication partner was connected with the EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable the EUT under transmission condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".

4.1.8 TEST RESULTS

ABOVE 1GHz DATA

For U-NII-1 Band

802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.1 PK	74.0	-4.9	1.13 H	31	66.70	2.40
2	5150.00	50.9 AV	54.0	-3.1	1.13 H	31	48.50	2.40
3	*5180.00	111.8 PK			1.00 H	18	72.40	39.40
4	*5180.00	101.5 AV			1.00 H	18	62.10	39.40
5	#10360.00	61.6 PK	68.3	-6.7	1.07 H	9	47.70	13.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	70.9 PK	74.0	-3.1	1.00 V	105	68.50	2.40
2	5150.00	52.6 AV	54.0	-1.4	1.00 V	105	50.20	2.40
3	*5180.00	112.8 PK			1.12 V	155	73.40	39.40
4	*5180.00	102.2 AV			1.12 V	155	62.80	39.40
5	#10360.00	62.1 PK	68.3	-6.2	1.00 V	85	48.20	13.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.4 PK	74.0	-4.6	1.02 H	11	67.00	2.40
2	5150.00	50.0 AV	54.0	-4.0	1.02 H	11	47.60	2.40
3	*5200.00	116.2 PK			1.00 H	20	76.70	39.50
4	*5200.00	105.6 AV			1.00 H	20	66.10	39.50
5	#10400.00	63.2 PK	68.3	-5.1	1.06 H	9	49.10	14.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	71.0 PK	74.0	-3.0	1.00 V	102	68.60	2.40
2	5150.00	51.6 AV	54.0	-2.4	1.00 V	102	49.20	2.40
3	*5200.00	118.4 PK			1.00 V	99	78.90	39.50
4	*5200.00	107.1 AV			1.00 V	99	67.60	39.50
5	#10400.00	67.1 PK	68.3	-1.2	1.66 V	286	53.00	14.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	115.7 PK			1.00 H	28	76.10	39.60
2	*5240.00	104.6 AV			1.00 H	28	65.00	39.60
3	5350.00	57.0 PK	74.0	-17.0	1.02 H	28	54.40	2.60
4	5350.00	45.1 AV	54.0	-8.9	1.02 H	28	42.50	2.60
5	#10480.00	66.0 PK	68.3	-2.3	1.00 H	11	50.70	15.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	115.9 PK			1.13 V	18	76.30	39.60
2	*5240.00	104.9 AV			1.13 V	18	65.30	39.60
3	5350.00	58.5 PK	74.0	-15.5	1.02 V	17	55.90	2.60
4	5350.00	46.1 AV	54.0	-7.9	1.02 V	17	43.50	2.60
5	#10480.00	62.9 PK	68.3	-5.4	1.00 V	213	47.60	15.30

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11n (20MHz)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.4 PK	74.0	-4.6	1.13 H	35	67.00	2.40
2	5150.00	51.1 AV	54.0	-2.9	1.13 H	35	48.70	2.40
3	*5180.00	111.9 PK			1.00 H	19	72.50	39.40
4	*5180.00	101.6 AV			1.00 H	19	62.20	39.40
5	#10360.00	61.8 PK	68.3	-6.5	1.00 H	21	47.90	13.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	70.8 PK	74.0	-3.2	1.00 V	100	68.40	2.40
2	5150.00	53.0 AV	54.0	-1.0	1.00 V	100	50.60	2.40
3	*5180.00	112.7 PK			1.00 V	162	73.30	39.40
4	*5180.00	102.3 AV			1.00 V	162	62.90	39.40
5	#10360.00	62.2 PK	68.3	-6.1	1.00 V	151	48.30	13.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	68.8 PK	74.0	-5.2	1.00 H	213	66.40	2.40
2	5150.00	51.7 AV	54.0	-2.3	1.00 H	213	49.30	2.40
3	*5200.00	116.2 PK			1.00 H	42	76.70	39.50
4	*5200.00	105.1 AV			1.00 H	42	65.60	39.50
5	#10400.00	64.8 PK	68.3	-3.5	1.14 H	12	50.70	14.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	71.0 PK	74.0	-3.0	1.00 V	107	68.60	2.40
2	5150.00	53.0 AV	54.0	-1.0	1.00 V	107	50.60	2.40
3	*5200.00	116.8 PK			1.00 V	162	77.30	39.50
4	*5200.00	105.5 AV			1.00 V	162	66.00	39.50
5	#10400.00	63.0 PK	68.3	-5.3	1.17 V	110	48.90	14.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	115.6 PK			1.05 H	184	76.00	39.60
2	*5240.00	104.5 AV			1.05 H	184	64.90	39.60
3	5350.00	57.2 PK	74.0	-16.8	1.54 H	112	54.60	2.60
4	5350.00	46.5 AV	54.0	-7.5	1.54 H	112	43.90	2.60
5	#10480.00	66.1 PK	68.3	-2.2	1.05 H	9	50.80	15.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	115.6 PK			1.00 V	98	76.00	39.60
2	*5240.00	105.0 AV			1.00 V	98	65.40	39.60
3	5350.00	58.4 PK	74.0	-15.6	1.02 V	99	55.80	2.60
4	5350.00	46.1 AV	54.0	-7.9	1.02 V	99	43.50	2.60
5	#10480.00	63.5 PK	68.3	-4.8	2.03 V	303	48.20	15.30

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11n (40MHz)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	67.0 PK	74.0	-7.0	1.01 H	310	64.60	2.40
2	5150.00	51.7 AV	54.0	-2.3	1.01 H	310	49.30	2.40
3	*5190.00	106.0 PK			1.00 H	20	66.50	39.50
4	*5190.00	95.5 AV			1.00 H	20	56.00	39.50
5	#10380.00	60.6 PK	68.3	-7.7	1.51 H	32	46.50	14.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.6 PK	74.0	-4.4	1.00 V	109	67.20	2.40
2	5150.00	53.0 AV	54.0	-1.0	1.00 V	109	50.60	2.40
3	*5190.00	108.2 PK			1.00 V	104	68.70	39.50
4	*5190.00	97.5 AV			1.00 V	104	58.00	39.50
5	#10380.00	61.2 PK	68.3	-7.1	1.00 V	51	47.10	14.10

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.9 PK	74.0	-7.1	1.00 H	41	64.50	2.40
2	5150.00	51.9 AV	54.0	-2.1	1.00 H	41	49.50	2.40
3	*5230.00	111.4 PK			1.00 H	18	71.80	39.60
4	*5230.00	101.5 AV			1.00 H	18	61.90	39.60
5	#10460.00	62.7 PK	68.3	-5.6	1.04 H	17	47.90	14.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	67.6 PK	74.0	-6.4	1.00 V	93	65.20	2.40
2	5150.00	53.0 AV	54.0	-1.0	1.00 V	93	50.60	2.40
3	*5230.00	114.4 PK			1.00 V	105	74.80	39.60
4	*5230.00	103.5 AV			1.00 V	105	63.90	39.60
5	#10460.00	62.5 PK	68.3	-5.8	1.04 V	304	47.70	14.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

802.11ac (80MHz)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	65.9 PK	74.0	-8.1	1.00 H	211	63.50	2.40
2	5150.00	51.0 AV	54.0	-3.0	1.00 H	211	48.60	2.40
3	*5210.00	101.2 PK			1.00 H	34	61.70	39.50
4	*5210.00	91.1 AV			1.00 H	34	51.60	39.50
5	#10420.00	59.9 PK	68.3	-8.4	1.01 H	56	45.50	14.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	65.8 PK	74.0	-8.2	1.00 V	92	63.40	2.40
2	5150.00	52.5 AV	54.0	-1.5	1.00 V	92	50.10	2.40
3	*5210.00	102.7 PK			1.00 V	162	63.20	39.50
4	*5210.00	91.8 AV			1.00 V	162	52.30	39.50
5	#10420.00	60.8 PK	68.3	-7.5	1.00 V	186	46.40	14.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

For U-NII-3 Band

802.11a

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	66.1 PK	68.3	-2.2	1.45 H	15	62.80	3.30
2	#5722.90	76.9 PK	78.3	-1.4	1.03 H	6	73.60	3.30
3	#5725.00	55.8 PK	78.3	-22.5	1.00 H	56	52.50	3.30
4	*5745.00	111.2 PK			1.00 H	15	70.90	40.30
5	*5745.00	101.3 AV			1.00 H	15	61.00	40.30
6	11490.00	59.8 PK	74.0	-14.2	1.02 H	64	43.90	15.90
7	11490.00	47.4 AV	54.0	-6.6	1.02 H	64	31.50	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	65.7 PK	68.3	-2.6	1.00 V	101	62.40	3.30
2	#5722.90	76.8 PK	78.3	-1.5	1.00 V	159	73.50	3.30
3	#5725.00	65.7 PK	78.3	-12.6	1.00 V	51	62.40	3.30
4	*5745.00	110.3 PK			1.00 V	98	70.00	40.30
5	*5745.00	100.2 AV			1.00 V	98	59.90	40.30
6	11490.00	62.5 PK	74.0	-11.5	1.00 V	74	46.60	15.90
7	11490.00	48.5 AV	54.0	-5.5	1.00 V	74	32.60	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	115.3 PK			1.15 H	18	75.00	40.30
2	*5785.00	104.3 AV			1.15 H	18	64.00	40.30
3	11570.00	65.4 PK	74.0	-8.6	1.05 H	9	49.50	15.90
4	11570.00	49.8 AV	54.0	-4.2	1.05 H	9	33.90	15.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	114.4 PK			1.00 V	15	74.10	40.30
2	*5785.00	103.3 AV			1.00 V	15	63.00	40.30
3	11570.00	65.1 PK	74.0	-8.9	1.00 V	292	49.20	15.90
4	11570.00	49.8 AV	54.0	-4.2	1.00 V	292	33.90	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	111.3 PK			1.00 H	20	70.80	40.50
2	*5825.00	101.3 AV			1.00 H	20	60.80	40.50
3	#5850.00	57.8 PK	78.3	-20.5	1.00 H	102	54.40	3.40
4	#5852.10	73.8 PK	78.3	-4.5	1.00 H	24	70.40	3.40
5	#5860.10	67.2 PK	68.3	-1.1	1.00 H	25	63.70	3.50
6	11650.00	62.5 PK	74.0	-11.5	1.05 H	62	46.60	15.90
7	11650.00	48.4 AV	54.0	-5.6	1.05 H	62	32.50	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	111.8 PK			1.00 V	27	71.30	40.50
2	*5825.00	100.5 AV			1.00 V	27	60.00	40.50
3	#5850.00	59.0 PK	78.3	-19.3	1.00 V	171	55.60	3.40
4	#5852.10	74.5 PK	78.3	-3.8	1.00 V	51	71.10	3.40
5	#5860.10	62.8 PK	68.3	-5.5	1.00 V	211	59.30	3.50
6	11650.00	62.7 PK	74.0	-11.3	1.05 V	51	46.80	15.90
7	11650.00	48.7 AV	54.0	-5.3	1.05 V	51	32.80	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11n (20MHz)

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	64.8 PK	68.3	-3.5	1.00 H	7	61.50	3.30
2	#5722.90	76.9 PK	78.3	-1.4	1.75 H	7	73.60	3.30
3	#5725.00	55.7 PK	78.3	-22.6	1.02 H	25	52.40	3.30
4	*5745.00	109.6 PK			1.00 H	15	69.30	40.30
5	*5745.00	99.9 AV			1.00 H	15	59.60	40.30
6	11490.00	59.4 PK	74.0	-14.6	1.03 H	324	43.50	15.90
7	11490.00	47.1 AV	54.0	-6.9	1.03 H	324	31.20	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	65.8 PK	68.3	-2.5	1.00 V	58	62.50	3.30
2	#5722.90	75.0 PK	78.3	-3.3	1.00 V	63	71.70	3.30
3	#5725.00	58.1 PK	78.3	-20.2	1.02 V	31	54.80	3.30
4	*5745.00	110.3 PK			1.00 V	16	70.00	40.30
5	*5745.00	99.4 AV			1.00 V	16	59.10	40.30
6	11490.00	60.4 PK	74.0	-13.6	1.03 V	59	44.50	15.90
7	11490.00	47.1 AV	54.0	-6.9	1.03 V	59	31.20	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	115.0 PK			1.00 H	25	74.70	40.30
2	*5785.00	104.0 AV			1.00 H	25	63.70	40.30
3	11570.00	61.1 PK	74.0	-12.9	1.12 H	151	45.20	15.90
4	11570.00	49.5 AV	54.0	-4.5	1.12 H	151	33.60	15.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	114.1 PK			1.02 V	162	73.80	40.30
2	*5785.00	103.0 AV			1.02 V	162	62.70	40.30
3	11570.00	64.7 PK	74.0	-9.3	1.84 V	265	48.80	15.90
4	11570.00	49.5 AV	54.0	-4.5	1.84 V	265	33.60	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	110.2 PK			1.00 H	2	69.70	40.50
2	*5825.00	100.0 AV			1.00 H	2	59.50	40.50
3	#5850.00	58.0 PK	78.3	-20.3	1.02 H	31	54.60	3.40
4	#5852.10	71.2 PK	78.3	-7.1	1.00 H	24	67.80	3.40
5	#5860.10	67.2 PK	68.3	-1.1	1.00 H	27	63.70	3.50
6	11650.00	62.4 PK	74.0	-11.6	1.02 H	63	46.50	15.90
7	11650.00	48.1 AV	54.0	-5.9	1.02 H	63	32.20	15.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	110.2 PK			1.00 V	13	69.70	40.50
2	*5825.00	99.5 AV			1.00 V	13	59.00	40.50
3	#5850.00	58.6 PK	78.3	-19.7	1.41 V	263	55.20	3.40
4	#5852.10	73.9 PK	78.3	-4.4	1.00 V	162	70.50	3.40
5	#5860.10	63.0 PK	68.3	-5.3	1.01 V	22	59.50	3.50
6	11650.00	62.1 PK	74.0	-11.9	1.04 V	201	46.20	15.90
7	11650.00	48.4 AV	54.0	-5.6	1.04 V	201	32.50	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

802.11n (40MHz)

CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	67.1 PK	68.3	-1.2	1.00 H	189	63.80	3.30
2	#5722.90	71.8 PK	78.3	-6.5	1.00 H	14	68.50	3.30
3	#5725.00	58.9 PK	78.3	-19.4	1.00 H	85	55.60	3.30
4	*5755.00	106.8 PK			1.08 H	16	66.50	40.30
5	*5755.00	96.5 AV			1.08 H	16	56.20	40.30
6	11510.00	60.9 PK	74.0	-13.1	1.00 H	354	45.00	15.90
7	11510.00	47.1 AV	54.0	-6.9	1.00 H	354	31.20	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	67.0 PK	68.3	-1.3	1.00 V	41	63.70	3.30
2	#5722.90	74.4 PK	78.3	-3.9	1.00 V	245	71.10	3.30
3	#5725.00	58.7 PK	78.3	-19.6	1.00 V	244	55.40	3.30
4	*5755.00	106.7 PK			1.01 V	8	66.40	40.30
5	*5755.00	95.9 AV			1.01 V	8	55.60	40.30
6	11510.00	61.4 PK	74.0	-12.6	1.02 V	64	45.50	15.90
7	11510.00	47.4 AV	54.0	-6.6	1.02 V	64	31.50	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	111.6 PK			1.00 H	11	71.20	40.40
2	*5795.00	101.1 AV			1.00 H	11	60.70	40.40
3	#5850.00	59.9 PK	78.3	-18.4	1.01 H	51	56.50	3.40
4	#5852.10	71.0 PK	78.3	-7.3	1.00 H	7	67.60	3.40
5	#5860.10	67.0 PK	68.3	-1.3	1.00 H	20	63.50	3.50
6	11590.00	61.0 PK	74.0	-13.0	1.02 H	64	45.20	15.80
7	11590.00	47.3 AV	54.0	-6.7	1.02 H	64	31.50	15.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	109.6 PK			1.00 V	110	69.20	40.40
2	*5795.00	99.1 AV			1.00 V	110	58.70	40.40
3	#5850.00	56.6 PK	78.3	-21.7	1.00 V	52	53.20	3.40
4	#5852.10	70.0 PK	78.3	-8.3	1.10 V	197	66.60	3.40
5	#5860.10	66.0 PK	68.3	-2.3	1.00 V	159	62.50	3.50
6	11590.00	61.4 PK	74.0	-12.6	1.05 V	64	45.60	15.80
7	11590.00	48.0 AV	54.0	-6.0	1.05 V	64	32.20	15.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

802.11ac (80MHz)

CHANNEL	TX Channel 155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	66.5 PK	68.3	-1.8	1.00 H	2	63.20	3.30
2	#5722.90	72.2 PK	78.3	-6.1	1.02 H	51	68.90	3.30
3	#5725.00	57.5 PK	78.3	-20.8	1.15 H	62	54.20	3.30
4	*5775.00	102.2 PK			1.00 H	13	61.90	40.30
5	*5775.00	92.5 AV			1.00 H	13	52.20	40.30
6	#5850.00	46.4 PK	78.3	-31.9	1.32 H	65	43.00	3.40
7	#5852.10	60.1 PK	78.3	-18.2	1.02 H	64	56.70	3.40
8	#5860.10	60.0 PK	68.3	-8.3	1.01 H	115	56.50	3.50
9	11550.00	59.5 PK	74.0	-14.5	1.21 H	63	43.60	15.90
10	11550.00	47.1 AV	54.0	-6.9	1.21 H	63	31.20	15.90

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5714.90	67.1 PK	68.3	-1.2	1.01 V	41	63.80	3.30
2	#5722.90	72.6 PK	78.3	-5.7	1.00 V	110	69.30	3.30
3	#5725.00	57.5 PK	78.3	-20.8	1.00 V	121	54.20	3.30
4	*5775.00	100.5 PK			1.00 V	59	60.20	40.30
5	*5775.00	90.5 AV			1.00 V	59	50.20	40.30
6	#5850.00	47.0 PK	78.3	-31.3	1.01 V	51	43.60	3.40
7	#5852.10	60.6 PK	78.3	-17.7	1.00 V	165	57.20	3.40
8	#5860.10	60.4 PK	68.3	-7.9	1.00 V	154	56.90	3.50
9	11550.00	61.9 PK	74.0	-12.1	1.02 V	34	46.00	15.90
10	11550.00	48.4 AV	54.0	-5.6	1.02 V	34	32.50	15.90

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

BELOW 1GHz WORST-CASE DATA :

802.11a

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	138.23	39.8 QP	43.5	-3.7	2.22 H	105	54.60	-14.80
2	200.99	34.7 QP	43.5	-8.8	1.24 H	109	51.20	-16.50
3	256.96	32.3 QP	46.0	-13.7	1.24 H	210	46.20	-13.90
4	375.10	29.9 QP	46.0	-16.1	1.99 H	236	40.50	-10.60
5	480.80	34.8 QP	46.0	-11.2	1.49 H	253	43.40	-8.60
6	600.50	32.2 QP	46.0	-13.8	1.24 H	303	38.40	-6.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	138.30	39.6 QP	43.5	-3.9	1.18 V	127	54.40	-14.80
2	202.55	35.0 QP	43.5	-8.5	1.24 V	115	51.50	-16.50
3	253.85	32.7 QP	46.0	-13.3	1.00 V	210	46.70	-14.00
4	375.10	30.8 QP	46.0	-15.2	1.99 V	244	41.40	-10.60
5	480.80	34.5 QP	46.0	-11.5	1.49 V	256	43.10	-8.60
6	625.37	31.5 QP	46.0	-14.5	1.24 V	213	37.10	-5.60

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	138.81	35.7 QP	43.5	-7.8	1.99 H	273	50.40	-14.70
2	210.32	32.6 QP	43.5	-10.9	1.00 H	119	48.70	-16.10
3	256.95	33.4 QP	46.0	-12.6	1.00 H	198	47.30	-13.90
4	480.00	34.2 QP	46.0	-11.8	1.53 H	236	42.80	-8.60
5	563.19	35.3 QP	46.0	-10.7	1.24 H	74	42.60	-7.30
6	687.55	33.9 QP	46.0	-12.1	1.00 H	211	39.00	-5.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	61.09	34.9 QP	40.0	-5.1	1.24 V	184	49.70	-14.80
2	148.14	33.8 QP	43.5	-9.7	1.24 V	217	47.70	-13.90
3	298.93	28.4 QP	46.0	-17.6	1.49 V	199	40.60	-12.20
4	480.00	34.4 QP	46.0	-11.6	1.00 V	205	43.00	-8.60
5	687.55	33.1 QP	46.0	-12.9	1.24 V	168	38.20	-5.10
6	900.51	39.3 QP	46.0	-6.7	1.00 V	263	40.50	-1.20

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 24, 2014	Apr. 23, 2015
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 23, 2013	Dec. 22, 2014
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 08, 2013	Jul. 07, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS


802.11a

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.27	49.96	38.58	50.23	38.85	65.18	55.18	-14.95	-16.33
2	0.31797	0.29	32.85	20.91	33.14	21.20	59.76	49.76	-26.62	-28.56
3	0.44688	0.30	33.44	23.35	33.74	23.65	56.93	46.93	-23.19	-23.28
4	4.84375	0.44	25.66	15.53	26.10	15.97	56.00	46.00	-29.90	-30.03
5	9.20703	0.49	29.60	15.09	30.09	15.58	60.00	50.00	-29.91	-34.42
6	11.04297	0.51	27.15	20.31	27.66	20.82	60.00	50.00	-32.34	-29.18

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.27	50.79	38.60	51.06	38.87	65.18	55.18	-14.12	-16.31
2	0.19687	0.28	46.26	32.11	46.54	32.39	63.74	53.74	-17.20	-21.35
3	0.35703	0.30	34.26	23.03	34.56	23.33	58.80	48.80	-24.24	-25.47
4	0.44688	0.30	34.14	23.33	34.44	23.63	56.93	46.93	-22.49	-23.30
5	0.62656	0.32	21.93	11.85	22.25	12.17	56.00	46.00	-33.75	-33.83
6	24.92188	0.57	30.09	25.36	30.66	25.93	60.00	50.00	-29.34	-24.07

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.26	55.76	39.31	56.02	39.57	66.00	56.00	-9.98	-16.43
2	0.17734	0.27	42.59	20.86	42.86	21.13	64.61	54.61	-21.75	-33.48
3	0.18906	0.28	53.20	38.48	53.48	38.76	64.08	54.08	-10.60	-15.32
4	0.23984	0.28	46.72	33.32	47.00	33.60	62.10	52.10	-15.10	-18.50
5	0.28672	0.29	42.13	29.18	42.42	29.47	60.62	50.62	-18.20	-21.15
6	6.28906	0.46	42.00	36.17	42.46	36.63	60.00	50.00	-17.54	-13.37

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.27	51.22	31.32	51.49	31.59	65.79	55.79	-14.30	-24.20
2	0.18516	0.28	52.50	34.22	52.78	34.50	64.25	54.25	-11.48	-19.76
3	0.23984	0.28	46.98	33.66	47.26	33.94	62.10	52.10	-14.84	-18.16
4	0.28281	0.29	42.41	27.74	42.70	28.03	60.73	50.73	-18.03	-22.70
5	0.73203	0.32	35.93	26.81	36.25	27.13	56.00	46.00	-19.75	-18.87
6	6.30469	0.47	42.21	36.01	42.68	36.48	60.00	50.00	-17.32	-13.52

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 TRANSMIT POWER MEASUREMENT

4.3.1 LIMITS OF TRANSMIT POWER MEASUREMENT

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p \leq 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
	√	Indoor Access Point	1 Watt (30 dBm)
		Mobile and Portable client device	250mW (24 dBm)
U-NII-2A		---	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C		---	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3	√	---	1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 D01 Multiple Transmitter Output v02r01 Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for NANT \leq 4;

Array Gain = 0 dB (i.e., no array gain) for channel widths \geq 40 MHz for any NANT;

Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT \geq 5.

For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.3.4 TEST PROCEDURE

FOR AVERAGE POWER MEASUREMENT

For 802.11a, 802.11n (20MHz), 802.11n (40MHz)

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

For 802.11ac (80MHz)

- 1) Set span to encompass the entire 26 dB EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 2) Set sweep trigger to "free run".
- 3) Set RBW = 1 MHz.
- 4) Set VBW \geq 3 MHz
- 5) Number of points in sweep \geq 2 Span / RBW.
- 6) Sweep time \leq (number of points in sweep) * T
- 7) Detector = RMS.
- 8) Trace mode = max hold.
- 9) Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 TEST RESULTS

POWER OUTPUT:

802.11a

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
36	5180	18.47	19.08	18.56	222.996	23.48	30	PASS
40	5200	21.91	22.47	21.29	466.429	26.69	30	PASS
48	5240	21.72	22.01	21.07	435.387	26.39	30	PASS
149	5745	16.92	17.22	17.41	157.008	21.96	30	PASS
157	5785	20.85	21.42	20.06	361.686	25.58	30	PASS
165	5825	17.87	18.41	18.07	194.699	22.89	30	PASS

802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
36	5180	18.41	19.02	18.47	219.449	23.41	30	PASS
40	5200	21.89	22.42	21.08	457.340	26.60	30	PASS
48	5240	21.77	22.02	21.06	437.179	26.41	30	PASS
149	5745	16.21	16.42	16.68	132.195	21.21	30	PASS
157	5785	20.85	21.41	20.01	360.207	25.57	30	PASS
165	5825	17.19	17.41	17.29	161.021	22.07	30	PASS



A D T

802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
38	5190	14.92	15.18	15.29	97.813	19.90	30	PASS
46	5230	21.29	21.01	20.22	365.965	25.63	30	PASS
151	5755	14.52	14.58	15.21	90.211	19.55	30	PASS
159	5795	19.21	19.62	19.08	255.900	24.08	30	PASS

802.11ac (80MHz)

CHAN.	CHAN. FREQ. (MHz)	MAXIMUM CONDUCTED POWER (dBm)			TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2				
42	5210	13.47	13.52	14.01	69.901	18.44	30	PASS
155	5775	13.02	13.01	13.92	64.704	18.11	30	PASS



26dB BANDWIDTH:

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)			PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2	
36	5180	24.88	26.86	26.65	PASS
40	5200	43.54	44.66	44.29	PASS
48	5240	43.05	42.88	43.84	PASS

802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)			PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2	
36	5180	25.52	27.33	27.63	PASS
40	5200	45.89	46.90	46.65	PASS
48	5240	45.35	44.44	47.49	PASS

802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)			PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2	
38	5190	46.01	45.61	45.89	PASS
46	5230	86.50	84.43	94.29	PASS

802.11ac (80MHz)


CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)			PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2	
42	5210	87.50	88.11	86.27	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)




4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT

4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
	√	Indoor Access Point	11dBm/ MHz
		Mobile and Portable client device	
U-NII-2A		---	11dBm/ MHz
U-NII-2C		---	11dBm/ MHz
U-NII-3	√	---	30dBm/ MHz

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

For U-NII-1 band:

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 30 kHz, Set VBW ≥ 1 MHz, Detector = RMS
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to “free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 500 kHz, Set VBW \geq 3 RBW, Detector = RMS
- 3) Sweep time = auto, trigger set to “free run”.
- 4) Trace average at least 100 traces in power averaging mode.
- 5) Record the max value and add $10 \log (1/\text{duty cycle})$

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as 4.3.6.



4.4.7 TEST RESULTS

For U-NII-1 Band

802.11a

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)			TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2			
36	5180	5.31	5.20	5.49	10.11	15.23	PASS
40	5200	8.51	8.13	8.64	13.20	15.23	PASS
48	5240	8.24	8.37	8.48	13.14	15.23	PASS

NOTE: 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

2. For U-NII-1 Band:

Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $17 - (7.77 - 6) = 15.23\text{dBm}$.

802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)			TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2			
36	5180	4.63	5.57	5.40	9.99	15.23	PASS
40	5200	8.28	8.62	8.58	13.27	15.23	PASS
48	5240	7.92	8.28	8.43	12.99	15.23	PASS

NOTE: 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

2. For U-NII-1 Band:

Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $17 - (7.77 - 6) = 15.23\text{dBm}$.

802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)			TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2			
38	5190	-1.67	-1.39	-1.48	3.26	15.23	PASS
46	5230	3.67	3.99	4.45	8.82	15.23	PASS

NOTE: 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

2. For U-NII-1 Band:

Directional gain = 3dBi + 10log(3) = 7.77dBi > 6dBi , so the power density limit shall be reduced to 17-(7.77-6) = 15.23dBm.

802.11ac (80MHz):

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)			TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2			
42	5210	-6.46	-3.13	-5.87	-0.13	15.23	PASS

NOTE: 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

2. For U-NII-1 Band:


Directional gain = 3dBi + 10log(3) = 7.77dBi > 6dBi , so the power density limit shall be reduced to 17-(7.77-6) = 15.23dBm.




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)



For U-NII-3 Band

802.11a

TX chain	Channel	Freq. (MHz)	PSD (dBm/500kHz)	10 log (N=3) dB	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	PASS /FAIL
0	149	5745	10.52	4.77	15.29	28.23	PASS
	157	5785	14.66	4.77	19.43	28.23	PASS
	165	5825	11.37	4.77	16.14	28.23	PASS
1	149	5745	11.16	4.77	15.93	28.23	PASS
	157	5785	14.71	4.77	19.48	28.23	PASS
	165	5825	11.86	4.77	16.63	28.23	PASS
2	149	5745	12.60	4.77	17.37	28.23	PASS
	157	5785	15.54	4.77	20.31	28.23	PASS
	165	5825	13.57	4.77	18.34	28.23	PASS

NOTE: Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (7.77 - 6) = 28.23\text{dBm}$.

802.11n (20MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/500kHz)	10 log (N=3) dB	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	PASS /FAIL
0	149	5745	9.00	4.77	13.77	28.23	PASS
	157	5785	14.99	4.77	19.76	28.23	PASS
	165	5825	10.26	4.77	15.03	28.23	PASS
1	149	5745	9.91	4.77	14.68	28.23	PASS
	157	5785	14.45	4.77	19.22	28.23	PASS
	165	5825	10.50	4.77	15.27	28.23	PASS
2	149	5745	11.02	4.77	15.79	28.23	PASS
	157	5785	15.33	4.77	20.10	28.23	PASS
	165	5825	11.75	4.77	16.52	28.23	PASS

NOTE: Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (7.77 - 6) = 28.23\text{dBm}$.

802.11n (40MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/500kHz)	10 log (N=3) dB	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	PASS /FAIL
0	151	5755	5.22	4.77	9.99	28.23	PASS
	159	5795	9.03	4.77	13.80	28.23	PASS
1	151	5755	5.19	4.77	9.96	28.23	PASS
	159	5795	9.41	4.77	14.18	28.23	PASS
2	151	5755	6.93	4.77	11.70	28.23	PASS
	159	5795	10.63	4.77	15.40	28.23	PASS

NOTE: Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30-(7.77-6) = 28.23\text{dBm}$.

802.11ac (80MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/500kHz)	10 log (N=3) dB	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	PASS /FAIL
0	155	5775	0.30	4.77	5.07	28.23	PASS
1	155	5775	2.54	4.77	7.31	28.23	PASS
2	155	5775	2.74	4.77	7.51	28.23	PASS


NOTE: Directional gain = $3\text{dBi} + 10\log(3) = 7.77\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30-(7.77-6) = 28.23\text{dBm}$.




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)




4.5 FREQUENCY STABILITY

4.5.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.

4.5.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5240MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
50	120	5239.9912	-0.00017	5239.9937	-0.00012	5239.9906	-0.00018	5239.9902	-0.00019
40	120	5240.0208	0.00040	5240.0216	0.00041	5240.0208	0.00040	5240.0234	0.00045
30	120	5239.9925	-0.00014	5239.9945	-0.00010	5239.9951	-0.00009	5239.9954	-0.00009
20	120	5240.0143	0.00027	5240.0153	0.00029	5240.0147	0.00028	5240.0169	0.00032
10	120	5240.0076	0.00015	5240.0078	0.00015	5240.0091	0.00017	5240.0078	0.00015
0	120	5239.9885	-0.00022	5239.9869	-0.00025	5239.9902	-0.00019	5239.9902	-0.00019
-10	120	5239.9877	-0.00023	5239.9886	-0.00022	5239.9897	-0.00020	5239.9870	-0.00025
-20	120	5240.0063	0.00012	5240.0072	0.00014	5240.0103	0.00020	5240.0067	0.00013
-30	120	5240.0143	0.00027	5240.0144	0.00027	5240.0109	0.00021	5240.0141	0.00027


FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5240MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	138	5240.0135	0.00026	5240.0156	0.00030	5240.0156	0.00030	5240.0159	0.00030
	120	5240.0143	0.00027	5240.0153	0.00029	5240.0147	0.00028	5240.0169	0.00032
	102	5240.0148	0.00028	5240.0154	0.00029	5240.0143	0.00027	5240.0160	0.00031

4.6 6dB BANDWIDTH MEASUREMENT

4.6.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.6.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
149	5745	16.39	16.60	16.42	0.5	PASS
157	5785	16.43	16.44	16.42	0.5	PASS
165	5825	16.42	16.39	16.41	0.5	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
149	5745	17.61	17.62	17.60	0.5	PASS
157	5785	17.83	17.62	17.83	0.5	PASS
165	5825	17.65	17.64	17.62	0.5	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
151	5755	36.57	36.48	36.45	0.5	PASS
159	5795	36.52	36.53	36.45	0.5	PASS

802.11ac (80MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 2		
155	5775	76.00	76.32	75.85	0.5	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---