

RF Exposure Report

Report No.: SA180730C06D

FCC ID: XU8TEW840APBO

Test Model: TEW-840APBO, TEW-842APBO, TEW-844APBO

Series Model: TEW-840APBO2K, TEW-844APBO2K

Received Date: Mar. 21, 2019

Test Date: Apr. 11 ~ Apr. 13, 2019

Issued Date: Apr. 19, 2019

Applicant: TRENDnet, Inc.

Address: 20675 Manhattan Place, Torrance, CA 90501 U.S.A.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180730C06D	Original release	Apr. 19, 2019

1 Certificate of Conformity

Product: 14 dBi WiFi AC867 Outdoor Directional PoE Access Point (Refer to note for more details)
Brand: TRENDnet
Test Model: TEW-840APBO, TEW-842APBO, TEW-844APBO
Series Model: TEW-840APBO2K, TEW-844APBO2K (Refer to note for more details)
Sample Status: Engineering sample
Applicant: TRENDnet, Inc.
Test Date: Apr. 11 ~ Apr. 13, 2019
Standards: FCC Part 2 (Section 2.1091)
 KDB 447498 D01 General RF Exposure Guidance v06
 IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Polly Chien, **Date:** Apr. 19, 2019
 Polly Chien / Specialist

Approved by : Bruce Chen, **Date:** Apr. 19, 2019
 Bruce Chen / Project Engineer

Note:

All models are listed as below. Model TEW-840APBO, TEW-842APBO and TEW-844APBO are the representative for final test.

Brand	Model	Product	Difference
TRENDnet	TEW-840APBO	14 dBi WiFi AC867 Outdoor Directional PoE Access Point	Internal direct 14dBi antenna
	TEW-840APBO2K	14 dBi WiFi AC867 Outdoor PoE Preconfigured Point-to-Point Bridge Kit	
	TEW-842APBO	5 dBi Wireless AC867 Outdoor PoE Omni-Directional Access Point	Accessory with external dipole 5dBi*2 antenna
	TEW-844APBO	19 dBi WiFi AC867 Outdoor Directional PoE Access Point	Internal direct 19dBi antenna
	TEW-844APBO2K	19 dBi WiFi AC867 Outdoor PoE Preconfigured Point-to-Point Bridge Kit	

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 25cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
Patch Ant. for model: TEW-840APBO and TEW-840APBO2K use only (CDD Mode)					
5180-5240	15.01	16.43	25	0.177	1
5745-5825	22.29	16.43	25	0.948	1
Patch Ant. for model: TEW-840APBO and TEW-840APBO2K use only (Beamforming Mode)					
5180-5240	11.99	16.43	25	0.088	1
5745-5825	19.21	16.43	25	0.467	1
Dipole Ant. for model: TEW-842APBO (CDD Mode)					
5180-5240	16.33	8.18	25	0.036	1
5745-5825	26.71	8.18	25	0.393	1
Dipole Ant. for model: TEW-842APBO (Beamforming Mode)					
5180-5240	13.32	8.18	25	0.018	1
5745-5825	23.70	8.18	25	0.196	1
Patch Ant. for model: TEW-844APBO and TEW-844APBO2K (CDD Mode)					
5180-5240	5.22	18.51	25	0.030	1
5745-5825	20.30	18.51	25	0.968	1
Patch Ant. for model: TEW-844APBO and TEW-844APBO2K (Beamforming Mode)					
5180-5240	2.21	18.51	25	0.015	1
5745-5825	17.23	18.51	25	0.477	1

Note:

1. Patch Ant. for model: ENS500-ACv2 and EAS100-14 Directional gain = 13.42dBi + 10log(2) = 16.43dBi
2. Dipole Ant. for model: ENS500EXT-ACv2 and EAS100EXT Directional gain = 5.17dBi + 10log(2) = 8.18dBi
3. Patch Ant. for model: EnStation5-ACv2 and EAS100-19 Directional gain = 15.50dBi + 10log(2) = 18.51dBi

---END---