

FCC RF Exposure

EUT Description: AX1800 Dual Band WiFi 6 Router
 Model No.: TRENDnet
 FCC ID: XU8TEW912DRU

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where :

Pd = power density in mW/cm²,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Test Result of RF Exposure Evaluation

2.4G WIFI

	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	16.18/41.495	1.0	0.01039	1.0	Pass
802.11g	14.57/28.642	1.0	0.00717	1.0	Pass
802.11n(20MHz)	14.39/27.479	1.0	0.00688	1.0	Pass
802.11n(40MHz)	13.23/21.038	1.0	0.00527	1.0	Pass
802.ax HE20	13.56/22.698	1.0	0.00568	1.0	Pass
802.ax HE40	13.66/23.227	1.0	0.00581	1.0	Pass

5.8G WIFI

	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
	18.51/70.95	1.0	0.01768	1.0	Pass
U-NII-3 a	22.42/174.58	1.0	0.04371	1.0	Pass
U-NII-3 ac(VHT20)	21.97/157.39	1.0	0.03941	1.0	Pass
U-NII-3 ac(VHT40)	22.66/184.50	1.0	0.04619	1.0	Pass
U-NII-3 ac(VHT80)	20.84/121.33	1.0	0.03038	1.0	Pass
U-NII-3 ax(HEW20)	22.61/182.38	1.0	0.04566	1.0	Pass
U-NII-3 ax(HEW40)	22.65/184.07	1.0	0.04609	1.0	Pass
U-NII-3 ax(HEW80)	20.44/110.66	1.0	0.02770	1.0	Pass

Turn-up power	
Mode	Peak power range(dBm)
2.4G WIFI	13.00-17.00
5.8G WIFI	18.50-24.00

WIFI	Output power (dBm/ mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2.4G WIFI	17.00/50.12	1.0	0.01255	1.0	Pass
5.8GWIFI	24.00/251.18	1.0	0.06289	1.0	Pass

Conclusion: No SAR is required