




IEEE 802.11n HT40 MHz mode (Antenna 1)







7.4. ANTENNA GAIN

MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

LIMITS

FCC	IC
Antenna Gain	
6 dBi	

TEST RESULTS

The EUT uses two PCB antennas, the maximum gain is 2.0dBi . The antenna used for transmitting is permanently attached and no consideration of replacement. Please see EUT photo for details.

Tnom	Vnom	Antenna 0			Antenna 1		
		lowest channel 2412 MHz	middle channel 2437 MHz	highest channel 2462 MHz	lowest channel 2412 MHz	middle channel 2437 MHz	highest channel 2462 MHz
Conducted power [dBm] Measured with 802.11b modulation		17.12	19.01	20.31	16.51	16.48	17.42
Radiated power [dBm] Measured with 802.11b modulation		19.03	21.02	22.18	18.32	18.39	19.35
Gain [dBi] Calculated		1.91	2.01	1.87	1.81	1.91	1.93
Measurement uncertainty		± 1.5 dB (cond.) / ± 3.0 dB (rad.)					



7.5. PEAK OUTPUT POWER

7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Power Meter	Anritsu	ML2495A	1204003	02/21/2016	02/20/2017
Power Sensor	Anritsu	MA2411B	1126150	02/21/2016	02/20/2017

7.5.3. TEST PROCEDURES (please refer to measurement standard)

9.1.1 RBW \geq DTS bandwidth

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.

- a) Set the RBW \geq *DTS bandwidth*.
- b) Set VBW \geq 3 RBW.
- c) Set span \geq 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



9.1.2 Integrated band power method


This procedure may be used when the maximum available RBW of the measurement instrument is less than the *DTS bandwidth*.

- a) Set the RBW = 1 MHz.
- b) Set the VBW ≥ 3 RBW
- c) Set the span $\geq 1.5 \times$ DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

9.1.3 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

7.5.4. TEST SETUP





7.5.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b (Antenna 0)

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	17.12	0.05152	Peak	1	PASS
Mid	2437	19.01	0.07962			PASS
High	2462	20.31	0.10740			PASS
Low	2412	14.93	0.03112	AVG	1	PASS
Mid	2437	17.00	0.05012			PASS
High	2462	18.55	0.07161			PASS

Test mode: IEEE 802.11b (Antenna 1)

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	16.51	0.04477	Peak	1	PASS
Mid	2437	16.48	0.04446			PASS
High	2462	17.42	0.05521			PASS
Low	2412	14.63	0.02904	AVG	1	PASS
Mid	2437	14.66	0.02924			PASS
High	2462	15.49	0.03540			PASS

Test mode: IEEE 802.11g (Antenna 0)

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	22.31	0.17022	Peak	1	PASS
Mid	2437	23.41	0.21928			PASS
High	2462	22.41	0.17418			PASS
Low	2412	14.85	0.03055	AVG	1	PASS
Mid	2437	16.74	0.04721			PASS
High	2462	15.38	0.03451			PASS



Test mode: IEEE 802.11g (Antenna 1)

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	18.75	0.07499	Peak	1	PASS
Mid	2437	20.75	0.11885			PASS
High	2462	18.72	0.07447			PASS
Low	2412	10.51	0.01125	AVG	1	PASS
Mid	2437	13.92	0.02466			PASS
High	2462	11.20	0.01318			PASS

Test mode: IEEE 802.11n HT20 MHz(Combine with Antenna 0 and Antenna 1)

Channel	Frequency (MHz)	Output Power (dBm)			Output Power (W)	Peak / AVG	Limit (W)	Result
		Antenna 0	Antenna 1	Total				
Low	2412	19.46	17.20	21.49	0.14079	Peak	1	PASS
Mid	2437	23.10	22.38	25.77	0.37716			PASS
High	2462	19.96	17.83	22.03	0.15976			PASS
Low	2412	10.67	8.33	12.67	0.01848	AVG	1	PASS
Mid	2437	17.57	15.84	19.80	0.09552			PASS
High	2462	12.39	9.73	14.27	0.02674			PASS

Test mode: IEEE 802.11n HT40 MHz(Combine with Antenna 0 and Antenna 1)

Channel	Frequency (MHz)	Output Power (dBm)			Output Power (W)	Peak / AVG	Limit (W)	Result
		Antenna 0	Antenna 1	Total				
Low	2422	19.11	17.26	21.29	0.13468	Peak	1	PASS
Mid	2437	20.98	19.13	23.16	0.20716			PASS
High	2452	19.06	17.75	21.46	0.14010			PASS
Low	2422	9.68	8.62	12.19	0.01657	AVG	1	PASS
Mid	2437	13.14	11.32	15.33	0.03416			PASS
High	2452	10.54	8.50	12.65	0.01840			PASS



7.6. BAND EDGES MEASUREMENT

7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).


7.6.2. TEST INSTRUMENTS

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2016	02/20/2017
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2016	02/20/2017
Amplifier	EMEC	EM330	060661	03/18/2016	03/17/2017
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2016	02/20/2017
Loop Antenna	COM-POWER	AL-130	121044	09/25/2015	09/24/2016
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2016	02/20/2017
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2016	02/27/2017
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2016	02/27/2017
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2016	02/20/2017
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The FCC Site Registration number is 101879.
 3. N.C.R = No Calibration Required.

7.6.3. TEST PROCEDURES (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO / Detector=PEAK
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

7.6.4. TEST SETUP





7.6.5. TEST RESULTS



Test Plot

IEEE 802.11b mode (Antenna 0)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	47.23	-6.60	53.83	74.00	-20.17	Peak	Vertical
2	2390.0000	36.06	-6.60	42.66	54.00	-11.34	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	47.94	-6.60	54.54	74.00	-19.46	Peak	Horizontal
2	2390.0000	37.29	-6.60	43.89	54.00	-10.11	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	47.55	-6.24	53.79	74.00	-20.21	Peak	Vertical
2	2483.5000	36.92	-6.24	43.16	54.00	-10.84	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	48.50	-6.24	54.74	74.00	-19.26	Peak	Horizontal
2	2483.5000	37.86	-6.24	44.10	54.00	-9.90	Average	Horizontal





IEEE 802.11b mode (Antenna 1)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	46.93	-6.60	53.53	74.00	-20.47	Peak	Vertical
2	2390.0000	36.13	-6.60	42.73	54.00	-11.27	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	50.69	-6.60	57.29	74.00	-16.71	Peak	Horizontal
2	2390.0000	38.74	-6.60	45.34	54.00	-8.66	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	48.67	-6.24	54.91	74.00	-19.09	Peak	Vertical
2	2483.5000	36.92	-6.24	43.16	54.00	-10.84	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	49.39	-6.24	55.63	74.00	-18.37	Peak	Horizontal
2	2483.5000	37.86	-6.24	44.10	54.00	-9.90	Average	Horizontal





IEEE 802.11g mode (Antenna 0)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	50.25	-6.60	56.85	74.00	-17.15	Peak	Vertical
2	2390.0000	38.29	-6.60	44.89	54.00	-9.11	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	61.56	-6.60	68.16	74.00	-5.84	Peak	Horizontal
2	2390.0000	43.51	-6.60	50.11	54.00	-3.89	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	50.02	-6.24	56.26	74.00	-17.74	Peak	Vertical
2	2483.5000	38.23	-6.24	44.47	54.00	-9.53	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	59.17	-6.24	65.41	74.00	-8.59	Peak	Horizontal
2	2483.5000	45.08	-6.24	51.32	54.00	-2.68	Average	Horizontal





IEEE 802.11g mode (Antenna 1)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	50.47	-6.60	57.07	74.00	-16.93	Peak	Vertical
2	2390.0000	37.48	-6.60	44.08	54.00	-9.92	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	59.55	-6.60	66.15	74.00	-7.85	Peak	Horizontal
2	2390.0000	44.76	-6.60	51.36	54.00	-2.64	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	50.95	-6.24	57.19	74.00	-16.81	Peak	Vertical
2	2483.5000	38.53	-6.24	44.77	54.00	-9.23	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	63.71	-6.24	69.95	74.00	-4.05	Peak	Horizontal
2	2483.5000	45.88	-6.24	52.12	54.00	-1.88	Average	Horizontal





IEEE 802.11n HT20 MHz mode (Combine with Antenna 0 and Antenna 1)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dB μ V)	Corrected (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	48.64	-6.60	55.24	74.00	-18.76	Peak	Vertical
2	2390.0000	37.97	-6.60	44.57	54.00	-9.43	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	61.11	-6.60	67.71	74.00	-6.29	Peak	Horizontal
2	2390.0000	45.11	-6.60	51.71	54.00	-2.29	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	49.51	-6.24	55.75	74.00	-18.25	Peak	Vertical
2	2483.5000	38.56	-6.24	44.80	54.00	-9.20	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	59.95	-6.24	66.19	74.00	-7.81	Peak	Horizontal
2	2483.5000	44.98	-6.24	51.22	54.00	-2.78	Average	Horizontal





IEEE 802.11n HT40 MHz mode (Combine with Antenna 0 and Antenna 1)

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	48.03	-6.60	54.63	74.00	-19.37	Peak	Vertical
2	2390.0000	38.47	-6.60	45.07	54.00	-8.93	Average	Vertical





No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	59.08	-6.60	65.68	74.00	-8.32	Peak	Horizontal
2	2390.0000	45.34	-6.60	51.94	54.00	-2.06	Average	Horizontal



Band Edges (CH High)



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	48.85	-6.24	55.09	74.00	-18.91	Peak	Vertical
2	2483.5000	39.49	-6.24	45.73	54.00	-8.27	Average	Vertical



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	60.28	-6.24	66.52	74.00	-7.48	Peak	Horizontal
2	2483.5000	46.49	-6.24	52.73	54.00	-1.27	Average	Horizontal



7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

7.7.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY52221469	02/21/2016	02/20/2017


7.7.3. TEST PROCEDURES (please refer to measurement standard)

§15.247(e) specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segment within the fundamental EBW during any time interval of continuous transmission. The same method as used to determine the conducted output power shall be used to determine the power spectral density (i.e., if peak-detected fundamental power was measured then use the peak PSD procedure and if average fundamental power was measured then use the average PSD procedure).

10.2 Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.7.4. TEST SETUP





7.7.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b (Antenna 0)

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-9.260	8	PASS
Mid	2437	-7.891		PASS
High	2462	-6.895		PASS

Test mode: IEEE 802.11b (Antenna 1)

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-8.574	8	PASS
Mid	2437	-8.892		PASS
High	2462	-7.934		PASS

Test mode: IEEE 802.11g (Antenna 0)

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-11.926	8	PASS
Mid	2437	-11.376		PASS
High	2462	-9.659		PASS

Test mode: IEEE 802.11g (Antenna 1)

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-13.326	8	PASS
Mid	2437	-10.900		PASS
High	2462	-14.143		PASS



Test mode: IEEE 802.11n HT20 MHz (Combine with Antenna 0 and Antenna 1)

Channel	Frequency (MHz)	PPSD (dBm)			Limit (dBm)	Test Result
		Antenna 0	Antenna 1	Total		
Low	2412	-15.694	-15.592	-12.632	8	PASS
Mid	2437	-11.841	-12.726	-9.251		PASS
High	2462	-14.227	-16.047	-12.032		PASS

Test mode: IEEE 802.11n HT40 MHz (Combine with Antenna 0 and Antenna 1)

Channel	Frequency (MHz)	PPSD (dBm)			Limit (dBm)	Test Result
		Antenna 0	Antenna 1	Total		
Low	2422	-18.770	-18.570	-15.659	8	PASS
Mid	2437	-15.239	-15.913	-12.553		PASS
High	2452	-17.988	-16.029	-13.889		PASS



Test Plot

IEEE 802.11b mode (Antenna 0)

PPSD (CH Low)




PPSD (CH Mid)








PPSD (CH High)



IEEE 802.11b mode (Antenna 1)

PPSD (CH Low)










IEEE 802.11g mode (Antenna 0)

PPSD (CH Low)






PPSD (CH Mid)





IEEE 802.11g mode (Antenna 1)










IEEE 802.11n HT20 MHz mode (Antenna 0)

PPSD (CH Low)






PPSD (CH Mid)





IEEE 802.11n HT20 MHz mode (Antenna 1)










IEEE 802.11n HT40 MHz mode (Antenna 0)

PPSD (CH Low)



PPSD (CH Mid)





IEEE 802.11n HT40 MHz mode (Antenna 1)

