

# RF EXPOSURE REPORT

**REPORT NO.:** SA130925E07

MODEL NO.: TV-IP862IC, TV-IP662WI

**FCC ID:** XU8TVIP662-862

**RECEIVED:** Sep. 17, 2013

**TESTED:** Sep. 27, 2013

**ISSUED:** Nov. 01, 2013

APPLICANT: TRENDnet, Inc.

ADDRESS: 20675 Manhattan Place, Torrance, CA

90501 USA

**ISSUED BY:** Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,

R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **TABLE OF CONTENTS**

RE	LEASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA130925E07	Original release	Nov. 01, 2013

Report No.: SA130925E07 3 of 6 Report Format Version 5.0.0



#### 1. CERTIFICATION

HD Wireless Day/Night PTZ Cloud

**PRODUCT:** Camera ,Megapixel Wireless Day/Night PTZ Network

Camera

**BRAND NAME:** TRENDnet

MODEL NO.: TV-IP862IC, TV-IP662WI

TEST SAMPLE: ENGINEERING SAMPLE

APPLICANT: TRENDnet, Inc.

**TESTED DATE:** Sep. 27, 2013

**STANDARDS:** FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

**IEEE C95.1** 

The above equipment (Model: TV-IP862IC) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : \_\_\_\_\_\_\_, DATE: Nov. 01, 2013

(Lori Chung, Specialist)

( May Chen, Manager )



#### 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)			POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)					
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE									
300-1500			F/1500	30					
1500-100,000			1.0	30					

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

#### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



### 5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm²)
2412 - 2462	410.204	2.23	20	0.13637	1.00

--- END ---