

FCC Part 15C

Measurement and Test Report


For

Launch Tech Co., Ltd.

Launch Industrial Park, North of Wuhe Rd., Banxuegang, Longgang,

Shenzhen, China

FCC ID: XUJ01DIAGUN

| | |
|--|---|
| Report Concerns: Original Report | Equipment Type: AUTOMOTIVE DIAGNOSIS COMPUTER |
| Model: | <u>X431 DIAGUN</u> |
| Report No.: | <u>STR09118021I-1</u> |
| Test/Witness Engineer: |  |
| Test Date: | <u>2009-10-16 to 2009-11-20</u> |
| Issue Date: | <u>2009-11-25</u> |
| Prepared By: | <p>SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101)</p> |
| Approved & Authorized By: |  <hr/> Jandy So / PSQ Manager |

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION..... | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| 1.2 TEST STANDARDS..... | 3 |
| 1.3 RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| 1.4 TEST METHODOLOGY..... | 4 |
| 1.5 TEST FACILITY..... | 4 |
| 1.6 EUT EXERCISE SOFTWARE..... | 4 |
| 1.7 ACCESSORIES EQUIPMENT LIST AND DETAILS..... | 4 |
| 1.8 EUT CABLE LIST AND DETAILS..... | 4 |
| 2. SUMMARY OF TEST RESULTS..... | 5 |
| 3. §15.203 - ANTENNA REQUIREMENT..... | 6 |
| 3.1 STANDARD APPLICABLE..... | 6 |
| 3.2 TEST RESULT..... | 6 |
| 4. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING..... | 7 |
| 4.1 STANDARD APPLICABLE..... | 7 |
| 4.2 TEST EQUIPMENT LIST AND DETAILS..... | 7 |
| 4.3 TEST PROCEDURE..... | 7 |
| 4.4 ENVIRONMENTAL CONDITIONS..... | 7 |
| 4.5 SUMMARY OF TEST RESULTS/PLOTS..... | 8 |
| 5. DWELL TIME OF A HOPPING CHANNEL..... | 10 |
| 5.1 STANDARD APPLICABLE..... | 10 |
| 5.2 TEST EQUIPMENT LIST AND DETAILS..... | 10 |
| 5.3 TEST PROCEDURE..... | 10 |
| 5.4 ENVIRONMENTAL CONDITIONS..... | 10 |
| 5.5 SUMMARY OF TEST RESULTS/PLOTS..... | 11 |
| 6. 20-DB BANDWIDTH..... | 13 |
| 6.1 STANDARD APPLICABLE..... | 13 |
| 6.2 TEST EQUIPMENT LIST AND DETAILS..... | 13 |
| 6.3 TEST PROCEDURE..... | 13 |
| 6.4 ENVIRONMENTAL CONDITIONS..... | 13 |
| 6.5 SUMMARY OF TEST RESULTS/PLOTS..... | 13 |
| 7. POWER OUTPUT..... | 16 |
| 7.1 STANDARD APPLICABLE..... | 16 |
| 7.2 TEST EQUIPMENT LIST AND DETAILS..... | 16 |
| 7.3 TEST PROCEDURE..... | 16 |
| 7.4 ENVIRONMENTAL CONDITIONS..... | 16 |
| 7.5 SUMMARY OF TEST RESULTS/PLOTS..... | 16 |
| 8. FIELD STRENGTH OF SPURIOUS EMISSIONS..... | 17 |
| 8.1 MEASUREMENT UNCERTAINTY..... | 17 |
| 8.2 STANDARD APPLICABLE..... | 17 |
| 8.3 TEST EQUIPMENT LIST AND DETAILS..... | 18 |
| 8.4 TEST PROCEDURE..... | 18 |
| 8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION..... | 19 |
| 8.6 ENVIRONMENTAL CONDITIONS..... | 19 |
| 8.7 SUMMARY OF TEST RESULTS/PLOTS..... | 19 |
| 9. OUT OF BAND EMISSIONS..... | 24 |
| 9.1 STANDARD APPLICABLE..... | 24 |
| 9.2 TEST EQUIPMENT LIST AND DETAILS..... | 24 |
| 9.3 TEST PROCEDURE..... | 24 |
| 9.4 ENVIRONMENTAL CONDITIONS..... | 24 |
| 9.5 SUMMARY OF TEST RESULTS/PLOTS..... | 25 |

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Launch Tech Co., Ltd.
 Address of applicant: Launch Industrial Park, North of Wuhe Rd., Banxuegang, Longgang, Shenzhen, China

Manufacturer: Launch Tech Co., Ltd.
 Address of manufacturer: Launch Industrial Park, North of Wuhe Rd., Banxuegang, Longgang, Shenzhen, China

General Description of E.U.T

| Items | Description |
|---------------------|-------------------------------|
| EUT Description: | AUTOMOTIVE DIAGNOSIS COMPUTER |
| Trade Name: | LAUNCH |
| Model No.: | X-431 DIAGUN |
| Rated Voltage: | DC 3.7V |
| Max. Output Power | -6dBm~13.5 dBm |
| Frequency range: | 2402MHz-2480MHz |
| Number of channels: | 79 |
| Channel Separation: | 1MHz |
| Type of Antenna: | Integral Antenna |
| Size: | 13.5X7.7X2.2cm |

Note: The test data is gathered from a production sample, provided by the manufacturer.

1.2 Test Standards

The following report is prepared on behalf of the Launch Tech Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Related Submittal(s)/Grant(s)

No Related Submittal(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted with Low Channel, Middle Channel and High Channel, accordingly in reference to the Operating Instructions.

1.5 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

1.6 EUT Exercise Software

The EUT exercise program used during the testing was designed to exercise the system components.

1.7 Accessories Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|-------|---------------|
| IBM | Notebook | T22 | LV14893 |

1.8 EUT Cable List and Details

| Cable Description | Length (M) | Shielded/Unshielded | With Core/Without Core |
|-------------------|------------|---------------------|------------------------|
| USB Cable 1 | 1.20 | Shielded | Without Core |
| USB Cable 2 | 1.20 | Shielded | Without Core |
| Power Cable | 1.60 | Unshielded | With Core |

2. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|-----------------------------|--------------------------------|-----------|
| § 15.203; § 15.247(b)(4)(i) | Antenna Requirement | Compliant |
| § 15.247(a)(1)(iii) | Quantity of Hopping Channel | Compliant |
| § 15.247(a)(1) | Channel Separation | Compliant |
| § 15.247(a)(1)(iii) | Time of Occupancy (Dwell time) | Compliant |
| § 15.247(a) | 20dB Bandwidth | Compliant |
| § 15.247(b)(1) | Power Output | Compliant |
| § 15.209(a)(f) | Radiated Emission | Compliant |
| § 15.247(c) | Band edge | Compliant |

3. §15.203 - ANTENNA REQUIREMENT

3.1 Standard Applicable

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a permanent antenna, fulfill the requirement of this section.

4. NUMBER OF HOPPING CHANNELS AND CHANNEL SPACING

4.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.2 Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Cal. Date | Due. Date |
|--------------|--------------------------|------------|---------------|------------|------------|
| Agilent | Spectrum Analyzer | E4402B-ESA | US41192821 | 2009-08-12 | 2010-08-11 |
| SCHWARZBECK | Trilog Broadband Antenna | VULB9163 | 9163-333 | 2009-08-12 | 2010-08-11 |

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

4.3 Test Procedure


Set the Lowest channel to the Highest Channel, observed the band of 2400MHz to 2438.5MHz, than count it out the number of channels for comparing with the FCC rules. Adjust channel spacing can be read by adjusting the Analyzer SPAN.

4.4 Environmental Conditions


| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

4.5 Summary of Test Results/Plots


No. of Channel=79




Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



Channel Spacing (High CH=1MHz)



5. DWELL TIME OF A HOPPING CHANNEL

5.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.2 Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Cal. Date | Due. Date |
|--------------|--------------------------|------------|---------------|------------|------------|
| Aglient | Spectrum Analyzer | E4402B-ESA | US41192821 | 2009-08-12 | 2010-08-11 |
| SCHWARZBECK | Trilog Broadband Antenna | VULB9163 | 9163-333 | 2009-08-12 | 2010-08-11 |

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

5.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=100KHz, Span = 0Hz.
4. Repeat above procedures until all frequency measured was complete.

5.4 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |


5.5 Summary of Test Results/Plots

The dwell time within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

$$\text{Dwell time} = \text{time slot length} * \text{hop rate} / \text{number of hopping channels} * 31.6\text{s}$$


Test data is corrected with the worse case, which the packet length is DH1.

CH Low:




$$\text{DH1 time slot} = 0.44 \text{ (ms)} * (1600/(79)) * 31.6 = 281.6 \text{ (ms)} < 400 \text{ (ms)}$$

CH Mid:



$$DH1 \text{ time slot} = 0.42 \text{ (ms)} * (1600/(79)) * 31.6 = 268.8 \text{ (ms)} < 400 \text{ (ms)}$$

CH High:



$$DH1 \text{ time slot} = 0.42 \text{ (ms)} * (1600/(79)) * 31.6 = 268.8 \text{ (ms)} < 400 \text{ (ms)}$$

6. 20-dB BANDWIDTH

6.1 Standard Applicable

According to 15.247(a)(1)(iii). For frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

6.2 Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Cal. Date | Due. Date |
|--------------|--------------------------|------------|---------------|------------|------------|
| Aglient | Spectrum Analyzer | E4402B-ESA | US41192821 | 2009-08-12 | 2010-08-11 |
| SCHWARZBECK | Trilog Broadband Antenna | VULB9163 | 9163-333 | 2009-08-12 | 2010-08-11 |

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

6.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. The spectrum analyzer as RBW=10KHz (1 % of Bandwidth.), Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.


6.4 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 53% |
| ATM Pressure: | 1018 mbar |


6.5 Summary of Test Results/Plots

| Frequency MHz | 20 dB Bandwidth kHz | Limit dB |
|------------------|------------------------|-------------|
| 2402 | 960.1 | / |
| 2441 | 972.6 | / |
| 2480 | 985.0 | / |


CH Low:



CH Mid:



CH High:



7. POWER OUTPUT

7.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

7.2 Test Equipment List and Details

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|--------------------------|---------------|-----------|---------------|------------|------------|
| Spectrum Analyzer | ROHDE&SCHWARZ | FSEA20 | DE25181 | 2009-08-12 | 2010-08-11 |
| Positioning Controller | C&C | CC-C-1F | N/A | 2009-08-12 | 2010-08-11 |
| Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 9163-333 | 2009-07-21 | 2010-07-20 |
| Horn Antenna | SCHWARZBECK | BBHX 9120 | 9120-426 | 2009-07-21 | 2010-07-20 |
| RF Switch | EM | EMSW18 | SW060023 | 2009-08-12 | 2010-08-11 |
| Amplifier | Agilent | 8447F | 3113A06717 | 2009-08-12 | 2010-08-11 |
| Coaxial Cable | SCHWARZBECK | AK9513 | 9513-10 | 2009-08-12 | 2010-08-11 |
| EMI Test Receiver | ROHDE&SCHWARZ | ESPI | 25498514 | 2009-08-12 | 2010-08-11 |

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

7.3 Test Procedure

The device under test has an integral antenna and the power was measured on a radiated basis.

7.4 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 55% |
| ATM Pressure: | 1011 mbar |

7.5 Summary of Test Results/Plots

| Channel/Frequency (MHz) | Power (mW) | Remark |
|-------------------------|------------|--------|
| 2402 | 19.86 | EIRP |
| 2441 | 21.97 | EIRP |
| 2480 | 17.98 | EIRP |

Note: The Antenna Gain is under considering.

8. FIELD STRENGTH OF SPURIOUS EMISSIONS

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 3.0 dB.

8.2 Standard Applicable

According to §15.247(c), 15.205 15.209(b) & 15.35 (b), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Section 15.209:

30 - 88 MHz 40 dBuV/m @3M

88 -216 MHz 43.5 dBuV/m @3M

216 -960 MHz 46 dBuV/m @3M

Above 960 MHz 54dBuV/m @3M

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 20 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209,WHICHEVER IS THE LESSER ATTENUATION.

Emissions that fall in the restricted bands (15.205) must be less than 54dBuV/m otherwise the spurious and harmonics must be attenuated by at least 20dB.

8.3 Test Equipment List and Details

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|--------------------------|---------------|-----------|---------------|------------|------------|
| Spectrum Analyzer | ROHDE&SCHWARZ | FSEA20 | DE25181 | 2009-08-12 | 2010-08-11 |
| Positioning Controller | C&C | CC-C-1F | N/A | 2009-08-12 | 2010-08-11 |
| Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 9163-333 | 2009-07-21 | 2010-07-20 |
| Horn Antenna | SCHWARZBECK | BBHX 9120 | 9120-426 | 2009-07-21 | 2010-07-20 |
| RF Switch | EM | EMSW18 | SW060023 | 2009-08-12 | 2010-08-11 |
| Amplifier | Agilent | 8447F | 3113A06717 | 2009-08-12 | 2010-08-11 |
| Coaxial Cable | SCHWARZBECK | AK9513 | 9513-10 | 2009-08-12 | 2010-08-11 |
| EMI Test Receiver | ROHDE&SCHWARZ | ESPI | 25498514 | 2009-08-12 | 2010-08-11 |


Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

8.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.6 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 52% |
| ATM Pressure: | 1012 mbar |

8.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst margin of:

-2.3dB μ V at 4882.0 MHz in the Horizontal polarization for High Channel, 30 MHz to 25 GHz, 3 Meters

From 30 MHz to 1 GHz


Test Mode: Bluetooth Transmission Mode

Horizontal



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct Factor(dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|--------------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 261.9753 | 27.78 | 9.05 | 36.83 | 46.00 | -9.17 | 21 | 200 | Peak |
| 2 | 299.3158 | 24.54 | 10.65 | 35.19 | 46.00 | -10.81 | 329 | 100 | Peak |
| 3 | 349.2500 | 22.77 | 11.85 | 34.62 | 46.00 | -11.38 | 34 | 100 | Peak |
| 4 | 399.0302 | 21.57 | 12.03 | 33.60 | 46.00 | -12.40 | 60 | 200 | Peak |
| 5 | 699.3046 | 22.63 | 17.29 | 39.92 | 46.00 | -6.08 | 110 | 200 | Peak |

Vertical



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct Factor(dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|--------------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 569.9688 | 21.17 | 13.64 | 34.81 | 46.00 | -11.19 | 87 | 200 | peak |
| 2 | 481.5112 | 22.15 | 11.53 | 33.68 | 46.00 | -12.32 | 68 | 100 | peak |
| 3 | 101.1797 | 21.24 | 8.33 | 29.57 | 43.50 | -13.93 | 52 | 100 | peak |
| 4 | 57.2654 | 21.50 | 7.66 | 29.16 | 40.00 | -10.84 | 359 | 100 | peak |
| 5 | 31.2919 | 24.69 | 6.77 | 31.46 | 40.00 | -8.54 | 46 | 200 | peak |

| Frequency MHz | Detector | Meter Reading dBuV | Direction Degree | Polar H / V | Antenna Loss dB | Cable loss dB | Amplifier dB | Correction Amplitude dBuV/m | Limit dBuV/m | Margin dB |
|------------------------------|----------|--------------------|------------------|-------------|-----------------|---------------|--------------|-----------------------------|--------------|-----------|
| Low Channel (1G to 25GHz) | | | | | | | | | | |
| 4804 | AV | 43.6 | 35 | H | 34.1 | 5.2 | 33 | 49.9 | 54 | -4.1 |
| 4804 | AV | 41.5 | 35 | V | 34.1 | 5.2 | 33 | 47.8 | 54 | -6.2 |
| 7206 | AV | 36.5 | 60 | H | 37.4 | 6.1 | 33.5 | 46.5 | 54 | -7.5 |
| 7206 | AV | 33.2 | 79 | V | 37.4 | 6.1 | 33.5 | 43.2 | 54 | -10.8 |
| 2402 | AV | 86.6 | 45 | H | 29.1 | 3.7 | 34 | 85.4 | | (Fund.) |
| 2402 | AV | 83.1 | 359 | V | 29.1 | 3.7 | 34 | 81.9 | | (Fund.) |
| 4804 | PK | 45.6 | 65 | H | 37.4 | 6.1 | 33.5 | 55.6 | 74 | -18.4 |
| 4804 | PK | 42.3 | 98 | V | 34.1 | 5.2 | 33 | 48.6 | 74 | -25.4 |
| 7206 | PK | 46.6 | 256 | H | 34.1 | 5.2 | 33 | 52.9 | 74 | -21.1 |
| 7206 | PK | 44.1 | 185 | V | 37.4 | 6.1 | 33.5 | 54.1 | 74 | -19.9 |
| 2402 | PK | 90.1 | 78 | H | 29.1 | 3.7 | 34 | 88.9 | | (Fund.) |
| 2402 | PK | 86.7 | 44 | V | 29.1 | 3.7 | 34 | 85.5 | | (Fund.) |
| Middle Channel (1G to 25GHz) | | | | | | | | | | |
| 4804 | AV | 43.5 | 57 | H | 34.1 | 5.2 | 33 | 49.8 | 54 | -4.2 |
| 4804 | AV | 41.2 | 35 | V | 34.1 | 5.2 | 33 | 47.5 | 54 | -6.5 |
| 7206 | AV | 34.6 | 60 | H | 37.4 | 6.1 | 33.5 | 44.6 | 54 | -9.4 |
| 7206 | AV | 31.2 | 79 | V | 37.4 | 6.1 | 33.5 | 41.2 | 54 | -12.8 |
| 2402 | AV | 86.4 | 45 | H | 29.1 | 3.7 | 34 | 85.2 | | (Fund.) |
| 2402 | AV | 84.2 | 359 | V | 29.1 | 3.7 | 34 | 83.0 | | (Fund.) |
| 4804 | PK | 47.1 | 65 | H | 37.4 | 6.1 | 33.5 | 57.1 | 74 | -16.9 |
| 4804 | PK | 45.3 | 98 | V | 34.1 | 5.2 | 33 | 51.6 | 74 | -22.4 |
| 7206 | PK | 43.2 | 256 | H | 34.1 | 5.2 | 33 | 49.5 | 74 | -24.5 |
| 7206 | PK | 36.4 | 185 | V | 37.4 | 6.1 | 33.5 | 46.4 | 74 | -27.6 |
| 2402 | PK | 91.4 | 78 | H | 29.1 | 3.7 | 34 | 90.2 | | (Fund.) |
| 2402 | PK | 85.7 | 44 | V | 29.1 | 3.7 | 34 | 84.5 | | (Fund.) |

| High Channel (1G to 25GHz) | | | | | | | | | | |
|----------------------------|----|------|-----|---|------|-----|------|------|----|---------|
| 4960 | AV | 39.4 | 17 | H | 37.4 | 6.1 | 33.5 | 49.4 | 54 | -4.6 |
| 4960 | AV | 36.5 | 13 | V | 37.4 | 6.1 | 33.5 | 46.5 | 54 | -7.5 |
| 7440 | AV | 34.7 | 355 | H | 34.1 | 5.2 | 33 | 41.0 | 54 | -13 |
| 7440 | AV | 32.4 | 66 | V | 34.1 | 5.2 | 33 | 38.7 | 54 | -15.3 |
| 2480 | AV | 87.5 | 63 | H | 29.1 | 3.7 | 34 | 86.3 | | (Fund.) |
| 2480 | AV | 82.1 | 85 | V | 29.1 | 3.7 | 34 | 80.9 | | (Fund.) |
| 4960 | PK | 48.6 | 50 | H | 34.1 | 5.2 | 33 | 54.9 | 74 | -19.1 |
| 4960 | PK | 46.1 | 59 | V | 34.1 | 5.2 | 33 | 52.4 | 74 | -21.6 |
| 7440 | PK | 38.5 | 269 | H | 37.4 | 6.1 | 33.5 | 48.5 | 74 | -25.5 |
| 7440 | PK | 34.2 | 64 | V | 37.4 | 6.1 | 33.5 | 44.2 | 74 | -29.8 |
| 2480 | PK | 89.4 | 85 | H | 29.1 | 3.7 | 34 | 88.2 | | (Fund.) |
| 2480 | PK | 86.6 | 55 | V | 29.1 | 3.7 | 34 | 85.4 | | (Fund.) |

Note: Testing is carried out with frequency rang 30MHz to the tenth harmonics, which above 5th Harmonics is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

9. OUT OF BAND EMISSIONS

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.2 Test Equipment List and Details

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|--------------------------|---------------|-----------|---------------|------------|------------|
| Spectrum Analyzer | ROHDE&SCHWARZ | FSEA20 | DE25181 | 2009-08-12 | 2010-08-11 |
| Positioning Controller | C&C | CC-C-1F | N/A | 2009-08-12 | 2010-08-11 |
| Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 9163-333 | 2009-07-21 | 2010-07-20 |
| Horn Antenna | SCHWARZBECK | BBHX 9120 | 9120-426 | 2009-07-21 | 2010-07-20 |
| RF Switch | EM | EMSW18 | SW060023 | 2009-08-12 | 2010-08-11 |
| Amplifier | Agilent | 8447F | 3113A06717 | 2009-08-12 | 2010-08-11 |
| Coaxial Cable | SCHWARZBECK | AK9513 | 9513-10 | 2009-08-12 | 2010-08-11 |
| EMI Test Receiver | ROHDE&SCHWARZ | ESPI | 25498514 | 2009-08-12 | 2010-08-11 |

Statement of Traceability: All calibrations have been performed per the NVLAP requirements traceable to the NIST.

9.3 Test Procedure

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW, VBW=100KHz, Span=100MHz, Sweep = auto
3. Set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2438.5MHz, then mark the higher-level emission for comparing with the FCC rules.

9.4 Environmental Conditions


| | |
|--------------------|-----------|
| Temperature: | 23°C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

9.5 Summary of Test Results/Plots


| Test mode | Frequency MHz | Limit dBuV /dB | Result |
|-----------|---------------|----------------|--------|
| Lowest | 2390.00 | <54dBuV | Pass |
| | 2400.00 | >20dB | Pass |
| Highest | 2483.50 | <54dBuV | Pass |

The edge emissions are below the FCC 15.209 Limits. Please refer to the test plots below.

Lowest Bandedge



Highest Bandedge



***** END OF REPORT *****