

TEST REPORT

Reference No..... : WTS17S1194413-2E V1
FCC ID : XUJHTT
Applicant..... : Launch Tech Co., Ltd.
Address..... : Launch Industrial Park, North of Wuhe Rd. Banxuegang, Longgang,
Shenzhen. China
Manufacturer : The same as above
Address..... : The same as above
Product..... : Vehicle VIN Checking Terminal, Professional full vehicle model
handheld diagnostic tool
Model(s) : HTT
Brand Name..... : LAUNCH
Standards..... : FCC CFR47 Part 15.247:2017
Date of Receipt sample : 2017-11-03
Date of Test : 2017-11-04 to 2017-12-11
Date of Issue..... : 2018-03-15
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District,
Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Ford Wang

Ford Wang / Project Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

Test Facility:**A. Accreditations for Conformity Assessment (International)**

Country/Region	Accreditation Body	Scope	Note
USA	A2LA (Certificate No.: 4243.01)	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India	International Services	WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note: 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. 2. IC Canada Registration No.: 7760A			

B. TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS	4
4 REVISION HISTORY	5
5 GENERAL INFORMATION.....	6
5.1 GENERAL DESCRIPTION OF E.U.T.	6
5.2 DETAILS OF E.U.T.	6
5.3 CHANNEL LIST.....	8
5.4 TEST MODE	9
6 TEST SUMMARY	10
7 EQUIPMENT USED DURING TEST	11
7.1 EQUIPMENTS LIST	11
7.2 DESCRIPTION OF SUPPORT UNITS	12
7.3 MEASUREMENT UNCERTAINTY	12
7.4 TEST EQUIPMENT CALIBRATION	12
8 CONDUCTED EMISSION	13
8.1 E.U.T. OPERATION	13
8.2 EUT SETUP.....	13
8.3 MEASUREMENT DESCRIPTION	13
8.4 CONDUCTED EMISSION TEST RESULT	14
9 RADIATED EMISSIONS.....	18
9.1 EUT OPERATION.....	18
9.2 TEST SETUP	19
9.3 SPECTRUM ANALYZER SETUP	20
9.4 TEST PROCEDURE	21
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	21
9.6 SUMMARY OF TEST RESULTS	22
10 CONDUCTED SPURIOUS EMISSIONS.....	31
10.1 TEST PROCEDURE.....	31
10.2 TEST RESULT	32
11 BAND EDGE MEASUREMENT	48
11.1 TEST PROCEDURE	48
11.2 TEST RESULT	49
12 6 DB BANDWIDTH MEASUREMENT	64
12.1 TEST PROCEDURE:.....	64
12.2 TEST RESULT:	64
13 MAXIMUM PEAK OUTPUT POWER	73
13.1 TEST PROCEDURE:.....	73
13.2 TEST RESULT:	74
14 POWER SPECTRAL DENSITY	83
14.1 TEST PROCEDURE:.....	83
14.2 TEST RESULT:	83
15 ANTENNA REQUIREMENT	92
16 RF EXPOSURE.....	93
17 PHOTOGRAPHS OF TEST SETUP AND EUT.....	94

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS17S11944 13-2E	2017-11-03	2017-11-04 to 2017-12-11	2018-03-14	original	-	Replaced
WTS17S11944 13-2E V1	2017-11-03	2017-11-04 to 2017-12-11	2018-03-15	Version 1	Updated	Valid

5 General Information

5.1 General Description of E.U.T.

Product:	Vehicle VIN Checking Terminal, Professional full vehicle model handheld diagnostic tool
Model(s):	HTT
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/n/ac HT20/n HT40
Bluetooth Version:	Bluetooth v4.1 with BLE
GPS:	Support
NFC:	Support
Hardware Version:	YZG40050H-MAINBOARD-V3.0.0
Software Version:	NRD90M test-keys
Highest frequency (Exclude Radio):	1.25GHz
Storage Location:	Internal Storage

5.2 Details of E.U.T.

Operation Frequency:	2.4G WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz 5G WiFi: 802.11a/n/ac (HT20): Band I: 5150-5250MHz, Band II: 5250-5350MHz(DFS), Band III: 5470-5725MHz(DFS), Band IV: 5725-5850MHz 802.11n/ac (HT40): Band I: 5190-5230MHz, Band II: 5270-5310MHz(DFS), Band III: 5510-5670MHz(DFS), Band IV: 5755-5795MHz Bluetooth: 2402~2480MHz NFC: 13.56MHz
Max. RF output power:	WiFi (2.4G): 18.67dBm WiFi (5G): 6.0dBm Bluetooth: 5.44dBm
Type of Modulation:	WiFi: CCK, OFDM Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK NFC: ASK, 2ASK
Antenna installation:	WiFi/Bluetooth: internal permanent antenna NFC: loop antenna
Antenna Gain:	WiFi (2.4G): 0.7dBi WiFi (5G): 0.7dBi Bluetooth: 0.7dBi

Ratings: Battery DC 3.8V, 4680mAh
DC 5V, 3.0A; 9V, 2.7A; 12V, 2.0A charging from adapter
(Adapter Input: AC100-240V, 50/60Hz 0.7A)

Adapter: Manufacturer: Dongguan Guangshu Electrical Technology Co., Ltd
Model No.: GS-QC24W

5.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
6dB Bandwidth	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Band Edge	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :1, Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

2, The all test were tested on continue transmission and 100% duty cycle.

6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Equipment Used during Test

7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	LARGE	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2017-04-29	2018-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-09	2018-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2017-04-09	2018-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2017-04-09	2018-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2017-04-09	2018-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-13	2018-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2017-04-13	2018-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2017-04-13	2018-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-09	2018-04-08
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2017-04-13	2018-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2017-04-13	2018-04-12

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-12	2018-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-12	2018-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-12	2018-09-11

7.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

7.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

8.1 E.U.T. Operation

Operating Environment :


Temperature:	21.5 °C
Humidity:	51.9 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode (802.11b mode low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Remark
1	0.2340	18.57	9.98	28.55	62.30	-33.75	QP	
2	0.2340	12.02	9.98	22.00	52.30	-30.30	AVG	
3	0.5620	28.00	10.07	38.07	56.00	-17.93	QP	
4	0.5620	21.41	10.07	31.48	46.00	-14.52	AVG	
5	1.1060	21.77	10.26	32.03	56.00	-23.97	QP	
6	1.1060	14.87	10.26	25.13	46.00	-20.87	AVG	
7	1.5140	20.84	10.15	30.99	56.00	-25.01	QP	
8	1.5140	13.60	10.15	23.75	46.00	-22.25	AVG	
9	4.8100	18.68	10.25	28.93	56.00	-27.07	QP	
10	4.8100	9.79	10.25	20.04	46.00	-25.96	AVG	
11	18.2300	8.64	10.44	19.08	60.00	-40.92	QP	
12	18.2300	2.42	10.44	12.86	50.00	-37.14	AVG	


Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1819	18.31	9.88	28.19	64.39	-36.20	QP	
2	0.1819	11.05	9.88	20.93	54.39	-33.46	AVG	
3	0.3580	17.30	10.06	27.36	58.77	-31.41	QP	
4	0.3580	11.63	10.06	21.69	48.77	-27.08	AVG	
5	0.5580	29.02	10.07	39.09	56.00	-16.91	QP	
6	0.5580	19.39	10.07	29.46	46.00	-16.54	AVG	
7	1.6019	19.82	10.16	29.98	56.00	-26.02	QP	
8	1.6019	13.95	10.16	24.11	46.00	-21.89	AVG	
9	5.6300	16.72	10.26	26.98	60.00	-33.02	QP	
10	5.6300	11.23	10.26	21.49	50.00	-28.51	AVG	
11	10.5980	13.91	10.37	24.28	60.00	-35.72	QP	
12	10.5980	8.86	10.37	19.23	50.00	-30.77	AVG	


Worst Mode: BLE mode (low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1740	14.71	9.87	24.58	64.76	-40.18	QP	
2	0.1740	9.77	9.87	19.64	54.76	-35.12	AVG	
3	0.3500	15.70	10.06	25.76	58.96	-33.20	QP	
4	0.3500	10.91	10.06	20.97	48.96	-27.99	AVG	
5	0.5580	25.32	10.07	35.39	56.00	-20.61	QP	
6	0.5580	21.15	10.07	31.22	46.00	-14.78	AVG	
7	1.1580	17.81	10.35	28.16	56.00	-27.84	QP	
8	1.1580	12.32	10.35	22.67	46.00	-23.33	AVG	
9	1.6260	18.55	10.16	28.71	56.00	-27.29	QP	
10	1.6260	13.23	10.16	23.39	46.00	-22.61	AVG	
11	10.5860	12.98	10.37	23.35	60.00	-36.65	QP	
12	10.5860	8.55	10.37	18.92	50.00	-31.08	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.5660	23.49	10.07	33.56	56.00	-22.44	QP	
2	0.5660	16.27	10.07	26.34	46.00	-19.66	AVG	
3	1.6140	18.75	10.16	28.91	56.00	-27.09	QP	
4	1.6140	13.04	10.16	23.20	46.00	-22.80	AVG	
5	2.1060	17.10	10.21	27.31	56.00	-28.69	QP	
6	2.1060	11.17	10.21	21.38	46.00	-24.62	AVG	
7	4.6860	16.23	10.26	26.49	56.00	-29.51	QP	
8	4.6860	11.18	10.26	21.44	46.00	-24.56	AVG	
9	0.2020	15.29	9.92	25.21	63.52	-38.31	QP	
10	0.2020	10.57	9.92	20.49	53.52	-33.03	AVG	
11	6.4820	12.17	10.27	22.44	60.00	-37.56	QP	
12	6.4820	7.89	10.27	18.16	50.00	-31.84	AVG	

9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:


Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.021	25.30	QP	21.84	40.00	7.14	29.54	-22.40
15.730	24.18	QP	21.35	40.00	5.53	29.54	-24.01
25.680	25.37	QP	20.67	40.00	6.04	29.54	-23.50
802.11g							
6.021	25.16	QP	21.84	40.00	7.00	29.54	-22.54
15.730	24.86	QP	21.35	40.00	6.21	29.54	-23.33
25.680	25.34	QP	20.67	40.00	6.01	29.54	-23.53
802.11n(HT20)							
6.021	25.35	QP	21.84	40.00	7.19	29.54	-22.35
15.730	24.61	QP	21.35	40.00	5.96	29.54	-23.58
25.680	25.19	QP	20.67	40.00	5.86	29.54	-23.68
802.11n(HT40)							
6.032	25.11	QP	21.84	40.00	6.95	29.54	-22.59
8.051	25.23	QP	21.02	40.00	6.25	29.54	-23.29
26.215	24.57	QP	20.55	40.00	5.12	29.54	-24.42


Test Frequency : 30MHz ~ 1GHz Remark: only the worst data (802.11n HT20 Low CH mode) were reported

Low Channel – Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	64.6594	44.36	-17.37	26.99	40.00	-13.01	QP	
2	84.9993	56.19	-20.34	35.85	40.00	-4.15	QP	
3	170.7923	40.07	-15.39	24.68	43.50	-18.82	QP	
4	277.0935	35.93	-14.18	21.75	46.00	-24.25	QP	
5	377.2590	32.69	-11.70	20.99	46.00	-25.01	QP	
6	533.8318	36.61	-8.10	28.51	46.00	-17.49	QP	


Low Channel – Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	37.4164	41.92	-16.81	25.11	40.00	-14.89	QP	
2	83.5220	55.53	-20.38	35.15	40.00	-4.85	QP	
3	138.3873	40.31	-15.41	24.90	43.50	-18.60	QP	
4	167.2366	41.68	-15.18	26.50	43.50	-17.00	QP	
5	263.8190	38.02	-14.37	23.65	46.00	-22.35	QP	
6	530.1013	35.37	-8.12	27.25	46.00	-18.75	QP	


Test Frequency : Above 1GHz Remark: only the worst data (802.11n HT20 Low CH mode) were reported

Low Channel – Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2416.000	118.85	-15.26	103.59				
2	9640.000	37.86	2.78	40.64	74.00	-33.36	peak	

Low Channel – Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2416.000	117.85	-15.26	102.59				
2	8920.000	35.45	1.40	36.85	74.00	-37.15	peak	

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:

Test Frequency: 9KHz~26MHz


Remark: only the worst data (GFSK modulation Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.021	25.03	QP	21.84	40.00	6.87	29.54	-22.67
15.730	25.62	QP	21.35	40.00	6.97	29.54	-22.57
25.680	24.27	QP	20.67	40.00	4.94	29.54	-24.60

Test Frequency : 30MHz ~ 1GHz


only the worst data (high Channel) were reported

High Channel – Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	42.8998	36.15	-16.54	19.61	40.00	-20.39	QP	
2	75.9773	53.73	-19.39	34.34	40.00	-5.66	QP	
3	187.7530	45.86	-16.64	29.22	43.50	-14.28	QP	
4	244.2321	38.11	-14.94	23.17	46.00	-22.83	QP	
5	360.4476	31.88	-12.16	19.72	46.00	-26.28	QP	
6	506.4791	32.47	-8.20	24.27	46.00	-21.73	QP	

High Channel – Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	76.7808	50.07	-19.62	30.45	40.00	-9.55	QP	
2	134.0882	35.17	-15.74	19.43	43.50	-24.07	QP	
3	179.3863	41.34	-15.94	25.40	43.50	-18.10	QP	
4	262.8955	44.20	-14.39	29.81	46.00	-16.19	QP	
5	315.4808	34.27	-13.43	20.84	46.00	-25.16	QP	
6	478.8456	30.12	-8.97	21.15	46.00	-24.85	QP	

Test Frequency : Above 1GHz


only the worst data (low Channel) were reported

low Channel - Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2401.660	101.64	-15.23	86.41				
2	6160.000	38.41	-1.35	37.06	74.00	-36.94	peak	

low Channel - Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.590	100.65	-15.24	85.41				
2	7792.000	34.09	1.40	35.49	74.00	-38.51	peak	

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 DTS Meas Guidance v04
Test Result: PASS
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:

Below 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 30MHz:

For WIFI mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

For BLE mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold

10.2 Test Result


9KHz – 30MHz

802.11b


Low Channel



Middle Channel




High Channel




802.11g


Low Channel



Middle Channel




High Channel




802.11n HT20


Low Channel



Middle Channel




High Channel




802.11n HT40


Low Channel



Middle Channel




High Channel




BLE


Low Channel



Middle Channel



High Channel




Above 30MHz

802.11b


Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



802.11g

Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20

Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT40

Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



BLE
Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



11 Band Edge Measurement



Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 DTS Meas Guidance v04
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

11.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:




TX 11g: Band edge-left side




TX 11g: Band edge-right side




TX 11n HT20: Band edge-left side




TX 11n HT20: Band edge-right side




TX 11n HT40: Band edge-left side




TX 11n HT40: Band edge-right side




BLE: Band edge-left side




BLE: Band edge-right side




TX 11b: Band edge-left side Horizontal



TX 11b: Band edge-left side Vertical




TX 11b: Band edge-right side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2460.618	118.94	-15.35	103.59				
2	2483.500	51.62	-15.39	36.23	74.00	-37.77	peak	

TX 11b: Band edge-right side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2461.314	120.10	-15.35	104.75				
2	2483.500	55.36	-15.39	39.97	74.00	-34.03	peak	

TX 11g: Band edge-left side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2416.384	119.75	-15.26	104.49				
2	2400.000	55.21	-15.24	39.97	74.00	-34.03	peak	

TX 11g: Band edge-left side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2413.944	119.08	-15.25	103.83				
2	2400.000	53.21	-15.24	37.97	74.00	-36.03	peak	


TX 11g: Band edge-right side Horizontal



TX 11g: Band edge-right side Vertical




TX 11n HT20: Band edge-left side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2408.576	119.39	-15.25	104.14				
2	2400.000	66.07	-15.24	50.83	74.00	-23.17	peak	

TX 11n HT20: Band edge-left side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2408.576	118.89	-15.25	103.64				
2	2400.000	55.07	-15.24	39.83	74.00	-34.17	peak	

TX 11n HT20: Band edge-right side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2460.792	118.59	-15.35	103.24				
2	2483.500	54.98	-15.39	39.59	74.00	-34.41	peak	

TX 11n HT20: Band edge-right side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2457.022	116.67	-15.34	101.33				
2	2483.500	55.98	-15.39	40.59	74.00	-33.41	peak	


TX 11n HT40: Band edge-left side Horizontal



TX 11n HT40: Band edge-left side Vertical




TX 11n HT40: Band edge-right side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2448.910	118.60	-15.33	103.27				
2	2483.500	51.99	-15.39	36.60	74.00	-37.40	peak	

TX 11n HT40: Band edge-right side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2464.120	117.68	-15.34	102.34				
2	2483.500	51.99	-15.39	36.60	74.00	-37.40	peak	

BLE: Band edge-left side Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.106	101.38	-15.24	86.14				
2	2400.000	63.39	-15.24	48.15	74.00	-25.85	peak	

BLE: Band edge-left side Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.106	102.88	-15.24	87.64				
2	2400.000	66.39	-15.24	51.15	74.00	-22.85	peak	

BLE: Band edge-right side Horizontal



BLE: Band edge-right side Vertical



12 6 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v04



12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

12.2 Test Result:


Operation mode	Test Channel	Bandwidth (MHz)	Limit (kHz)
TX 11b	Channel 1	10.060	500
	Channel 6	10.060	500
	Channel 11	10.060	500
TX 11g	Channel 1	16.417	500
	Channel 6	16.417	500
	Channel 11	16.417	500
TX 11n HT20	Channel 1	17.645	500
	Channel 6	17.677	500
	Channel 11	17.677	500
TX 11n HT40	Channel 3	36.01	500
	Channel 6	36.01	500
	Channel 9	36.01	500
BLE	Channel 0	0.713	500
	Channel 19	0.707	500
	Channel 39	0.713	500

Test result plot:







Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6





Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




BLE: channel 0



BLE: channel 19





13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v04

13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v04

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq$ DTS bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1$ MHz.
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the $span \geq 1.5 \times$ DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

13.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	17.77	1W/30dBm
	Middle-2437	18.67	1W/30dBm
	High-2462	17.45	1W/30dBm
TX 11g	Low-2412	17.27	1W/30dBm
	Middle-2437	17.85	1W/30dBm
	High-2462	17.42	1W/30dBm
TX 11n HT20	Low-2412	17.48	1W/30dBm
	Middle-2437	18.09	1W/30dBm
	High-2462	17.09	1W/30dBm
TX 11n HT40	Low-2422	17.79	1W/30dBm
	Middle-2437	17.04	1W/30dBm
	High-2452	16.95	1W/30dBm
BLE	Low-2402	-2.45	1W/30dBm
	Middle-2440	-2.76	1W/30dBm
	High-2480	-2.36	1W/30dBm

Test Plot


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19



BLE: channel 39



14 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v04

14.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v04 section 10.2


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

14.2 Test Result:


Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-8.64	8dBm per 3kHz
	Middle-2437	-6.81	8dBm per 3kHz
	High-2462	-6.41	8dBm per 3kHz
TX 11g	Low-2412	-16.36	8dBm per 3kHz
	Middle-2437	-15.85	8dBm per 3kHz
	High-2462	-16.89	8dBm per 3kHz
TX 11n HT20	Low-2412	-16.20	8dBm per 3kHz
	Middle-2437	-16.97	8dBm per 3kHz
	High-2462	-15.87	8dBm per 3kHz
TX 11n HT40	Low-2422	-19.18	8dBm per 3kHz
	Middle-2437	-18.46	8dBm per 3kHz
	High-2452	-20.11	8dBm per 3kHz
BLE	Low-2402	-18.63	8dBm per 3kHz
	Middle-2440	-18.34	8dBm per 3kHz
	High-2480	-17.93	8dBm per 3kHz



Test Plot

Mode: TX 11b channel 1




Mode: TX 11b channel 6







Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19



BLE: channel 39



15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

16 RF Exposure

Remark: refer to SAR test report: WTS17S1194415E.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: WTS17S1194413E_Photo.

=====**End of Report**=====