

TEST REPORT

Reference No..... : WTS18S12133148-2W
FCC ID : XUJROXIE
Applicant..... : Launch Tech Co., Ltd.
Address..... : Launch Industrial Park, North of Wuhe Rd. Banxuegang, Longgang,
Shenzhen, China
Manufacturer : The same as above
Address..... : The same as above
Product..... : Automotive AI Inspection Terminal
Model(s) : ROXIE W
Brand Name..... : LAUNCH
Standards..... : FCC CFR47 Part 15.247:2017
Date of Receipt sample : 2018-12-20
Date of Test : 2018-12-21 to 2019-01-06
Date of Issue..... : 2019-01-07
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District,
Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Ford Wang

Ford Wang / Project Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation, the certification number is 4243.01) of USA, CNAS (China National Accreditation Service for Conformity Assessment, the registration number is L3110) of China. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC (The Federal Communications Commission), CEC (California energy efficiency), ISED (Innovation, Science and Economic Development Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek (ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

Test Facility:**A. Accreditations for Conformity Assessment (International)**

Country/Region	Scope Covered By	Scope	Note
USA	ISO/IEC 17025	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note: 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. 2. ISED CAB identifier: CN0013			

B. TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS	4
4 REVISION HISTORY	6
5 GENERAL INFORMATION.....	7
5.1 GENERAL DESCRIPTION OF E.U.T.	7
5.2 DETAILS OF E.U.T.	7
5.3 CHANNEL LIST.....	8
5.4 TEST MODE	9
6 TEST SUMMARY	10
7 EQUIPMENT USED DURING TEST	11
7.1 EQUIPMENTS LIST	11
7.2 DESCRIPTION OF SUPPORT UNITS	12
7.3 MEASUREMENT UNCERTAINTY	12
7.4 TEST EQUIPMENT CALIBRATION	12
8 CONDUCTED EMISSION	13
8.1 E.U.T. OPERATION	13
8.2 EUT SETUP.....	13
8.3 MEASUREMENT DESCRIPTION	13
8.4 CONDUCTED EMISSION TEST RESULT	14
9 RADIATED EMISSIONS.....	16
9.1 EUT OPERATION.....	16
9.2 TEST SETUP	17
9.3 SPECTRUM ANALYZER SETUP	18
9.4 TEST PROCEDURE	19
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
9.6 SUMMARY OF TEST RESULTS	20
10 CONDUCTED SPURIOUS EMISSIONS.....	33
10.1 TEST PROCEDURE.....	33
10.2 TEST RESULT	34
11 BAND EDGE MEASUREMENT	46
11.1 TEST PROCEDURE	46
11.2 TEST RESULT	47
12 6 DB BANDWIDTH MEASUREMENT	51
12.1 TEST PROCEDURE:.....	51
12.2 TEST RESULT:	51
13 MAXIMUM PEAK OUTPUT POWER	58
13.1 TEST PROCEDURE:.....	58
13.2 TEST RESULT:	59
14 DUTY CYCLE.....	66
15 POWER SPECTRAL DENSITY	67
15.1 TEST PROCEDURE:.....	67
15.2 TEST RESULT:	67
16 ANTENNA REQUIREMENT	74
17 RF EXPOSURE.....	75

18 PHOTOGRAPHS OF TEST SETUP AND EUT..... 76

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S12133 148-2W	2018-12-20	2018-12-21 to 2019-01-06	2019-01-07	original	-	Valid

5 General Information

5.1 General Description of E.U.T.

Product:	Automotive AI Inspection Terminal
Model(s):	ROXIE W
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Hardware Version:	B622-MB-V1.0-181112
Software Version:	V60501_007
Highest frequency (Exclude Radio):	1.25GHz
Storage Location:	Internal Storage
Note:	N/A

5.2 Details of E.U.T.

Operation Frequency:	802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz
Max. RF output power:	WiFi(2.4G): 20.41dBm
Type of Modulation:	WiFi: CCK, OFDM
Antenna installation:	WiFi: internal permanent antenna
Antenna Gain:	WiFi(2.4G): 2.92dBi
Ratings:	Battery DC 3.7V 6100mAh Car Battery DC 12V 1.2A DC 5V, 2A, charging from adapter (Adapter Input: 100-240V~50/60Hz, 0.35A)
Adapter :	Manufacturer: Shenzhen TEKA Technology Co., Ltd. Model No.: TEKA012-1201000EU (sale without adapter)

5.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Equipment Used during Test

7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2018-09-12	2019-09-11
2.	LISN	R&S	ENV216	101215	2018-09-12	2019-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2018-09-12	2019-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2018-09-12	2019-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2018-09-12	2019-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2018-09-12	2019-09-11
4.	Cable	LARGE	RF300	-	2018-09-12	2019-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2018-04-29	2019-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2018-04-09	2019-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2018-04-09	2019-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2018-09-12	2019-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2018-04-09	2019-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2018-04-09	2019-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018-04-13	2019-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2018-04-13	2019-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2018-04-13	2019-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2018-04-09	2019-04-08
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2018-04-13	2019-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2018-04-13	2019-04-12

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2018-09-12	2019-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2018-09-12	2019-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2018-09-12	2019-09-11

7.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

7.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207
 Test Method: ANSI C63.10:2013
 Test Result: PASS
 Frequency Range: 150kHz to 30MHz
 Class/Severity: Class B
 Limit:

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	5	46
5 to 30	60	50

8.1 E.U.T. Operation

Operating Environment :


Temperature: 21.5 °C
 Humidity: 51.9 % RH
 Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode (802.11b mode low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.4180	19.00	10.27	29.27	57.49	-28.22	QP	
2	0.4180	13.97	10.27	24.24	47.49	-23.25	AVG	
3	0.5140	15.88	10.26	26.14	56.00	-29.86	QP	
4	0.5140	9.49	10.26	19.75	46.00	-26.25	AVG	
5	0.6380	17.51	10.32	27.83	56.00	-28.17	QP	
6	0.6380	10.31	10.32	20.63	46.00	-25.37	AVG	
7	0.7860	19.25	10.36	29.61	56.00	-26.39	QP	
8	0.7860	11.59	10.36	21.95	46.00	-24.05	AVG	
9	1.0620	20.54	10.40	30.94	56.00	-25.06	QP	
10	1.0620	13.95	10.40	24.35	46.00	-21.65	AVG	
11	1.6460	19.11	10.44	29.55	56.00	-26.45	QP	
12	1.6460	12.79	10.44	23.23	46.00	-22.77	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.5940	16.81	10.30	27.11	56.00	-28.89	QP	
2	0.5940	9.69	10.30	19.99	46.00	-26.01	AVG	
3	0.9180	15.01	10.38	25.39	56.00	-30.61	QP	
4	0.9180	8.87	10.38	19.25	46.00	-26.75	AVG	
5	1.1380	15.49	10.40	25.89	56.00	-30.11	QP	
6	1.1380	9.67	10.40	20.07	46.00	-25.93	AVG	
7	1.4660	17.78	10.43	28.21	56.00	-27.79	QP	
8	1.4660	11.89	10.43	22.32	46.00	-23.68	AVG	
9	1.6140	18.34	10.44	28.78	56.00	-27.22	QP	
10	1.6140	12.26	10.44	22.70	46.00	-23.30	AVG	
11	2.3940	15.67	10.48	26.15	56.00	-29.85	QP	
12	2.3940	7.33	10.48	17.81	46.00	-28.19	AVG	

9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018; ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

- Sweep Speed Auto
- IF Bandwidth..... 10kHz
- Video Bandwidth..... 10kHz
- Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

- Sweep Speed Auto
- Detector PK
- Resolution Bandwidth..... 100kHz
- Video Bandwidth..... 300kHz

Above 1GHz

- Sweep Speed Auto
- Detector PK
- Resolution Bandwidth..... 1MHz
- Video Bandwidth..... 3MHz
- Detector Ave.
- Resolution Bandwidth..... 1MHz
- Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high -pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.020	25.55	QP	21.84	40.00	7.39	29.54	-22.15
15.730	25.39	QP	21.35	40.00	6.74	29.54	-22.80
25.680	24.57	QP	20.67	40.00	5.24	29.54	-24.30
802.11g							
6.020	25.22	QP	21.84	40.00	7.06	29.54	-22.48
15.730	25.16	QP	21.35	40.00	6.51	29.54	-23.03
25.680	25.51	QP	20.67	40.00	6.18	29.54	-23.36
802.11n(HT20)							
6.020	25.01	QP	21.84	40.00	6.85	29.54	-22.69
15.730	25.34	QP	21.35	40.00	6.69	29.54	-22.85
25.680	25.46	QP	20.67	40.00	6.13	29.54	-23.41
802.11n(HT40)							
6.020	25.80	QP	21.84	40.00	7.64	29.54	-21.90
15.730	25.49	QP	21.35	40.00	6.84	29.54	-22.70
25.680	25.32	QP	20.67	40.00	5.99	29.54	-23.55

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Low Channel 2412MHz									
223.45	40.45	QP	331	1.7	H	-11.62	28.83	46.00	-17.17
223.45	35.68	QP	342	1.7	V	-11.62	24.06	46.00	-21.94
4824.00	49.04	PK	239	1.9	V	-1.06	47.98	74.00	-26.02
4824.00	45.66	Ave	239	1.9	V	-1.06	44.60	54.00	-9.40
7236.00	42.27	PK	28	1.6	H	1.33	43.60	74.00	-30.40
7236.00	41.47	Ave	28	1.6	H	1.33	42.80	54.00	-11.20
2313.55	46.35	PK	292	1.6	V	-13.19	33.16	74.00	-40.84
2313.55	37.95	Ave	292	1.6	V	-13.19	24.76	54.00	-29.24
2377.93	44.71	PK	214	1.6	H	-13.14	31.57	74.00	-42.43
2377.93	38.29	Ave	214	1.6	H	-13.14	25.15	54.00	-28.85
2486.34	42.81	PK	338	1.8	V	-13.08	29.73	74.00	-44.27
2486.34	38.63	Ave	338	1.8	V	-13.08	25.55	54.00	-28.45

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	40.02	QP	108	1.4	H	-11.62	28.40	46.00	-17.60
223.45	36.32	QP	139	1.7	V	-11.62	24.70	46.00	-21.30
4874.00	48.70	PK	108	1.9	V	-0.62	48.08	74.00	-25.92
4874.00	46.47	Ave	108	1.9	V	-0.62	45.85	54.00	-8.15
7311.00	41.59	PK	208	1.1	H	2.21	43.80	74.00	-30.20
7311.00	42.21	Ave	208	1.1	H	2.21	44.42	54.00	-9.58
2326.56	45.44	PK	160	1.9	V	-13.19	32.25	74.00	-41.75
2326.56	38.18	Ave	160	1.9	V	-13.19	24.99	54.00	-29.01
2371.06	43.72	PK	274	1.9	H	-13.14	30.58	74.00	-43.42
2371.06	36.49	Ave	274	1.9	H	-13.14	23.35	54.00	-30.65
2496.64	43.99	PK	237	1.2	V	-13.08	30.91	74.00	-43.09
2496.64	37.94	Ave	237	1.2	V	-13.08	24.86	54.00	-29.14

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: High Channel 2462MHz									
223.45	39.97	QP	264	1.9	H	-11.62	28.35	46.00	-17.65
223.45	36.74	QP	278	1.9	V	-11.62	25.12	46.00	-20.88
4924.00	47.92	PK	194	1.5	V	-0.24	47.68	74.00	-26.32
4924.00	45.50	Ave	194	1.5	V	-0.24	45.26	54.00	-8.74
7386.00	41.18	PK	141	1.9	H	2.84	44.02	74.00	-29.98
7386.00	42.31	Ave	141	1.9	H	2.84	45.15	54.00	-8.85
2342.06	46.07	PK	277	1.4	V	-13.19	32.88	74.00	-41.12
2342.06	37.12	Ave	277	1.4	V	-13.19	23.93	54.00	-30.07
2370.32	44.23	PK	262	1.1	H	-13.14	31.09	74.00	-42.91
2370.32	38.53	Ave	262	1.1	H	-13.14	25.39	54.00	-28.61
2499.64	42.60	PK	155	1.7	V	-13.08	29.52	74.00	-44.48
2499.64	37.28	Ave	155	1.7	V	-13.08	24.20	54.00	-29.80

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Low Channel 2412MHz									
223.45	41.32	QP	200	1.6	H	-11.62	29.70	46.00	-16.30
223.45	37.94	QP	233	1.2	V	-11.62	26.32	46.00	-19.68
4824.00	49.27	PK	245	1.6	V	-1.06	48.21	74.00	-25.79
4824.00	45.98	Ave	245	1.6	V	-1.06	44.92	54.00	-9.08
7236.00	40.32	PK	93	1.8	H	1.33	41.65	74.00	-32.35
7236.00	41.37	Ave	93	1.8	H	1.33	42.70	54.00	-11.30
2332.19	45.95	PK	312	1.8	V	-13.19	32.76	74.00	-41.24
2332.19	37.12	Ave	312	1.8	V	-13.19	23.93	54.00	-30.07
2385.49	44.15	PK	28	1.3	H	-13.14	31.01	74.00	-42.99
2385.49	37.97	Ave	28	1.3	H	-13.14	24.83	54.00	-29.17
2487.43	44.03	PK	0	1.5	V	-13.08	30.95	74.00	-43.05
2487.43	37.23	Ave	0	1.5	V	-13.08	24.15	54.00	-29.85

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: Middle Channel 2437MHz									
223.45	41.77	QP	357	1.8	H	-11.62	30.15	46.00	-15.85
223.45	38.86	QP	261	1.2	V	-11.62	27.24	46.00	-18.76
4874.00	49.92	PK	108	1.7	V	-0.62	49.30	74.00	-24.70
4874.00	46.35	Ave	108	1.7	V	-0.62	45.73	54.00	-8.27
7311.00	39.75	PK	224	1.8	H	2.21	41.96	74.00	-32.04
7311.00	40.80	Ave	224	1.8	H	2.21	43.01	54.00	-10.99
2324.19	45.13	PK	116	1.4	V	-13.19	31.94	74.00	-42.06
2324.19	39.30	Ave	116	1.4	V	-13.19	26.11	54.00	-27.89
2365.33	42.28	PK	55	1.3	H	-13.14	29.14	74.00	-44.86
2365.33	36.97	Ave	55	1.3	H	-13.14	23.83	54.00	-30.17
2497.14	44.12	PK	305	1.4	V	-13.08	31.04	74.00	-42.96
2497.14	36.68	Ave	305	1.4	V	-13.08	23.60	54.00	-30.40

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11g: High Channel 2462MHz									
223.45	40.73	QP	266	1.6	H	-11.62	29.11	46.00	-16.89
223.45	40.27	QP	309	1.4	V	-11.62	28.65	46.00	-17.35
4924.00	50.89	PK	89	1.2	V	-0.24	50.65	74.00	-23.35
4924.00	44.90	Ave	89	1.2	V	-0.24	44.66	54.00	-9.34
7386.00	38.53	PK	92	1.7	H	2.84	41.37	74.00	-32.63
7386.00	40.39	Ave	92	1.7	H	2.84	43.23	54.00	-10.77
2334.80	45.26	PK	213	1.8	V	-13.19	32.07	74.00	-41.93
2334.80	37.62	Ave	213	1.8	V	-13.19	24.43	54.00	-29.57
2370.44	44.47	PK	299	1.8	H	-13.14	31.33	74.00	-42.67
2370.44	37.98	Ave	299	1.8	H	-13.14	24.84	54.00	-29.16
2495.31	44.87	PK	197	1.7	V	-13.08	31.79	74.00	-42.21
2495.31	37.20	Ave	197	1.7	V	-13.08	24.12	54.00	-29.88

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: Low Channel 2412MHz									
223.45	39.76	QP	131	1.5	H	-11.62	28.14	46.00	-17.86
223.45	39.04	QP	329	1.6	V	-11.62	27.42	46.00	-18.58
4824.00	50.18	PK	290	1.3	V	-1.06	49.12	74.00	-24.88
4824.00	44.67	Ave	290	1.3	V	-1.06	43.61	54.00	-10.39
7236.00	37.87	PK	272	1.8	H	1.33	39.20	74.00	-34.80
7236.00	38.94	Ave	272	1.8	H	1.33	40.27	54.00	-13.73
2318.60	46.70	PK	320	1.1	V	-13.19	33.51	74.00	-40.49
2318.60	38.49	Ave	320	1.1	V	-13.19	25.30	54.00	-28.70
2370.52	42.76	PK	42	2.0	H	-13.14	29.62	74.00	-44.38
2370.52	38.49	Ave	42	2.0	H	-13.14	25.35	54.00	-28.65
2497.85	44.95	PK	216	1.2	V	-13.08	31.87	74.00	-42.13
2497.85	36.84	Ave	216	1.2	V	-13.08	23.76	54.00	-30.24

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: Middle Channel 2437MHz									
223.45	40.79	QP	152	1.3	H	-11.62	29.17	46.00	-16.83
223.45	40.27	QP	48	1.5	V	-11.62	28.65	46.00	-17.35
4874.00	49.21	PK	65	2.0	V	-0.62	48.59	74.00	-25.41
4874.00	43.58	Ave	65	2.0	V	-0.62	42.96	54.00	-11.04
7311.00	37.01	PK	104	1.2	H	2.21	39.22	74.00	-34.78
7311.00	39.27	Ave	104	1.2	H	2.21	41.48	54.00	-12.52
2318.86	45.22	PK	356	1.6	V	-13.19	32.03	74.00	-41.97
2318.86	37.18	Ave	356	1.6	V	-13.19	23.99	54.00	-30.01
2385.79	44.85	PK	297	1.4	H	-13.14	31.71	74.00	-42.29
2385.79	37.81	Ave	297	1.4	H	-13.14	24.67	54.00	-29.33
2495.27	43.71	PK	87	1.2	V	-13.08	30.63	74.00	-43.37
2495.27	38.69	Ave	87	1.2	V	-13.08	25.61	54.00	-28.39

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: High Channel 2462MHz									
223.45	40.45	QP	6	1.8	H	-11.62	28.83	46.00	-17.17
223.45	40.72	QP	243	1.8	V	-11.62	29.10	46.00	-16.90
4924.00	48.51	PK	163	1.3	V	-0.24	48.27	74.00	-25.73
4924.00	42.68	Ave	163	1.3	V	-0.24	42.44	54.00	-11.56
7386.00	36.37	PK	162	1.2	H	2.84	39.21	74.00	-34.79
7386.00	39.84	Ave	162	1.2	H	2.84	42.68	54.00	-11.32
2330.93	46.92	PK	163	1.4	V	-13.19	33.73	74.00	-40.27
2330.93	38.83	Ave	163	1.4	V	-13.19	25.64	54.00	-28.36
2369.45	42.53	PK	57	1.0	H	-13.14	29.39	74.00	-44.61
2369.45	37.93	Ave	57	1.0	H	-13.14	24.79	54.00	-29.21
2489.59	45.00	PK	267	1.2	V	-13.08	31.92	74.00	-42.08
2489.59	37.55	Ave	267	1.2	V	-13.08	24.47	54.00	-29.53

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n40: Low Channel 2422MHz									
223.45	41.04	QP	14	1.3	H	-11.62	29.42	46.00	-16.58
223.45	41.73	QP	320	1.9	V	-11.62	30.11	46.00	-15.89
4844.00	47.01	PK	319	1.2	V	-1.06	45.95	74.00	-28.05
4844.00	41.07	Ave	319	1.2	V	-1.06	40.01	54.00	-13.99
7266.00	34.73	PK	77	1.5	H	1.33	36.06	74.00	-37.94
7266.00	38.05	Ave	77	1.5	H	1.33	39.38	54.00	-14.62
2348.79	45.42	PK	133	1.2	V	-13.19	32.23	74.00	-41.77
2348.79	37.71	Ave	133	1.2	V	-13.19	24.52	54.00	-29.48
2381.65	42.12	PK	285	1.2	H	-13.14	28.98	74.00	-45.02
2381.65	38.69	Ave	285	1.2	H	-13.14	25.55	54.00	-28.45
2495.50	43.42	PK	225	1.4	V	-13.08	30.34	74.00	-43.66
2495.50	36.11	Ave	225	1.4	V	-13.08	23.03	54.00	-30.97

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n40: Middle Channel 2437MHz									
223.45	40.95	QP	349	1.9	H	-11.62	29.33	46.00	-16.67
223.45	40.81	QP	137	1.9	V	-11.62	29.19	46.00	-16.81
4874.00	47.44	PK	260	1.7	V	-0.62	46.82	74.00	-27.18
4874.00	40.78	Ave	260	1.7	V	-0.62	40.16	54.00	-13.84
7311.00	35.68	PK	24	1.3	H	2.21	37.89	74.00	-36.11
7311.00	38.11	Ave	24	1.3	H	2.21	40.32	54.00	-13.68
2321.65	46.68	PK	202	1.8	V	-13.19	33.49	74.00	-40.51
2321.65	37.07	Ave	202	1.8	V	-13.19	23.88	54.00	-30.12
2372.00	42.15	PK	314	1.9	H	-13.14	29.01	74.00	-44.99
2372.00	36.30	Ave	314	1.9	H	-13.14	23.16	54.00	-30.84
2491.10	42.36	PK	51	1.9	V	-13.08	29.28	74.00	-44.72
2491.10	36.65	Ave	51	1.9	V	-13.08	23.57	54.00	-30.43

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n40: High Channel 2452MHz									
223.45	41.11	QP	16	1.6	H	-11.62	29.49	46.00	-16.51
223.45	41.46	QP	109	1.0	V	-11.62	29.84	46.00	-16.16
4904.00	46.90	PK	234	1.7	V	-0.24	46.66	74.00	-27.34
4904.00	40.06	Ave	234	1.7	V	-0.24	39.82	54.00	-14.18
7356.00	36.02	PK	275	1.3	H	2.84	38.86	74.00	-35.14
7356.00	37.43	Ave	275	1.3	H	2.84	40.27	54.00	-13.73
2336.41	45.69	PK	94	1.8	V	-13.19	32.50	74.00	-41.50
2336.41	38.30	Ave	94	1.8	V	-13.19	25.11	54.00	-28.89
2361.43	44.21	PK	327	1.3	H	-13.14	31.07	74.00	-42.93
2361.43	38.36	Ave	327	1.3	H	-13.14	25.22	54.00	-28.78
2494.07	43.93	PK	189	1.1	V	-13.08	30.85	74.00	-43.15
2494.07	36.77	Ave	189	1.1	V	-13.08	23.69	54.00	-30.31

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018; ANSI C63.10:2013
Test Result:	PASS
Limit:	

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to ≈ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW $\approx [3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

10.2 Test Result


9KHz – 30MHz

802.11b


Low Channel



Middle Channel




High Channel




802.11g


Low Channel



Middle Channel




High Channel




802.11n HT20


Low Channel



Middle Channel




High Channel




802.11n HT40


Low Channel



Middle Channel



High Channel




Above 30MHz

802.11b


Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



802.11g


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20

Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



802.11n HT40

Low Channel

Fundamental



Middle Channel

Fundamental



High Channel

Fundamental



11 Band Edge Measurement



Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018; ANSI C63.10:2013
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

11.1 Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:




TX 11g: Band edge-left side




TX 11g: Band edge-right side




TX 11n HT20: Band edge-left side




TX 11n HT20: Band edge-right side



TX 11n HT40: Band edge-left side



TX 11n HT40: Band edge-right side



12 6 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018;

ANSI C63.10:2013



12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

12.2 Test Result:


Operation mode	Test Channel	Bandwidth (MHz)
TX 11b	Channel 1	10.060
	Channel 6	10.060
	Channel 11	10.060
TX 11g	Channel 1	15.830
	Channel 6	15.473
	Channel 11	15.665
TX 11n HT20	Channel 1	16.365
	Channel 6	16.118
	Channel 11	16.118
TX 11n HT40	Channel 3	35.350
	Channel 6	35.440
	Channel 9	35.320

Test result plot:








Mode: TX 11g channel 6




Mode: TX 11g channel 11







Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018;

ANSI C63.10:2013

13.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq DTS$ bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set span $\geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1$ MHz.
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the span $\geq 1.5 \times DTS$ bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

13.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	20.41	1W/30dBm
	Middle-2437	19.50	1W/30dBm
	High-2462	19.26	1W/30dBm
TX 11g	Low-2412	20.35	1W/30dBm
	Middle-2437	20.10	1W/30dBm
	High-2462	19.76	1W/30dBm
TX 11n HT20	Low-2412	18.66	1W/30dBm
	Middle-2437	19.74	1W/30dBm
	High-2462	19.67	1W/30dBm
TX 11n HT40	Low-2422	15.55	1W/30dBm
	Middle-2437	15.30	1W/30dBm
	High-2452	15.03	1W/30dBm



Test Plot

Mode: TX 11b channel 1




Mode: TX 11b channel 6







Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



14 Duty cycle

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10: 2013
Test Limit:	N/A
Test Result:	PASS
Remark:	EUT transmitting continuously

15 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018;
ANSI C63.10:2013

15.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05 August 24, 2018 section 10.2


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

15.2 Test Result:


Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-4.30	8dBm per 3kHz
	Middle-2437	-0.63	8dBm per 3kHz
	High-2462	-5.41	8dBm per 3kHz
TX 11g	Low-2412	-8.43	8dBm per 3kHz
	Middle-2437	-9.32	8dBm per 3kHz
	High-2462	-8.56	8dBm per 3kHz
TX 11n HT20	Low-2412	-9.87	8dBm per 3kHz
	Middle-2437	-7.67	8dBm per 3kHz
	High-2462	-9.94	8dBm per 3kHz
TX 11n HT40	Low-2422	-15.08	8dBm per 3kHz
	Middle-2437	-14.45	8dBm per 3kHz
	High-2452	-15.63	8dBm per 3kHz



Test Plot

Mode: TX 11b channel 1




Mode: TX 11b channel 6







Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



16 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

17 RF Exposure

Remark: Please refer to SAR test report: WTS18S12133148-1W.

18 Photographs of test setup and EUT.

Note: Please refer to appendix: WTS18S12133148W_Photo.

=====**End of Report**=====