



TEST REPORT

APPLICANT : Y Soft Corporation, a.s.
PRODUCT NAME : Ultralight Print Multireader MF+
MODEL NAME : ML02065
BRAND NAME : YSoft SafeQ
FCC ID : XUY0YX0ML02065
STANDARD(S) : FCC 47CFR Part 2(2.1091)
RECEIPT DATE : 2021-03-16
TEST DATE : 2021-05-21
ISSUE DATE : 2021-07-14

Edited by: Liang Yumei
Liang Yumei (Rapporteur)
Approved by: Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
 - 1.1. Applicant and Manufacturer Information..... 3
 - 1.2. Equipment under Test (EUT) Description..... 3
 - 1.3. Photographs of the EUT..... 4
 - 1.4. Applied Reference Documents 4
- 2. RF Exposure Limits..... 5
- 3. MPE Requirement 6
 - 3.1. General Information..... 6
 - 3.2. Test Information 6
 - 3.3. Test Setup 6
- 4. Assess Results 7
 - 4.1. Test Equipment List..... 7
 - 4.2. Test Results 7
- 5. Measurement Uncertainty 9
- Annex A General Information..... 10

Change History		
Version	Date	Reason for change
1.0	2021-07-14	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Y Soft Corporation, a.s.
Applicant Address:	Technicka 2948/13, Brno, 61600, Czech Republic
Manufacturer:	Y Soft Corporation, a.s.
Manufacturer Address:	Technicka 2948/13, Brno, 61600, Czech Republic

1.2. Equipment under Test (EUT) Description

Product Name:	Ultralight Print Multireader MF+
Product Serial No.:	(N/A, marked #1 by test site)
Hardware Version:	1.5.1
Software Version:	1.3.0
Frequency Bands:	125KHz NFC:13.56MHz
Modulation Mode:	125KHz: AM NFC: AM
Antenna Type:	Coil Antenna

Note:

When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.



1.3. Photographs of the EUT

Please refer to the External Photos for the Photos of the EUT

1.4. Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method determination /Remark
FCC 47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Evaluation: mobile devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation

Note 1: The test item is not applicable.
Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



2. RF Exposure Limits

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices: 47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength(A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.1–1.34	614	1.63	*(100)	30
1.34-30	824/f _M	2.19/f _M	*(180/f _M ²)	30
30-300	27.5	0.073	0.2	30

Note:

f_M = frequency in MHz* = Plane-wave equivalent power density

3. MPE Requirement


3.1. General Information

For devices designed for typical desktop applications, RF exposure evaluation should be conducted assuming a user separation distance of 0 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from Surface of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device.

3.2. Test Information

The EUT working at normal charging mode, use the E-Probe measure the H-field Strength, E-field Strength separately.

3.3. Test Setup



4. Assess Results

4.1. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
STT	Broadband Field meter	SEM-600	D-1044	2018.05.29	2021.05.28
STT	Probe	LF-04	I-1044	2018.05.29	2021.05.28
STT	Probe holder	TR-01	N/A	N/A	N/A
STT	Optical fiber line	L=5M	N/A	N/A	N/A

4.2. Test Results

EUT:	Test Date: 2021.05.21
Temperature: 18~25 °C	Humidity: 20~60%

E-field Strength Result (Test frequency 125KHz)					
Test Loading	Exposure Position	Distance (cm)	E-Field Strength (Max. V/m)	Limit (V/m)	Verdict
125Kbps	Front Side	15	1.59	614	PASS
	Back Side	15	0.12	614	PASS
	Left Side	15	0.13	614	PASS
	Right Side	15	0.14	614	PASS
	Top Surface	15	0.92	614	PASS



H-field Strength Result (Test frequency 125KHz)					
Test Loading	Exposure Position	Distance (cm)	H-Field Strength (Max. A/m)	Limit (A/m)	Verdict
125Kbps	Front Side	15	0.1348	1.63	PASS
	Back Side	15	0.0066	1.63	PASS
	Left Side	15	0.0065	1.63	PASS
	Right Side	15	0.007	1.63	PASS
	Top Surface	15	0.0439	1.63	PASS

Note:

1. According to the user manual, output power from each primary coil is less than or equal to 15 watts.
2. This device designed for typical desktop applications, therefore mobile exposure conditions are applied and client device is placed directly in contact with the transmitter.
3. The maximum radiated emission of NFC mode at 3m is 63.19dB μ V/m recorded in SZ21030228W02, which is adjusted to power density is closed to 0mW/cm².
4. This device contains transmitters that may operate simultaneously

No.	Applicable Combination	Yes or No
1	125KHz+NFC	Yes

5. therefore simultaneous transmission analysis is required and should be compliance the following requirement:

$$\sum_{i=1} \frac{\text{E-Field}}{\text{limit } i} + \frac{\text{PD}}{\text{Limit } 2} \leq 1 \quad \text{and} \quad \sum_{i=1} \frac{\text{H-Field}}{\text{limit } i} + \frac{\text{PD}}{\text{Limit } 2} \leq 1$$

Applicable Combination	Strength		Power Density		Result
	E-Field	Limit ₁	NFC	Limit ₂	
125KHz+NFC	1.59	614	0	1	0.003

Transmission Condition	Strength		Power Density		Result
	H-Field	Limit ₁	Bluetooth	Limit ₂	
125KHz+NFC	0.1348	1.63	0	1	0.083



5. Measurement Uncertainty

Test Item	Uncertainty
Uncertainty for Radiated Frequency	7×10^8
Uncertainty for test site temperature and humidity	0.6 °C
	3%

Note:

95% confidence levels, k=2



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

Note:

The main report is end here and the other Annex (B) will be submitted separately.

***** END OF MAIN REPORT *****