

FCC PART 15 SUBPART C / IC RSS-210 TEST REPORT

for

TPMS

Model No.: RB1-012

FCC ID: XVBM2F02

IC: 9368A-M2F02

of

Applicant: Standard Motor Products, Inc.

Address: 37-18 Northern Boulevard, Long Island City, New York 11101,
United States

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477, TW0020, TW1072


Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC-5107A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21810-18505-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com




Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.2.1	<i>Location</i>	3
1.2.2	<i>Details of accreditation status</i>	3
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS	3
1.5	TEST ITEM	4
1.6	TEST STANDARDS	4
2	TECHNICAL TEST	5
2.1	SUMMARY OF TEST RESULTS	5
2.2	TEST ENVIRONMENT	5
2.3	TEST EQUIPMENT UTILIZED	6
2.4	GENERAL TEST PROCEDURE	9
3	TEST RESULTS (ENCLOSURE)	10
3.1	TRANSMISSION REQUIREMENTS	11
3.1.1	<i>Limit of Transmission Time</i>	11
3.1.2	<i>Results for the duration and silent period measurement</i>	11
3.2	OUTPUT POWER (FIELD STRENGTH)	12
3.3	OUT OF BAND RADIATED EMISSIONS	16
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	17
3.5	SPURIOUS EMISSION RADIATED, TRANSMITTER	18
3.6	CHANNEL BANDWIDTH	39
3.7	ANTENNA REQUIREMENT	40
3.8	DUTY CYCLE	41
3.9	CONDUCTED MEASUREMENT AT (AC) POWER LINE	42
3.10	EQUIPMENT MODIFICATION	43

Appendix: Diagrams and Photos



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.


Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.


The test report may only be reproduced or published in full.


Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services (Taiwan) Co., Ltd.

Tester:

March 18, 2019	Spencer Yang	
_____	_____	_____
Date	WTS-Lab.	Name
		Signature

Technical responsibility for area of testing:

March 18, 2019	Kevin Wang	
_____	_____	_____
Date	WTS	Name
		Signature



Registration number: W6M21810-18505-C-1

FCC ID: XVBM2F02

IC: 9368A-M2F02

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,
Wanli Dist., New Taipei City 207,
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1


1.3 Details of approval holder

Name:	Standard Motor Products, Inc.
Street:	37-18 Northern Boulevard,
Town:	Long Island City, New York 11101,
Country:	United States
Telephone:	./.
Fax:	./.

1.4 Application details

Date of receipt of test item: January 14, 2019

Date of test: from January 14, 2019 to March 14, 2019



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

1.5 Test item

Description of test item: TPMS
Type identification: RB1-012
Brand name: SMP
FCC Multi-listing model number: RB1-004, RB1-005, RB1-006, RB1-007, RB1-008, RB1-013, RB1-014, RB1-018, RB1-023, RB1-024, RB1-026, RB1-027, RB1-030
IC Multi-listing model number: RB1-013, RB1-014, RB1-018
Transmitting frequency: 433.92 MHz
Operation mode: Simplex
Voltage supply: Battery 3 Vd.c. (CR2450HR)

(The device is tested under fresh battery condition.)

Antenna type: Incorporated Antenna

Photos: see Appendix


1.6 Manufacturer (if applicable)

Name: Orange Electronic Co., Ltd
Street: 5F., No.29, Keya Rd., Daya Dist.,
Town: Taichung City 428,
Country: Taiwan

Additional information: ./.

1.7 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.231 (e) (2017-10)
CANADA RSS-210 Issue 9 (2016-08)
CANADA RSS-Gen Issue 5 (2018-04)



Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

2.2 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Details of power supply: Battery 3 Vd.c. (CR2450HR)

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission	Expanded Uncertainty : AMN : 1.30 dB Voltage probe : 1.36 dB
Estimation Result of Uncertainty of Radiated Emission(3M)	Expanded Uncertainty : 0.009-30 MHz : 2.02 dB 30-1000 MHz : 3.49 dB 1-18 GHz : 3.01 dB 18-40 GHz : 2.43 dB
Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Frequency Drift Measurement Frequency stability	Expanded Uncertainty : 6.11 Hz
Estimation Result of Uncertainty of Band Edge Measurement	Expanded Uncertainty : 0.98 dBc


The decision rule is : Measurement uncertainty is not taken into account.



Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

2.3 Test equipment utilized


No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2018/5/30	2019/5/29
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2018/11/1	2019/10/31
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2018/8/21	2019/8/20
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2018/7/13	2019/7/12
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2018/9/25	2019/9/24
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2018/7/16	2019/7/15
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2018/5/30	2019/5/29
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2018/5/21	2019/5/20
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2018/7/13	2019/7/12
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2018/7/12	2019/7/11
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2019/3/15	2020/3/14
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2019/1/29	2020/1/28
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2018/4/13	2019/4/12
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2018/4/26	2019/4/25
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2019/2/26	2020/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2019/3/5	2020/3/4
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2019/2/26	2020/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2019/3/15	2020/3/14
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2018/9/17	2019/9/16
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2018/9/18	2019/9/17
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2018/4/16	2019/4/15
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2019/2/13	2020/2/12
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02


ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2019/1/15	2020/1/14
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2018/5/29	2019/5/28
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2019/2/26	2020/2/28
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2019/3/15	2020/3/14
ETSTW-RE 147	Bi-log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2019/3/15	2020/3/14
ETSTW-RE 151	Thermohyrometer	608-h1	45104376	TESTO	2018/8/17	2019/8/16
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2018/5/10	2019/5/9
ETSTW-EMS 008	Exposure Level Tester	ELT-400	G-0009	Narda	2018/7/17	2019/7/16
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2019/3/5	2020/3/4
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2019/2/26	2020/2/28
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2018/10/19	2019/10/18
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2019/1/14	2020/1/13
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2019/1/14	2020/1/13
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2019/1/14	2020/1/13
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2019/1/14	2020/1/13
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2018/9/12	2019/9/11
ETSTW-GSM 024	Radio Communication Analyzer	MT8821C	None	Anritsu	2019/3/5	2020/3/4
ETSTW-GSM 025	Band Reject Filter	BRM19835	001	Micro-Tronics	2018/8/9	2019/8/8
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2019/2/21	2020/2/20
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2018/7/2	2019/7/1
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2019/2/26	2020/2/28
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2018/5/14	2019/5/13
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S Cable 9)	279067	HUBER+SUHNER	2019/2/26	2020/2/28
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S Cable 10)	238092	HUBER+SUHNER	2019/3/15	2020/3/14



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2019/3/15	2020/3/14
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2019/3/15	2020/3/14
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2018/6/9	2019/6/8
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2019/3/15	2020/3/14
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2019/3/15	2020/3/14
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM- NM-25000	170239	EMCI	2018/6/9	2019/6/8
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.10-2013 6.3 using a spectrum analyzer. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was the 100 kHz and the video bandwidth was 300 kHz.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.


Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
33 20 dB μ V + 10.36 dB/m + 6 dB = 36.36 dB μ V/m @3m

ANSI STANDARD C63.10-2013 6.2.2 MEASUREMENT PROCEDURES: The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table). The EUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10th harmonic of the fundamental.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

ANSI STANDARD C63.10-2009 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21810-18505-C-1

FCC ID: XVBM2F02

IC: 9368A-M2F02

3 Test results (enclosure)


1st test

test after modification

production test

TEST CASE	Para. Number	Required	Test passed	Test failed
Transmission Requirements	FCC 15.231(e) IC RSS-210 Annex 1 A1.1.1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission	FCC 15.231(e) IC RSS-210 A1.2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Bandwidth of Emission	FCC 15.231(c) IC RSS-210 A1.3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency Tolerance	FCC 15.231(d) IC RSS-210 A1.1.4	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Period Alternate Field Strength Requirements	FCC 15.231(e) IC RSS-210 2.7 Table 5	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna Requirement	FCC 15.203 IC RSS-Gen	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Conducted Measurement at (AC) Power Line	FCC 15.207 IC RSS-Gen	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

The following is intentionally left blank.



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

3.1 Transmission Requirements

FCC 15.231(e)

3.1.1 Limit of Transmission Time

Devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

3.1.2 Results for the duration and silent period measurement

This manually operated transmitter employs software to control the duration of each transmission and silent period between transmissions. The real measured result for the duration of each transmission is _____ ms, and the result for silent period between transmissions is _____ second.

ASK


This transmitter is operated by automatic activation, and the duration of each transmission and silent period between transmissions will be controlled by software. The real measured result for the duration of each transmission is 855.769231 ms, and the result for silent period between transmissions is 60.326763 second.

FSK

This transmitter is operated by automatic activation, and the duration of each transmission and silent period between transmissions will be controlled by software. The real measured result for the duration of each transmission is 758.012821 ms, and the result for silent period between transmissions is 60.454167 second.


Explanation: See attached diagrams in appendix.

Test equipment used : ETSTW-RE 004, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147



Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

3.2 Output Power (Field Strength)



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.9185	54.37	peak	25.49	79.86	92.80	210	90	-12.94	
*	433.9185	38.97	AVG	25.49	64.46	72.80	210	90	-8.34	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02


Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %

File : Power
 120.0 dBuV/m

Data : #2

Date: 1/16/2019
 Time: 1:56:37 AM



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	433.9185	38.87	peak	25.49	64.36	92.80	140	310	-28.44	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02


Radiated Emission Measurement

Operator: Sky
 Temperature: 21.2 °C
 Humidity: 72.8 %

File : Power
 110.0 dBuV/m

Data : #1

Date: 1/15/2019
 Time: 10:05:32 PM



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.8913	49.12	peak	25.49	74.61	92.80	130	0	-18.19	
*	433.8913	34.94	AVG	25.49	60.43	72.80	130	0	-12.37	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Sky

File :Power
 110.0 dBuV/m


Data :#2

Date: 1/15/2019

Temperature:21.2 °C

Time: 10:08:42 PM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18505

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz


Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.8944	56.18	peak	25.49	81.67	92.80	150	255	-11.13	
*	433.8944	42.00	AVG	25.49	67.49	72.80	150	255	-5.31	

Limit 15.231(e)

Fundamental Frequency (MHz)	Field strength of fundamental, limit $\mu\text{V/m}$
40.66 – 40.70	1,000
70 – 130	500
130 – 174	500 to 1,500
174 – 260	1,500
260 – 470	1,500 to 5,000** (433.92 MHz: 72.87 dB $\mu\text{V/m}$ = 4398.681 $\mu\text{V/m}$)
Above 470	5,000

Test equipment used: ETSTW-RE 004, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

3.3 Out of Band Radiated Emissions

FCC Rule: 15.231(e) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Guidance on Measurement of pulsed emission: 15.35(c)

“the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.”

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms or one period})$

Limits:

For frequencies (Average measurements)

Correction factor conform 15.35 (c) (Average measurements)

Duty cycle correction :

Max. Peak reading – duty cycle correction


Max permitted average Limits = Max permitted Fundamental limit – 20 dB

For example for 315 fundamental carrier:

Max permitted average Limit: $72.87 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 52.87 \text{ dB}\mu\text{V/m}$

For frequencies above 1GHz (Peak measurements).

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)



Registration number: W6M21810-18505-C-1
FCC ID: XVBM2F02
IC: 9368A-M2F02

3.4 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.231 (b), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 8000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of pulsed emission:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

For frequencies above 1GHz (Average measurements).

The correction factor, based on the channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log(\text{dwell time}/100\text{ms})$


No duty cycle correction was added to the reading

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)

Above 960 MHz

For mode DSSS CW: $54 \text{ dB}\mu\text{V}/\text{m} + 20 \text{ dB} = 74 \text{ dB}\mu\text{V}/\text{m}$

Explanation: See attached diagrams.



Registration number: W6M21810-18505-C-1

FCC ID: XVBM2F02

IC: 9368A-M2F02

3.5 Spurious Emission radiated, Transmitter

Spurious emission was measured with modulation (declared by manufacturer).

The limits on the field strength of the spurious emission in the table § 15.231(e) are based on the fundamental frequency of the intentional radiator. Spurious emission shall be attenuated to the average (or alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

In addition, radiated emission which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).


SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :1

Data :#2

Date: 1/16/2019

Time: 2:06:12 AM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	127.9360	27.87	peak	-6.37	21.50	43.50	100	210	-22.00	
	264.8297	27.28	peak	-6.71	20.57	46.00	100	90	-25.43	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :2

Data :#1


Date: 1/16/2019

Temperature:21.2 °C

80.0 dBuV/m

Time: 2:09:07 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	867.8207	43.13	QP	4.24	47.37	72.80	100	130	-25.43	
*	983.1663	28.03	peak	6.67	34.70	54.00	100	285	-19.30	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :2

Data :#2


Date: 1/16/2019

Temperature:21.2 °C

80.0 dBuV/m

Time: 2:12:11 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	868.1363	43.57	peak	4.25	47.82	72.80	100	55	-24.98	
*	985.9720	28.39	peak	6.75	35.14	54.00	100	220	-18.86	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#1


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 2:27:20 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1300.601	59.63	peak	-9.00	50.63	74.00	150	70	-23.37	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#4


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 2:34:01 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1301.778	77.68	peak	-9.00	68.68	74.00	150	10	-5.32	
*	1301.778	62.28	AVG	-9.00	53.28	54.00	150	10	-0.72	
	1735.471	51.15	peak	-7.09	44.06	72.80	150	170	-28.74	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#2


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 2:29:43 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2601.202	44.75	peak	-3.29	41.46	72.80	150	100	-31.34	
	3050.100	43.39	peak	-3.22	40.17	72.80	150	35	-32.63	
	3823.647	42.71	peak	-0.56	42.15	74.00	150	240	-31.85	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#5


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 2:39:42 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2601.202	49.39	peak	-3.29	46.10	72.80	150	325	-26.70	
	3038.076	44.54	peak	-3.24	41.30	72.80	150	180	-31.50	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :3

Data :#3

Date: 1/16/2019

Time: 2:31:43 AM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#6


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 2:41:12 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Sky
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :1

Data :#1

Date: 1/15/2019

Time: 10:13:50 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	124.1483	29.53	peak	-6.47	23.06	43.50	100	80	-20.44	
	275.6512	27.11	peak	-6.24	20.87	46.00	100	55	-25.13	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Sky
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :1

Data :#2

Date: 1/15/2019

Time: 10:15:14 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	124.1483	27.89	peak	-6.47	21.42	43.50	100	225	-22.08	
	261.5831	27.63	peak	-6.85	20.78	46.00	100	40	-25.22	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Sky
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :2

Data :#1

Date: 1/15/2019

Time: 10:17:36 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	868.1363	55.43	QP	4.25	59.68	72.80	150	250	-13.12	
*	868.1363	41.76	AVG	4.25	46.01	52.80	150	250	-6.79	
	969.1381	27.95	peak	6.26	34.21	54.00	100	170	-19.79	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Sky
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :2

Data :#2

Date: 1/15/2019

Time: 10:18:50 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	868.1363	48.07	peak	4.25	52.32	72.80	100	30	-20.48	
*	868.1363	34.16	AVG	4.25	38.41	52.80	100	30	-14.39	
	992.9860	27.53	peak	6.96	34.49	54.00	100	185	-19.51	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :3

Data :#1

Date: 1/16/2019

Time: 12:41:25 AM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1301.748	76.13	peak	-9.00	67.13	74.00	180	280	-6.87	
*	1301.748	61.95	AVG	-9.00	52.95	54.00	180	280	-1.05	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :3

Data :#4

Date: 1/16/2019

Time: 12:48:45 AM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1300.601	57.94	peak	-9.00	48.94	74.00	150	225	-25.06	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen

File :3

Data :#2


Date: 1/16/2019

Temperature:21.2 °C

90.0 dBuV/m

Time: 12:43:51 AM

Humidity:72.8 %



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2601.202	45.72	peak	-3.29	42.43	72.80	150	20	-30.37	
*	3470.942	46.53	peak	-2.15	44.38	72.80	150	175	-28.42	
	3907.816	45.48	peak	-0.25	45.23	74.00	150	65	-28.77	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :3

Data :#5

Date: 1/16/2019

Time: 12:51:00 AM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18505

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2601.202	46.00	peak	-3.29	42.71	72.80	150	300	-30.09	
*	3038.076	52.29	peak	-3.24	49.05	72.80	150	145	-23.75	
	3470.942	47.81	peak	-2.15	45.66	72.80	150	80	-27.14	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18505-C-1
 FCC ID: XVBM2F02
 IC: 9368A-M2F02

Radiated Emission Measurement

Operator: Allen
 Temperature: 21.2 °C
 Humidity: 72.8 %


File :3

Data :#3

Date: 1/16/2019

Time: 12:46:16 AM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18505

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------