

**FCC PART 15 SUBPART C / IC RSS-210 TEST REPORT**

**for**

**TPMS**

**Model No.: TP3-001**

**FCC ID: XVBW3F01**

**IC: 9368A-W3F01**

**of**

Applicant: Standard Motor Products, Inc.

Address: 37-18 Northern Boulevard, Long Island City, New York 11101,  
United States

Tested and Prepared

by

**Worldwide Testing Services (Taiwan) Co., Ltd.**

**FCC Registration No.: TW1477, TW0020, TW1072**


**Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC-5107A-1**

**A2LA Accredited No.: 2732.01**



**Report No.: W6M21810-18504-C-1**

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.  
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: [wts@wts-lab.com](mailto:wts@wts-lab.com)




Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

## **TABLE OF CONTENTS**

1	GENERAL INFORMATION .....	2
1.1	NOTES .....	2
1.2	TESTING LABORATORY .....	3
1.2.1	<i>Location</i> .....	3
1.2.2	<i>Details of accreditation status</i> .....	3
1.3	DETAILS OF APPROVAL HOLDER .....	3
1.4	APPLICATION DETAILS .....	3
1.5	TEST ITEM .....	4
1.6	TEST STANDARDS .....	4
2	TECHNICAL TEST .....	5
2.1	SUMMARY OF TEST RESULTS .....	5
2.2	TEST ENVIRONMENT .....	5
2.3	TEST EQUIPMENT UTILIZED .....	6
2.4	GENERAL TEST PROCEDURE .....	9
3	TEST RESULTS (ENCLOSURE) .....	10
3.1	TRANSMISSION REQUIREMENTS .....	11
3.1.1	<i>Limit of Transmission Time</i> .....	11
3.1.2	<i>Results for the duration and silent period measurement</i> .....	11
3.2	OUTPUT POWER (FIELD STRENGTH) .....	12
3.3	OUT OF BAND RADIATED EMISSIONS .....	16
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS .....	17
3.5	SPURIOUS EMISSION RADIATED, TRANSMITTER .....	18
3.6	CHANNEL BANDWIDTH .....	39
3.7	ANTENNA REQUIREMENT .....	40
3.8	DUTY CYCLE .....	41
3.9	CONDUCTED MEASUREMENT AT (AC) POWER LINE .....	42
3.10	EQUIPMENT MODIFICATION .....	43

Appendix: Diagrams and Photos



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

**1 General Information**

**1.1 Notes**

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services (Taiwan) Co., Ltd.

**Tester:**


December 3, 2018	Leon Chueh	<i>Leon Chueh</i>
------------------	------------	-------------------

Date	WTS-Lab.	Name	Signature
------	----------	------	-----------

**Technical responsibility for area of testing:**

December 3, 2018	Kevin Wang	<i>Kevin Wang</i>
------------------	------------	-------------------

Date	WTS	Name	Signature
------	-----	------	-----------



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

## **1.2 Testing laboratory**

### 1.2.1 Location

#### OATS

No.5-1, Lishui, Shuang Sing Village,  
Wanli Dist., New Taipei City 207,  
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

#### Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

### 1.2.2 Details of accreditation status

#### Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477, TW0020, TW1072

Industry Canada filed test laboratory Reg. No. IC 5679A-1, IC 5107A-1


## **1.3 Details of approval holder**

Name:	Standard Motor Products, Inc.
Street:	37-18 Northern Boulevard,
Town:	Long Island City, New York 11101,
Country:	United States
Telephone:	./.
Fax:	./.

## **1.4 Application details**

Date of receipt of test item: October 9, 2018

Date of test: from October 11, 2018 to December 3, 2018



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

## **1.5 Test item**

Description of test item: TPMS  
Type identification: TP3-001  
Brand name: SMP  
Multi-listing model number: TP3-002, TP3-003, TP3-004  
Transmitting frequency: 433.92 MHz  
Operation mode: Simplex  
Voltage supply: Battery 3 Vd.c. (CR2050HR)  
(The device is tested under fresh battery condition.)  
Antenna type: Incorporated Antenna  
Photos: see Appendix

## **1.6 Manufacturer (if applicable)**

Name: Orange Electronic Co., Ltd  
Street: 5F., No.29, Keya Rd., Daya Dist.,  
Town: Taichung City 428,  
Country: Taiwan

Additional information: ./.

## **1.7 Test standards**

Technical standard : FCC RULES PART 15 SUBPART C § 15.231 (e) (2017-10)  
CANADA RSS-210 Issue 9 (2016-09)  
CANADA RSS-Gen Issue 5 (2018-04)



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

## 2 Technical test

### 2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 3 were ascertained in the course of the tests performed.

### 2.2 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Details of power supply: Battery 3 Vd.c. (CR2050HR)


Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission	Expanded Uncertainty : 1.54 dB
Estimation Result of Uncertainty of Radiated Emission(3M)	Expanded Uncertainty : 0.009-30 MHz : 2.17 dB 30-1000 MHz : 3.57 dB 1-18 GHz : 2.60 dB 18-40 GHz : 2.58 dB
Estimation Result of Uncertainty of Bandwidth Measurement 20 dB Bandwidth, Occupied bandwidth, Channel bandwidth, Necessary Bandwidth	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Frequency Drift Measurement Frequency stability	Expanded Uncertainty : 6.09 Hz
Estimation Result of Uncertainty of Band Edge Measurement	Expanded Uncertainty : 0.98 dBc



Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## 2.3 Test equipment utilized

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2018/5/30	2019/5/29
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2018/11/1	2019/10/31
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2018/8/21	2019/8/20
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2018/7/13	2019/7/12
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2018/9/25	2019/9/24
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2018/7/16	2019/7/15
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2018/5/30	2019/5/29
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2018/5/21	2019/5/20
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2018/7/13	2019/7/12
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2018/7/12	2019/7/11
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2018/3/26	2019/3/25
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2018/1/23	2019/1/22
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2018/4/13	2019/4/12
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2018/4/26	2019/4/25
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2018/3/1	2019/2/28
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2018/3/6	2019/3/5
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2018/3/1	2019/2/28
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2018/3/30	2019/3/29
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2018/9/17	2019/9/16
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2018/9/18	2019/9/17
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2018/4/16	2019/4/15
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2018/2/23	2019/2/22
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2018/1/15	2019/1/14
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	Function test	
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2018/5/29	2019/5/28
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2018/8/8	2019/8/7
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2018/2/27	2019/2/26
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2018/8/8	2019/8/7
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2018/3/30	2019/3/29
ETSTW-RE 147	Bi-log Hybrid Antenna	MCTD 2786B	BLB16M04005	ETC	2018/3/23	2019/3/22
ETSTW-RE 151	Thermohyrometer	608-h1	45104376	TESTO	2018/8/17	2019/8/16
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2018/5/10	2019/5/9
ETSTW-EMS 008	Exposure Level Tester	ELT-400	G-0009	Narda	2018/7/17	2019/7/16
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2018/2/27	2019/2/26
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2018/3/2	2019/3/1
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2018/10/19	2019/10/18
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2018/1/11	2019/1/10
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2018/1/11	2019/1/10
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2018/1/11	2019/1/10
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2018/1/11	2019/1/10
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2018/9/12	2019/9/11
ETSTW-GSM 024	Radio Communication Analyzer	MT8821C	None	Anritsu	2018/3/7	2019/3/6
ETSTW-GSM 025	Band Reject Filter	BRM19835	001	Micro-Tronics	2018/8/9	2019/8/8
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2018/2/22	2019/2/21
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2018/7/2	2019/7/1
ETSTW-Cable 026	Microwave Cable	SUCOFLEX 104	279075	HUBER+SUHNER	2018/2/27	2019/2/26
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2018/5/14	2019/5/13
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2018/9/18	2019/9/17
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S Cable 9)	279067	HUBER+SUHNER	2018/2/27	2019/2/26
ETSTW-Cable 031	Microwave Cable	SUCOFLEX 104 (S Cable 10)	238092	HUBER+SUHNER	2018/3/30	2019/3/29






# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 048	Microwave Cable	SUCOFLEX 104	325519	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2018/6/9	2019/6/8
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2018/3/30	2019/3/29
ETSTW-Cable 066	SMA type cable	32022	None	ASTROLAB	2018/8/30	2019/8/29
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM- NM-25000	170239	EMCI	2018/6/9	2019/6/8
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

## **2.4 General Test Procedure**

**POWER LINE CONDUCTED INTERFERENCE:** The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

**RADIATION INTERFERENCE:** The test procedure used was ANSI STANDARD C63.10-2013 6.3 using a spectrum analyzer. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was the 100 kHz and the video bandwidth was 300 kHz.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB $\mu$ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.


Example:

Freq (MHz)      METER READING + ACF + CABLE LOSS (to the receiver) = FS  
33                      20 dB $\mu$ V + 10.36 dB/m + 6 dB = 36.36 dB $\mu$ V/m @3m

**ANSI STANDARD C63.10-2013 6.2.2 MEASUREMENT PROCEDURES:** The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table). The EUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to 10<sup>th</sup> harmonic of the fundamental.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

**ANSI STANDARD C63.10-2009 B.2.7:** Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

**3 Test results (enclosure)**


1st test

test after modification

production test

TEST CASE	Para. Number	Required	Test passed	Test failed
Transmission Requirements	FCC 15.231(e) IC RSS-210 Annex 1 A1.1.1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission	FCC 15.231(e) IC RSS-210 A1.2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Bandwidth of Emission	FCC 15.231(c) IC RSS-210 A1.3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency Tolerance	FCC 15.231(d) IC RSS-210 A1.1.4	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Period Alternate Field Strength Requirements	FCC 15.231(e) IC RSS-210 2.7 Table 5	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna Requirement	FCC 15.203 IC RSS-Gen	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Conducted Measurement at (AC) Power Line	FCC 15.207 IC RSS-Gen	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**The following is intentionally left blank.**



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

### **3.1 Transmission Requirements**

FCC 15.231(e)

#### 3.1.1 Limit of Transmission Time

Devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

#### 3.1.2 Results for the duration and silent period measurement

This manually operated transmitter employs software to control the duration of each transmission and silent period between transmissions. The real measured result for the duration of each transmission is \_\_\_\_\_ ms, and the result for silent period between transmissions is \_\_\_\_\_ second.

ASK


This transmitter is operated by automatic activation, and the duration of each transmission and silent period between transmissions will be controlled by software. The real measured result for the duration of each transmission is 691.3827655 ms, and the result for silent period between transmissions is 60.46092184 second.

FSK

This transmitter is operated by automatic activation, and the duration of each transmission and silent period between transmissions will be controlled by software. The real measured result for the duration of each transmission is 561.1222445 ms, and the result for silent period between transmissions is 60.6012024 second.


Explanation: See attached diagrams in appendix.

Test equipment used : ETSTW-RE 004, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147



Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## 3.2 Output Power (Field Strength)



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.9495	49.55	peak	25.49	75.04	92.80	380	35	-17.76	
*	433.9495	43.19	AVG	25.49	68.68	72.80	380	35	-4.12	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01


## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %

File : Power  
 110.0 dBuV/m

Data : #2

Date: 10/22/2018  
 Time: 5:17:03 PM



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.9470	54.40	peak	25.49	79.89	92.80	140	310	-12.91	
*	433.9470	46.67	AVG	25.49	72.16	72.80	140	310	-0.64	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01


### Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %

File : Power  
 110.0 dBuV/m

Data : #1

Date: 10/22/2018  
 Time: 4:33:18 PM



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.8990	48.84	peak	25.49	74.33	92.80	130	40	-18.47	
*	433.8990	39.07	AVG	25.49	64.56	72.80	130	40	-8.24	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

### Radiated Emission Measurement


Operator: Sky

File :Power  
 110.0 dBuV/m

Data :#2

Date: 10/22/2018  
 Time: 4:35:55 PM

Temperature:23.5 °C  
 Humidity:70 %



Site : Chamber

Condition : FCC 15.231(433MHz)Power(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18504

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK


Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	433.8978	56.18	peak	25.49	81.67	92.80	130	300	-11.13	
*	433.8978	46.41	AVG	25.49	71.90	72.80	130	300	-0.90	

Limit 15.231(e)

Fundamental Frequency (MHz)	Field strength of fundamental, limit $\mu\text{V/m}$
40.66 – 40.70	1,000
70 – 130	500
130 – 174	500 to 1,500
174 – 260	1,500
260 – 470	1,500 to 5,000** (433.92 MHz: 72.87 dB $\mu\text{V/m}$ = 4398.681 $\mu\text{V/m}$ )
Above 470	5,000

Test equipment used: ETSTW-RE 004, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147





Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

### **3.3 Out of Band Radiated Emissions**

FCC Rule: 15.231(e) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Guidance on Measurement of pulsed emission: 15.35(c)

“the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.”

Duty Cycle correction =  $20 \log (\text{dwell time}/100\text{ms or one period})$

Limits:

For frequencies (Average measurements)

Correction factor conform 15.35 (c) (Average measurements)

Duty cycle correction :

Max. Peak reading – duty cycle correction


Max permitted average Limits = Max permitted Fundamental limit – 20 dB

For example for 315 fundamental carrier:

Max permitted average Limit:  $67.66 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 47.66 \text{ dB}\mu\text{V/m}$

For frequencies above 1GHz (Peak measurements).

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)



Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

**3.4 Transmitter Radiated Emissions in restricted Bands**

FCC Rules: 15.231 (b), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 8000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of pulsed emission:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

For frequencies above 1GHz (Average measurements).

The correction factor, based on the channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = 20 log (dwell time/100ms)


No duty cycle correction was added to the reading

Modified Limits for peak conform 15.35 (b) = Max Permitted average Limits + 20dB (because Peak detector is used)

Above 960 MHz

For mode DSSS CW: 54 dBμV/m + 20 dB = 74 dBμV/m

Explanation: See attached diagrams.



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

## **3.5 Spurious Emission radiated, Transmitter**

Spurious emission was measured with modulation (declared by manufacturer).

The limits on the field strength of the spurious emission in the table § 15.231(e) are based on the fundamental frequency of the intentional radiator. Spurious emission shall be attenuated to the average (or alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

In addition, radiated emission which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.


Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.






# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)<e>

EUT : W6M21810-18504

M/N:

Test Mode : TX 433.92MHz


Note : ASK

Polarization: *Vertical*

Power : 3 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	133.3466	27.13	peak	-6.36	20.77	43.50	100	55	-22.73	
	247.5150	26.55	peak	-7.49	19.06	46.00	100	170	-26.94	




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement


Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %



Site : Chamber  
 Condition : FCC 15.231(433MHz) 300-1000(PK)<e>  
 EUT : W6M21810-18504  
 M/N:  
 Test Mode : TX 433.92MHz  
 Note : ASK

Polarization: *Horizontal*  
 Power : 3 Vd.c.  
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	675.9520	28.08	peak	0.61	28.69	72.80	100	45	-44.11	
*	910.2204	27.98	peak	5.05	33.03	72.80	100	275	-39.77	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :2

Data :#2

Date: 10/22/2018

Time: 5:57:01 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

EUT : W6M21810-18504

M/N:

Test Mode : TX 433.92MHz


Note : ASK

Polarization: **Vertical**

Power : 3 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	688.5771	27.87	peak	0.74	28.61	72.80	100	90	-44.19	
*	842.8858	28.09	peak	3.71	31.80	72.80	100	110	-41.00	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#1

Date: 10/22/2018

Time: 7:10:21 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.

M/N:


Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1178.357	42.65	peak	-9.35	33.30	74.00	150	210	-40.70	
*	1669.339	43.14	peak	-7.59	35.55	74.00	150	180	-38.45	






# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

### Radiated Emission Measurement


Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %



Site : Chamber  
 Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>  
 EUT : W6M21810-18504  
 M/N:  
 Test Mode : TX 433.92MHz  
 Note : ASK

Polarization: **Vertical**  
 Power : 3 Vd.c.  
 Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1304.609	42.59	peak	-9.00	33.59	74.00	150	30	-40.41	
	1735.887	53.75	peak	-7.08	46.67	72.80	150	190	-26.13	
*	1735.887	47.39	AVG	-7.08	40.31	52.80	150	190	-12.49	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#2

Date: 10/22/2018

Time: 7:15:29 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2432.866	43.14	peak	-4.01	39.13	72.80	150	275	-33.67	
*	3150.301	42.36	peak	-2.83	39.53	72.80	150	135	-33.27	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#5

Date: 10/22/2018

Time: 7:17:48 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2621.242	42.72	peak	-3.40	39.32	72.80	150	270	-33.48	
*	3470.942	46.11	peak	-2.15	43.96	72.80	150	60	-28.84	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

### Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#3

Date: 10/22/2018

Time: 7:39:31 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

### Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#6

Date: 10/22/2018

Time: 7:40:38 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: **Vertical**

EUT : W6M21810-18504

Power : 3 V.d.c.

M/N:


Distance: 3m

Test Mode : TX 433.92MHz

Note : ASK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :1

Data :#2

Date: 10/22/2018

Time: 10:45:15 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 30-300(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	137.6753	27.90	peak	-6.42	21.48	43.50	100	255	-22.02	
	270.7816	26.67	peak	-6.45	20.22	46.00	100	40	-25.78	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :2

Data :#1

Date: 10/22/2018

Time: 10:40:39 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.

M/N:


Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	635.2703	28.05	peak	-0.06	27.99	72.80	100	90	-44.81	
*	848.4970	27.89	peak	3.85	31.74	72.80	100	160	-41.06	





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :2

Data :#2

Date: 10/22/2018

Time: 10:42:21 PM

80.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 300-1000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	617.0340	28.10	peak	-0.57	27.53	72.80	100	135	-45.27	
*	890.5811	27.81	peak	4.69	32.50	72.80	100	270	-40.30	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#1

Date: 10/22/2018

Time: 10:18:55 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1206.413	42.85	peak	-9.39	33.46	74.00	150	55	-40.54	
*	1749.499	43.21	peak	-6.96	36.25	72.80	150	170	-36.55	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#4

Date: 10/22/2018

Time: 10:20:10 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 1000-2000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1444.890	43.32	peak	-8.81	34.51	74.00	150	280	-39.49	
	1735.576	55.17	peak	-7.09	48.08	72.80	155	70	-24.72	
*	1735.576	45.40	AVG	-7.09	38.31	52.80	155	70	-14.49	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#2

Date: 10/22/2018

Time: 10:26:17 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	3470.942	45.50	peak	-2.15	43.35	72.80	150	225	-29.45	
	3907.816	43.26	peak	-0.25	43.01	74.00	150	60	-30.99	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 10/22/2018

Temperature:23.5 °C

Time: 10:27:48 PM

Humidity:70 %

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 2000-4000(PK)<e>

Polarization: *Vertical*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2216.433	43.33	peak	-4.98	38.35	74.00	150	30	-35.65	
	3470.942	54.18	peak	-2.15	52.03	72.80	150	60	-20.77	
*	3470.942	44.41	AVG	-2.15	42.26	52.80	150	60	-10.54	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

### Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#3

Date: 10/22/2018

Time: 10:29:36 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: *Horizontal*

EUT : W6M21810-18504

Power : 3 Vd.c.


M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

## Radiated Emission Measurement

Operator: Sky  
 Temperature: 23.5 °C  
 Humidity: 70 %


File :3

Data :#6

Date: 10/22/2018

Time: 10:30:44 PM

90.0 dBuV/m



Site : Chamber

Condition : FCC 15.231(433MHz) 4000-8000(PK)<e>

Polarization: Vertical

EUT : W6M21810-18504

Power : 3 Vd.c.

M/N:

Distance: 3m

Test Mode : TX 433.92MHz

Note : FSK

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

### Note


1. Correction Factor = Antenna factor + Cable loss - Preamplifier
2. The formula of measured value as: Test Result = Reading + Correction Factor
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty for 3m measurement : 30-1000 MHz = ± 3.57 dB, 1-18 GHz = ±2.60 dB, 18-40 GHz = ±2.58 dB ; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2. The decision rule is "false acceptance".

All other not noted test plots do not contain significant test results in relation to the limits

Test results: The unit meet the FCC requirements.

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 062, ETSTW-RE 142,

ETSTW-RE 147



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

**3.6 Channel Bandwidth**

Measurement of Necessary Bandwidth (BN)

ASK

Used frequency	Bandwidth	Limit
433.92 MHz	68.13627255 kHz	1.0848 MHz

FSK

Used frequency	Bandwidth	Limit
433.92 MHz	118.23647295 kHz	1.0848 MHz


Explanation: The bandwidth fulfills the requirements of FCC § 15.231, see attached diagrams.

Limits:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test equipment used: ETSTW-RE 004






Registration number: W6M21810-18504-C-1  
FCC ID: XVBW3F01  
IC: 9368A-W3F01

**3.7 Antenna requirement**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

Explanation: This Incorporated Antenna is integral antenna which passes antenna requirement.

The equipment meets the requirements	yes <input checked="" type="checkbox"/>	no <input type="checkbox"/>
--------------------------------------	--	--------------------------------



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

### **3.8 Duty Cycle**

The correction factor, based on the channel dwell time in a 100ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the measured value.

Average Reading = Peak Reading (dBuV/m) + Duty Cycle Correction

Duty Cycle Correction = 20 log (Cycle)

In order to determine the Duty Cycle, the EUT is measured as:


#### ASK

Testing Mode	T period (ms)	T on (ms)	Duty Cycle	Duty Cycle Correction 20*log(Duty Cycle)
Transmitting mode	100	41.08216	0.410821643	-7.73

#### FSK

Testing Mode	T period (ms)	T on (ms)	Duty Cycle	Duty Cycle Correction 20*log(Duty Cycle)
Transmitting mode	100	32.46492	0.3246492	-9.77

Test equipment used: ETSTW-RE 004



Registration number: W6M21810-18504-C-1  
 FCC ID: XVBW3F01  
 IC: 9368A-W3F01

**3.9 Conducted Measurement at (AC) Power Line**

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level	
	quasi-peak (dB $\mu$ V/m)	average (dB $\mu$ V/m)
-- kHz	--	--


Note

1. The formula of measured value as: Test Result = Reading + Correction Factor
2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Measurement uncertainty =  $\pm 1.54$  dB; Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2. The decision rule is “false acceptance”.
6. Up Line: QP Limit Line, Down Line: Ave Limit Line.
7. This test is not required because the EUT is battery-used.

**Limits:**

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 003, ETSTW-CE 016, ETSTW-RE 045



Registration number: W6M21810-18504-C-1

FCC ID: XVBW3F01

IC: 9368A-W3F01

**3.10 Equipment Modification**

No modification was made by Worldwide Testing Services (Taiwan) Co., Ltd..