



11AX40MIMO\_Ant1\_5310\_1000~40000




11AX40MIMO\_Ant2\_5310\_30~1000




11AX40MIMO\_Ant2\_5310\_1000~40000








11AX40MIMO\_Ant1\_5510\_30~1000




11AX40MIMO\_Ant1\_5510\_1000~40000




11AX40MIMO\_Ant2\_5510\_30~1000








11AX40MIMO\_Ant2\_5510\_1000~40000




11AX40MIMO\_Ant1\_5550\_30~1000




11AX40MIMO\_Ant1\_5550\_1000~40000








11AX40MIMO\_Ant2\_5550\_30~1000




11AX40MIMO\_Ant2\_5550\_1000~40000




11AX40MIMO\_Ant1\_5670\_30~1000








11AX40MIMO\_Ant1\_5670\_1000~40000




11AX40MIMO\_Ant2\_5670\_30~1000




11AX40MIMO\_Ant2\_5670\_1000~40000








11AX40MIMO\_Ant1\_5755\_30~1000




11AX40MIMO\_Ant1\_5755\_1000~40000




11AX40MIMO\_Ant2\_5755\_30~1000








11AX40MIMO\_Ant2\_5755\_1000~40000




11AX40MIMO\_Ant1\_5795\_30~1000




11AX40MIMO\_Ant1\_5795\_1000~40000








11AX40MIMO\_Ant2\_5795\_30~1000




11AX40MIMO\_Ant2\_5795\_1000~40000




11AX80MIMO\_Ant1\_5210\_30~1000








11AX80MIMO\_Ant1\_5210\_1000~40000




11AX80MIMO\_Ant2\_5210\_30~1000




11AX80MIMO\_Ant2\_5210\_1000~40000








11AX80MIMO\_Ant1\_5290\_30~1000




11AX80MIMO\_Ant1\_5290\_1000~40000




11AX80MIMO\_Ant2\_5290\_30~1000








11AX80MIMO\_Ant2\_5290\_1000~40000






11AX80MIMO\_Ant1\_5530\_30~1000




11AX80MIMO\_Ant1\_5530\_1000~40000













11AX80MIMO\_Ant1\_5610\_1000~40000




11AX80MIMO\_Ant2\_5610\_30~1000




11AX80MIMO\_Ant2\_5610\_1000~40000








11AX80MIMO\_Ant1\_5775\_30~1000




11AX80MIMO\_Ant1\_5775\_1000~40000



11AX80MIMO\_Ant2\_5775\_30~1000







11AX80MIMO\_Ant2\_5775\_1000~40000





## 7. Restricted Bands Requirement

### 7.1 Test Standard and Limit

#### 7.1.1 Test Standard

**RSS-Gen 8.10 & RSS 247 5.5**

**FCC Part 15.205 & FCC Part 15.407(b)**

#### 7.1.2 Test Limit

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3

NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.


**Note:** According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.






## 7.2 Test Setup

### Radiated measurement



### Conducted measurement



## 7.3 Test Procedure

### ---Radiated measurement

- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- The Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.





**--- Conducted measurement**

- a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
- c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies  $\leq 30$  MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies  $> 1000$  MHz).
- d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
- e) Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

$E$  is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

$d$  is the specified measurement distance in m

f) Compare the resultant electric field strength level with the applicable regulatory limit.

g) Perform the radiated spurious emission test.

**7.4 Deviation From Test Standard**

No deviation

**7.5 EUT Operating Mode**

Please refer to the description of test mode.

**7.6 Test Data**


Please refer to the following pages.





-----Radiation Test

Temperature:	23.6°C	Relative Humidity:	49%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11a Mode 5180 MHz (U-NII-1)		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	53.52	12.08	65.60	74.00	-8.40	peak	P
2 *	5150.000	39.21	12.08	51.29	54.00	-2.71	AVG	P
3	5175.900	88.82	12.17	100.99			peak	
4	5176.200	80.76	12.17	92.93			AVG	


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11a Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	52.34	12.08	64.42	74.00	-9.58	peak	P
2 *	5150.000	38.62	12.08	50.70	54.00	-3.30	AVG	P
3	5175.900	87.64	12.17	99.81			peak	
4	5182.600	79.83	12.19	92.02			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11a Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5316.000	86.72	12.50	99.22			peak	
2	5322.700	79.03	12.53	91.56			AVG	
3	5350.000	49.85	12.68	62.53	74.00	-11.47	peak	P
4 *	5350.000	38.23	12.68	50.91	54.00	-3.09	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11a Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5316.000	85.70	12.50	98.20			peak	
2	5317.300	78.29	12.50	90.79			AVG	
3	5350.000	51.82	12.68	64.50	74.00	-9.50	peak	P
4 *	5350.000	39.05	12.68	51.73	54.00	-2.27	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	43.38	12.08	55.46	74.00	-18.54	peak	P
2 *	5150.000	35.82	12.08	47.90	54.00	-6.10	AVG	P
3	5176.800	85.60	12.17	97.77			peak	
4	5177.600	77.69	12.18	89.87			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	48.66	12.08	60.74	74.00	-13.26	peak	P
2 *	5150.000	37.11	12.08	49.19	54.00	-4.81	AVG	P
3	5175.200	80.88	12.17	93.05			AVG	
4	5181.400	89.85	12.19	102.04			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5321.300	74.65	12.52	87.17			AVG	
2	5321.400	82.82	12.52	95.34			peak	
3	5350.000	40.85	12.68	53.53	74.00	-20.47	peak	P
4 *	5350.000	34.95	12.68	47.63	54.00	-6.37	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5321.400	82.43	12.52	94.95			AVG	
2	5321.500	88.07	12.52	100.59			peak	
3	5350.000	49.02	12.68	61.70	74.00	-12.30	peak	P
4 *	5350.000	38.43	12.68	51.11	54.00	-2.89	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	47.60	12.08	59.68	74.00	-14.32	peak	P
2 *	5150.000	34.96	12.08	47.04	54.00	-6.96	AVG	P
3	5183.000	85.27	12.19	97.46			peak	
4	5183.000	77.05	12.19	89.24			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	48.88	12.08	60.96	74.00	-13.04	peak	P
2 *	5150.000	36.33	12.08	48.41	54.00	-5.59	AVG	P
3	5173.000	89.22	12.17	101.39			peak	
4	5176.900	81.28	12.17	93.45			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5321.400	78.07	12.52	90.59			AVG	
2	5323.000	85.78	12.54	98.32			peak	
3	5350.000	47.81	12.68	60.49	74.00	-13.51	peak	P
4 *	5350.000	36.24	12.68	48.92	54.00	-5.08	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5316.200	90.33	12.50	102.83			peak	
2	5321.400	81.50	12.52	94.02			AVG	
3	5350.000	53.01	12.68	65.69	74.00	-8.31	peak	P
4 *	5350.000	37.30	12.68	49.98	54.00	-4.02	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	45.27	12.08	57.35	74.00	-16.65	peak	P
2 *	5150.000	35.49	12.08	47.57	54.00	-6.43	AVG	P
3	5179.000	76.51	12.18	88.69			AVG	
4	5183.400	86.81	12.19	99.00			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5180 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	47.92	12.08	60.00	74.00	-14.00	peak	P
2 *	5150.000	36.58	12.08	48.66	54.00	-5.34	AVG	P
3	5175.000	91.50	12.17	103.67			peak	
4	5176.300	81.43	12.17	93.60			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5316.800	87.37	12.50	99.87			peak	
2	5318.800	77.45	12.51	89.96			AVG	
3	5350.000	44.52	12.68	57.20	74.00	-16.80	peak	P
4 *	5350.000	36.45	12.68	49.13	54.00	-4.87	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5320 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5321.600	79.82	12.52	92.34			AVG	
2	5323.300	90.41	12.54	102.95			peak	
3	5350.000	44.96	12.68	57.64	74.00	-16.36	peak	P
4 *	5350.000	35.76	12.68	48.44	54.00	-5.56	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	49.50	12.08	61.58	74.00	-12.42	peak	P
2 *	5150.000	37.37	12.08	49.45	54.00	-4.55	AVG	P
3	5181.600	73.03	12.19	85.22			AVG	
4	5186.550	80.78	12.20	92.98			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	49.28	12.08	61.36	74.00	-12.64	peak	P
2 *	5150.000	37.74	12.08	49.82	54.00	-4.18	AVG	P
3	5178.900	76.43	12.18	88.61			AVG	
4	5193.900	85.70	12.24	97.94			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5314.800	76.54	12.49	89.03			peak	
2	5315.100	71.26	12.49	83.75			AVG	
3	5350.000	43.74	12.68	56.42	74.00	-17.58	peak	P
4 *	5350.000	35.07	12.68	47.75	54.00	-6.25	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5298.900	75.90	12.40	88.30			AVG	
2	5323.350	82.31	12.54	94.85			peak	
3	5350.000	48.40	12.68	61.08	74.00	-12.92	peak	P
4 *	5350.000	36.30	12.68	48.98	54.00	-5.02	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	45.69	12.08	57.77	74.00	-16.23	peak	P
2 *	5150.000	35.34	12.08	47.42	54.00	-6.58	AVG	P
3	5178.950	70.31	12.18	82.49			AVG	
4	5186.300	78.38	12.20	90.58			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	49.69	12.08	61.77	74.00	-12.23	peak	P
2 *	5150.000	38.41	12.08	50.49	54.00	-3.51	AVG	P
3	5175.150	76.32	12.17	88.49			AVG	
4	5203.200	84.07	12.26	96.33			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5307.450	80.44	12.44	92.88			peak	
2	5313.300	72.76	12.48	85.24			AVG	
3	5350.000	48.69	12.68	61.37	74.00	-12.63	peak	P
4 *	5350.000	35.91	12.68	48.59	54.00	-5.41	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5301.900	76.32	12.41	88.73			AVG	
2	5316.600	84.26	12.50	96.76			peak	
3	5350.000	50.96	12.68	63.64	74.00	-10.36	peak	P
4 *	5350.000	37.54	12.68	50.22	54.00	-3.78	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	46.75	12.08	58.83	74.00	-15.17	peak	P
2 *	5150.000	35.34	12.08	47.42	54.00	-6.58	AVG	P
3	5178.950	80.89	12.18	93.07			peak	
4	5193.950	70.11	12.24	82.35			AVG	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE40) Mode 5190 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	53.36	12.08	65.44	74.00	-8.56	peak	P
2 *	5150.000	39.48	12.08	51.56	54.00	-2.44	AVG	P
3	5177.850	76.26	12.18	88.44			AVG	
4	5178.900	87.95	12.18	100.13			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5304.200	82.24	12.42	94.66			peak	
2	5307.200	71.29	12.44	83.73			AVG	
3	5350.000	46.62	12.68	59.30	74.00	-14.70	peak	P
4 *	5350.000	35.04	12.68	47.72	54.00	-6.28	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE40) Mode 5310 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5299.100	84.29	12.40	96.69			peak	
2	5316.350	75.89	12.50	88.39			AVG	
3	5350.000	51.90	12.68	64.58	74.00	-9.42	peak	P
4 *	5350.000	38.61	12.68	51.29	54.00	-2.71	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5210 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	44.17	12.08	56.25	74.00	-17.75	peak	P
2 *	5150.000	35.50	12.08	47.58	54.00	-6.42	AVG	P
3	5176.800	70.66	12.17	82.83			AVG	
4	5178.900	77.41	12.18	89.59			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5210 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5137.500	54.39	12.04	66.43	74.00	-7.57	peak	P
2 *	5137.500	40.08	12.04	52.12	54.00	-1.88	AVG	P
3	5150.000	46.19	12.08	58.27	74.00	-15.73	peak	P
4	5150.000	37.13	12.08	49.21	54.00	-4.79	AVG	P
5	5172.900	75.15	12.16	87.31			AVG	
6	5176.500	81.38	12.17	93.55			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5290 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5259.000	75.73	12.33	88.06			peak	
2	5261.700	68.00	12.34	80.34			AVG	
3	5350.000	43.58	12.68	56.26	74.00	-17.74	peak	P
4 *	5350.000	35.13	12.68	47.81	54.00	-6.19	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5290 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5324.100	82.58	12.54	95.12			peak	
2	5324.100	73.58	12.54	86.12			AVG	
3	5350.000	48.24	12.68	60.92	74.00	-13.08	peak	P
4	5350.000	36.74	12.68	49.42	54.00	-4.58	AVG	P
5	5386.200	53.13	12.89	66.02	74.00	-7.98	peak	P
6 *	5386.200	39.45	12.89	52.34	54.00	-1.66	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE80) Mode 5210 MHz (U-NII-1)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5150.000	44.22	12.08	56.30	74.00	-17.70	peak	P
2 *	5150.000	36.01	12.08	48.09	54.00	-5.91	AVG	P
3	5176.200	71.23	12.17	83.40			AVG	
4	5179.200	76.78	12.18	88.96			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE80) Mode 5210 MHz (U-NII-1)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5118.300	47.14	11.98	59.12	74.00	-14.88	peak	P
2 *	5118.300	38.54	11.98	50.52	54.00	-3.48	AVG	P
3	5150.000	46.36	12.08	58.44	74.00	-15.56	peak	P
4	5150.000	36.51	12.08	48.59	54.00	-5.41	AVG	P
5	5176.500	74.12	12.17	86.29			AVG	
6	5177.400	83.42	12.18	95.60			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE80) Mode 5290 MHz (U-NII-2A)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5259.900	77.80	12.33	90.13			peak	
2	5261.700	68.39	12.34	80.73			AVG	
3	5350.000	45.17	12.68	57.85	74.00	-16.15	peak	P
4 *	5350.000	35.36	12.68	48.04	54.00	-5.96	AVG	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ax(HE80) Mode 5290 MHz (U-NII-2A)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5319.000	78.10	12.52	90.62			peak	
2	5324.100	74.19	12.54	86.73			AVG	
3	5350.000	41.73	12.68	54.41	74.00	-19.59	peak	P
4	5350.000	36.64	12.68	49.32	54.00	-4.68	AVG	P
5	5367.300	52.52	12.79	65.31	74.00	-8.69	peak	P
6 *	5367.300	38.65	12.79	51.44	54.00	-2.56	AVG	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11a Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	44.63	13.30	57.93	68.30	-10.37	peak	P
2	5495.900	83.65	13.41	97.06			AVG	
3	5497.100	75.55	13.41	88.96			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11a Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5466.500	52.40	13.28	65.68	68.30	-2.62	peak	P
2	5470.000	49.18	13.30	62.48	68.30	-5.82	peak	P
3	5495.900	90.47	13.41	103.88			peak	
4	5496.300	81.33	13.41	94.74			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11a Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5695.500	74.92	13.59	88.51			AVG	
2	5695.900	83.79	13.59	97.38			peak	
3 *	5725.000	52.71	13.58	66.29	74.00	-7.71	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



Temperature:	23.6°C	Relative Humidity:	49%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5700 MHz (U-NII-2C)		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5695.900	86.81	13.59	100.40			peak	
2	5702.600	78.50	13.60	92.10			AVG	
3 *	5725.000	53.21	13.58	66.79	74.00	-7.21	peak	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5464.700	46.10	13.28	59.38	68.30	-8.92	peak	P
2	5470.000	43.82	13.30	57.12	68.30	-11.18	peak	P
3	5495.100	74.70	13.41	88.11			AVG	
4	5503.700	82.79	13.43	96.22			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	44.99	13.30	58.29	68.30	-10.01	peak	P
2	5501.200	81.63	13.43	95.06			AVG	
3	5501.400	91.24	13.43	104.67			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5696.500	73.75	13.59	87.34			AVG	
2	5702.600	84.92	13.60	98.52			peak	
3 *	5725.000	45.74	13.58	59.32	74.00	-14.68	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5696.600	88.04	13.59	101.63			peak	
2	5699.000	80.10	13.60	93.70			AVG	
3 *	5725.000	51.55	13.58	65.13	74.00	-8.87	peak	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	45.22	13.30	58.52	68.30	-9.78	peak	P
2	5498.700	76.36	13.43	89.79			AVG	
3	5505.600	84.43	13.43	97.86			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5465.100	51.48	13.28	64.76	68.30	-3.54	peak	P
2	5470.000	50.25	13.30	63.55	68.30	-4.75	peak	P
3	5496.100	90.40	13.41	103.81			peak	
4	5496.300	81.42	13.41	94.83			AVG	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5702.500	75.26	13.60	88.86			AVG	
2	5705.600	84.39	13.60	97.99			peak	
3 *	5725.000	48.83	13.58	62.41	74.00	-11.59	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5696.700	88.77	13.59	102.36			peak	
2	5697.500	80.57	13.59	94.16			AVG	
3	5725.000	53.27	13.58	66.85	74.00	-7.15	peak	P
4 *	5727.000	56.02	13.58	69.60	74.00	-4.40	peak	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5500 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	44.16	13.30	57.46	68.30	-10.84	peak	P
2	5495.100	86.57	13.41	99.98			peak	
3	5498.000	76.49	13.43	89.92			AVG	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



Temperature:	23.6°C	Relative Humidity:	49%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5500 MHz (U-NII-2C)		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5467.400	50.54	13.28	63.82	68.30	-4.48	peak	P
2	5470.000	48.74	13.30	62.04	68.30	-6.26	peak	P
3	5496.800	90.80	13.41	104.21			peak	
4	5498.900	81.64	13.43	95.07			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ax(HE20) Mode 5700 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5699.000	75.04	13.60	88.64			AVG	
2	5703.400	86.26	13.60	99.86			peak	
3 *	5725.000	51.00	13.58	64.58	74.00	-9.42	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



Temperature:	23.6°C	Relative Humidity:	49%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5700 MHz (U-NII-2C)		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5695.200	91.11	13.59	104.70			peak	
2	5698.100	80.43	13.60	94.03			AVG	
3 *	5725.000	57.62	13.58	71.20	74.00	-2.80	peak	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5510 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	46.70	13.30	60.00	68.30	-8.30	peak	P
2	5513.900	78.41	13.42	91.83			peak	
3	5514.950	69.63	13.42	83.05			AVG	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5510 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	52.32	13.30	65.62	68.30	-2.68	peak	P
2	5501.450	77.54	13.43	90.97			AVG	
3	5513.750	86.93	13.42	100.35			peak	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5670 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5661.600	67.63	13.53	81.16			AVG	
2	5673.900	78.25	13.55	91.80			peak	
3 *	5725.000	44.75	13.58	58.33	74.00	-15.67	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5670 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5673.900	84.83	13.55	98.38			peak	
2	5675.100	75.38	13.56	88.94			AVG	
3 *	5725.000	44.86	13.58	58.44	74.00	-15.56	peak	P


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5510 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5470.000	44.19	13.30	57.49	68.30	-10.81	peak	P
2	5507.150	71.40	13.43	84.83			AVG	
3	5507.450	79.33	13.43	92.76			peak	

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5510 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	5466.500	51.82	13.28	65.10	68.30	-3.20	peak	P
2	5470.000	47.36	13.30	60.66	68.30	-7.64	peak	P
3	5506.250	86.43	13.43	99.86			peak	
4	5516.450	77.78	13.42	91.20			AVG	


**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)





<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5670 MHz (U-NII-2C)		
<b>Remark:</b>			




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5661.150	69.38	13.53	82.91			AVG	
2	5664.300	78.04	13.53	91.57			peak	
3 *	5725.000	44.25	13.58	57.83	74.00	-16.17	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)



<b>Temperature:</b>	23.6°C	<b>Relative Humidity:</b>	49%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5670 MHz (U-NII-2C)		
<b>Remark:</b>			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5676.000	76.77	13.56	90.33			AVG	
2	5677.800	84.92	13.57	98.49			peak	
3 *	5725.000	44.45	13.58	58.03	74.00	-15.97	peak	P

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)
3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG (dBuV/m)

