Antenna Specification


No.	Contents	Number of Page	Page
INO.	Contents	Number of Page	Page Code
1	Antenna describe	2	2
2	External view drawing	2	2
3	Antenna Pattern	3	4

1. Antenna describe.

Frequency range	2400 MHz-2500 MHz
Antenna type	PCB Antenna
Antenna plate	Monoploe
Antenna gain(Peak)	-0.58 dBi
Antenna impedance	50Ω
V.S.W.R	<= 2.0 Max

2. External view drawing.

Company: mm




3. Antenna Pattern.

2D Pattern

Horizontal: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -40 Scale: 5/div




Frequency		Gain(dB)	
(MHz)	Max	Min	Avg
2400	-1.26174	-30.0801	-7.18716
2450	-0.765802	-36.5604	-7.48023
2500	-0.585582	-22.0315	-6.59127

Vertical: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -30 Scale: 5/div

SHENZHEN PENGLIN ELECTRONIC CO., LTD



Frequency		Gain(dB)	Avg
(MHz)	Max	Min	
2400	-5.2537	-22.1424	-12.4294
2450	-2.4652	-24.5837	-10.4702
2500	-1.86120	-29.5214	-9.20432