

TEST REPORT

Applicant: Trane US, Inc.

Address of Applicant: 6200 Troup Highway, TYLER, Texas 75707, United States

Manufacturer/Factory: Computime Electronics (Shenzhen) Company Limited

Address of Manufacturer/Factory: Yuekenguangyu Industrial Park, Kangqiao Road 88#, Danzhotou Community, Nanwan Street office, Longgang District, Shenzhen, China.

Equipment Under Test (EUT)

Product Name: COLOR WIFI Z-WAVE THERMOSTAT

Model No.: TCONT824AS52DC, ACONT824AS52DC, BAYSTAT814B, TCONT830AS52DB

Trade Mark: TRANE

FCC ID: XVR-CONT8247

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: September 13, 2022

Date of Test: September 14-29, 2022

Date of report issued: September 29, 2022

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	September 29, 2022	Original

Prepared By:




Date:

September 29, 2022

Project Engineer

Check By:



Date:

September 29, 2022

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
4.1 MEASUREMENT UNCERTAINTY.....	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT.....	5
5.2 TEST MODE.....	6
5.3 DESCRIPTION OF SUPPORT UNITS.....	6
5.4 TEST FACILITY.....	6
5.5 TEST LOCATION.....	6
5.6 ADDITIONAL INSTRUCTIONS.....	6
6 TEST INSTRUMENTS LIST.....	7
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT:.....	9
7.2 CONDUCTED EMISSIONS.....	10
7.3 RADIATED EMISSION METHOD.....	15
7.3.1 <i>Field Strength of The Fundamental Signal and spurious emissions</i>	18
7.4 20dB OCCUPY BANDWIDTH.....	27
8 TEST SETUP PHOTO.....	28
9 EUT CONSTRUCTIONAL DETAILS.....	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	COLOR WIFI Z-WAVE THERMOSTAT
Model No.:	TCONT824AS52DC, ACONT824AS52DC, BAYSTAT814B, TCONT830AS52DB
Test Model No.:	TCONT824AS52DC
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Test sample(s) ID:	GTS202209000083-1
Sample(s) Status:	Engineer sample
Serial No.:	N/A
Hardware Version:	V5.0
Software Version:	5.9.6.20220530
Operation Frequency:	908.42MHz, 916MHz
Modulation type:	Z-wave
Antenna Type:	Integral antenna
Antenna gain:	2dBi(declare by manufacturer)
Power supply:	AC 24V

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

908.42MHz:

Axis	X	Y	Z
Field Strength(dBuV/m)	90.06	91.49	89.27

916MHz:

Axis	X	Y	Z
Field Strength(dBuV/m)	88.45	89.19	87.21

5.3 Description of Support Units

Manufacture	Description	Model	SN.
N/A	AC-AC adapter	N/A	N/A
Lenovo	PC	E40	N/A

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **IC —Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 02, 2020	July 01, 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 22, 2022	April 21, 2023
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 21, 2022	March 20, 2023
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June 12, 2022	June 11, 2023
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 23, 2022	June 22, 2023
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	April 22, 2022	April 21, 2023
9	Coaxial Cable	GTS	N/A	GTS211	April 22, 2022	April 21, 2023
10	Coaxial cable	GTS	N/A	GTS210	April 22, 2022	April 21, 2023
11	Coaxial Cable	GTS	N/A	GTS212	April 22, 2022	April 21, 2023
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	April 22, 2022	April 21, 2023
13	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 23, 2022	June 22, 2023
14	Band filter	Amindeon	82346	GTS219	June 23, 2022	June 22, 2023
15	Power Meter	Anritsu	ML2495A	GTS540	June 23, 2022	June 22, 2023
16	Power Sensor	Anritsu	MA2411B	GTS541	June 23, 2022	June 22, 2023
17	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 22, 2022	April 21, 2023
18	Splitter	Agilent	11636B	GTS237	June 23, 2022	June 22, 2023
19	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 30, 2021	Nov. 29, 2022
20	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 22, 2022	April 21, 2023
21	Breitband hornantenna	SCHWARZBECK	BBHA 9170	GTS579	Oct. 17, 2021	Oct. 16, 2022
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 17, 2021	Oct. 16, 2022
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 17, 2021	Oct. 16, 2022
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June 23, 2022	June 22, 2023
25	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 22, 2022	April 21, 2023

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May 14, 2022	May 13, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 24, 2022	April 23, 2023
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 23, 2022	June 22, 2023
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	April 22, 2022	April 21, 2023
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	JINCHUANG	GSP-8A	GTS639	April 28, 2022	April 27, 2023
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	April 15, 2022	April 14, 2023
9	ISN	SCHWARZBECK	NTFM 8158	GTS565	April 22, 2022	April 21, 2023
10	High voltage probe	SCHWARZBECK	TK9420	GTS537	April 22, 2022	April 21, 2023

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 22, 2022	April 21, 2023
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 22, 2022	April 21, 2023
3	Spectrum Analyzer	Agilent	E4440A	GTS536	April 22, 2022	April 21, 2023
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 22, 2022	April 21, 2023
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 22, 2022	April 21, 2023
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 22, 2022	April 21, 2023
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 22, 2022	April 21, 2023
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 22, 2022	April 21, 2023


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	April 25, 2022	April 24, 2023
2	Barometer	KUMAO	SF132	GTS647	July 26, 2022	July 25, 2023

7 Test results and Measurement Data

7.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	The antenna is integral antenna, reference to the appendix II for details.

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	 <p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure:	<ol style="list-style-type: none"> 1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					


Measurement data:

Test mode:	Transmitting mode(908.42MHz)	Phase Polarity:	Line
------------	------------------------------	-----------------	------




Freq	Reading	LISN/ISN	Cable	Limit	Over	Remark	
MHz	dBuV	factor	loss	Level	level		
		dB	dB	dBuV	dBuV	dB	
0.32	23.87	9.98	0.01	33.86	59.80	-25.94	QP
0.32	15.33	9.98	0.01	25.32	49.80	-24.48	Average
0.50	18.29	9.96	0.01	28.26	56.00	-27.74	QP
0.50	10.08	9.96	0.01	20.05	46.00	-25.95	Average
0.63	23.46	9.96	0.02	33.44	56.00	-22.56	QP
0.63	12.87	9.96	0.02	22.85	46.00	-23.15	Average
0.95	22.84	9.96	0.03	32.83	56.00	-23.17	QP
0.95	13.72	9.96	0.03	23.71	46.00	-22.29	Average
1.11	20.37	9.94	0.03	30.34	56.00	-25.66	QP
1.11	11.76	9.94	0.03	21.73	46.00	-24.27	Average
1.97	20.52	9.84	0.04	30.40	56.00	-25.60	QP
1.97	20.67	9.84	0.04	30.55	46.00	-15.45	Average


Test mode:	Transmitting mode(908.42MHz)	Phase Polarity:	Neutral
------------	------------------------------	-----------------	---------



Test mode:	Transmitting mode(916MHz)	Phase Polarity:	Line
------------	---------------------------	-----------------	------




Test mode:	Transmitting mode(916MHz)	Phase Polarity:	Neutral
------------	---------------------------	-----------------	---------




Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 10GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	902-928MHz	94.00		QP Value	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	Below 30MHz				
	 <p>Below 1GHz</p>				

	 <p>Above 1GHz</p>					
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 					
<p>Test environment:</p>	<p>Temp.:</p>	<p>25 °C</p>	<p>Humid.:</p>	<p>52%</p>	<p>Press.:</p>	<p>1 012mbar</p>
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>					

Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

■ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


7.3.1 Field Strength of The Fundamental Signal and spurious emissions

QP value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
908.42	94.00	23.97	4.88	37.36	85.49	94.00	-8.51	Vertical
908.42	100.00	23.97	4.88	37.36	91.49	94.00	-2.51	Horizontal
916.00	91.61	24.03	4.91	37.36	83.19	94.00	-10.81	Vertical
916.00	97.61	24.03	4.91	37.36	89.19	94.00	-4.81	Horizontal


■ 30MHz-1GHz

Test mode:	Transmitting mode (908.42MHz)	Antenna Polarity:	Horizontal
------------	-------------------------------	-------------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
95.762	53.57	9.25	0.00	36.07	26.75	43.50	-16.75	QP
203.523	57.81	9.40	0.00	36.62	30.59	43.50	-12.91	QP
250.301	55.39	11.44	0.00	36.77	30.06	46.00	-15.94	QP
451.135	49.04	16.72	0.00	37.06	28.70	46.00	-17.30	QP
902.000	41.05	23.92	0.00	37.36	27.61	46.00	-18.39	QP
928.000	39.85	24.13	0.00	37.37	26.61	46.00	-19.39	QP

Test mode:	Transmitting mode (908.42MHz)	Antenna Polarity:	Vertical
------------	-------------------------------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
107.888	55.68	10.32	0.00	36.16	29.84	43.50	-13.66	QP
250.301	52.96	11.44	0.00	36.77	27.63	46.00	-18.37	QP
287.990	49.71	12.70	0.00	36.87	25.54	46.00	-20.46	QP
411.824	47.66	15.95	0.00	37.02	26.59	46.00	-19.41	QP
902.000	40.05	23.92	0.00	37.36	26.61	46.00	-19.39	QP
928.000	40.79	24.13	0.00	37.37	27.55	46.00	-18.45	QP

Test mode:	Transmitting mode (916MHz)	Antenna Polarity:	Horizontal
------------	----------------------------	-------------------	------------




Test mode:	Transmitting mode (916MHz)	Antenna Polarity:	Vertical
------------	----------------------------	-------------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
119.856	57.39	11.19	0.00	36.23	32.35	43.50	-11.15	QP
131.758	58.71	11.93	0.00	36.30	34.34	43.50	-9.16	QP
143.830	55.94	12.44	0.00	36.36	32.02	43.50	-11.48	QP
801.786	49.63	22.72	0.00	37.30	35.05	46.00	-10.95	QP
902.000	42.06	23.92	0.00	37.36	28.62	46.00	-17.38	QP
928.000	40.18	24.13	0.00	37.37	26.94	46.00	-19.06	QP


■ Above 1GHz

Test mode:	Transmitting mode (908.42MHz)	Antenna Polarity:	Horizontal
------------	-------------------------------	-------------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1432.000	49.39	24.53	2.25	38.95	37.22	74.00	-36.78	Peak
2413.000	50.02	27.30	2.93	38.57	41.68	74.00	-32.32	Peak
3583.000	46.57	28.72	3.82	38.45	40.66	74.00	-33.34	Peak
4663.000	44.66	30.66	4.54	38.33	41.53	74.00	-32.47	Peak
5077.000	44.12	31.71	4.90	38.43	42.30	74.00	-31.70	Peak
6931.000	45.37	35.33	6.18	38.89	47.99	74.00	-26.01	Peak

Test mode:	Transmitting mode (908.42MHz)	Antenna Polarity:	Vertical
------------	-------------------------------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1756.000	50.62	25.67	2.44	38.60	40.13	74.00	-33.87	Peak
2719.000	48.48	27.93	3.17	38.60	40.98	74.00	-33.02	Peak
3439.000	47.12	28.60	3.67	38.51	40.88	74.00	-33.12	Peak
4681.000	44.29	30.71	4.55	38.34	41.21	74.00	-32.79	Peak
5212.000	43.51	31.90	5.00	38.48	41.93	74.00	-32.07	Peak
6976.000	44.43	35.44	6.23	38.90	47.20	74.00	-26.80	Peak

Test mode:	Transmitting mode (916MHz)	Antenna Polarity:	Horizontal
------------	----------------------------	-------------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1756.000	49.48	25.67	2.44	38.60	38.99	74.00	-35.01	Peak
3079.000	46.61	28.60	3.49	38.58	40.12	74.00	-33.88	Peak
3583.000	46.04	28.72	3.82	38.45	40.13	74.00	-33.87	Peak
5005.000	44.14	31.61	4.84	38.40	42.19	74.00	-31.81	Peak
6391.000	43.20	33.91	5.76	38.78	44.09	74.00	-29.91	Peak
6922.000	44.17	35.31	6.17	38.88	46.77	74.00	-27.23	Peak

Test mode:	Transmitting mode (916MHz)	Antenna Polarity:	Vertical
------------	----------------------------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1135.000	49.84	24.40	2.09	39.60	36.73	74.00	-37.27	Peak
2197.000	46.68	27.04	2.68	38.48	37.92	74.00	-36.08	Peak
3448.000	46.54	28.60	3.69	38.51	40.32	74.00	-33.68	Peak
4717.000	44.24	30.81	4.57	38.34	41.28	74.00	-32.72	Peak
5068.000	44.40	31.70	4.88	38.43	42.55	74.00	-31.45	Peak
6751.000	43.87	34.90	6.02	38.85	45.94	74.00	-28.06	Peak

Remark:

1. $Final\ Level = Receiver\ Read\ level + Antenna\ Factor + Cable\ Loss - Preamplifier\ Factor$

7.4 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 902MHz~928MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

908.42MHz

Operation Frequency	20dB bandwidth(kHz)	Result
908.42MHz	11.015	Pass
916MHz	9.734	Pass

Test plot as follows:



8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----