

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

WIFI 2.4G

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2437MHz	28.16	654.636	0.08785	1.0	PASS

Remark: antenna gain=-1.71dBi

z-wave

Frequency	Field strength (dBuV/m@3m)	EIRP (dBm)	P _{conducted} (dBm)	P _{conducted} (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
908.42MHz	91.11	-4.05	2.55	1.799	0.00008	0.61	PASS
916MHz	91.13	-4.03	2.57	1.807	0.00008	0.61	PASS

Remark: antenna gain=-6.6dBi

Simultaneous Transmission

Mode	WIFI	z-wave	
		908.42MHz	916MHz
Output power (dBm)	28.16	2.55	2.57
Output power (mW)	654.636	1.799	1.807
Antenna gain (dBi)	-1.71	-6.6	-6.6
ERP (mW)	441.57	0.24	0.24
P _{th} / ERP _{th}	3060	1853	
$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$		0.214	
$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$		0.144	
$\sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k}$		0.088	
$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k}$		0.446	
Limit		1	

The max power density is less than MPE exempt limit, so it is compliance.