

# TEST REPORT

<p><b>DT&amp;C Co., Ltd.</b> 42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel : 031-321-2664, Fax : 031-321-1664</p>	<p>Report No : DRTFCC1609-0121 Pages:(1) / (7) page</p>	
---	---	---

1. Customer

- Name : IDRO Co., Ltd.
- Address : (I-ui-dong, 305, (lui-dong, Guangkyo Business Center)), 305, 156, Gwanggyo-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea

2. Use of Report : FCC Original Grant

3. Product Name (FCC ID): Wireless Charger (XVY-IDROWC-100)

4. Date of Test : 2016-08-11

5. Test Method Used : FCC Part 1.1310

6. Testing Environment : See appended test report

7. Test Result :  Pass  Fail

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by Name : Jaejin Lee (Signature)	Technical Manager Name : Geunki Son (Signature)
-------------	--	--

2016 . 09 . 06 .

**DT&C Co., Ltd.**

## Test Report Version

Test Report No.	Date	Description
DRTFCC1609-0121	Sep. 06, 2016	Initial issue

## **CONTENTS**

<b>1. Equipment information .....</b>	<b>4</b>
1.1 Equipment description .....	4
1.2 Support equipment.....	4
<b>2. Information about test items .....</b>	<b>5</b>
2.1 Test Configuration and Mode .....	5
2.2 Tested environment.....	5
<b>3. E and H field strength .....</b>	<b>6</b>

## 1. Equipment information

### 1.1 Equipment description

FCC Equipment Class	Part 15 Low Power Transmitter Below 1705 kHz (DCD)
Equipment type	Wireless Charger
Equipment model name	IDROWC-100
Equipment add model name	NA
Equipment serial no.	Identical prototype
Hardware version	2.0
Frequency range	110 ~ 205kHz
Output power	Max : 5 W
Power	AC 120V 60Hz
Antenna type	Coil Antenna(single coil)

### 1.2 Support equipment

Equipment	Model No.	Serial No.	Manufacturer	Note
Travel adapter	NA	NA	SAMSUNG	-
Client device	WPC RX Board	NA	LG Innotek	-
-	-	-	-	-

Note: The above equipment was supported by manufacturer.

## 2. Information about test items

### 2.1 Test Configuration and Mode

#### •Test configuration

The field strength of both E-field and H-field were measured at 10 cm using RF exposure survey meter with E-field and H-field probes for determining compliance with the MPE requirements of FCC Part 1.1310

During measurements, the wireless charging pad (EUT) was loaded with the client device using the resistor as described below summary table for test modes and conditions.

These testing were performed at test configuration as test setup diagram on clause 3 of this test report.

EUT was placed on a non-conductive turntable, and the client device with resistive load for drawing various load current. This device uses a wireless charging circuit for power transfer operating at the frequency of 110 KHz ~ 205 KHz. Thus, the 300 KHz RF exposure limits were used as below table

#### •Test mode

This device has been tested with the below test modes and charging current conditions:

Test Mode (Charging Current)	Load condition	Support Equipment
Low mA	50.0 $\Omega$	Client device(WPC RX Board)
Mid mA	16.0 $\Omega$	
High mA	5.3 $\Omega$	

#### • Limit

	Frequency	E-Field limit	H-Field limit
FCC Part 1.1310	300 kHz ~ 3 MHz	614 V/m	1.63 A/m


### 2.2 Tested environment

Temperature	: 24 °C
Relative humidity content	: 41 % R.H.
Details of power supply	: AC 120 V 60 Hz

### 3. E and H field strength

For RF exposure purposes, the E and H field strengths are measured separately with E and H probes and meters at different locations surrounding the test setup.

▪ **Test setup diagram**



▪ **Measurement procedure: KDB 680106**

These testing were performed at test configuration as above diagram.

EUT was placed on a turntable, and the measurement distance of 10 Cm from the center of the probe to the edge of the device. And test was performed all sides of the EUT(except bottom side).

▪ **Measurement data:**

Test Mode	E-field(V/m)					Limit(V/m)
	Front	Rear	Left	Right	Top	
Low mA	3.000	2.590	1.910	2.960	4.490	614
Mid mA	3.290	3.240	2.090	2.910	<b>4.800</b>	
High mA	2.980	2.780	2.250	2.740	4.630	

Test Mode	H-field(A/m)					Limit(A/m)
	Front	Rear	Left	Right	Top	
Low mA	<b>0.205</b>	0.157	0.150	0.162	0.154	1.64
Mid mA	0.193	0.160	0.154	0.146	0.169	
High mA	0.203	0.163	0.169	0.158	0.167	

**•Test equipment list**

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next. Cal.Date (yy/mm/dd)	S/N
EMF Meter	NARDA	ELT-400	16/07/13	18/07/13	N-0342
EMF probe	NARDA	B-Field Probe	16/07/13	18/07/13	M-0779
Broadband field meter	NARDA	NBM-550	16/08/02	18/08/02	E-1275
Broadband field probe	NARDA	EF-0391	16/08/02	18/08/02	D-0894