



■ Report No.: DDT-R18060607-1E6

■ Issued Date: Jul. 31, 2018

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	KOKKIA, INC
<b>Address</b>	:	43575 Mission Blvd, #302, Fremont, CA94539,USA
<b>Equipment under Test</b>	:	Digital Bluetooth Splitter Transmitter
<b>Model No.</b>	:	USB_Splitter/USB_Splitter_Pro
<b>Trade Mark</b>	:	KOKKIA
<b>FCC ID</b>	:	XWA-USBX-X
<b>Manufacturer</b>	:	KOKKIA, INC
<b>Address</b>	:	43575 Mission Blvd, #302, Fremont, CA94539,USA

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## TABLE OF CONTENTS

Test report declares.....	3
1. General information.....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory .....	5
2. RF Exposure evaluation for FCC .....	5

## TEST REPORT DECLARE

<b>Applicant</b>	:	KOKKIA, INC
<b>Address</b>	:	43575 Mission Blvd, #302, Fremont, CA94539,USA
<b>Equipment under Test</b>	:	Digital Bluetooth Splitter Transmitter
<b>Model No.</b>	:	USB_Splitter/USB_Splitter_Pro
<b>Trade mark</b>	:	KOKKIA
<b>Manufacturer</b>	:	KOKKIA, INC
<b>Address</b>	:	43575 Mission Blvd, #302, Fremont, CA94539,USA

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R18060607-1E6	
<b>Date of Receipt:</b>	Jul. 18, 2018	<b>Date of Test:</b> Jul. 18, 2018 ~ Jul. 31, 2018

**Prepared By:**

*Ella Gong*  
Ella Gong/Engineer



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 31, 2018	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Digital Bluetooth Splitter Transmitter
Model Number	: USB_Splitter/USB_Splitter_Pro
Difference of model number	: All models are identical except the software functions, USB_Splitter_Pro add the Aptx function, therefore the test performed on the model USB_Splitter.
EUT function description	: Please reference user manual of this device
Power supply	: DC 3.3V from PC or Notebook
Radio Specification	: Bluetooth V4.1
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1Mbps, 2Mbps, 3Mbps
Antenna Type	: Clip antenna, maximum PK gain: 2.3dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2480MHz, 0.81dBm (1.21mW) output power]

$(1.21/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.381 < 3.0$  for 1-g SAR

Then SAR evaluation is not required

**END OF REPORT**