



Product Service

**Choose certainty.
Add value.**

Report On

FCC Testing of the
Sepura Ltd STP8080
In accordance with FCC CFR 47 Part 15C and
Industry Canada RSS-210

COMMERCIAL-IN-CONFIDENCE

FCC ID: XX6STP8080
IC ID: 8739A-STP8080

Document 75915053 Report 03 Issue 1

June 2012



Product Service

TÜV SÜD Product Service Ltd, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuvps.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

FCC Testing of the
Sepura Ltd STP8080
In accordance with FCC CFR 47 Part 15C and
Industry Canada RSS-210

Document 75915053 Report 03 Issue 2

June 2012

PREPARED FOR

Sepura Ltd
Radio House
St Andrews Road
Cambridge
CB4 1GR

PREPARED BY

Natalie Bennett
Senior Administrator (Technical)

APPROVED BY

Mark Jenkins
Authorised Signatory

DATED

12 June 2012

This report has been up-issued to Issue 2 to include references to RSS-210.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 15C and Industry Canada RSS-210. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s);

A Guy





CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Brief Summary of Results 5
1.3	Application Form 6
1.4	Product Information 8
1.5	Test Conditions 8
1.6	Deviations from the Standard 8
1.7	Modification Record 8
2	TEST DETAILS 9
2.1	Spurious and Band Edge Emissions 10
3	TEST EQUIPMENT USED 25
3.1	Test Equipment Used 26
3.2	Measurement Uncertainty 27
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT 28
4.1	Accreditation, Disclaimers and Copyright 29



Product Service

SECTION 1

REPORT SUMMARY

FCC Testing of the
Sepura Ltd STP8080
In accordance with FCC CFR 47 Part 15C and Industry Canada RSS-210



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the FCC Testing of the Sepura Ltd STP8080 to the requirements of FCC CFR 47 Part 15C and Industry Canada RSS-210.

Objective	To perform FCC Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Sepura Ltd
Model Number(s)	STP8080
Serial Number(s)	2PN601020G471E0
Number of Samples Tested	1
Test Specification/Issue/Date	FCC CFR 47 Part 15C (2010) Industry Canada RSS-210 (2010)
Incoming Release Date	Application Form 07 September 2011
Disposal Reference Number Date	Held Pending Disposal Not Applicable Not Applicable
Order Number Date	319138/T0201 10 August 2011
Start of Test	23 September 2011
Finish of Test	23 September 2011
Name of Engineer(s)	A Guy
Related Document(s)	ANSI C63.10: 2009

This testing was performed to FCC CFR 47 Part 15C; 2010 but a comparison has been made between this and the latest version FCC CFR 47 Part 15C; 2011 and as there are no changes to the testing covered by this report the product can be deemed to be compliant with the latest version.



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with FCC CFR 47 Part 15C and Industry Canada RSS-210 is shown below.

Section	Spec Clause		Test Description	Result	Comments/Base Standard
	FCC	IC			
Bluetooth					
2.1	15.247 (d)	A8.5	Spurious and Band Edge Emissions	Pass	



1.3 APPLICATION FORM

APPLICANT'S DETAILS	
COMPANY NAME :	SEPURA plc
ADDRESS :	Radio House St Andrews Road Cambridge CB4 1GR
NAME FOR CONTACT PURPOSES :	Bob Allen
TELEPHONE NO 01223 877291	FAX NO: E-MAIL bob.allen@sepura.com

EQUIPMENT INFORMATION			
Model name/number	STP8000	Identification/Part number	STP8080
Hardware Version	Revision B	Software Version	V10
Manufacturer	Plexus Melex	Country of Origin	Romania Austria
FCC ID	XX6STP8080	Industry Canada ID	8739A-STP8080
Technical description (a brief description of the intended use and operation) Tetra hand portable for TMO, DMO and repeater use. Fitted with Bluetooth and GPS Modules			
<u>Supply Voltage:</u> ☐ AC mains ☐ DC (external) ☒ DC (internal) State AC voltage V State DC voltage V State DC voltage 7.4 V and AC frequency Hz and DC current A and Battery type LI Polymer			
<u>Frequency characteristics:</u> Transmitter Frequency range 809 MHz to 824 MHz 854 MHz to 869 MHz Receiver Frequency range 854 MHz to 869 MHz (if different) Channel spacing 25KHz (if channelized)			
Designated TX test frequencies: Bottom: 809.025 MHz Middle: 816.525 MHz Top: 823.975 MHz			
Designated TX test frequencies: Bottom: 854.025 MHz Middle: 861.525 MHz Top: 868.975 MHz			
Designated RX test frequencies: Bottom: 854.025 MHz Middle: 861.525 MHz Top: 868.975 MHz			
Intermediate Frequencies : 69.25 MHz Highest Internally Generated Frequency : 3144.84 MHz on GPS Chip			
<u>Power characteristics:</u> Maximum transmitter power 1.8W ☐ Continuous transmission ☒ Intermittent transmission (Continuous transmission 1 slot in 4 transmission) If intermittent, can transmitter be set to continuous transmit test mode? Yes with care at 4 slots in 4, for emission mask only Minimum transmitter power W (if variable)			
<u>Antenna characteristics:</u> ☒ Antenna connector ☐ Temporary antenna connector ☐ Integral antenna State impedance 50 ohm State impedance ohm State gain dBi			



Product Service

Modulation characteristics:			
[]	Amplitude	☒ [X]	Other
[]	Frequency	Details: Pi/4DQPSK	
[]	Phase	(GMSK, QSPK etc)	
Can the transmitter operate un-modulated?		Yes simulated	
ITU Class of emission: 25K0Q1D			
Battery/Power Supply			
Model name/number		Identification/Part number	
Manufacturer		Country of Origin	
Ancillaries (if applicable)		See Attached Sheet	
Model name/number		Identification/Part number	
Manufacturer		Country of Origin	
Extreme conditions:			
Maximum temperature	55°C	Minimum temperature	-20°C
Maximum supply voltage	7.4V	Minimum supply voltage	6.4 V

I hereby declare that I am entitled to sign on behalf of the applicant and that the information supplied is correct and complete.

Signature :

Name : Bob Allen

Position held : Test Authority

Date : 07 September 2011



Product Service

1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) was a Sepura Ltd STP8080. A full technical description can be found in the manufacturer's documentation.

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure.

The EUT was powered from a 7.4 V DC supply.

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standards or test plan were made during testing.

1.7 MODIFICATION RECORD

Modification 0 - No modifications were made to the test sample during testing.



Product Service

SECTION 2

TEST DETAILS

FCC Testing of the
Sepura Ltd STP8080
In accordance with FCC CFR 47 Part 15C and Industry Canada RSS-210



Product Service

2.1 SPURIOUS AND BAND EDGE EMISSIONS

2.1.1 Specification Reference

FCC CFR 47 Part 15C, Clause 15.247 (d)
Industry Canada RSS-210, Clause A8.5

2.1.2 Equipment Under Test and Modification State

STP8080 S/N: 2PN601020G471E0 - Modification State 0

2.1.3 Date of Test

23 September 2011

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Procedure

The band edge measurements were performed in accordance with ANSI C63.10, Clause 6.9.3. The results were analysed to ensure compliance with restricted bands. The EUT was set to the lowest and highest operating frequencies.

2.1.6 Environmental Conditions

Ambient Temperature	20.0°C
Relative Humidity	46.0%



Product Service


2.1.7 Test Results

7.4 V DC Supply

Spurious Radiated Emissions

2402 MHz

30 MHz to 1 GHz



Frequency (MHz)	QP Level (dBuV/m)	QP Limit (dBuV/m)	QP Margin (dBuV/m)	Angle (Deg)	Height (m)	Polarity
32.844	27.1	39.1	-12.0	269	2.75	Vertical
372.619	23.4	46.4	-23.0	0	1.00	Horizontal
391.370	23.9	46.4	-22.5	356	1.00	Horizontal
460.542	26.0	46.4	-20.4	0	1.00	Horizontal
647.582	28.3	46.4	-18.1	344	1.00	Horizontal
940.847	31.8	46.4	-14.6	10	1.00	Horizontal




Product Service

1 GHz to 25 GHz

Frequency (GHz)	Antenna Polarisation	Antenna Height (cm)	EUT Arc (degrees)	Final Peak (dBµV/m)	Final Average (dBµV/m)
4.802	Vertical	158	111	46.61	33.29


1 GHz to 4 GHz






Product Service

4 GHz to 8 GHz




8 GHz to 13 GHz






Product Service

13 GHz to 18 GHz




18 GHz to 25 GHz





Product Service

2441 MHz30 MHz to 1 GHz

Frequency (MHz)	QP Level (dBμV/m)	QP Limit (dBμV/m)	QP Margin (dBμV/m)	Angle (Deg)	Height (m)	Polarity
32.402	27.2	40.0	-12.8	317	1.00	Vertical
411.771	25.0	46.0	-21.0	353	1.00	Vertical
460.657	27.0	46.0	-19.0	348	1.00	Horizontal
540.027	28.0	46.0	-18.0	312	1.00	Horizontal
706.657	29.0	46.0	-17.0	0	1.00	Horizontal
940.959	32.8	46.0	-13.2	301	1.00	Vertical




Product Service

1 GHz to 25 GHz

Frequency (GHz)	Antenna Polarisation	Antenna Height (cm)	EUT Arc (degrees)	Final Peak (dBµV/m)	Final Average (dBµV/m)
4.882	Vertical	100	180	46.15	33.58


1 GHz to 4 GHz






Product Service

4 GHz to 8 GHz




8 GHz to 13 GHz






Product Service

13 GHz to 18 GHz




18 GHz to 25 GHz





2480 MHz

30 MHz to 1 GHz



Frequency (MHz)	QP Level (dBμV/m)	QP Limit (dBμV/m)	QP Margin (dBμV/m)	Angle (Deg)	Height (m)	Polarity
33.153	27.0	40.0	-13.0	213	1.00	Vertical
460.664	26.5	46.0	-19.5	282	3.95	Vertical
564.156	28.1	46.0	-17.9	4	1.00	Horizontal
706.535	29.0	46.0	-17.0	142	3.20	Horizontal
775.389	30.2	46.0	-15.8	100	1.00	Vertical
905.427	31.4	46.0	-14.6	360	1.00	Vertical




Product Service

1 GHz to 25 GHz

Frequency (GHz)	Antenna Polarisation	Antenna Height (cm)	EUT Arc (degrees)	Final Peak (dBµV/m)	Final Average (dBµV/m)
4.960	Vertical	105	154	45.52	32.59
9.920	Vertical	205	279	51.22	N/A*

*Within non-restricted band.


1 GHz to 4 GHz






Product Service

4 GHz to 8 GHz




8 GHz to 13 GHz






Product Service

13 GHz to 18 GHz



18 GHz to 25 GHz



Limit

Peak (dBμV/m)	Average (dBμV/m)
74.0	54.0




Product Service

Band Edge Emissions

2402 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	40.75	8.77






Product Service

2480 MHz

Polarisation	Final Peak (dBµV/m)	Final Average (dBµV/m)
Horizontal	47.37	21.41



Limit

Peak (dBµV/m)	Average (dBµV/m)
74.0	54.0



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.1 - Radiated Emissions					
Antenna (Double Ridge Guide, 1GHz-18GHz)	EMCO	3115	234	12	12-Nov-2011
Antenna (Double Ridge Guide, 1GHz-18GHz)	EMCO	3115	235	12	12-Nov-2011
Amplifier (Low Noise, 18GHz-40GHz)	Narda	NARDA DB02-0447	237	12	24-Jun-2012
Dual Power Supply Unit	Thurlby	PL320	288	-	TU
Antenna (Double Ridge Guide)	Q-Par Angus Ltd	QSH 180K	1511	24	2-Aug-2012
Mast Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Test Receiver	Rohde & Schwarz	ESIB26	2085	12	14-Dec-2011
Antenna (Bilog)	Chase	CBL6143	2904	24	12-May-2013
Amplifier (8 - 18GHz)	Phase One	PS06-0061	3176	12	5-Jul-2012
High Pass Filter (3GHz)	RLC Electronics	F-100-3000-5-R	3349	12	27-May-2012
Signal Generator, 9kHz to 6GHz	Rohde & Schwarz	SMB 100A	3499	12	24-May-2012
Tilt Antenna Mast	maturo GmbH	TAM 4.0-P	3916	-	TU
Mast Controller	maturo GmbH	NCD	3917	-	TU
Low Noise Amplifier	Wright Technologies	APS04-0085	3969	12	8-Jul-2012

TU – Traceability Unscheduled

O/P MON – Output Monitored with Calibrated Equipment



Product Service

3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	MU
Spurious and Band Edge Emissions	30MHz to 1GHz: ± 5.1 dB 1GHz to 40GHz: ± 6.3 dB



Product Service

SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service Limited

© 2012 TÜV SÜD Product Service Limited