MDE\_NXP\_0901



NXP Semiconductors Hugues de Perthuis 2 esplanade Anton Philips, Campus EffiScience, Colombelles BP2000 France

Holger Leutfeld 17.08.2010 Phone +49 (0) 2102 749 317 Fax +49 (0) 2102 749 350 e-Mail : Holger.Leutfeld@7layers.de

# Maximum Permissible Exposure for product: OM12000 / FCC ID XXMOM12000

Dear Mr. de Perthuis,

please find enclosed your Maximum Permissible Exposure calculations for the NXP Module OM12000 / FCC ID: XXMOM12000.

Best Regards

lo. feut feid

Holger Leutfeld (Project Manager)

7 layers AG in: Borsigstrasse 11 40880 Ratingen, Germany Phone: +49 (0) 2102 749 0 Fax: +49 (0) 2102 749 350 www.7Layers.com Aufsichtsratsvorsitzender •

Chairman of the Supervisory Board: Markus Becker Vorstand • Board: Dr. Hans Jürgen Meckelburg Wilfried Klassmann Registergericht • registered

Düsseldorf, HRB 44096 USt-IdNr • VAT No.: DE 203159652 TAX No. 147/5869/0385



## Maximum Permissible Exposure

(as specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure)

Frequency range (MHz)	Power density (mW/cm²)
300 – 1500	f/1500
1,500 – 100000	1.0

(as specified in Table 2 in EN 1999/519-EC)

Frequency range (MHz)	Power density (mW/cm²)
400 – 2000	f/2000
2000 - 300000	1 mW/cm <sup>2</sup>



## Calculations 850 MHz band

Maximum RMS output power at Antenna terminal31.84 dBmMaximum RMS output power at Antenna terminal under consideration of the duty<br/>cycle effect (2TX Slots)25.82 dBm

Maximum output power at Antenna terminal (Please see report MDE\_NXP\_0901\_FCCb)

Prediction distance R:	20 cm
Prediction frequency:	824.20 MHz

MPE limit **S**: 0.5494 mW/cm<sup>2</sup>

Equation OET bulletin 65, page 18, edition 97-01:  $S = EF^*P^*G / (4\pi R^2)$ 

- S = power density
- P = power input to the antenna

 ${\sf G}$  = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum permissible antenna gain considering S limit 8.59 dBi

Maximal permissible antenna gain considering output power limitation of 7 Watts ERP (FCC §22.931).

 $G = 10 \times \log(7000) - 32.25 + 2.14$ 

8.34 dBi

#### Prediction

The maximum allowed MPE value of 0.5494 mW/cm<sup>2</sup>will be reached in a distance of 20 cm in case that an antenna with an antenna gain of 8.59 dBi is udsed. Considering the max output power of 7 Watts ERP (FCC §22.931) for mobile stations the maximum antenna gain is 8.34 dBi, which is lower than 8.59 dBi. For mobile stations the antenna gain is limited to 8.34 dBi in accordance to the FCC regulations.

32.25 dBm



## Calculations 1900 MHz band

Maximum RMS output power at Antenna terminal28.45 dBmMaximum RMS output power at Antenna terminal under consideration of the duty<br/>cycle effect (2TX Slots)22.43 dBm

Maximum output power at Antenna terminal (Please see report MDE\_NXP\_0901\_FCCc)

28.80 dBm

Prediction distance R:20 cmPrediction frequency:1850.2 MHz

MPE limit **S**: 1 mW/cm<sup>2</sup>

Equation OET bulletin 65, page 18, edition 97-01:  $S = EF^*P^*G / (4\pi R^2)$ 

- S = power density
- P = power input to the antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the centre of radiation of the antenna

Maximum permissible antenna gain (Table 1B of 47 CFR 1.1310):	14.58 dBi
Maximum permissible antenna gain for mobile / portable stations:	4.21 dBi
(Considering 2 Watts EIRP FCC §24.235: G=10*log(2000)-28.80)	

### Prediction

The maximum allowed MPE value of 1 mW/cm<sup>2</sup> will be reached in a distance of 20 cm in case that an antenna with an antenna gain of 14.58 dBi is used. Considering the max output power of 2 Watts EIRP (FCC §24.235) for mobile / portable stations the maximum antenna gain is 4.21 dBi, which is lower than 14.58 dBi. For mobile and portable stations the antenna gain is limited to 4.21 dBi in accordance with the FCC regulations.