

RF EXPOSURE EVALUATION REPORT

Testing laboratory:

SK Tech Co., Ltd.
88, Geulgaetul-ro, 81beon-gil,
Wabu-eup, Namyangju-si,
Gyeonggi-do, Korea
TEL: +82-31-576-2204
FAX: +82-31-576-2205

Test Report Number: SKT-RET-230006

Date of issue: April 24, 2023

Applicant:

Intellian Technologies, Inc.
18-7, Jinwisandan-ro, Jinwi-myeon (Chungho-ri)
Pyeongtaek-si, Gyeonggi-do, 17709 Korea

Manufacturer:

Intellian Technologies, Inc.
18-7, Jinwisandan-ro, Jinwi-myeon (Chungho-ri)
Pyeongtaek-si, Gyeonggi-do, 17709 Korea

Product:

OW130L

Model:

PS-OW130P

FCC ID:

XXZ-INTOW130L

Project number:

SKTEU23-0067


EUT received:

January 13, 2023

Type of Evaluation:

RF Exposure Evaluation

The above equipment has been tested by SK Tech Co., Ltd., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product or system, which was tested.



Changwon Yang / **Testing Engineer**



Jongsoo Yoon / **Technical Manager**

This report shall not be reproduced except in full, without the written approval of SK Tech Co., Ltd. The client should not use it to claim product endorsement by any government agencies.



Revision History of Test Report

Rev.	Revisions	Effect page	Approved by	Date
-	Initial issue	All	Jongsoo Yoon	April 24, 2023



TABLE OF CONTENTS

1	Description of equipment under test (EUT).....	4
2	FCC Exposure Limits	4
3	Prediction of MPE limit at given distance	5



1 Description of equipment under test (EUT)

Product: OW130L
 Model: PS-OW130P
 Serial number: None (prototype)
 Hardware version: prototype
 Software version: prototype

Model differences:

Model name	Difference	Tested (checked)
PS-OW130P	fully tested model that was provided by the applicant.	<input checked="" type="checkbox"/>

Technical data:

Technologies	Bandwidth	Max. power output (conducted)	Max. antenna gain	Max. EIRP
Satellite 14000 MHz to 14500 MHz	19.8 MHz	26.8 dBm	43.1 dBi	69.9 dBm
Satellite 14000 MHz to 14500 MHz	39.6 MHz	29.8 dBm	43.1 dBi	72.9 dBm

2 FCC Exposure Limits

2.1. FCC, CFR 47 Section

The table below is excerpted from Table 1 of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), (ii) Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
1500 - 100000	1.0	30

where f = frequency in MHz

NOTE: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



3 Prediction of MPE limit at given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

Linear form $S = PG / 4\pi R^2$

Where: *S* is the power density (W/m^2)

P is the power delivered to the antenna (*W*)

G is the antenna gain observed in the far-field region (linear)

R is the distance from antenna to point of interest (*m*)

Prediction: worst case [under FCC, CFR 47 Section]

Technologies:		Satellite		
	Frequency	14 263	14 272.9	MHz
PG	Declared max power (EIRP)	69.9	72.9	dBm
R	Distance	1250	1250	cm
S	MPE limit for uncontrolled exposure	1.0	1.0	mW/cm ²
	Calculated Power density:	0.498	0.993	mW/cm²

This prediction demonstrates the following:

The power density levels at a distance of 12.5 meters are below the maximum levels allowed by regulations.