

RF Exposure Report (FCC)

Report No.: WIR132223-RF Exposure Rev. 2

Test Model: OW11Fx

Test Date: July 1, 2024

Issued Date: July 25, 2024

Applicant: Intellian Technologies USA Inc
2600 Tower Oaks Boulevard, Suite 400

Address: Rockville, MD 20852
United States

Issued By: Eurofins Electrical and Electronic Testing NA, Inc.

Lab Address: 914 W. Patapsco Avenue, Baltimore, MD 21230



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins Electrical and Electronic Testing NA, Inc. While use of the A2LA logo in this report reflects Eurofins Electrical and Electronic Testing NA, Inc. accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins Electrical and Electronic Testing NA, Inc. is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

1. Certificate of Conformity

Product: OW11Fx

FCC ID: XXZ-OW11FX

Brand: Intellian Technologies USA Inc

Test Model: OW11Fx

Applicant: Intellian Technologies USA Inc

Test Date: July 1, 2024

Standard: 47 CFR FCC Part 2.1093



Donald Salguero
Wireless Laboratory Engineer

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements.



Michael Griffiths
Manager, Wireless Laboratory

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	July 8, 2024	Initial Issue.
1	July 10, 2024	Added Appendix.
2	July 25, 2024	Updated FCC ID.

2. RF Exposure

Requirement:

47 CFR 2.1091(c)(1)

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for mobile devices with single RF sources having either more than an available maximum time-averaged power of 1 mW or more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), whichever is greater. For mobile devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 of this chapter is necessary if the ERP of the device is greater than ERP_{20cm} in the formula below. If the ERP of a single RF source at distances from 20 centimeters to 40 centimeters and frequencies from 0.3 GHz to 6 GHz is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP) in comparison with the following formula only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

47 CFR 2.1091(c)(2)

For multiple mobile or portable RF sources within a device operating in the same time averaging period, routine environmental evaluation is required if the formula in § 1.1307(b)(3)(ii)(B) of this chapter is applied to determine the exemption ratio and the result is greater than 1.

Evaluation:

FCC RF exposure

Limit per 1.1310 for a transmitter operating on frequency range (1500-100000 MHz) : **1mW/cm²**

Scenario: Antenna installed such that main lobe is aimed at 37 degrees elevation from the horizon.

Operating Frequency: 14-14.5 GHz

Max Conducted Power: 18.16dBm

Max Off-Axis Antenna Gain between 0-10 degrees of elevation: 7.2dBi

EIRP: 25.36 dBm = 344 mW

Operational Duty Cycle = 20%

Duty Cycle Corrected Max EIRP = 68.8 mW

$$S = \frac{EIRP}{4\pi r^2} \left[\frac{mW}{cm^2} \right]$$

Solving for the safe distance

$$r = \sqrt{\frac{EIRP}{4\pi S}} \text{ [cm]}$$

$$R = \sqrt{(68.8 / (4 * 3.1416 * 1))} = 2.34 \text{ cm}$$

Minimum safe distance for a mobile/fixed device is 20 cm

Since $R \leq 20\text{cm}$, EUT's Safe separation distance is 20 cm

3. Appendix

Subject: Intellian Flat Panel Enterprise Series (OW11Fx)

To Whom it May Concern:

This letter is intended as formal communication that Intellian's Flat Panel Enterprise Series (OW11Fx) utilizes the same hardware, firmware and software across all three variants of the portfolio.

There are no variations or modifications between the OW11FL, OW11FM and OW11FV. The capabilities required to support the associated use cases within each market are managed through software.

Please do not hesitate to reach out if you have any questions or require further clarification.

Sincerely,

A handwritten signature in black ink, appearing to be 'Toni Kousiafes', with a long horizontal stroke extending to the right.

Toni Kousiafes

VP of Product Management | Advanced Development Center

Intellian Technologies