



TEST REPORT

Part 15 Subpart B&C 15.247

Equipment under test Portable SKIN/HAIR Diagnosis System

Model name ASNII

FCC ID XYCASNII

Applicant Aram Huvis Co., Ltd.

Manufacturer Aram Huvis Co., Ltd.

Date of test(s) 2012.11.17 ~ 2012.12.03

Date of issue 2012.12.10

Issued to

Aram Huvis Co., Ltd.

801 Byucksan Technopia, 434-6 Sangdaewon-dong, Sunnam-City, Kyungki-do, Korea



Issued by

KES Co., Ltd.

C3701 Dongil Techno Town, 889-1, Gwanyang 2-dong, Dongan-gu, Anyang-si,
Gyeonggi-do, 431-716, Korea

477-6, Hageo-ri, Yeoju-eup, Yeoju-gun, Gyeonggi-do, 469-803, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
J.J. Lee Test engineer	Gyu-cheol Shin Technical manager

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Revision history

Revision	Date of issue	Test report No.	Description
-	2012.12.10	KES-RF-120086	Initial



KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

TABLE OF CONTENTS

1.0	General product description.....	4
1.1	Test frequency.....	4
1.2	Information about variant model	4
1.3	Device modifications	4
1.4	Device Information	4
1.5	Test facility	5
1.6	Laboratory accreditations and listings	5
2.0	Summary of tests	6
2.1	Test data	7
2.1.1	Pre-scanned output power	7
2.1.2	6 dB bandwidth.....	8
2.1.3	Output power.....	15
2.1.4	Power spectral density.....	17
2.1.5	Radiated spurious emissions and conducted spurious emissions	24
2.1.6	AC conducted emissions	54
Appendix A. Test equipment used for test		57

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

1.0 General product description

Equipment under test	Portable SKIN/HAIR Diagnosis System
Model name	ASNII
Serial number	N/A
Frequency Range	2 412 MHz ~ 2 462 MHz(802.11 b/g/n_HT20) // 2 422 MHz ~ 2 452 MHz(802.11 n_HT40) 2 402 MHz ~ 2 480 MHz(Bluetooth BDR & EDR)
Modulation technique	DSSS, OFDM, GFSK, 8DPSK
Number of channels	11(802.11 b/g/n_HT20) // 7(802.11 n_HT40) // 79(Bluetooth BDR & EDR)
Antenna type & gain	Fixed type(Chip antenna) // 0.9 dBi
Power source	DC 3.7 V

1.1 Test frequency

- 802.11 b/g/n_HT20

	Low channel	Middle channel	High channel
Frequency (MHz)	2 412	2 437	2 462

- 802.11 n_HT40

	Low channel	Middle channel	High channel
Frequency (MHz)	2 422	2 437	2 452

1.2 Information about variant model

N/A

1.3 Device modifications

N/A

1.4 Device Information

- The average output power is < 60/f(GHz) calculated result and RF exposure evaluation is passed.
- The device transmits simultaneously for WiFi & Bluetooth.

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

1.5 Test facility

C3701 Dongil Techno Town, 889-1, Gwanyang 2-dong, Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
477-6, Hageo-ri, Yeosu-eup, Yeosu-gun, Gyeonggi-do, 469-803, Korea

The open area test site is constructed in conformance with the requirements ANSI C63.4-2003.

1.6 Laboratory accreditations and listings

Country	Agency	Scope of accreditation	Certificate No.
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	343818
KOREA	KC	EMI (10 meter Open Area Test Site and two conducted sites) Radio (3 & 10 meter Open Area Test Sites and one conducted site)	KR0100
CANADA	IC	3 & 10 meter Open Area Test Sites and one conducted site	4769B-1

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

2.0 Summary of tests

Section in FCC Part 15	Parameter	Status
15.247(a)(2)	6 dB bandwidth	C
15.247(b)(3)	Output power	C
15.247(e)	Power spectral density	C
15.205, 15.209	Radiated spurious emission and conducted spurious emission	C
15.207	AC conducted emissions	C
Note: C=Complies NC=Not complies NT=Not tested NA=Not applicable		

Statement;

The measurement procedures described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2003) and the guidance provided in KDB 558074 D01 v02 (10/04/2012) were used in the measurement of the DUT.

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

2.1 Test data

2.1.1 Pre-scanned output power

Preliminary tests were performed in different data rate as below table and the highest power data rates(802.11b, 802.11g, 802.11n(HT20 // HT40)) were chosen for full test in the following section to demonstrate compliance to the FCC limit line.

Test mode	Detector mode	Conducted power(dB m)			
		Data rate(Mbps)			
		1	2	5.5	11
802.11b (Middle channel)	Peak	12.878	12.872	12.427	12.054
	Average	10.185	7.564	7.707	7.716


Test mode	Detector mode	Conducted power(dB m)							
		Data rate(Mbps)							
		6	9	12	18	24	36	48	54
802.11g (Middle channel)	Peak	19.151	19.078	19.121	19.097	19.045	19.102	19.093	19.126
	Average	10.050	9.984	10.002	9.993	9.954	10.028	9.972	10.034

Test mode	Detector mode	Conducted power(dB m)							
		Data rate(Mbps)							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n(HT20) (Middle channel)	Peak	18.324	18.676	18.394	18.413	18.384	18.502	18.498	18.510
	Average	10.090	10.143	10.096	10.102	10.092	10.104	10.100	10.107

Test mode	Detector mode	Conducted power(dB m)							
		Data rate(Mbps)							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n(HT40) (Middle channel)	Peak	18.992	19.075	19.415	19.135	19.213	19.084	19.129	19.312
	Average	9.982	10.004	10.058	10.009	10.016	10.006	10.013	10.040

2.1.2 6 dB bandwidth

Test setup



Test procedure

The testing follows KDB publication No. 558074 D01 v02 DTS measurement.

1. Set resolution bandwidth (RBW) = 1~5 % or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test results


Operation mode	Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
802.11b	2 412	10.043	0.5
	2 437	10.014	
	2 462	10.043	
802.11g	2 412	16.585	
	2 437	16.556	
	2 462	16.556	
802.11n(HT20)	2 412	17.829	
	2 437	17.800	
	2 462	17.800	
802.11n(HT40)	2 422	36.527	
	2 437	36.469	
	2 452	36.520	




KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Low channel // 802.11b // 6 dB bandwidth



Middle channel // 802.11b // 6 dB bandwidth







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

High channel // 802.11b // 6 dB bandwidth



Low channel // 802.11g // 6 dB bandwidth







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Middle channel // 802.11g // 6 dB bandwidth



High channel // 802.11g // 6 dB bandwidth







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Low channel // 802.11n(HT20) // 6 dB bandwidth



Middle channel // 802.11n(HT20) // 6 dB bandwidth







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

High channel // 802.11n(HT20) // 6 dB bandwidth



Low channel // 802.11n(HT40) // 6 dB bandwidth







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Middle channel // 802.11n(HT40) // 6 dB bandwidth




High channel // 802.11n(HT40) // 6 dB bandwidth



2.1.3 Output power

Test setup



Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmit-ting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**KES Co., Ltd.**


C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test results

Test mode	Frequency(MHz)	Detector mode	Results (dBm)	Limit(dBm)
802.11b (1 Mbps)	2 412	Peak	12.649	30
		Average	9.929	
	2 437	Peak	12.878	
		Average	10.185	
	2 462	Peak	12.864	
		Average	10.142	
802.11g (6 Mbps)	2 412	Peak	18.894	
		Average	10.000	
	2 437	Peak	19.151	
		Average	10.050	
	2 462	Peak	19.816	
		Average	10.566	
802.11n(HT20) (MCS1)	2 412	Peak	18.345	
		Average	10.106	
	2 437	Peak	18.676	
		Average	10.143	
	2 462	Peak	19.394	
		Average	10.638	
802.11n(HT40) (MCS2)	2 422	Peak	19.904	
		Average	9.798	
	2 437	Peak	19.415	
		Average	10.058	
	2 452	Peak	19.550	
		Average	9.900	

2.1.4 Power spectral density

Test setup



Test procedure

The testing follows KDB publication No. 558074 D01v02 DTS measurement Section 9.1 Option 1

Measurement procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW(no less than 3 kHz) and repeat.


Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


Test results

Operation mode	Frequency(MHz)	Measured PSD(dBm)	Limit(dBm)
802.11b (1 Mbps)	2 412	-22.60	8
	2 437	-23.05	
	2 462	-22.73	
802.11g (6 Mbps)	2 412	-22.56	
	2 437	-22.48	
	2 462	-22.63	
802.11n(HT20) (MCS1)	2 412	-21.36	
	2 437	-21.78	
	2 462	-21.47	
802.11n(HT40) (MCS2)	2 422	-22.32	
	2 437	-22.48	
	2 452	-23.64	


802.11b // Low channel




802.11b // Middle channel



802.11b // High channel



802.11g // Low channel







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11g // Middle channel



802.11g // High channel







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


802.11n(HT20) // Low channel




802.11n(HT20) // Middle channel




802.11n(HT20) // High channel




802.11n(HT40) // Low channel



802.11n(HT40) // Middle channel




802.11n(HT40) // High channel




2.1.5 Radiated spurious emissions and conducted spurious emissions

Test setup for radiated spurious emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz emissions.



Test setup for conducted spurious emissions



Test procedures for radiated spurious emissions

Radiated emissions from the EUT were measured according to the dictates in section 10.0 of KDB 558074 [9 kHz to 30 MHz]

The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Quasi-peak function and specified bandwidth with maximum hold mode.

The spectrum analyzer is set to:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 200 Hz for Quasi-peak detection (QP) at frequency below 9 kHz~ 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 9 kHz for Quasi-peak detection (QP) at frequency below 150 kHz~ 30 MHz.

[30 MHz to 1 GHz and 1 GHz to 24 GHz]

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity.

The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer 120 kHz for Peak detection (PK) or Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

Note;

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

Test procedure for conducted spurious emissions

Per the guidance of KDB 558074, section 10.1.1, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in page 42 of the test report. The limit for out of band spurious emission at the band edge is 20dB below the fundamental emission level measured in a 100 kHz bandwidth.

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Limit for radiated spurious emissions

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu\text{V/m}$)
0.009 ~ 0.490	300	2400 / F(kHz)
0.490 ~ 1.705	30	24000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Limit for conducted spurious emission

According to 15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test results (Below 30 MHz) – Worst case configuration: 802.11g

The frequency spectrum from 9 kHz to 30 MHz was investigated.

Radiated emissions		Ant.	Correction factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Pol.	Ant. factor (dB/m)	Cable loss (dB)	F _d (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Below 30	Not detected							

※ Remark

1. All spurious emission at channels are almost the same below 30 MHz, so that high channel was chosen at representative in final test.
2. Actual = Reading + Ant. factor + Cable loss + F_d
3. $F_d = 40 \log(D_m / D_s)$

Where:

- F_d = Distance factor in dB
D_m = Measurement distance in meters
D_s = Specification distance in meters

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test results (Below 1 000 MHz) – Worst case configuration: 802.11g

The frequency spectrum from 30 MHz to 1 000 MHz was investigated.

Radiated emissions		Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Pol.	Ant. factor (dB/m)	Cable loss (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
59.1	8.72	V	13.14	0.97	22.83	40.00	17.17
153.7	7.35	H	13.11	1.56	22.02	43.50	21.48
197.3	13.87	V	10.17	1.75	25.79	43.50	17.71
207.0	9.88	H	10.18	1.79	21.85	43.50	21.65
226.4	10.67	H	10.85	1.84	23.36	46.00	22.64
226.4	13.07	V	10.85	1.84	25.76	46.00	20.24
250.7	9.33	H	11.69	1.90	22.92	46.00	23.08
284.6	7.71	H	12.84	1.96	22.51	46.00	23.49
284.6	8.83	V	12.84	1.96	23.63	46.00	22.37
481.1	9.95	H	17.33	2.49	29.77	46.00	16.23
599.9	9.01	V	19.73	2.86	31.60	46.00	14.40
718.7	8.01	V	21.13	3.20	32.34	46.00	13.66


※ Remark

1. All spurious emission at channels are almost the same below 1 GHz, so that middle channel was chosen at representative in final test.
2. Actual = Reading + Ant. factor + Cable loss
3. Detector mode: Quasi peak
4. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.




Test results (Above 1 000 MHz)

802.11b // Low channel // Peak, Horizontal



802.11b // Low channel // Peak, Vertical







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11b // High channel // Peak, Horizontal



802.11b // High channel // Peak, Vertical



The frequency spectrum from 1 GHz to 25 GHz was investigated. No Emissions were found above 20 dB below the limit.

802.11b // Low channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 392.3	45.75	Peak	H	28.32	-38.87	35.20	74.00	38.80
2 396.8	44.52	Peak	V	28.33	-38.87	33.98	74.00	40.02

802.11b // Middle channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000	Not detected	-	-	-	-	-	74.00	-

802.11b // High channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 492.8	49.27	Peak	H	28.52	-38.72	39.07	74.00	34.93
2 502.6	49.03	Peak	V	28.54	-38.70	38.87	74.00	35.13

※ Remark


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Actual = Reading + Ant. factor + Amp + CL (Cable loss)
5. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.




KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11g // Low channel // Peak, Horizontal



802.11g // Low channel // Peak, Vertical







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11g // High channel // Peak, Horizontal



802.11g // High channel // Peak, Vertical



**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

The frequency spectrum from 1 GHz to 25 GHz was investigated. No Emissions were found above 20 dB below the limit.

802.11g // Low channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 330.6	44.64	Peak	H	28.19	-38.99	33.84	74.00	40.16
2 369.1	46.00	Peak	V	28.27	-38.92	35.35	74.00	38.65
2 390.5	52.46	Peak	H	28.31	-38.88	41.89	74.00	32.11
2 390.7	52.13	Peak	V	28.31	-38.88	41.56	74.00	32.44
2 395.0	59.00	Peak	V	28.32	-38.87	48.45	74.00	25.55
2 397.6	61.06	Peak	V	28.33	-38.86	50.53	74.00	23.47
2 399.3	59.06	Peak	H	28.33	-38.86	48.53	74.00	25.47

802.11g // Middle channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000	Not detected	-	-	-	-	-	74.00	-

802.11g // High channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 483.6	56.94	Peak	V	28.50	-38.73	46.71	74.00	27.29
2 517.8	49.21	Peak	H	28.57	-38.68	39.10	74.00	34.90

※ Remark


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Actual = Reading + Ant. factor + Amp + CL (Cable loss)
5. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.




KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT20) // Low channel // Peak, Horizontal



802.11n(HT20) // Low channel // Peak, Vertical







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT20) // High channel // Peak, Horizontal



802.11n(HT20) // High channel // Peak, Vertical





The frequency spectrum from 1 GHz to 25 GHz was investigated. No Emissions were found above 20 dB below the limit.

802.11n(HT20) // Low channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 374.3	51.67	Peak	H	28.28	-38.91	41.04	74.00	32.96
2 383.3	51.50	Peak	V	28.30	-38.89	40.91	74.00	33.09
2 389.6	55.57	Peak	V	28.31	-38.88	45.00	74.00	29.00
2 391.7	54.63	Peak	H	28.32	-38.87	44.08	74.00	29.92
2 396.4	56.37	Peak	H	28.32	-38.87	45.82	74.00	28.18
2 398.9	58.53	Peak	V	28.33	-38.86	48.00	74.00	26.00

802.11n(HT20) // Middle channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000	Not detected	-	-	-	-	-	74.00	-

802.11n(HT20) // High channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 515.1	49.04	Peak	H	28.57	-38.69	38.92	74.00	35.08
2 485.4	59.27	Peak	V	28.51	-38.73	49.05	74.00	24.95
2 491.6	50.67	Peak	V	28.52	-38.72	40.47	74.00	33.53

※ Remark


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Actual = Reading + Ant. factor + Amp + CL (Cable loss)
5. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.




KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT40) // Low channel // Peak, Horizontal



802.11n(HT40) // Low channel // Peak, Vertical







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT40) // High channel // Peak, Horizontal



802.11n(HT40) // High channel // Peak, Vertical



The frequency spectrum from 1 GHz to 25 GHz was investigated. No Emissions were found above 20 dB below the limit.

802.11n(HT40) // Low channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 391.3	56.55	Peak	V	28.31	-38.88	45.98	74.00	28.02
2 397.6	53.92	Peak	H	28.33	-38.86	43.39	74.00	30.61
2 399.1	59.89	Peak	V	28.33	-38.86	49.36	74.00	24.64
2 356.9	49.88	Peak	V	28.24	-38.94	39.18	74.00	34.82

802.11n(HT40) // Middle channel

Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Above 1 000	Not detected	-	-	-	-	-	74.00	-

802.11n(HT40) // High channel



Radiated emissions			Ant.	Correction factors		Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detector mode	Pol.	Ant. factor (dB/m)	Amp + CL (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2 484.0	59.76	Peak	V	28.50	-38.73	49.53	74.00	24.47
2 487.9	48.84	Peak	H	28.51	-38.73	38.62	74.00	35.38
2 488.1	58.22	Peak	V	28.51	-38.73	48.00	74.00	26.00
2 510.2	48.85	Peak	V	28.56	-38.69	38.72	74.00	35.28

※ Remark



1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Actual = Reading + Ant. factor + Amp + CL (Cable loss)
5. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.

Test results: conducted spurious emission

802.11b // Low channel



802.11b // Middle channel







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11b // High channel







KES Co., Ltd.


C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11g // Low channel





802.11g // Middle channel



N/A



802.11g // High channel




802.11n(HT20) // Low channel



802.11n(HT20) // Middle channel

N/A









KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT20) // High channel




802.11n(HT40) // Low channel



802.11n(HT40) // Middle channel

N/A







KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

802.11n(HT40) // High channel



2.1.6 AC conducted emissions

Frequency range of measurement

150 kHz to 30 MHz

Instrument settings

IF Band Width: 9 kHz

Test procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m. Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit


According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dBμV/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

※ Remark

Decreases with the logarithm of the frequency.

Test results



Final Measurement Results

Frequency MHz	QP Level dBμV	QP Limit dBμV	QP Delta dB
0.246	44.11	61.89	17.78
0.258	42.22	61.50	19.28
0.351	34.09	58.94	24.85
0.585	35.60	56.00	20.40
0.735	38.82	56.00	17.18
1.461	38.03	56.00	17.97
12.387	39.41	60.00	20.59
13.503	38.30	60.00	21.70
22.899	43.89	60.00	16.11

Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
0.246	25.86	51.89	26.03
0.258	26.42	51.50	25.08
0.351	21.29	48.94	27.65
0.585	22.83	46.00	23.17
0.735	26.12	46.00	19.88
1.461	25.10	46.00	20.90
12.387	30.77	50.00	19.23
13.503	31.58	50.00	18.42
22.899	34.23	50.00	15.77


Note;

Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).



KES Co., Ltd.

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr



Final Measurement Results

Frequency MHz	QP Level dBm	QP Limit dBm	QP Delta dB
0.201	39.51	63.57	24.06
0.258	39.11	61.50	22.39
0.291	37.95	60.50	22.55
0.729	36.29	56.00	19.71
0.882	33.81	56.00	22.19
1.158	34.19	56.00	21.81
12.306	38.81	60.00	21.19
13.332	37.67	60.00	22.33
23.232	43.45	60.00	16.55

Frequency MHz	AV Level dBm	AV Limit dBm	AV Delta dB
0.201	19.52	53.57	34.05
0.258	25.29	51.50	26.21
0.291	26.53	50.50	23.97
0.729	23.95	46.00	22.05
0.882	22.17	46.00	23.83
1.158	20.83	46.00	25.17
12.306	31.11	50.00	18.89
13.332	30.71	50.00	19.29
23.232	33.34	50.00	16.66

Note;

Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).

**KES Co., Ltd.**

C-3701 Dongil Techno Town, 889-1, Gwanyang 2-dong,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Appendix A. Test equipment used for test

Equipment	Manufacturer	Model	Calibration due.
Spectrum Analyzer	R&S	FSV30	2013.01.10
8360B Series Swept Signal Generator	HP	83630B	2013.06.06
Attenuator	HP	8495B	2013.05.04
Attenuator	HP	8494B	2013.05.04
AC POWER SOURCE ANALYZER	HP	6813A	2013.07.06
Loop Antenna	R&S	HFH2-Z2.335.4711.52	2013.03.10
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	2013.10.25
Horn Antenna	A.H. System	SAS-571	2013.03.22
Horn Antenna	A.H. System	SAS-572	2013.09.07
High Pass Filter	Wainwright Instrument	WHJS3000-10TT	2013.01.10
Preamplifier	A.H. System	PAM-0118	2013.05.04
Power Amplifier	MITEQ	AFS43-01002600	2013.10.07
EMC Analyzer	Agilent	E7405A	2013.05.04
EMI TEST Receiver	R & S	ESHS10	2013.05.04
LISN	R & S	ENV216	2013.02.27
LISN	EMCO	3810/2	2013.04.18
Wideband Power Sensor	R&S	NRP-Z81	2012.12.21

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook(Laptop)	Samsung Electronics	NT-R410Y	Z9YJ93CS300631H

Appendix B. Test setup photos

Radiated field emissions



AC conducted emission

