

# MPE TEST REPORT

**Applicant** Asiatelco Technologies Co.  
**FCC ID** XYO-BTG35L  
**Product** GPS TRACKER  
**Brand** BTG IoT  
**Model** BTG35L  
**Report No.** R2404A0349-M1V1  
**Issue Date** April 19, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Prepared by: Wei Fangying*

*Approved by: Fan Guangchang*

**Eurofins TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Table of Contents

|     |   |    |
|-----|---|----|
| 1   | Test Laboratory .....                     | 4  |
| 1.1 | Notes of the Test Report.....             | 4  |
| 1.2 | Test Facility.....                        | 4  |
| 1.3 | Testing Location.....                     | 4  |
| 1.4 | Laboratory Environment .....              | 4  |
| 2   | Description of Equipment Under Test ..... | 5  |
| 3   | Maximum Tune up and Antenna Gain .....    | 6  |
| 4   | MPE Limit.....                            | 8  |
| 5   | RF Exposure Evaluation Result.....        | 10 |
|     | ANNEX A: The EUT Appearance .....         | 11 |

| Version | Revision Description         | Issue Date     |
|---------|------------------------------|----------------|
| Rev.0   | Initial issue of report.     | April 17, 2024 |
| Rev.1   | Update data and information. | April 19, 2024 |

Note: This revised report (Report No.: R2404A0349-M1V1) supersedes and replaces the previously issued report (Report No.: R2404A0349-M1). Please discard or destroy the previously issued report and dispose of it accordingly.

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2 Test Facility

### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

## 1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.  
 Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
 City: Shanghai  
 Post code: 201201  
 Country: P. R. China  
 Contact: Fan Guangchang  
 Telephone: +86-021-50791141/2/3  
 Fax: +86-021-50791141/2/3-8000  
 Website: <https://www.eurofins.com/electrical-and-electronics>  
 E-mail: Jack.Fan@cpt.eurofinscn.com

## 1.4 Laboratory Environment

|   |                          |
|---|--------------------------|
| Temperature   | Min. = 18°C, Max. = 25°C |
| Relative humidity   | Min. = 20%, Max. = 80%   |
| Ground system resistance  | < 0.5 Ω                  |
| Ambient noise is checked and found very low and in compliance with requirement of standards.<br>Reflection of surrounding objects is minimized and in compliance with requirement of standards. |                          |

## 2 Description of Equipment Under Test

### Client Information

|                             |  |
|-----------------------------|--|
| <b>Applicant</b>            | Asiatelco Technologies Co.   |
| <b>Applicant address</b>    | 289 Bisheng Road, Building 8, 3F, Zhang jiang Hi-Tech Park, Pudong, Shanghai 201204, China |
| <b>Manufacturer</b>         | Asiatelco Technologies Co.   |
| <b>Manufacturer address</b> | 289 Bisheng Road, Building 8, 3F, Zhang jiang Hi-Tech Park, Pudong, Shanghai 201204, China |

### General Technologies

| EUT Description   |                                |             |             |
|---|--------------------------------|-------------|-------------|
| Model   | BTG35L                         |             |             |
| IMEI  | 862620060015379                |             |             |
| Hardware Version  | p2                             |             |             |
| Software Version  | v5.6.9.23                      |             |             |
| Frequency   | Band                           | TX (MHz)    | RX (MHz)    |
|   | GSM 850                        | 824 ~ 849   | 869 ~ 894   |
|   | GSM 1900                       | 1850 ~ 1910 | 1930 ~ 1990 |
|   | WCDMA Band II                  | 1850 ~ 1910 | 1930 ~ 1990 |
|   | WCDMA Band V                   | 824 ~ 849   | 869 ~ 894   |
|   | LTE Band 2                     | 1850 ~ 1910 | 1930 ~ 1990 |
|   | LTE Band 4                     | 1710 ~ 1755 | 2110 ~ 2155 |
|   | LTE Band 5                     | 824 ~ 849   | 869 ~ 894   |
|   | LTE Band 7                     | 2500 ~ 2570 | 2620 ~ 2690 |
| Date of Testing   | April 9, 2024 ~ April 11, 2024 |             |             |
| Date of Sample Received   | March 11, 2024                 |             |             |
| <p>Note:</p> <ol style="list-style-type: none"> <li>1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.</li> <li>2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.</li> </ol> |                                |             |             |

### 3 Maximum Tune up and Antenna Gain

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

| Number of timeslots in uplink assignment | Permissible nominal reduction of maximum output power (dB) |
|--|--|
| 1  | 0  |
| 2  | 0 to 3,0   |
| 3  | 1,8 to 4,8   |
| 4  | 3,0 to 6,0   |

Each Tx slots maximum tune up use the most strictest factor for evaluation by making calculation.

| Band    |           | Burst-Averaged output power (adjusted for tune up) (dBm) | Division Factors | Frame-Averaged output power (adjusted for tune up) (dBm) |
|---------|-----------|--|------------------|--|
| GSM850  | 1 Txslot  | 36.00  | -9.03            | 26.97  |
|         | 2 Txslots | 36.00  | -6.02            | 29.98  |
|         | 3 Txslots | 34.20  | -4.26            | 29.94  |
|         | 4 Txslots | 33.00  | -3.01            | <b>29.99</b>   |
| GSM1900 | 1 Txslot  | 33.00  | -9.03            | 23.97  |
|         | 2 Txslots | 33.00  | -6.02            | 26.98  |
|         | 3 Txslots | 31.20  | -4.26            | 26.94  |
|         | 4 Txslots | 30.00  | -3.01            | <b>26.99</b>   |

Note:

Division Factors

To average the power, the division factor is as follows:

1Txslot = 1 transmit time slot out of 8 time slots

=> conducted power divided by (8/1) => -9.03 dB

2Txslots = 2 transmit time slots out of 8 time slots

=> conducted power divided by (8/2) => -6.02 dB

3Txslots = 3 transmit time slots out of 8 time slots

=> conducted power divided by (8/3) => -4.26 dB

4Txslots = 4 transmit time slots out of 8 time slots

=> conducted power divided by (8/4) => -3.01 dB

| Band          | Maximum Tune up Power |        | Antenna Gain<br>(dBi) | Numeric Gain |
|---------------|-----------------------|--------|-----------------------|--------------|
|               | (dBm)                 | (mW)   |                       |              |
| GSM 850       | 29.99                 | 997.70 | 2.91                  | 1.95         |
| GSM 1900      | 26.99                 | 500.04 | 3.50                  | 2.24         |
| WCDMA Band II | 25.00                 | 316.23 | 3.50                  | 2.24         |
| WCDMA Band V  | 25.00                 | 316.23 | 2.91                  | 1.95         |
| LTE Band 2    | 25.00                 | 316.23 | 3.50                  | 2.24         |
| LTE Band 4    | 25.70                 | 371.54 | 4.66                  | 2.92         |
| LTE Band 5    | 25.70                 | 371.54 | 2.91                  | 1.95         |
| LTE Band 7    | 25.70                 | 371.54 | 6.27                  | 4.24         |

## 4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range<br>(MHz)                                | Electric Field<br>Strength<br>(V/m) | Magnetic Field<br>Strength<br>(A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Averaging Time<br>(minutes) |
|---|-------------------------------------|-------------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                                     |                                     |  |                             |
| 0.3-3.0 .....   | 614                                 | 1.63                                | *(100)                                 | 6                           |
| 3-30 .....  | 1842/f                              | 4.89/f                              | *(900/f <sup>2</sup> )                 | 6                           |
| 30-300 .....  | 61.4                                | 0.163                               | 1.0                                    | 6                           |
| 300-1500 .....  |                                     |                                     | f/300                                  | 6                           |
| 1500-100,000 .....                                      |                                     |                                     | 5                                      | 6                           |
| (B) Limits for General Population/Uncontrolled Exposure |                                     |                                     |  |                             |
| 0.3-1.34 .....  | 614                                 | 1.63                                | *(100)                                 | 30                          |
| 1.34-30 .....   | 824/f                               | 2.19/f                              | *(180/f <sup>2</sup> )                 | 30                          |
| 30-300 .....  | 27.5                                | 0.073                               | 0.2                                    | 30                          |
| 300-1500 .....  |                                     |                                     | f/1500                                 | 30                          |
| 1500-100,000 .....                                      |                                     |                                     | 1.0                                    | 30                          |

f = frequency in MHz

\* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



The maximum permissible exposure for 300~1500 MHz is  $f/1500$ , for 1500~100,000MHz is 1.0. So

| Band          | The Maximum Permissible Exposure (mW/cm <sup>2</sup> ) |
|---------------|--|
| GSM850        | 0.549  |
| GSM1900       | 1.000  |
| WCDMA Band II | 1.000  |
| WCDMA Band V  | 0.549  |
| LTE Band 2    | 1.000  |
| LTE Band 4    | 1.000  |
| LTE Band 5    | 0.549  |
| LTE Band 7    | 1.000  |

## 5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

| Band                        | Maximum Tune up (dBm) | Antenna Gain (dBi) | Maximum EIRP (dBm) | PG (mW)  | Result (mW/cm <sup>2</sup> ) | Limit Value (mW/cm <sup>2</sup> ) |
|-----------------------------|-----------------------|--------------------|--------------------|----------|------------------------------|-----------------------------------|
| GSM 850                     | 29.99                 | 2.91               | 32.900             | 1949.845 | 0.388                        | 0.549                             |
| GSM 1900                    | 26.99                 | 3.50               | 30.490             | 1119.438 | 0.223                        | 1.000                             |
| WCDMA Band II               | 25.00                 | 3.50               | 28.500             | 707.946  | 0.141                        | 1.000                             |
| WCDMA Band V                | 25.00                 | 2.91               | 27.910             | 618.016  | 0.123                        | 0.549                             |
| LTE Band 2                  | 25.00                 | 3.50               | 28.500             | 707.946  | 0.141                        | 1.000                             |
| LTE Band 4                  | 25.70                 | 4.66               | 30.360             | 1086.426 | 0.216                        | 1.000                             |
| LTE Band 5                  | 25.70                 | 2.91               | 28.610             | 726.106  | 0.144                        | 0.549                             |
| LTE Band 7                  | 25.70                 | 6.27               | 31.970             | 1573.983 | 0.313                        | 1.000                             |
| Note: R = 20cm<br>π= 3.1416 |                       |                    |                    |          |                              |                                   |

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

**IMPORTANT NOTE:** To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

\*\*\*\*\*END OF REPORT \*\*\*\*\*