

# RF EXPOSURE REPORT

**REPORT NO.:** SA980611A09-1

**MODEL NO.:** TPC-2A Plus

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT :** i-Mobile Technology Corporation

**ADDRESS :** 8F., No.8, Alley 15, Lane 120, Sec. 1, Neihu Rd.,  
Neihu District, Taipei City 114, Taiwan (R.O.C.)

**ISSUED BY :** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien, 244 Taiwan

## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	5.0	3.2
EIRP Power	7.4	5.5

**\*Note:** The antenna is PCB Antenna with 2.4 dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 5.5mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---