


Skullcandy

FLYR

WARRANTY GUIDE



Scan to get started.

Balayez pour commencer.

Warranty information at: skullcandy.com/warranty

Renseignements sur la garantie à: skullcandy.com/warranty

FCC Compliance Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
-- Reorient or relocate the receiving antenna.
-- Increase the separation between the equipment and receiver.
-- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
-- Consult the dealer or an experienced radio/TV technician for help.

ISED Compliance Statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with

Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: (1) This device may not cause interference.(2)This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :(1)L'appareil ne doit pas produire de brouillage;(2)L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

ISED SAR Compliance Statement

This equipment complies with ISED radiation exposure limits set forth for an uncontrolled environment. End user must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. The portable device is designed to meet the requirements for exposure to radio waves established by the ISED. These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported within this standard during product certification for use when properly worn on the head. Cet équipement est conforme aux limites d'exposition aux rayonnements ISED établies pour un environnement non contrôlé. L'utilisateur final doit suivre les instructions spécifiques pour satisfaire les normes. Cet émetteur ne doit pas être co-implanté ou fonctionner en conjonction avec toute autre antenne ou transmetteur. Le dispositif portatif est conçu pour répondre aux exigences d'exposition aux ondes radio établie par le développement énergétique DURABLE. Ces exigences un

Questions Visit: www.skullcandy.com
Si vous avez des questions, allez sur : www.skullcandy.com
Si tienes dudas, visita: www.skullcandy.com
Domande Visitare il sito: www.skullcandy.com
Fazer perguntas: www.skullcandy.com
Bei Fragen: www.skullcandy.com
Voor vragen bezoek: www.skullcandy.com
For spørsmål se: www.skullcandy.com
Vastauksia löytyy: www.skullcandy.com
For spørsmål, besøk: www.skullcandy.com
Vid frågor, besök: www.skullcandy.com
Если у вас возникнут вопросы, посетите: www.skullcandy.com
如有问题请访问： www.skullcandy.com
質問がある場合はこちらをご覧ください： www.skullcandy.com
문의 사항: www.skullcandy.com
www.skullcandy.com: تۆۋەنلەر خەۋەرلەر ئالماشتۇرۇش ياكى تەۋەنلەر ئارقىلىق

PLFR
MODEL: S6PPY
FCC ID: Y22-S6PPY
IC: 10486A-S6PPY

R-C-Sku-S6PPY
018-220194

UK CA CE ENEC NOM NYCE

Americas
Skullcandy, Inc.
6301 N Landmark Dr.
Park City, UT 84098 U.S.A.
Skullcandy.com

Canada
Skullcandy Canada ULC
329 Railway St. Unit 205
Vancouver, BC, V6A 1A4 Canada
Skullcandy.ca

Europe
Skullcandy Europe BV
Postbus 425
5500AK Veldhoven Nederland
Skullcandy.eu

México
Skullcandy Mexico S de RL de CV
Aristoteles 218
Polanco IV Seccion, Miguel Hidalgo
11550, México City, México
Skullcandy.mx

Skullcandy UK LTD
Andrews House
College Road
Guildford
GU1 4QB
Skullcandy.co.uk

EN Made in China.
FR Fabriqué au China.
ES Hecho en China.
ZH 中国制造.

EN Speaker Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free filed 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm, Gewicht: 314 g. **JP** スピーカードライバー : 50mm, インピーダンス : 34オーム、自由空間での出力 : <10dBm、重量 : 314g。 **ES** Controlador de altavoz: 50 mm, impedancia: 34 ohmios, THD<1%@1KHz, distancia 10 mm en campo libre 4%, banda de frecuencia: 2402MHz-2480MHz, potencia máxma: <10dBm, Peso: 314g. **DA** Lydsprechertræter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Afstand 10 mm i frien felt 4%, Frekvensband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm, Impédance : 34 Ohms, THD<1%@1KHz, distance de 10 mm en champ libre 4%, Bande de fréquence : 2402MHz-2480MHz, Puissance maximale : <10dBm, Poids : 314g. **DE** Lautsprechertriebter: 50 mm, Impedanz: 34 Ohm, THD<1%@1KHz, Abstand 10 mm im freien Feld 4%, Frequenzband: 2402MHz-2480MHz, Max. Leistung: <10dBm. **UK** Driver: 50mm, Impedance: 34 Ohms, THD<1%@1KHz, distance 10mm in free field 4%, Frequency Band: 2402MHz-2480MHz, Max Power: <10dBm, Weight: 314g. **FR** Haut-parleur : 50 mm,