

ANTENNA PASSIVE TEST REPORT

Application No. ZEWM2209001119OA
Applicant SKULLCANDY, INC.
Manufacturer SKULLCANDY, INC.
Product Name Rail ANC / Rail ANC XT
Model No. S2IPW
Standards ANSI/IEEE Std 149-2008
Date Initial Sample(s) Received 2022.09.19
Testing Start Date 2022.09.21
Testing Finish Date 2023.01.01
Report Issue Date 2023.03.06

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

YuanYu Luo

Prepared by

Max. Huang

Reviewed By

Ervin Li

Approved by



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

Revision Version

Report No.	Version	Date	Memo
ZEWM2209001119OA02	00	2023.03.06	Initial creation of report



TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Testing Laboratory	4
1.2	Details of Applicant	4
1.3	Details of Manufacturer	4
1.4	General Description of EUT.....	5
1.5	Test Procedure	5
1.6	Test Specification	6
1.7	Laboratory Environment.....	6
2	OTA MEASUREMENTS SYSTEM CONFIGURATION.....	7
2.1	Test Configuration	7
3	TEST EQUIPMENT LIST	8
4	MEASUREMENT UNCERTAINTY	9
5	TEST RESULTS	10
6	PATTERN PLOTS.....	12
6.1	Return Loss.....	12
6.2	VSWR	13
6.3	Stimulus	14
7	2-D ANTENNA PATTERN(THETA=90°)	15
8	3-D ANTENNA PATTERN	16
9	THE EUT AND TEST CONFIGURATION.....	18



1 General Information

1.1 Testing Laboratory

Test Lab	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057
Contact	Simon Ling
Tel.	+86 (0) 755 2601 2053
Fax	+86 (0) 755 2671 0594
E-mail	Simon.Ling@sgs.com

1.2 Details of Applicant

Applicant's Name	SKULLCANDY, INC.
Applicant's Address	6301 N Landmark Dr Park City UT 84098, Utah United States of America
Contact	James Nance
Tel.	1(435) 729-2698
Fax	N/A
E-mail	James Nance@skullcandy.com

1.3 Details of Manufacturer

Manufacturer's Name	SKULLCANDY, INC.
Manufacturer's Address	6301 N Landmark Dr Park City UT 84098, Utah United States of America
Contact	James Nance
Tel.	1(435) 729-2698
Fax	N/A
E-mail	James Nance@skullcandy.com



1.4 General Description of EUT

Device Description:	Rail ANC / Rail ANC XT
Device Manufacturer:	SKULLCANDY, INC.
Device Model:	S2IPW
Hardware Version:	1.0
Software Version:	V028

1.5 Test Procedure

Testing is performed according to the **ANSI/IEEE Std 149-2008**.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.6 Test Specification

Identity	Document Title
ANSI/IEEE Std 149-2008	IEEE Standard Test Procedures for Antennas

1.7 Laboratory Environment

Temperature	Min. =19°C , Max. = 25°C	
Relative humidity	Min. =40% , Max. =72%	
Shield effect	0.7-6GHz	> 100dB
Ground resistance	<0.5Ω	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center, EMC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 OTA Measurements System Configuration

2.1 Test Configuration

Great-Circle-Cut method is used to measure the antenna 3D GAIN of EUT in OTA qualified anechoic chamber. Equipment Under Test (EUT) geometry centre vertical projection at the centre of platform, the distance from EUT to measurement antenna is 5m



F-1. OTA Measurement System Configuration

3 Test Equipment List

Type of Equipment	Model Number	Manufacture	Calibration Date	Valid Period
Network Analyzer	E5071C S/N MY46523591	Keysight	2022/4/11	2023/4/10
Quad-Ridge Horn Antenna 700 MHz-10 GHz	EMCO 3164-08 S/N 161915	ETS-Lindgren L.P.	N/A	N/A
MAPS Controller	EMCENTER S/N 160485	ETS-Lindgren L.P.	N/A	N/A



4 Measurement Uncertainty

Item	2400-2500 MHz (dB)
Gain	0.88
Efficiency	0.88
Measurement Uncertainty (95% CONFIDENCE INTERVAL) K=2	



5 Test Results

Free Space Left #1			
Frequency (MHz)	Efficiency (dB)	Efficiency (%)	Gain (dBi)
2350	-7.50	17.77	-1.04
2355	-7.24	18.89	-0.72
2360	-6.91	20.36	-0.54
2365	-6.76	21.08	-0.28
2370	-6.65	21.62	-0.24
2375	-6.59	21.93	-0.06
2380	-6.37	23.06	0.13
2385	-6.25	23.72	0.28
2390	-6.01	25.08	0.55
2395	-5.83	26.12	0.68
2400	-5.79	26.35	0.74
2402	-5.75	26.59	0.68
2405	-5.69	27.00	0.78
2410	-5.55	27.83	0.91
2415	-5.40	28.82	0.98
2420	-5.29	29.61	1.19
2425	-5.19	30.25	1.18
2430	-5.16	30.46	1.30
2435	-5.09	30.99	1.26
2440	-4.95	32.00	1.49
2441	-4.93	32.12	1.49
2445	-4.91	32.30	1.37
2450	-4.88	32.52	1.49
2455	-4.91	32.28	1.34
2460	-4.97	31.81	1.38

Free Space Right #1			
Frequency (MHz)	Efficiency (dB)	Efficiency (%)	Gain (dBi)
2350	-6.68	21.46	-0.12
2355	-6.41	22.88	0.19
2360	-6.15	24.25	0.34
2365	-6.11	24.51	0.44
2370	-6.04	24.89	0.38
2375	-6.03	24.93	0.45
2380	-5.86	25.93	0.55
2385	-5.83	26.12	0.62
2390	-5.66	27.18	0.77
2395	-5.56	27.78	0.89
2400	-5.51	28.12	0.93
2402	-5.45	28.53	0.90
2405	-5.41	28.75	1.02
2410	-5.30	29.54	1.13
2415	-5.25	29.82	1.11
2420	-5.26	29.76	1.17
2425	-5.27	29.74	1.16
2430	-5.29	29.59	1.16
2435	-5.22	30.05	1.28
2440	-5.10	30.92	1.38
2441	-5.08	31.04	1.42
2445	-5.09	30.99	1.45
2450	-5.09	30.94	1.43
2455	-5.18	30.36	1.41
2460	-5.26	29.78	1.35




2465	-4.99	31.67	1.24
2470	-5.20	30.17	1.10
2475	-5.21	30.15	1.07
2480	-5.42	28.69	0.88
2482	-5.40	28.82	0.99
2485	-5.36	29.14	1.00
2490	-5.41	28.78	0.86
2495	-5.20	30.22	1.15
2500	-5.24	29.94	0.94
2505	-5.30	29.53	0.92
2510	-5.46	28.45	0.61
2515	-5.77	26.51	0.33
2520	-5.92	25.57	0.12
2525	-6.15	24.24	-0.08
2530	-6.20	23.98	-0.14
2535	-6.32	23.32	-0.24
2540	-6.31	23.38	-0.23
2545	-6.25	23.69	-0.21
2550	-6.34	23.23	-0.30
2555	-6.42	22.80	-0.43
2560	-6.69	21.41	-0.71
2565	-6.86	20.60	-0.96
2570	-7.13	19.36	-1.29
2575	-7.27	18.74	-1.47
2580	-7.32	18.52	-1.55

2465	-5.30	29.48	1.34
2470	-5.52	28.05	1.14
2475	-5.52	28.06	1.15
2480	-5.73	26.74	0.96
2482	-5.70	26.90	0.94
2485	-5.62	27.39	1.07
2490	-5.70	26.89	1.01
2495	-5.49	28.24	1.17
2500	-5.63	27.34	1.11
2505	-5.73	26.76	0.98
2510	-5.92	25.58	0.89
2515	-6.15	24.26	0.57
2520	-6.21	23.94	0.58
2525	-6.41	22.87	0.32
2530	-6.39	22.96	0.33
2535	-6.55	22.14	0.13
2540	-6.52	22.28	0.12
2545	-6.56	22.05	0.07
2550	-6.69	21.42	-0.11
2555	-6.84	20.69	-0.21
2560	-7.14	19.30	-0.52
2565	-7.30	18.63	-0.57
2570	-7.57	17.51	-0.83
2575	-7.65	17.19	-0.83
2580	-7.74	16.82	-0.94




6 Pattern Plots

6.1 Return Loss




Free Space Left #1




Free Space Right #1



6.2 VSWR




Free Space Left #1




Free Space Right #1



6.3 Stimulus




Free Space Left #1






Free Space Right #1



7 2-D Antenna Pattern(Theta=90°)




8 3-D Antenna Pattern



Free Space Left #1





Free Space Right #1




9 The EUT and Test Configuration




Photo of EUT #1






Free Space Left View #1



Free Space Right View #1





Free Space Left Impedance Setup #1



Free Space Right Impedance Setup #1

---END---

