

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
SHENZHEN APEXIS ELECTRONIC CO., LTD.

IP Camera
Model No.: APM-J6235-WS

FCC ID: Y2EAPM-J6235-WS

Prepared for : SHENZHEN APEXIS ELECTRONIC CO., LTD.
Address : 502 East Keji Building, ShenZhen High-Tech Ind-Park,
Nanshan District, Shenzhen, 518057, China

Prepared by : Accurate Technology Co., Ltd.
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20131556
Date of Test : July 22-27, 2013
Date of Report : July 29, 2013

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Carrier Frequency of Channels	6
1.3. Test Procedure	6
1.4. Special Accessory and Auxiliary Equipment	6
1.5. Description of Test Facility	7
1.6. Measurement Uncertainty	7
2. MEASURING DEVICE AND TEST EQUIPMENT	8
3. OPERATION OF EUT DURING TESTING	9
3.1. Operating Mode	9
3.2. Configuration and peripherals	10
4. TEST PROCEDURES AND RESULTS	11
5. 6DB BANDWIDTH MEASUREMENT.....	12
5.1. Block Diagram of Test Setup.....	12
5.2. The Requirement For Section 15.247(a)(2).....	12
5.3. EUT Configuration on Measurement	12
5.4. Operating Condition of EUT	12
5.5. Test Procedure	13
5.6. Test Result	13
6. MAXIMUM PEAK OUTPUT POWER	27
6.1. Block Diagram of Test Setup.....	27
6.2. The Requirement For Section 15.247(b)(3).....	27
6.3. EUT Configuration on Measurement	27
6.4. Operating Condition of EUT	27
6.5. Test Procedure	28
6.6. Test Result	29
7. POWER SPECTRAL DENSITY MEASUREMENT	42
7.1. Block Diagram of Test Setup.....	42
7.2. The Requirement For Section 15.247(e).....	42
7.3. EUT Configuration on Measurement	42
7.4. Operating Condition of EUT	42
7.5. Test Procedure	43
7.6. Test Result	44
8. BAND EDGE COMPLIANCE TEST	58
8.1. Block Diagram of Test Setup.....	58
8.2. The Requirement For Section 15.247(d)	58
8.3. EUT Configuration on Measurement	58
8.4. Operating Condition of EUT	59
8.5. Test Procedure	59
8.6. Test Result	60
9. RADIATED SPURIOUS EMISSION TEST	93
9.1. Block Diagram of Test Setup.....	93
9.2. The Limit For Section 15.247(d)	94
9.3. Restricted bands of operation	94

9.4.	Configuration of EUT on Measurement	95
9.5.	Operating Condition of EUT	95
9.6.	Test Procedure	95
9.7.	The Field Strength of Radiation Emission Measurement Results	96
10.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	180
10.1.	Block Diagram of Test Setup.....	180
10.2.	The Requirement For Section 15.247(d)	180
10.3.	EUT Configuration on Measurement	180
10.4.	Operating Condition of EUT	181
10.5.	Test Procedure	181
10.6.	Test Result	181
11.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A)	194
11.1.	Block Diagram of Test Setup.....	194
11.2.	The Emission Limit	194
11.3.	Configuration of EUT on Measurement	195
11.4.	Operating Condition of EUT	195
11.5.	Test Procedure	195
11.6.	Power Line Conducted Emission Measurement Results	196
12.	ANTENNA REQUIREMENT.....	199
12.1.	The Requirement	199
12.2.	Antenna Construction	199

Test Report Certification

Applicant : SHENZHEN APEXIS ELECTRONIC CO., LTD.
Manufacturer : SHENZHEN APEXIS ELECTRONIC CO., LTD.
EUT Description : IP Camera
(A) MODEL NO.: APM-J6235-WS
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: DC 5V (Power by Adapter)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4: 2009


The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03r01 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

Date of Test : July 22-27, 2013

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	IP Camera
Model Number	:	APM-J6235-WS
Frequency Range	:	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz
Number of Channels	:	802.11b/g/n (20MHz):11 802.11n (40MHz): 7
Trade Name	:	
Antenna Gain	:	2dBi
Power Supply	:	DC 5V (Power by adapter)
Adapter	:	Model number: SAW-0502000 Input: AC 100-240V; 50/60Hz 0.5A Output: DC 5V/2000mA
Data Rate	:	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: up to 150Mbps
Applicant	:	SHENZHEN APEXIS ELECTRONIC CO., LTD.
Address	:	502 East Keji Building, ShenZhen High-Tech Ind-Park, Nanshan District, Shenzhen, 518057, China
Manufacturer	:	SHENZHEN APEXIS ELECTRONIC CO., LTD.
Address	:	F5, NO.53, Dalangshan, Wanfeng, Shajing, Shenzhen, China
Date of sample received	:	July 17, 2013
Date of Test	:	July 22-27, 2013

1.2.Carrier Frequency of Channels

802.11b, 802.11g, 802.11n (20MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

802.11n (40MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
03	2422	09	2452
04	2427	---	---
05	2432	---	---
06	2437	---	---

1.3.Test Procedure

The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03r01 for compliance to FCC 47CFR 15.247 requirements

1.4.Special Accessory and Auxiliary Equipment

n.a.

1.5. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	Accurate Technology Co., Ltd.
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.6. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 12, 2013	Jan. 11, 2014
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 12, 2013	Jan. 11, 2014
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 12, 2013	Jan. 11, 2014
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 12, 2013	Jan. 11, 2014
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Feb. 6, 2013	Feb. 5, 2014
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Feb. 6, 2013	Feb. 5, 2014
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Feb. 6, 2013	Feb. 5, 2014
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Feb. 6, 2013	Feb. 5, 2014
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 12, 2013	Jan. 11, 2014
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 12, 2013	Jan. 11, 2014
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 12, 2013	Jan. 11, 2014
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 12, 2013	Jan. 11, 2014

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **1.802.11b Transmitting mode**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

2.802.11g Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

3.802.11n (20MHz) Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

4.802.11n (40MHz) Transmitting mode



Low Channel: 2422MHz

Middle Channel: 2437MHz

High Channel: 2452MHz

5. On with Wi-Fi

3.2.Configuration and peripherals



4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 6DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



(EUT: IP Camera)

5.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3. EUT Configuration on Measurement

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. IP Camera (EUT)

Model Number : APM-J6235-WS
 Serial Number : N/A
 Manufacturer : SHENZHEN APEXIS ELECTRONIC CO., LTD.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

5.5. Test Procedure

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6. Test Result

PASS.

Date of Test:	July 24, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60HZ
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	8.08	> 0.5MHz
Middle	2437	8.04	> 0.5MHz
High	2462	8.08	> 0.5MHz

The test was performed with 802.11g


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	15.16	> 0.5MHz
Middle	2437	15.44	> 0.5MHz
High	2462	15.44	> 0.5MHz

The test was performed with 802.11n (Bandwidth: 20 MHz)			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	16.08	> 0.5MHz
Middle	2437	16.08	> 0.5MHz
High	2462	16.36	> 0.5MHz


The test was performed with 802.11n (Bandwidth: 40 MHz)			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2422	36.44	> 0.5MHz
Middle	2437	36.48	> 0.5MHz
High	2452	36.40	> 0.5MHz

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz(20MHz)




802.11n Channel High 2462MHz(20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz(40MHz)




802.11n Channel High 2452MHz(40MHz)



6. MAXIMUM PEAK OUTPUT POWER

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

6.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. IP Camera (EUT)

Model Number : APM-J6235-WS
 Serial Number : N/A
 Manufacturer : SHENZHEN APEXIS ELECTRONIC CO., LTD.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The EUT was tested according to Section 9.1.2 of the 558074 D01 DTS Meas Guidance v03r01

6.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.3. a) Set the RBW = 1 MHz.

b) Set the VBW $\geq$ 3 RBW

c) Set the span $\geq$ 1.5 x DTS bandwidth.

d) Detector = peak.

e) Sweep time = auto couple.

f) Trace mode = max hold.

g) Allow trace to fully stabilize.

6.5.4.h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

6.5.5. Measurement the maximum peak output power.

6.6.Test Result

PASS.

Date of Test:	July 24, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60HZ
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.45	5.56	30 dBm / 1 W
Middle	2437	7.67	5.85	30 dBm / 1 W
High	2462	7.69	5.87	30 dBm / 1 W

The test was performed with 802.11g

Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.84	6.08	30 dBm / 1 W
Middle	2437	7.32	5.40	30 dBm / 1 W
High	2462	6.58	4.55	30 dBm / 1 W

The test was performed with 802.11n (20MHz)


Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.87	6.12	30 dBm / 1 W
Middle	2437	6.08	4.06	30 dBm / 1 W
High	2462	7.31	5.38	30 dBm / 1 W

The test was performed with 802.11n (40MHz)


Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2422	7.65	5.82	30 dBm / 1 W
Middle	2437	7.83	6.07	30 dBm / 1 W
High	2452	7.41	5.51	30 dBm / 1 W

The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz (20MHz)




802.11n Channel High 2462MHz (20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz (40MHz)



802.11n Channel High 2452MHz (40MHz)



7. POWER SPECTRAL DENSITY MEASUREMENT

7.1. Block Diagram of Test Setup



(EUT: IP Camera)

7.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. IP Camera (EUT)

Model Number : APM-J6235-WS
 Serial Number : N/A
 Manufacturer : SHENZHEN APEXIS ELECTRONIC CO., LTD.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The EUT was tested according to Section 10.2 of the 558074 D01 DTS Meas Guidance v03r01.

7.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.3. Measurement Procedure PKPSD (peak PSD):

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.5.4. Measurement the maximum power spectral density.

7.6. Test Result

PASS.

Date of Test:	July 24, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60HZ
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-16.45	8 dBm
Middle	2437	-16.13	8 dBm
High	2462	-15.14	8 dBm

The test was performed with 802.11g

Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-18.80	8 dBm
Middle	2437	-18.61	8 dBm
High	2462	-19.12	8 dBm

The test was performed with 802.11n (20MHz)


Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-20.79	8 dBm
Middle	2437	-19.93	8 dBm
High	2462	-18.98	8 dBm

The test was performed with 802.11n (40MHz)


Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2422	-24.68	8 dBm
Middle	2437	-24.85	8 dBm
High	2452	-24.74	8 dBm

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz (20MHz)




802.11n Channel High 2462MHz(20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz(40MHz)



802.11n Channel High 2452MHz(40MHz)



8. BAND EDGE COMPLIANCE TEST

8.1. Block Diagram of Test Setup



(EUT: IP Camera)

8.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.3. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.3.1. IP Camera (EUT)

Model Number	:	APM-J6235-WS
Serial Number	:	N/A
Manufacturer	:	SHENZHEN APEXIS ELECTRONIC CO., LTD.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz MHz. We select 2412MHz, 2462MHz and 2422MHz, 2452MHz TX frequency to transmit.

8.5. Test Procedure

Conducted Band Edge:

8.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

8.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

Radiate Band Edge:

8.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

8.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

8.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

8.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

8.5.7. The band edges was measured and recorded.

8.6. Test Result

Pass**Conducted test**

Date of Test:	July 24, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60HZ
Test Mode:	TX	Test Engineer:	Pei

The test was performed with 802.11b

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	39.68	> 20dBc
2462	40.86	> 20dBc

The test was performed with 802.11g

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	36.95	> 20dBc
2462	37.35	> 20dBc


The test was performed with 802.11n (20MHz)

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	36.38	> 20dBc
2462	37.87	> 20dBc


The test was performed with 802.11n (40MHz)

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2422	26.96	> 20dBc
2452	26.87	> 20dBc


802.11b Channel Low 2412MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)



802.11n Channel High 2462MHz (20MHz)



802.11n Channel Low 2422MHz (40MHz)




802.11n Channel High 2452MHz (40MHz)



*RBW 100 kHz Marker 1 [T1]
 *VBW 300 kHz -13.62 dBm
 Ref 20 dBm Att 50 dB SWT 15 ms 2.458060000 GHz

1 PK
 MAXH



Radiated Band Edge Result

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Low 2412MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2310.000	40.00	49.97	-7.81	32.19	42.16	54.00	74.00	-21.81	-31.84	Vertical
2359.168	40.28	51.20	-7.73	32.55	43.47	54.00	74.00	-21.45	-30.53	Vertical
2390.000	42.82	51.4	-7.53	35.29	43.51	54.00	74.00	-18.71	-30.49	Vertical
2310.000	39.18	46.79	-7.81	31.37	38.98	54.00	74.00	-22.63	-35.02	Horizontal
2342.882	40.15	48.46	-7.79	32.36	40.67	54.00	74.00	-21.64	-33.33	Horizontal
2390.000	36.99	43.96	-7.53	29.46	36.43	54.00	74.00	-24.54	-37.57	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel High 2462MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	32.88	45.88	-7.37	27.74	38.51	54.00	74.00	-26.26	-35.49	Vertical
2491.627	36.18	47.66	-7.39	28.79	40.27	54.00	74.00	-25.21	-33.73	Vertical
2500.000	34.28	43.96	-7.40	26.88	36.56	54.00	74.00	-27.12	-37.44	Vertical
2483.500	33.69	44.87	-7.37	26.32	37.50	54.00	74.00	-27.68	-36.50	Horizontal
2494.641	35.28	46.34	-7.39	27.89	38.95	54.00	74.00	-26.11	-35.05	Horizontal
2500.000	31.28	43.81	-7.40	23.88	36.41	54.00	74.00	-30.12	-37.59	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Low 2412MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2310.000	37.61	48.53	-7.81	29.80	40.72	54.00	74.00	-24.20	-33.28	Vertical
2345.380	38.29	50.02	-7.79	30.50	42.23	54.00	74.00	-23.50	-31.77	Vertical
2390.000	35.91	46.54	-7.53	28.38	39.01	54.00	74.00	-25.62	-34.99	Vertical
2310.000	38.91	47.47	-7.81	31.10	39.66	54.00	74.00	-22.90	-34.34	Horizontal
2344.686	38.22	49.93	-7.79	30.43	42.14	54.00	74.00	-23.57	-31.86	Horizontal
2390.000	36.43	45.66	-7.53	28.90	38.13	54.00	74.00	-25.10	-35.87	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel High 2462MHz	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	34.17	45.47	-7.37	26.80	38.10	54.00	74.00	-27.20	35.90	Vertical
2494.006	35.91	46.64	-7.40	28.51	39.24	54.00	74.00	-25.49	-34.76	Vertical
2500.000	32.58	44.82	-7.40	25.18	37.42	54.00	74.00	-28.82	-36.58	Vertical
2483.500	34.67	44.50	-7.37	27.30	37.13	54.00	74.00	-26.70	-36.87	Horizontal
2493.848	34.19	45.47	-7.40	26.79	38.07	54.00	74.00	-27.21	-35.93	Horizontal
2500.000	36.48	45.21	-7.40	29.08	37.81	54.00	74.00	-24.92	-36.19	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel Low 2412MHz (20MHz)	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2310.000	39.33	48.26	-7.81	31.52	40.45	54.00	74.00	-22.48	-33.55	Vertical
2358.191	39.36	50.86	-7.74	31.62	43.12	54.00	74.00	-22.38	-30.88	Vertical
2390.000	34.58	44.94	-7.53	27.05	37.41	54.00	74.00	-26.95	-36.59	Vertical
2310.000	39.24	47.88	-7.81	31.43	40.07	54.00	74.00	-22.57	-33.93	Horizontal
2343.160	39.88	50.17	-7.79	32.09	42.38	54.00	74.00	-21.91	-31.62	Horizontal
2390.000	34.81	45.76	-7.53	27.28	38.23	54.00	74.00	-26.72	-35.77	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel High 2462MHz (20MHz)	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	33.80	44.77	-7.37	26.43	37.40	54.00	74.00	-27.57	-36.60	Vertical
2492.102	35.17	48.02	-7.39	27.78	40.63	54.00	74.00	26.22	-33.37	Vertical
2500.000	32.93	44.65	-7.40	25.53	37.25	54.00	74.00	-28.47	-36.75	Vertical
2483.500	34.28	45.40	-7.37	26.91	38.03	54.00	74.00	-27.09	-35.97	Horizontal
2493.372	37.72	46.17	-7.39	30.53	38.78	54.00	74.00	-23.47	-35.22	Horizontal
2500.000	35.91	44.68	-7.40	28.51	37.28	54.00	74.00	-25.49	-36.72	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test:	July 26, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11n Channel Low 2422MHz (40MHz)	Test Engineer:	Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2310.000	43.08	50.94	-7.81	35.27	43.13	54.00	74.00	-18.73	-30.87	Vertical
2342.646	42.18	52.49	-7.79	34.39	44.70	54.0	74.00	-19.61	-29.30	Vertical
2390.000	43.99	51.17	-7.53	36.46	43.64	54.00	74.00	-17.54	-30.36	Vertical
2310.000	40.28	47.08	-7.81	32.47	39.27	54.00	74.00	-21.53	-34.73	Horizontal
2335.020	43.17	50.71	-7.80	35.37	42.91	54.00	74.00	-18.63	-31.09	Horizontal
2390.000	39.83	47.97	-7.53	32.30	40.44	54.00	74.00	-21.70	-33.56	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Date of Test: July 26, 2013

Temperature: 25°C

EUT: IP Camera

Humidity: 50%

Model No.: APM-J6235-WS

Power Supply: AC 120V/60Hz

802.11n Channel High 2452MHz

Test Mode: (40MHz)

Test Engineer: Pei

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	41.89	48.40	-7.37	34.52	41.03	54.00	74.00	-19.48	-32.97	Vertical
2494.262	41.00	48.52	-7.39	33.61	41.13	54.00	74.00	-20.39	-32.87	Vertical
2500.000	38.91	46.08	-7.40	31.51	38.68	54.00	74.00	-22.49	-35.32	Vertical
2483.500	35.17	44.87	-7.37	27.80	37.50	54.00	74.00	-26.20	-36.50	Horizontal
2494.262	36.99	46.29	-7.39	29.60	38.90	54.00	74.00	-24.40	-35.10	Horizontal
2500.000	33.55	44.48	-7.40	26.15	37.08	54.00	74.00	-27.85	-36.92	Horizontal

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2557
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 1(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/18/32
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	46.79	-7.81	38.98	74.00	-35.02	peak			
2	2310.000	39.18	-7.81	31.37	54.00	-22.63	AVG			
3	2342.882	48.46	-7.79	40.67	74.00	-33.33	peak			
4	2342.882	40.15	-7.79	32.36	54.00	-21.64	AVG			
5	2390.000	43.96	-7.53	36.43	74.00	-37.57	peak			
6	2390.000	36.99	-7.53	29.46	54.00	-24.54	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2558
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 1(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/22/34
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	49.97	-7.81	42.16	74.00	-31.84	peak			
2	2310.000	40.00	-7.81	32.19	54.00	-21.81	AVG			
3	2359.168	51.20	-7.73	43.47	74.00	-30.53	peak			
4	2359.168	40.28	-7.73	32.55	54.00	-21.45	AVG			
5	2390.000	51.04	-7.53	43.51	74.00	-30.49	peak			
6	2390.000	42.82	-7.53	35.29	54.00	-18.71	AVG			


ACCURATE TECHNOLOGY CO., LTD.


 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

 Job No.: star #2559
 Standard: FCC 15C PK
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 49 %
 EUT: IP Camera
 Mode: TX Channel 11(802.11b)
 Model: APM-J6235-WS
 Manufacturer: APEXIS

 Polarization: Vertical
 Power Source: AC 120V/60Hz
 Date: 13/07/26/
 Time: 13/27/41
 Engineer Signature:
 Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	45.88	-7.37	38.51	74.00	-35.49	peak			
2	2483.500	32.88	-7.37	27.74	54.00	-26.26	AVG			
3	2491.627	47.66	-7.39	40.27	74.00	-33.73	peak			
4	2491.627	36.18	-7.39	28.79	54.00	-25.21	AVG			
5	2500.000	43.96	-7.40	36.56	74.00	-37.44	peak			
6	2500.000	34.28	-7.40	26.88	54.00	-27.12	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2560

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 11(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 13/32/24

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.87	-7.37	37.50	74.00	-36.50	peak			
2	2483.500	33.69	-7.37	26.32	54.00	-27.68	AVG			
3	2494.641	46.34	-7.39	38.95	74.00	-35.05	peak			
4	2494.641	35.28	-7.39	27.89	54.00	-26.11	AVG			
5	2500.000	43.81	-7.40	36.41	74.00	-37.59	peak			
6	2500.000	31.28	-7.40	23.88	54.00	-30.12	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2565
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 1(802.11g)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/52/31
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	47.47	-7.81	39.66	74.00	-34.34	peak			
2	2310.000	38.91	-7.81	31.10	54.00	-22.90	AVG			
3	2344.686	49.93	-7.79	42.14	74.00	-31.86	peak			
4	2344.686	38.22	-7.79	30.43	54.00	-23.57	AVG			
5	2390.000	45.66	-7.53	38.13	74.00	-35.87	peak			
6	2390.000	36.43	-7.53	28.90	54.00	-25.10	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2564
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 1(802.11g)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/48/54
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	48.53	-7.81	40.72	74.00	-33.28	peak			
2	2310.000	37.61	-7.81	29.80	54.00	-24.20	AVG			
3	2345.380	50.02	-7.79	42.23	74.00	-31.77	peak			
4	2345.380	38.29	-7.79	30.50	54.00	-23.50	AVG			
5	2390.000	46.54	-7.53	39.01	74.00	-34.99	peak			
6	2390.000	35.91	-7.53	28.38	54.00	-25.62	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2563
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 11(802.11g)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/44/42
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	45.47	-7.37	38.10	74.00	-35.90	peak			
2	2483.500	34.17	-7.37	26.80	54.00	-27.20	AVG			
3	2494.006	46.64	-7.40	39.24	74.00	-34.76	peak			
4	2494.006	35.91	-7.40	28.51	54.00	-25.49	AVG			
5	2500.000	44.82	-7.40	37.42	74.00	-36.58	peak			
6	2500.000	32.58	-7.40	25.18	54.00	-28.82	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2562

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 11(802.11g)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 13/38/10

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.50	-7.37	37.13	74.00	-36.87	peak			
2	2483.500	34.67	-7.37	27.30	54.00	-26.70	AVG			
3	2493.848	45.47	-7.40	38.07	74.00	-35.93	peak			
4	2493.848	34.19	-7.40	26.79	54.00	-27.21	AVG			
5	2500.000	45.21	-7.40	37.81	74.00	-36.19	peak			
6	2500.000	36.48	-7.40	29.08	54.00	-24.92	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2566
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: IP Camera
Mode: TX Channel 1(802.11n)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/07/26/
Time: 13/58/23
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	47.88	-7.81	40.07	74.00	-33.93	peak			
2	2310.000	39.24	-7.81	31.43	54.00	-22.57	AVG			
3	2343.160	50.17	-7.79	42.38	74.00	-31.62	peak			
4	2343.160	39.88	-7.79	32.09	54.00	-21.91	AVG			
5	2390.000	45.76	-7.53	38.23	74.00	-35.77	peak			
6	2390.000	34.81	-7.53	27.28	54.00	-26.72	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2567

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 1(802.11n)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/03/14

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	48.26	-7.81	40.45	74.00	-33.55	peak			
2	2310.000	39.33	-7.81	31.52	54.00	-22.48	AVG			
3	2358.191	50.86	-7.74	43.12	74.00	-30.88	peak			
4	2358.191	39.36	-7.74	31.62	54.00	-22.38	AVG			
5	2390.000	44.94	-7.53	37.41	74.00	-36.59	peak			
6	2390.000	34.58	-7.53	27.05	54.00	-26.95	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2568

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 11(802.11n)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/10/25

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.77	-7.37	37.40	74.00	-36.60	peak			
2	2483.500	33.80	-7.37	26.43	54.00	-27.57	AVG			
3	2492.102	48.02	-7.39	40.63	74.00	-33.37	peak			
4	2492.102	35.17	-7.39	27.78	54.00	-26.22	AVG			
5	2500.000	44.65	-7.40	37.25	74.00	-36.75	peak			
6	2500.000	32.93	-7.40	25.53	54.00	-28.47	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2569

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 11(802.11n)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/15/12

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	45.40	-7.37	38.03	74.00	-35.97	peak			
2	2483.500	34.28	-7.37	26.91	54.00	-27.09	AVG			
3	2493.372	46.17	-7.39	38.78	74.00	-35.22	peak			
4	2493.372	37.92	-7.39	30.53	54.00	-23.47	AVG			
5	2500.000	44.68	-7.40	37.28	74.00	-36.72	peak			
6	2500.000	35.91	-7.40	28.51	54.00	-25.49	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2573

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 3(802.11n)40MHz

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/39/42

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	47.08	-7.81	39.27	74.00	-34.73	peak			
2	2310.000	40.28	-7.81	32.47	54.00	-21.53	AVG			
3	2335.020	50.71	-7.80	42.91	74.00	-31.09	peak			
4	2335.020	43.17	-7.80	35.37	54.00	-18.63	AVG			
5	2390.000	47.97	-7.53	40.44	74.00	-33.56	peak			
6	2390.000	39.83	-7.53	32.30	54.00	-21.70	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2572

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 3(802.11n)40MHz

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/33/52

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	50.94	-7.81	43.13	74.00	-30.87	peak			
2	2310.000	43.08	-7.81	35.27	54.00	-18.73	AVG			
3	2342.646	52.49	-7.79	44.70	74.00	-29.30	peak			
4	2342.646	42.18	-7.79	34.39	54.00	-19.61	AVG			
5	2390.000	51.17	-7.53	43.64	74.00	-30.36	peak			
6	2390.000	43.99	-7.53	36.46	54.00	-17.54	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2571

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: IP Camera

Mode: TX Channel 9(802.11n)40MHz

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/26/

Time: 14/27/55

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.40	-7.37	41.03	74.00	-32.97	peak			
2	2483.500	41.89	-7.37	34.52	54.00	-19.48	AVG			
3	2494.262	48.52	-7.39	41.13	74.00	-32.87	peak			
4	2494.262	41.00	-7.39	33.61	54.00	-20.39	AVG			
5	2500.000	46.08	-7.40	38.68	74.00	-35.32	peak			
6	2500.000	38.91	-7.40	31.51	54.00	-22.49	AVG			




ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: star #2570	Polarization: Horizontal
Standard: FCC 15C PK	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 13/07/26/
Temp.(C)/Hum.(%) 23 C / 49 %	Time: 14/21/19
EUT: IP Camera	Engineer Signature:
Mode: TX Channel 9(802.11n)40MHz	Distance: 3m
Model: APM-J6235-WS	
Manufacturer: APEXIS	

Note: Report No.:ATE20131556




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.87	-7.37	37.50	74.00	-36.50	peak			
2	2483.500	35.17	-7.37	27.80	54.00	-26.20	AVG			
3	2494.262	46.29	-7.39	38.90	74.00	-35.10	peak			
4	2494.262	36.99	-7.39	29.60	54.00	-24.40	AVG			
5	2500.000	44.48	-7.40	37.08	74.00	-36.92	peak			
6	2500.000	33.55	-7.40	26.15	54.00	-27.85	AVG			

9. RADIATED SPURIOUS EMISSION TEST

9.1. Block Diagram of Test Setup


9.1.1. Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode

(EUT: IP Camera)

9.1.2. Semi-Anechoic Chamber Test Setup Diagram



9.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3.Restricted bands of operation

9.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

9.4.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4.1.IP Camera (EUT)

Model Number : APM-J6235-WS
 Serial Number : N/A
 Manufacturer : SHENZHEN APEXIS ELECTRONIC CO., LTD.

9.5.Operating Condition of EUT

9.5.1.Setup the EUT and simulator as shown as Section 9.1.

9.5.2.Turn on the power of all equipment.

9.5.3.Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

9.6.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The worst-case data rate for this channel to be 1Mbps for 802.11b mode and 6Mbps for 802.11g mode and 150Mbps for 802.11n mode, based on previous with 802.11 WLAN product design architectures.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

9.7.The Field Strength of Radiation Emission Measurement Results

PASS.

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Low 2412MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
40.8445	55.20	-20.15	35.05	40.00	-4.95	Vertical
119.8555	64.19	-22.52	41.67	43.50	-1.83	
239.9874	64.80	-19.80	45.00	46.50	-1.50	
360.4476	60.69	-15.92	44.77	46.50	-1.73	
239.9874	63.93	-19.80	44.13	46.50	-2.37	Horizontal
300.3672	62.10	-17.86	44.24	46.50	-2.26	
360.4476	60.73	-15.92	44.81	46.50	-1.69	
601.4265	55.89	-11.65	44.24	46.50	-2.26	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel Middle 2437MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	57.48	-21.57	35.91	40.00	-4.09	Vertical
239.9874	64.76	-19.80	44.96	46.50	-1.54	
360.4476	60.06	-15.92	44.14	46.50	-2.36	
601.4265	56.27	-11.65	44.62	46.50	-1.88	
239.9874	64.48	-19.80	44.68	46.50	-1.82	Horizontal
330.1949	57.90	-16.98	40.92	46.50	-5.58	
360.4476	60.29	-15.92	44.37	46.50	-2.13	
601.4265	55.90	-11.65	44.25	46.50	-2.25	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11b Channel High 2462MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	58.12	-21.57	36.55	40.00	-3.45	Vertical
119.8555	64.45	-22.52	41.93	43.50	-1.57	
239.9874	64.20	-19.80	44.40	46.50	-2.10	
360.4476	60.25	-15.92	44.33	46.50	-2.17	
239.9874	64.85	-19.80	45.05	46.50	-1.45	Horizontal
315.4806	60.65	-17.52	43.13	46.50	-3.37	
360.4476	61.05	-15.92	45.13	46.50	-1.37	
601.4265	55.73	-11.65	44.08	46.50	-2.42	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Low 2412MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
74.6568	57.83	-2.61	36.22	40.00	-3.78	Vertical
119.8555	64.42	-22.52	41.90	43.50	-1.60	
239.9874	63.79	-19.80	43.99	46.50	-2.51	
360.4476	61.18	-15.92	45.25	46.50	-1.24	
239.9874	63.63	-19.80	43.83	46.50	-2.67	Horizontal
322.1886	61.24	-17.31	43.93	46.50	-2.57	
360.4476	60.99	-15.92	45.07	46.50	-1.43	
601.4265	55.70	-11.65	44.05	46.50	-2.45	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel Middle 2437MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
74.3954	56.84	-21.59	35.25	40.00	-4.75	Vertical
119.8555	64.72	-22.52	42.20	43.50	-1.30	
239.9874	64.61	-19.80	44.81	46.50	-1.69	
360.4476	60.78	-15.92	44.86	46.50	-1.64	
239.9874	63.53	-19.80	43.73	46.50	-2.77	Horizontal
324.4560	61.52	-17.22	44.30	46.50	-2.20	
360.4476	60.70	-15.92	44.78	46.50	-1.72	
601.4265	55.02	-11.65	43.37	46.50	-3.13	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
Test Mode:	802.11g Channel High 2462MHz	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	59.31	-21.57	37.74	40.00	-2.26	Vertical
119.8555	64.11	-22.52	41.59	43.50	-1.91	
239.9874	64.81	-19.80	45.01	46.50	-1.49	
360.4476	60.22	-15.92	44.30	46.50	-2.20	
239.9874	64.86	-19.80	45.06	46.50	-1.44	Horizontal
324.4560	61.77	-17.22	44.55	46.50	-1.95	
360.4476	61.33	-15.92	45.41	46.50	-1.09	
601.4265	56.02	-11.65	44.37	46.50	-2.13	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel Low 2412MHz		
Test Mode:	(20MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
74.3954	57.88	-21.59	36.29	40.00	-3.71	Vertical
239.9874	63.87	-19.80	44.07	46.50	-2.43	
360.4476	61.06	-15.9	45.14	46.50	-1.36	
601.4265	54.53	-11.65	42.88	46.50	-3.62	
239.9874	64.23	-19.80	44.43	46.50	-2.07	Horizontal
32.4560	60.53	-17.22	43.31	46.50	-3.19	
360.4476	60.68	-15.92	44.76	46.50	-1.74	
601.4265	55.71	-11.65	44.06	46.50	-2.44	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel Middle 2437MHz		
Test Mode:	(20MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	58.06	-21.57	36.49	40.00	-3.51	Vertical
119.8555	64.30	-22.52	41.78	43.50	-1.72	
239.9874	63.50	-19.80	43.70	46.50	-2.80	
360.4476	60.60	-15.92	44.68	46.50	-1.82	
239.9874	64.60	-19.80	44.80	46.50	-1.70	Horizontal
324.4560	60.15	-17.22	42.93	46.50	-3.57	
360.4476	60.22	-15.92	44.30	46.50	-2.20	
601.4265	55.58	-11.65	43.93	46.50	-2.57	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel High 2462MHz		
Test Mode:	(20MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.6170	57.86	-21.55	36.31	40.00	-3.69	Vertical
239.9874	63.85	-19.80	44.05	46.50	-2.45	
300.3672	62.22	-17.86	44.36	46.50	-2.14	
360.4476	60.73	-15.92	44.81	46.50	-1.69	
239.9874	64.63	-19.80	44.83	46.50	-1.67	Horizontal
324.4560	61.23	-17.22	44.01	46.50	-2.49	
360.4476	60.11	-15.92	44.19	46.50	-2.31	
601.4265	56.38	-11.65	44.73	46.50	-1.77	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel Low 2422MHz		
Test Mode:	(40MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	58.58	-21.57	37.01	40.00	-2.99	Vertical
119.8555	64.07	-22.52	41.55	43.50	-1.95	
239.9874	63.91	-19.80	44.11	46.50	-2.39	
360.4476	61.06	15.92	45.14	46.50	-1.36	
239.9874	64.75	-19.80	44.95	46.50	-1.55	Horizontal
324.4561	60.87	-17.22	43.65	46.50	-2.85	
360.4476	60.66	-15.92	44.74	46.50	-1.76	
601.4265	55.64	-11.65	43.99	46.50	-2.51	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel Middle 2437MHz		
Test Mode:	(40MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
74.3955	57.64	-21.59	36.05	40.00	-3.95	Vertical
119.8556	64.25	-22.52	41.73	43.50	-1.77	
239.9874	64.20	-19.80	44.40	46.50	-2.10	
360.4476	61.04	-15.92	45.12	46.50	-1.38	
239.9874	64.50	-19.80	44.70	46.50	-1.80	Horizontal
315.4806	60.08	-17.52	42.56	46.50	-3.94	
360.4476	59.45	-15.92	43.53	46.50	-2.97	
601.4265	56.58	-11.65	44.93	46.50	-1.57	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**

Date of Test:	July 25, 2013	Temperature:	25°C
EUT:	IP Camera	Humidity:	50%
Model No.:	APM-J6235-WS	Power Supply:	AC 120V/60Hz
	802.11n Channel High 2452MHz		
Test Mode:	(40MHz)	Test Engineer:	Pei

For 30MHz-1000MHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
73.8756	57.80	-21.57	36.23	40.00	-3.77	Vertical
119.8555	64.77	-22.52	42.25	43.50	-1.25	
239.9874	63.78	-19.80	43.98	46.50	-2.52	
360.4476	61.00	-15.92	45.08	46.50	-1.42	
239.9874	64.18	-19.80	44.38	46.50	-2.12	Horizontal
300.3672	61.36	-17.86	43.50	46.50	-3.00	
360.4476	60.53	-15.92	44.61	46.50	-1.89	
601.4265	56.16	-11.65	44.51	46.50	-1.99	

For 1GHz-25GHz

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

Frequency (MHz)	Reading(dBμV/m)		Factor Corr. (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dBμV/m)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
-	-	-	-	-	-	-	-	-	-	Vertical
-	-	-	-	-	-	-	-	-	-	Horizontal

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.**2. *: Denotes restricted band of operation.****3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.**



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2259
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 1(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 8/50/33
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	40.8445	55.20	-20.15	35.05	40.00	-4.95	QP			
2	119.8555	64.19	-22.52	41.67	43.50	-1.83	QP			
3	239.9874	64.80	-19.80	45.00	46.50	-1.50	QP			
4	360.4476	60.69	-15.92	44.77	46.50	-1.73	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2260

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 8/53/27

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	239.9874	63.93	-19.80	44.13	46.50	-2.37	QP			
2	300.3672	62.10	-17.86	44.24	46.50	-2.26	QP			
3	360.4476	60.73	-15.92	44.81	46.50	-1.69	QP			
4	601.4265	55.89	-11.65	44.24	46.50	-2.26	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2283	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 13/07/25/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 10/14/58
EUT: IP Camera	Engineer Signature: STAR
Mode: TX Channel 1(802.11b)	Distance: 3m
Model: APM-J6235-WS	
Manufacturer: APEXIS	

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2284	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 13/07/25/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 10/18/33
EUT: IP Camera	Engineer Signature: STAR
Mode: TX Channel 1(802.11b)	Distance: 3m
Model: APM-J6235-WS	
Manufacturer: APEXIS	

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2307
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 1(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 11/41/59
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2308

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 11/45/06

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2261

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 6(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 8/55/06

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	239.9874	64.48	-19.80	44.68	46.50	-1.82	QP			
2	330.1949	57.90	-16.98	40.92	46.50	-5.58	QP			
3	360.4476	60.29	-15.92	44.37	46.50	-2.13	QP			
4	601.4265	55.90	-11.65	44.25	46.50	-2.25	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2262
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 6(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 8/58/43
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	73.8756	57.48	-21.57	35.91	40.00	-4.09	QP			
2	239.9874	64.76	-19.80	44.96	46.50	-1.54	QP			
3	360.4476	60.06	-15.92	44.14	46.50	-2.36	QP			
4	601.4265	56.27	-11.65	44.62	46.50	-1.88	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2285

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 6(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 10/22/09

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2286

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 6(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 10/25/59

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2309
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 6(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 11/48/39
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2310

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 6(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 11/51/03

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2263
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 11(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 9/03/33
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	73.8756	58.12	-21.57	36.55	40.00	-3.45	QP			
2	119.8555	64.45	-22.52	41.93	43.50	-1.57	QP			
3	239.9874	64.20	-19.80	44.40	46.50	-2.10	QP			
4	360.4476	60.25	-15.92	44.33	46.50	-2.17	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2264

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 11(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 9/07/29

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	239.9874	64.85	-19.80	45.05	46.50	-1.45	QP			
2	315.4806	60.65	-17.52	43.13	46.50	-3.37	QP			
3	360.4476	61.05	-15.92	45.13	46.50	-1.37	QP			
4	601.4265	55.73	-11.65	44.08	46.50	-2.42	QP			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2287
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 11(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 10/28/42
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2288

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 11(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 10/31/20

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: star #2311
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: IP Camera
Mode: TX Channel 11(802.11b)
Model: APM-J6235-WS
Manufacturer: APEXIS

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/07/25/
Time: 11/54/27
Engineer Signature: STAR
Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2312

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 11(802.11b)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 11/58/06

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2265

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11g)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 9/11/22

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	239.9874	63.63	-19.80	43.83	46.50	-2.67	QP			
2	322.1886	61.24	-17.31	43.93	46.50	-2.57	QP			
3	360.4476	60.99	-15.92	45.07	46.50	-1.43	QP			
4	601.4265	55.70	-11.65	44.05	46.50	-2.45	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2266

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11g)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz

Date: 13/07/25/

Time: 9/16/08

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	74.6568	57.83	-21.61	36.22	40.00	-3.78	QP			
2	119.8555	64.42	-22.52	41.90	43.50	-1.60	QP			
3	239.9874	63.79	-19.80	43.99	46.50	-2.51	QP			
4	360.4476	61.18	-15.92	45.26	46.50	-1.24	QP			


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2289

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11g)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 10/35/06

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2290

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: IP Camera

Mode: TX Channel 1(802.11g)

Model: APM-J6235-WS

Manufacturer: APEXIS

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/07/25/

Time: 10/38/54

Engineer Signature: STAR

Distance: 3m

Note: Report No.:ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------


ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star #2313	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 13/07/25/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 12/03/41
EUT: IP Camera	Engineer Signature: STAR
Mode: TX Channel 1(802.11g)	Distance: 3m
Model: APM-J6235-WS	
Manufacturer: APEXIS	

Note: Report No.: ATE20131556



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
-----	----------------	---------------------	----------------	--------------------	-------------------	----------------	----------	----------------	------------------	--------