

**FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                                      |                                      |  |                                 |
|--|--------------------------------------|--------------------------------------|--|---------------------------------|
| <b>Frequency Range (MHz)</b>                                   | <b>Electric Field Strength (V/m)</b> | <b>Magnetic Field Strength (A/m)</b> | <b>Power Density (mW/cm<sup>2</sup>)</b> | <b>Averaging Time (minutes)</b> |
| 0.3–1.34   | 614                                  | 1.63                                 | *(100)                                   | 30                              |
| 1.34–30  | 824/f                                | 2.19/f                               | *(180/f <sup>2</sup> )                   | 30                              |
| 30–300   | 27.5                                 | 0.073                                | 0.2                                      | 30                              |
| 300–1500   | /                                    | /                                    | f/1500                                   | 30                              |
| 1500–100,000   | /                                    | /                                    | 1.0                                      | 30                              |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculation formula:**

Prediction of power density at the distance of the applicable MPE limit

S = PG/4πR<sup>2</sup> = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

**Calculated Data:**

| Operation Mode   | Frequency (MHz) | Antenna Gain |           | Conducted output power including Tune-up Tolerance |        | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|------------------|-----------------|--------------|-----------|--|--------|--------------------------|-------------------------------------|---------------------------------|
|                  |                 | (dBi)        | (numeric) | (dBm)  | (mW)   |                          |                                     |                                 |
| WLAN 2.4G        | 2412-2462       | 3            | 2.00      | 28   | 630.96 | 20.00                    | 0.25                                | 1.0                             |
| LTE/WCDMA Band 2 | 1850-1910       | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 1.0                             |
| LTE/WCDMA Band 4 | 1710-1755       | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 1.0                             |
| LTE/WCDMA Band 5 | 824-849         | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 0.5493                          |
| LTE Band 12      | 699-716         | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 0.466                           |
| LTE Band 13      | 777-787         | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 0.518                           |
| LTE Band 14      | 788-798         | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 0.5253                          |
| LTE Band 66      | 1710-1780       | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 1.0                             |
| LTE Band 71      | 663-698         | 4            | 2.51      | 25   | 316.23 | 20.00                    | 0.158                               | 0.442                           |

The device contains a certified WWAN module, FCC ID: XMR201909EC25AFX, the WLAN and WWAN can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{WLAN}/S_{limit-WLAN} + S_{WWAN}/S_{limit-WWAN}$$

$$=0.25/1 + 0.158/0.442$$

$$=0.61$$

$$< 1.0$$

**Result:** The device meet FCC MPE at 20 cm distance