

## Maximum Permissible Exposure Report

### 1. Product Information

FCC ID	: Y3H706120181227
EUT	: HD wireless video transmitter
Test Model	: 7061
Power Supply	: Adapter power: Model: GPE012A-050200-Z Input: AC 100-240V, 50/60Hz 0.3A Output: 5V/2000mA
Hardware Version	: 7061T01
Software Version	: V3.07
WIFI (5.2G Band)	:
Frequency Range	: 5190 – 5230 MHz
Channel Number	: 2 channels for 40MHz bandwidth (5190 – 5230 MHz)
Modulation Type	: IEEE 802.11n HT40: OFDM
WIFI (5.8G Band)	:
Frequency Range	: 5755 – 5795 MHz
Channel Number	: 2 channels for 40MHz bandwidth (5755 – 5795 MHz)
Modulation Type	: IEEE 802.11n HT40: OFDM
Antenna Description	:
	Two same External and Ingrate Antennas, support 2T2R MIMO technology ANT0 & ANT1 are used for 5.2GWIFI TX/RX and 5.8G Band, 5.0dBi (Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

### 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

The EUT can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	5G Wi-Fi Chain 0	External and Ingrate Antenna	5 GHz – 6 GHz	5.00 dBi
Antenna 1	5G Wi-Fi Chain 1	External and Ingrate Antenna	5 GHz – 6 GHz	5.00 dBi

### 6. Conducted Power

#### [5GHz WLAN Band 1]

IEEE 802.11n HT40				
Frequency (MHz)	Antenna 0		Antenna 1	
	5190	5230	5190	5230
Average Conducted Power (dBm)	10.06	13.25	10.70	12.40

#### [5GHz WLAN Band 3]

IEEE 802.11n HT40				
Frequency (MHz)	Antenna 0		Antenna 1	
	5755	5795	5755	5795
Average Conducted Power (dBm)	13.38	11.41	11.98	10.26

## 7. Manufacturing Tolerance

[5GHz WLAN Band 1]

IEEE 802.11n HT40				
Frequency (MHz)	Antenna 0		Antenna 1	
	5190	5230	5190	5230
Target (dBm)	11.0	14.0	11.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0

[5GHz WLAN Band 3]

IEEE 802.11n HT40				
Frequency (MHz)	Antenna 0		Antenna 1	
	5755	5795	5755	5795
Target (dBm)	14.0	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0	1.0

## 8. Measurement Results

### 8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[5GHz WLAN Band 1]

[Antenna 0]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11n HT40	15.00	31.6228	5.0000	3.1623	100%	0.0199	1.0000

[Antenna 1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11n HT40	15.00	31.6228	5.0000	3.1623	100%	0.0199	1.0000

[5GHz WLAN Band 3]

[Antenna 0]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11n HT40	15.00	31.6228	5.0000	3.1623	100%	0.0199	1.0000

[Antenna 1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW					
IEEE 802.11n HT40	13.00	19.9526	5.0000	3.1623	100%	0.0126	1.0000

Remark:

1. Output power including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

### 8.2 Simultaneous Transmission MPE Evaluation

The sample supports 2T2R MIMO technology for 5G WLAN.

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\Sigma$  of MPE ratios  $\leq$  1.0

### 8.2.1 Summary simultaneous transmission information

Modulation Type	Work Frequency Band	Transmit Antenna		Antenna 0 Antenna 1 Synchronization transmit
		Antenna 0	Antenna 1	
IEEE 802.11n HT40	UNII Band 1 / Band 3	Yes	Yes	Yes

### 8.2.2 Summary simultaneous transmission results

*Antenna 0 and Antenna 1 for 5G WLAN Band 1*

Modulation Type	MPE <sub>Antenna 0</sub> Ratios	MPE <sub>Antenna 1</sub> Ratios	$\Sigma$ MPE ratios	Limit	Results
IEEE 802.11n HT40	0.0199	0.0199	0.1	1.0	PASS

*Antenna 0 and Antenna 1 for 5G WLAN Band 3*

Modulation Type	MPE <sub>Antenna 0</sub> Ratios	MPE <sub>Antenna 1</sub> Ratios	$\Sigma$ MPE ratios	Limit	Results
IEEE 802.11n HT40	0.0199	0.0126	0.1	1.0	PASS

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----