

## Maximum Permissible Exposure Report

### 1. Product Information

FCC ID: : Y3H711831182021

EUT : PRO Z

Test Model : 7118+3118

Power Supply : Input: 12V $\overline{=}$ 2000mA  
: For AC Adapter Input:100-240V~, 50/60Hz, 0.75A  
Adapter Output: 12V $\overline{=}$ 2000mA 24W

Hardware Version : V2.0

Software Version : v2.61.3

5.2G :

Frequency Range : 5230MHz

Channel Number : 1 channels for 40MHz bandwidth

Frequency : 5230MHz

Modulation Type : OFDM

Antenna Description : External Antenna, 5dBi(max.)

5.8G :

Frequency Range : 5755MHz~5795MHz

Channel Number : 2 channels for 40MHz bandwidth

Frequency : 5755MHz,5795MHz

Modulation Type : OFDM

Antenna Description : External Antenna, 5dBi(max.)

Exposure category : General population/uncontrolled environment

EUT Type : Production Unit

Device Type : fixed Device

## 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

## 3. Limit

### 3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

### 3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

#### 4. MPE Calculation Method

Predication of MPE limit at a given distance  
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

#### 5. Antenna Information

C2M can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna	External Antenna	5230MHz	5.0dBi	WHDI Antenna
Antenna	External Antenna	5755MHz~5795MHz	5.0dBi	WHDI Antenna

## 6. Conducted Power

### [5.2G Max Conducted Power]

Modulation Mode	Antenna	Channel	Result[dBm]	Verdict
OFDM	Ant1	5230	14.37	PASS
OFDM	Ant2	5230	14.32	PASS
OFDM	Ant1+ Ant2	5230	17.36	PASS

### [5.8G Max Conducted Power]

Modulation Mode	Antenna	Channel	Result[dBm]	Verdict
OFDM	Ant1	5755	9.34	PASS
		5795	9.12	PASS
OFDM	Ant2	5755	9.52	PASS
		5795	9.32	PASS
OFDM	Ant1+Ant2	5755	12.44	PASS
		5795	12.23	PASS

## 7. Measurement Results

5.2G			
Channel	5230-Ant1	5230-Ant2	5230-Ant1+Ant2
Target (dBm)	14.0	14.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.8G-ANT1			
Channel	5755	5795	/
Target (dBm)	9.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
5.8G-ANT2			
Channel	5755	5795	/
Target (dBm)	9.0	9.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/
5.8G-ANT1+ ANT2			
Channel	5755	5795	/
Target (dBm)	12.0	12.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/

## 8. Evaluation Results

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW			
5.2G	15.0	31.6228	5.0	0.0199	1.0000
5.2G-MIMO	18.0	63.0957	5.0	0.0397	1.0000
5.8G	10.0	10.0000	5.0	0.0063	1.0000
5.8GMIMO	13.0	19.9526	5.0	0.0126	1.0000

### Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. MPE values =  $PG/4\pi R^2$

## 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----