



Test Number: 200-15

6. Measurement Data (continued)

- 6.13. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN 5.5, RSS 102)
 - 6.12.1. 15.247(i) (1.1307 (b)(1) Requirements
 - Requirement: Portable devices are subject to radio frequency radiation exposure requirements.

For a 1-g SAR, the test exclusion result must be \leq 3.0.

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by the following formula:

SAR Test Exclusion = $\frac{P_{MAX}}{d_{MIN}} \times \sqrt{f_{(GHz)}}$ (1)

- P_{MAX} mW Maximum power of channel, including tune-up tolerance
- d_{MIN} mm Minimum test separation distance, mm (\leq 50 mm)
- $f_{(GHz)}$ GHz $f_{(GHz)}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)
- FCC OET 447498 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Result: The device under test meets the exclusion requirement detailed in FCC OET 447498.

Input:		(mW)	0.28	0.56	1.09
	d _{MIN}	(mm)	5.00	5.00	5.00
	$\mathbf{f}_{(GHz)}$		2.402	2.441	2.480
Test Ex	clusion	:	0.37	0.09	0.17
Limit Exemption:			3.00	3.00	3.00

¹ Taken from column 7 of the table in Section 6.6 of this test.

6.12.2. RSS-102 Issue 5 Requirements

Requirement: SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are subject to radio frequency radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5.

Frequency (MHz)	Separation Distance (mm)	Maximum Power (mW)	RSS-102 Limit (mW)	Result
2402.00	≤5	0.28	4.26	Compliant
2441.00	≤5	0.56	4.05	Compliant
2480.00	≤5	1.09	3.94	Compliant