

Maximum Permissible Exposure

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

$$P = \text{Peak output power (mW)}$$

$$G = \text{Antenna numeric gain (numeric)}$$

$$d = \text{Separation distance (cm)}$$

$$\text{Numeric Gain} = 10 ^ {(G \text{ (dBi)})/10}$$

The peak power in the table below is calculated by assuming a worst case scenario where all of the EUT transmitters are operating simultaneously in the same band. The Peak Power in mW is the highest transmitter power measured and summed across all transmitters.

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

Freq. Band (MHz)	Antenna Gain		Peak Combined Output Power		Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
	dBi	Numeric	(dBm)	(mW)		
5.8	30.0	1000.00	29.99	997.7	281.8	281.8

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310

Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §5.5

Before equipment certification is granted, the application requirements of RSS-102 shall be met.