

MPE CALCULATION

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	1500 ~100,000MHz
Power Density Limit:	1 mW/ cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

MPE test Result

Radio Mode	Frequency (MHz)	Meas Output Power (dBm)	Antenna Gain (dBi)	Power Density (mw/cm ²)	Max tune-up Power (dBm)	Scaled Power Density (mw/cm ²)	Power Density Limit(mw/cm ²)
UMTS Band 2	1930 - 1995	24.24	3	0.105	24.5	0.112	1
LTE Band 7	2620 - 2690	22.87	3	0.077	24.5	0.112	1

Total Power density= 0.112 mW/cm² + 0.112 mW/cm² = 0.224 mW/cm² < 1mW/ cm²

The Above Result had shown that Device complied with MPE requirement.

Completed By: Nima Molaei

Date: Nov 14st, 2014

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188