
FCC Part 90& RSS-119

Test Report

Report No.: AGC12111011SZ16-1F1

TEST NAME : FCC Part 90 & RSS-119

FCC ID : Y4GCU600-1

IC ID : 9415A-CU6001

PRODUCT DESIGNATION : Two way radio

BRAND NAME : COVALUE

TEST MODEL NAME : CU600-1

CLIENT : SHENZHEN COVALUE COMMUNICATIONS CO., LTD.

DATE OF ISSUE : Dec.16, 2010

STANDARD(S) : FCC Part 90& RSS-119 Rules

Attestation of **Global Compliance Co., Ltd.**

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION.....	4
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 SPECIAL ACCESSORIES	5
1.6 EQUIPMENT MODIFICATIONS.....	5
2. SYSTEM TEST CONFIGURATION	6
2.1 EUT CONFIGURATION.....	6
2.2 EUT EXERCISE.....	6
2.3 GENERAL TECHNICAL REQUIREMENTS.....	6
2.4 CONFIGURATION OF TESTED SYSTEM.....	6
3. SUMMARY OF TEST RESULTS	7
4. DESCRIPTION OF TEST MODES	8
5. CONDUCTED LIMITS	9
5.1 PROVISIONS APPLICABLE.....	9
5.2 MEASUREMENT PROCEDURE.....	9
5.3 TEST SETUP BLOCK DIAGRAM.....	10
5.4 TEST EQUIPMENT USED	10
5.5 TEST RESULT	11
6. FREQUENCY TOLERANCE	13
6.1 PROVISIONS APPLICABLE.....	13
6.2 MEASUREMENT PROCEDURE.....	13
6.3 TEST SETUP BLOCK DIAGRAM.....	14
6.4 TEST EQUIPMENT USED:	14
6.5 TEST RESULT	14
7. EMISSION BANDWIDTH	21
7.1 PROVISIONS APPLICABLE.....	21
7.2 MEASUREMENT PROCEDURE.....	21
7.3 TEST SETUP BLOCK DIAGRAM.....	21
7.4 MEASUREMENT EQUIPMENT USED:	21
7.5 MEASUREMENT RESULT:	22
8. UNWANTED RADIATION	24
8.1 PROVISIONS APPLICABLE.....	24
8.2 MEASUREMENT PROCEDURE.....	24

8.3 TEST SETUP BLOCK DIAGRAM.....	25
8.4 MEASUREMENT EQUIPMENT USED:.....	27
8.5 MEASUREMENT RESULTS:.....	27
8.6 EMISSION MASK PLOT	30
9. MODULATION CHARACTERISTICS	32
9.1 PROVISIONS APPLICABLE.....	32
9.2 MEASUREMENT METHOD	32
9.3 MEASUREMENT INSTRUMENTS.....	32
9.4 MEASUREMENT RESULT.....	33
10.1 PROVISIONS APPLICABLE.....	39
10.2 TEST PROCEDURE.....	39
10.3 TEST INSTRUMENTS.....	39
10.4 TEST RESULT.....	40
10.4 CONDUCT SPURIOUS PLOT	41
11. TRANSMITTER FREQUENCY BEHAVIOR	44
11.1 PROVISIONS APPLICABLE	44
11.2 TEST METHOD	44
11.3 TEST INSTRUMENTS	44
12. RADIATED EMISSION ON RECEIVING MODE	49
12.1 PROVISIONS APPLICABLE	49
12.2 TEST METHOD.....	49
12.3 TEST INSTRUMENTS	49
12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS).....	50
13. AUDIO LOW PASS FILTER RESPONSE	52
13.1 LIMITS	52
13.2. METHOD OF MEASUREMENTS.....	52
13.3 TEST DATA	52
APPENDIX I.....	57
PHOTOGRAPHS OF SETUP	57
APPENDIX II.....	59
EXTERNAL VIEW OF EUT.....	59

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a single channel Two-way Radio designed for voice communication. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only
Modulation	FM
Emission Type	F3E
Emission Bandwidth	10.26kHz/15.15kHz (Limite:11.25KHz/20KHz)
Peak Frequency Deviation	1.44 KHz for 12.5 KHz Channel Separation (Limit \leq \pm 2.5 KHz)
	2.87 KHz for 25 KHz Channel Separation (Limit \leq \pm 5 KHz)
Maximum Transmitter Power	37.70dBm for 12.5 KHz Channel Separation
	37.44dBm for 25.0KHz Channel Separation
Output power Modification	5W (It was fixed by the manufacturer, any individual can't arbitrarily change it)
Antenna Designation	Detachable
Power Supply	DC 7.4V by battery
Battery Endpoint	DC 7.4V
Operation Frequency Range and Channel	Frequency Range:136MHz to 174MHz Channel Separation: 12.5KHz and 25KHz
	Top Channel: 173.975MHz, Centre Channel: 152.225MHz, Bottom Channel:136.225MHz,
Frequency Tolerance	0.644ppm for 12.5 KHz Channel Separation 0.888 ppm for 25.0 KHz Channel Separation
Transmitter Spurious (Worst case)	-37.22dBm

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: Y4GCU600-1 and IC ID: 9415A-CU6001, filing to comply with the FCC Part 90 and RSS-119 requirements.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2003; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located on the address of Attestation of Global Compliance Co., Ltd. 2F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei, Xixiang, Baoan District, Shenzhen. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 and IC requirements in documents RS212.

FCC register No.: 259865

1.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission’s requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

- (1). Section 15.207: Conducted Limits
- (2). Section 90.205: Maximum ERP is dependent upon the station’s antenna HAAT and required service area
- (3). Section 90.207: Modulation Characteristic
- (4). Section 90.209: Occupied Bandwidth
- (5). Section 90.210: Emission Mask
- (6). Section 90.213: Frequency Tolerance
- (7). Section 90.214: Transient Frequency Behavior
- (8). Section 15.109: Radiated Emission

2.4 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	Identifier	Note
1	Two way Radio	CU600-1	FCC ID: Y4GCU600-1 IC ID: 9415A-CU6001	EUT
2	--	--	--	--
--	--	--	--	--

3. SUMMARY OF TEST RESULTS

FCC Rules	RSS-119	Description Of Test	Result
§15.207	RSS-Gen	Conducted Emission	Compliant
§90.205	§5.4	Maximum Transmitter Power	Compliant
§90.207	§5.13	Modulation Characteristic	Compliant
§90.209	§5.5	Occupied Bandwidth	Compliant
§90.210	§5.8	Emission Mask	Compliant
§90.213	§5.3	Frequency Tolerance	Compliant
§90.214	§5.9	Transient Frequency Behavior	Compliant
§15.109	RSS-Gen	Radiated Emission	Compliant

4. DESCRIPTION OF TEST MODES

The EUT (Handheld two way radio) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation (12.5 KHz/ 25 KHz).

5. CONDUCTED LIMITS

5.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.


Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

5.2 MEASUREMENT PROCEDURE

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) The EUT received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- (5) All support equipments received AC power from a second LISN, if any.
- (6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (7) Analyzer / Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
During the above scans, the emissions were maximized by cable manipulation.

5.3 TEST SETUP BLOCK DIAGRAM




5.4 TEST EQUIPMENT USED

Conducted Emission Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Cal. Date
TEST RECEIVER	R&S	FCKL1528	A0304230	2010.06
LISN	SCHWARZBECK	NSLK8127	A0304233	2010.06

5.5 TEST RESULT

LINE CONDUCTED EMISSION TEST-L



Site: Conduction

Phase: **L1**

Temperature: 26

Limit: FCC Class B Conduction(QP)

Power: AC 110V/60Hz

Humidity: 60 %

EUT: Two way Radio


M/N: CU600-1

Mode: charge

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1700	27.67		9.21	10.18	37.85		19.39	64.96	54.96	-27.11	-35.57	P	
2	0.3620	29.17		12.61	10.31	39.48		22.92	58.68	48.68	-19.20	-25.76	P	
3	0.6740	27.90		7.75	10.34	38.24		18.09	56.00	46.00	-17.76	-27.91	P	
4	1.4340	27.00		9.93	10.38	37.38		20.31	56.00	46.00	-18.62	-25.69	P	
5	3.4020	25.88		8.11	10.52	36.40		18.63	56.00	46.00	-19.60	-27.37	P	

LINE CONDUCTED EMISSION TEST-N



Site: Conduction Phase: **N** Temperature: 26
 Limit: FCC Class B Conduction(QP) Power: AC 110V/60Hz Humidity: 60 %
 EUT: Two way Radio
 M/N: CU600-1
 Mode: charge
 Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2940	28.68		6.44	10.29	38.97		16.73	60.41	50.41	-21.44	-33.68	P	
2	0.3980	29.17		12.06	10.33	39.50		22.39	57.89	47.89	-18.39	-25.50	P	
3	0.9020	27.91		8.99	10.41	38.32		19.40	56.00	46.00	-17.68	-26.60	P	
4	3.3500	25.58		8.45	10.52	36.10		18.97	56.00	46.00	-19.90	-27.03	P	

6. FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- a). According to FCC Part 2 Section 2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- c). According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5KHz channel separation and 0.0005% for 25KHz channel separation.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 TEST SETUP BLOCK DIAGRAM



6.4 TEST EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
Receiver	R&S	ESIB26	A0304218	2010.06
Climate Chamber	Albatross	--	--	2010.12

6.5 TEST RESULT

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.4V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	136.225059	0.433
40	7.4	136.225041	0.301
30	7.4	136.225031	0.228
20	7.4	136.225029	0.213
10	7.4	136.225011	0.081
0	7.4	136.225007	0.051
-10	7.4	136.225004	0.029
-20	7.4	136.225002	0.015
-30	7.4	136.225013	0.095

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	152.225073	0.480
40	7.4	152.225062	0.407
30	7.4	152.225053	0.348
20	7.4	152.225033	0.217
10	7.4	152.225031	0.204
0	7.4	152.225027	0.177
-10	7.4	152.225021	0.138
-20	7.4	152.225018	0.118
-30	7.4	152.225011	0.072

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	173.975074	0.425
40	7.4	173.975069	0.397
30	7.4	173.975058	0.333
20	7.4	173.975043	0.247
10	7.4	173.975048	0.276
0	7.4	173.975042	0.241
-10	7.4	173.975038	0.218
-20	7.4	173.975029	0.167
-30	7.4	173.975015	0.086

Bottom Channel @ 25.0 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	136.225072	0.529
40	7.4	136.225067	0.492
30	7.4	136.225054	0.396
20	7.4	136.225045	0.330
10	7.4	136.225033	0.242
0	7.4	136.225021	0.154
-10	7.4	136.225011	0.081
-20	7.4	136.225009	0.066
-30	7.4	136.225021	0.154

Middle Channel @ 25.0 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	152.225108	0.709
40	7.4	152.225097	0.637
30	7.4	152.225085	0.558
20	7.4	152.225065	0.427
10	7.4	152.225043	0.282
0	7.4	152.225039	0.256
-10	7.4	152.225028	0.184
-20	7.4	152.225026	0.171
-30	7.4	152.225008	0.053

Top Channel @ 25.0 KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	7.4	173.975105	0.604
40	7.4	173.975096	0.552
30	7.4	173.975086	0.494
20	7.4	173.975076	0.437
10	7.4	173.975065	0.374
0	7.4	173.975057	0.328
-10	7.4	173.975047	0.270
-20	7.4	173.975043	0.247
-30	7.4	173.975026	0.149

(2) Frequency stability versus input voltage (Battery End Point voltage is 6.4V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	136.225081	0.595
40	6.4	136.225076	0.558
30	6.4	136.225059	0.433
20	6.4	136.225052	0.382
10	6.4	136.225043	0.316
0	6.4	136.225035	0.257
-10	6.4	136.225032	0.235
-20	6.4	136.225021	0.154
-30	6.4	136.225011	0.081

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	152.225098	0.644
40	6.4	152.225076	0.499
30	6.4	152.225069	0.453
20	6.4	152.225059	0.388
10	6.4	152.225049	0.322
0	6.4	152.225045	0.296
-10	6.4	152.225032	0.210
-20	6.4	152.225021	0.138
-30	6.4	152.225021	0.138

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	173.975091	0.523
40	6.4	173.975089	0.512
30	6.4	173.975076	0.437
20	6.4	173.975043	0.247
10	6.4	173.975032	0.184
0	6.4	173.975022	0.126
-10	6.4	173.975029	0.167
-20	6.4	173.975026	0.149
-30	6.4	173.975025	0.144

Bottom Channel @ 25.0 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	136.225121	0.888
40	6.4	136.225111	0.815
30	6.4	136.225098	0.719
20	6.4	136.225068	0.499
10	6.4	136.225059	0.433
0	6.4	136.225048	0.352
-10	6.4	136.225044	0.323
-20	6.4	136.225038	0.279
-30	6.4	136.225022	0.161

Middle Channel @ 25.0 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	152.225114	0.749
40	6.4	152.225099	0.650
30	6.4	152.225089	0.585
20	6.4	152.225078	0.512
10	6.4	152.225068	0.447
0	6.4	152.225066	0.434
-10	6.4	152.225052	0.342
-20	6.4	152.225042	0.276
-30	6.4	152.225031	0.204

Top Channel @ 25.0 KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	6.4	173.975121	0.696
40	6.4	173.975117	0.673
30	6.4	173.975098	0.563
20	6.4	173.975089	0.512
10	6.4	173.975065	0.374
0	6.4	173.975042	0.241
-10	6.4	173.975036	0.207
-20	6.4	173.975032	0.184
-30	6.4	173.975029	0.167

(3) Frequency stability versus input voltage (Battery Fully Charged voltage is 8.51V)

Bottom Channel @ 12.5 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	136.225083	0.609
40	8.51	136.225072	0.529
30	8.51	136.225052	0.382
20	8.51	136.225051	0.374
10	8.51	136.22502	0.147
0	8.51	136.225032	0.235
-10	8.51	136.225031	0.228
-20	8.51	136.225019	0.139
-30	8.51	136.225013	0.095

Middle Channel @ 12.5 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	152.225093	0.611
40	8.51	152.225073	0.480
30	8.51	152.225065	0.427
20	8.51	152.225054	0.355
10	8.51	152.225047	0.309
0	8.51	152.225042	0.276
-10	8.51	152.225031	0.204
-20	8.51	152.225028	0.184
-30	8.51	152.225023	0.151

Top Channel @ 12.5KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	173.975097	0.558
40	8.51	173.975081	0.466
30	8.51	173.975071	0.408
20	8.51	173.975042	0.241
10	8.51	173.975031	0.178
0	8.51	173.975029	0.167
-10	8.51	173.975021	0.121
-20	8.51	173.975023	0.132
-30	8.51	173.975028	0.161

Bottom Channel @ 25.0 KHz Channel Separation

Reference Frequency:	136.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	136.225118	0.866
40	8.51	136.225114	0.837
30	8.51	136.225095	0.697
20	8.51	136.225067	0.492
10	8.51	136.225055	0.404
0	8.51	136.225043	0.316
-10	8.51	136.225041	0.301
-20	8.51	136.225039	0.286
-30	8.51	136.225021	0.154

Middle Channel @ 25.0 KHz Channel Separation

Reference Frequency:	152.225 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	152.225111	0.729
40	8.51	152.225095	0.624
30	8.51	152.225087	0.572
20	8.51	152.225064	0.420
10	8.51	152.225062	0.407
0	8.51	152.225061	0.401
-10	8.51	152.225054	0.355
-20	8.51	152.225046	0.302
-30	8.51	152.225036	0.236

Top Channel @ 25.0 KHz Channel Separation

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	8.51	173.975108	0.621
40	8.51	173.975111	0.638
30	8.51	173.975095	0.546
20	8.51	173.975082	0.471
10	8.51	173.975061	0.351
0	8.51	173.975041	0.236
-10	8.51	173.975031	0.178
-20	8.51	173.975037	0.213
-30	8.51	173.975025	0.144

7. EMISSION BANDWIDTH


7.1 PROVISIONS APPLICABLE

According to FCC Part 90 Section 90.209: The authorized bandwidth shall be 11.25 KHz for 12.5 KHz and 20 KHz for 25 KHz

7.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by 2.5 KHz Sine wave audio signal, The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing).
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW= 300 Hz, Span =50 KHz.
- 4). Set SPA Max hold. Mark peak, -26 dB.

7.3 TEST SETUP BLOCK DIAGRAM




7.4 MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2010.06
MODULATION ANALYZER	HP	8901B	3104A03367	2010.06
BROADBAND ANT.	R&S	HL562	A0304224	2010.06


7.5 MEASUREMENT RESULT:

26 dB Bandwidth Measurement Result						
Operating Frequency	12.5 KHz Channel Separation			25 KHz Channel Separation		
	Test Data	Limits	Result	Test Data	Limits	Result
136.225MHz	10.21 KHz	11.25 KHz	Pass	14.98KHz	20.00 KHz	Pass
152.225MHz	10.26KHz	11.25 KHz	Pass	15.15 KHz	20.00 KHz	Pass
173.975MHz	10.21 KHz	11.25 KHz	Pass	15.11 KHz	20.00 KHz	Pass

Occupied bandwidth of Middle Channel (Maximum) @ 12.5KHz Channel Separation



Occupied bandwidth of Middle Channel (Maximum) @ 25KHz Channel Separation



8. UNWANTED RADIATION

8.1 PROVISIONS APPLICABLE

8.1.1 According to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with 12.5 KHz channel bandwidth:

- (1). On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB
- (2). On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least $7.27(f_d - 2.88 \text{ KHz})$ dB
- (3). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

8.1.2 According to Section 90.210, Emission mask B. For transmitters designed to transmit with 25 KHz channel separation and equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as following:


- (1), On any frequency removed from the assigned frequency by more than 50 percent, but no more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2), On any frequency removed from the assigned frequency by more than 100 percent, but no more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3), On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log(P)$ dB.

8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.


- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

8.3 TEST SETUP BLOCK DIAGRAM




SUBSTITUTION METHOD: (Radiated Emissions)

Radiated Below 1GHz



Radiated Above 1 GHz



8.4 MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2010.06
TEST RECEIVER	R&S	ESIB26	A0304218	2010.06
LOOP ANTENNA	R&S	HFH2-Z2	A0304220	2010.06
HORN ANT.	R&S	HF906	100150	2010.06
BROADBAND ANT.	R&S	HL562	A0304224	2010.06

8.5 MEASUREMENT RESULTS:

Measurement Result for 12.5 KHz Channel Separation-5W

On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_o of more than 12.5 KHz: At least $50+10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.

Limit: At least $50+10 \log(P) = 50+10\log(5)=57$

Measurement Result For 25 KHz Channel Separation-5W

On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43+10\log(P)$ dB.

Limit: At least $43+10 \log(P) = 43+10\log(5)=50$

Measurement Result for 25 KHz Channel Separation @ 136.225MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
136.225	v	0		pass
272.450	v	78.25(-41.25dBm)	57	pass
408.675	v	74.46(-37.46dBm)	57	pass
544.900	v	76.22(-39.22dBm)	57	pass
681.125	v	84.25	57	pass
817.350	v	92.34	57	pass
953.575	v	93.55	57	pass
1089.800	v	96.45	57	pass
1226.025	v	96.67	57	pass
1362.250	v	97.45	57	pass

Measurement Result for 25 KHz Channel Separation @ 152.225MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
152.225	v	0		pass
304.450	v	75.77(-38.77dBm)	57	pass
456.675	v	82.22	57	pass
608.900	v	83.35	57	pass
761.125	v	85.67	57	pass
913.350	v	94.57	57	pass
1065.575	v	96.45	57	pass
1217.800	v	97.78	57	pass
1370.025	v	98.22	57	pass
1522.250	v	96.35	57	pass

Measurement Result for 25 KHz Channel Separation @ 173.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
173.975	v	0		pass
347.950	v	78.24(-41.24dBm)	57	pass
521.925	v	80.52	57	pass
695.900	v	82.65	57	pass
869.875	v	86.57	57	pass
1043.850	v	95.76	57	pass
1217.825	v	96.49	57	pass
1391.800	v	97.57	57	pass
1565.775	v	96.47	57	pass
1739.750	v	96.59	57	pass

Measurement Result for 12.5 KHz Channel Separation @ 136.225MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
136.225	v	0		pass
272.450	v	77.67(-40.67dBm)	50	pass
408.68	v	74.22(-37.22dBm)	50	pass
544.900	v	76.01(-39.01dBm)	50	pass
681.125	v	84.24	50	pass
817.350	v	82.78	50	pass
953.575	v	92.54	50	pass
1089.800	v	91.76	50	pass
1226.025	v	92.43	50	pass
1362.250	v	92.24	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 152.225MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
152.225	v	0		pass
304.450	v	75.44(-38.44dBm)	50	pass
456.675	v	79.39	50	pass
608.900	v	81.46	50	pass
761.125	v	85.65	50	pass
913.350	v	90.31	50	pass
1065.575	v	93.11	50	pass
1217.800	v	94.12	50	pass
1370.025	v	94.21	50	pass
1522.250	v	94.26	50	pass

Measurement Result for 12.5 KHz Channel Separation @ 469.95MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit	Result(P/F)
469.950	v	0		pass
939.900	v	76.43(-39.43dBm)	50	pass
1409.850	v	83.34	50	pass
1879.800	v	85.64	50	pass
2349.750	v	87.27	50	pass
2819.700	v	91.65	50	pass
3289.650	v	92.15	50	pass
3759.600	v	94.21	50	pass
4229.550	v	95.21	50	pass
4699.500	v	97.22	50	pass


Notes: The emissions were scanned from 30 MHz to 10th harmonics; The worst case for Transmitter spurious is 37dBm-74.22dBc=-37.22dBm

8.6 EMISSION MASK PLOT


The detailed procedure employed for Emission Mask measurements are specified as following:

- The transmitter shall be modulated by a 2.5 kHz audio signal,
- The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing)

The Worst Emission Mask for 12.5 KHz channel Separation (5W)



The Worst Emission Mask for 25 KHz channel Separation (5W)



9. MODULATION CHARACTERISTICS

9.1 PROVISIONS APPLICABLE

According to CFR 47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

9.2 MEASUREMENT METHOD

9.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1KHz using this level as a reference (0dB) and vary the input level from -20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

9.2.2 Audio Frequency Response

- (1). Configure the EUT as shown in figure 1.
- (2). Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0 dB).
- (3). Vary the Audio frequency from 100 Hz to 10 KHz and record the frequency deviation.
- (4). Audio Frequency Response = $20\log_{10} (\text{Deviation of test frequency}/\text{Deviation of 1 KHz reference})$.




Figure 1: Modulation characteristic measurement configuration

9.3 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
Modulation Analyzer	HP	8901B	3104A03367	2010.06


9.4 MEASUREMENT RESULT

(a). Modulation Limit:

Middle Channel @ 12.5 KHz Channel Separations

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz	Peak Freq. Deviation At 1000 Hz	Peak Freq. Deviation At 1500 Hz	Peak Freq. Deviation At 3000 Hz
-20	0.03	0.21	0.31	0.42
-15	0.05	0.36	0.51	0.63
-10	0.07	0.56	0.81	1.09
-5	0.10	0.99	1.42	1.47
0	0.22	1.54	1.73	1.55
+5	0.28	1.81	1.82	1.59
+10	0.21	1.75	1.83	1.50
+15	0.21	1.73	1.75	1.51
+20	0.41	1.65	1.69	1.52


Modulation Limit



Middle Channel @ 25KHz Channel Separation

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz	Peak Freq. Deviation At 1000 Hz	Peak Freq. Deviation At 1500 Hz	Peak Freq. Deviation At 3000 Hz
-20	0.03	0.32	0.51	0.71
-15	0.05	0.68	0.91	1.32
-10	0.08	1.24	1.48	2.01
-5	0.15	1.96	2.69	2.53
0	0.32	2.98	3.24	3.11
+5	0.45	3.51	3.47	3.21
+10	0.37	3.54	3.32	3.18
+15	0.51	3.41	3.28	3.08
+20	0.31	3.47	3.41	3.09

Modulation Limit




(b). Audio Frequency Response:

12.5 KHz Channel Separation

Frequency (Hz)	Deviation (KHz)
100	--
200	--
300	0.09
400	0.16
500	0.23
600	0.29
700	0.34
800	0.39
900	0.44
1000	0.50
1200	0.60
1400	0.70
1600	0.81
1800	0.92
2000	1.03
2200	1.14
2400	1.23
2600	1.31
2800	1.36
3000	1.39
3200	1.41
3400	1.43
3600	1.44
3800	1.01
4000	0.94
4500	0.51
5000	0.38
5500	0.26
6000	0.17
6500	0.13
7000	0.05
7500	0.02
8000	--
8500	--
9000	--
9500	--


Frequency Response of Middle Channel



25 KHz Channel Separation

Frequency (Hz)	Deviation (KHz)
100	--
200	--
300	0.17
400	0.32
500	0.46
600	0.57
700	0.68
800	0.78
900	0.88
1000	1.00
1200	1.19
1400	1.40
1600	1.62
1800	1.83
2000	2.06
2200	2.27
2400	2.46
2600	2.61
2800	2.72
3000	2.78
3200	2.82
3400	2.85
3600	2.87
3800	2.01
4000	1.87
4500	1.01
5000	0.76
5500	0.52
6000	0.34
6500	0.26
7000	0.10
7500	0.03
8000	--
8500	--
9000	--
9500	--
10000	--

Frequency Response of Middle Channel



10. MAXIMUM TRANSMITTER POWER (CONDUCTED OUTPUT POWER)

10.1 PROVISIONS APPLICABLE

Per FCC §2.1046 and §90.205: Maximum ERP is dependent upon the station’s antenna HAAT and required service area.

RSS-119 4.1 and §5.4: The output power shall be within ±1.0 dB of the manufacturer's rated power.

10.2 TEST PROCEDURE

The RF output of Two-way Radio was conducted to a spectrum analyzer through an appropriate attenuator.

The transmitter shall be modulated by a 2.5 kHz audio signal,


The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing) and 5 kHz (25 kHz channel spacing)

Measure and record the transmitter output power, using a measurement (resolution) bandwidth at least two to three times the occupied bandwidth for transmitters equipped to capture the true peak emission of the equipment under test.

10.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2010.06

10.4 TEST CONFIGURATION



10.5 TEST RESULT

The maximum Conducted Power (CP) is


5 W for 12.5 KHz Channel Separation

5W for 25.0 KHz Channel Separation


Conducted Power Measurement Results		
Channel Separation	Channel	Measurement Result (dBm)
		For 37dBm(5W)
12.5 KHz	Bottom(136.225MHz)	37.58
	Middle(152.225MHz)	37.70
	Top (173.975MHz)	37.62
25 KHz	Bottom(136.225MHz)	37.44
	Middle(152.225MHz)	37.24
	Top (173.975MHz)	37.21

10.4 CONDUCT SPURIOUS PLOT


Conduct Spurious Emission @ 136.225MHz (30MHz-1GHz)




Conduct Spurious Emission @ 136.225MHz (1GHz-2GHz)




Conduct Spurious Emission @ 152.225MHz (30MHz-1GHz)




Conduct Spurious Emission @ 152.225MHz (1GHz-2GHz)



Conduct Spurious Emission @ 173.975MHz (30MHz-1GHz)



Conduct Spurious Emission @ 173.975MHz (1GHz-2GHz)



11. TRANSMITTER FREQUENCY BEHAVIOR

11.1 PROVISIONS APPLICABLE

Section 90.214

Time intervals ^{1, 2}	Maximum frequency difference ³	All equipment	
		150 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels			
t ₁ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
t ₂	± 12.5 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
t ₁ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
t ₂	± 6.25 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels			
t ₁ ⁴	± 6.25 kHz	5.0 ms	10.0 ms
t ₂	± 3.125 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 6.25 kHz	5.0 ms	10.0 ms

¹ t_{on} is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing.

t₁ is the time period immediately following t_{on}.

t₂ is the time period immediately following t₁.

t₃ is the time period from the instant when the transmitter is turned off until t_{off}.

t_{off} is the instant when the 1 kHz test signal starts to rise.

² During the time from the end of t₂ to the beginning of t₃, the frequency difference must not exceed the limits specified in §90.213.

³ Difference between the actual transmitter frequency and the assigned transmitter frequency.

⁴ If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

11.2 TEST METHOD

TIA/EIA-603 2.2.19

11.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
Signal Generator	R&S	SMT02	A0304261	2010.09
Storage Oscilloscope	Tektronix	TDS3052	B017447	2010.10

11.4 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR


ton: The switch-on instant t_{on} of a transmitter is defined by the condition when the output power, measured at the antenna terminal, exceeds 0,1 % of the full output power (-30 dBc).


t1: period of time starting at t_{on} and finishing according to above 11.1

t2: period of time starting at the end of t_1 and finishing according to above 11.1

toff: switch-off instant defined by the condition when the output power falls below 0,1 % of the full output power (-30 dBc).


t3: period of time that finishing at t_{off} and starting according to above 11.1






11.5 MEASURE RESULT


Transmitter Frequency Behavior @ 25 KHz Channel Separation--Off to On




Transmitter Frequency Behaviour @ 25 KHz Channel Separation--On to Off



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--Off to On



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--On to Off



12. Radiated Emission on Receiving Mode

12.1 PROVISIONS APPLICABLE

FCC Part 15 Subpart B Section 15.109


12.2 TEST METHOD

ANSI C 63.4: 2003

12.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2010.06
TEST RECEIVER	R&S	ESIB26	A0304218	2010.06
LOOP ANTENNA	R&S	HFH2-Z2	A0304220	2010.06
HORN ANT.	R&S	HF906	100150	2010.06
BROADBAND ANT.	R&S	HL562	A0304224	2010.06

12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS)
RADIATED EMISSION TEST RESULTS – HORIZONTAL




Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Two way Radio
M/N: CU600-1
Mode: Receive
Note:

Polarization: *Horizontal*
Power:DC 7.4V
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		181.9667	15.88	18.36	34.24	43.50	-9.26	peak			
2	*	364.6500	18.57	19.14	37.71	46.00	-8.29	peak			
3		380.8167	13.56	19.30	32.86	46.00	-13.14	peak			
4		411.5333	10.61	21.18	31.79	46.00	-14.21	peak			
5		612.0000	4.05	25.00	29.05	46.00	-16.95	peak			
6		820.5500	9.14	28.09	37.23	46.00	-8.77	peak			
7		911.0833	4.66	29.41	34.07	46.00	-11.93	peak			

RADIATED EMISSION TEST RESULTS – VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: Two way Radio
 M/N: CU600-1
 Mode: Receive
 Note:

Polarization: *Vertical*
 Power: DC7.4V
 Distance: 3m

Temperature: 26
 Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		41.3167	26.48	5.21	31.69	40.00	-8.31	peak			
2	*	76.8833	26.28	7.90	34.18	40.00	-5.82	peak			
3		408.3000	11.31	21.08	32.39	46.00	-13.61	peak			
4		612.0000	4.63	25.00	29.63	46.00	-16.37	peak			
5		728.4000	7.28	26.69	33.97	46.00	-12.03	peak			
6		815.7000	2.83	28.53	31.36	46.00	-14.64	peak			
7		911.0833	4.30	29.41	33.71	46.00	-12.29	peak			

13. Audio Low Pass Filter Response

13.1 LIMITS

2.1047(a): Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

90.242(b)(8): Recommended audio filter attenuation characteristics are given below:

Audio band	Minimum Attenuation Rel. to 1 KHz Attenuation
3 –20 KHz 20 – 30 KHz	$60 \log_{10}(f/3)$ dB where f is in KHz 50dB

13.2. METHOD OF MEASUREMENTS


The rated audio input signal was applied to the input of the audio low-pass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT Digital Spectrum Analyzer. Tests were repeated at different audio signal frequencies from 0 to 50 KHz.

13.3 TEST DATA

12.5 KHz Channel Spacing, F3E, Frequency of All Modulation States

Frequency (KHz)	Audio In (dBV)	Audio Out (dBV)	Attenuation (Out - In) (dB)	Attenuation Rel. to 1 KHz (dB)	Recommended Attenuation (dB)
0.1	-36.71	-40.74	-4.0	-41.2	--
0.2	-36.71	-23.04	13.7	-23.5	--
0.4	-36.71	-9.48	27.2	-9.9	--
0.6	-36.71	-4.57	32.1	-5.0	--
0.8	-36.71	-1.71	35.0	-2.1	--
1.0	-36.71	0.43	37.1	0.0	--
1.5	-36.71	2.01	38.7	1.6	--
2.0	-36.71	1.71	38.4	1.3	--
2.5	-36.71	1.08	37.8	0.6	--
3.0	-36.71	0.19	36.9	-0.2	0
3.5	-36.71	-8.49	28.2	-8.9	-4
4.0	-36.71	-24.52	12.2	-25.0	-7
4.5	-36.71	-39.11	-2.4	-39.5	-11
5.0	-36.71	-52.20	-15.5	-52.6	-13
6.0	-36.71	-67.89	-31.2	-68.3	-18
7.0	-36.71	-70.00	-33.3	-70.4	-22
8.0	-36.71	-70.00	-33.3	-70.4	-26
9.0	-36.71	-70.00	-33.3	-70.4	-29
10.0	-36.71	-70.00	-33.3	-70.4	-31
12.0	-36.71	-70.00	-33.3	-70.4	-36
14.0	-36.71	-70.00	-33.3	-70.4	-40
16.0	-36.71	-70.00	-33.3	-70.4	-44
18.0	-36.71	-70.00	-33.3	-70.4	-47
20.0	-36.71	-70.00	-33.3	-70.4	-50
25.0	-36.71	-70.00	-33.3	-70.4	-50
30.0	-36.71	-70.00	-33.3	-70.4	-50
35.0	-36.71	-70.00	-33.3	-70.4	-50
40.0	-36.71	-70.00	-33.3	-70.4	-50
45.0	-36.71	-70.00	-33.3	-70.4	-50
50.0	-36.71	-70.00	-33.3	-70.4	-50


Note: Due to the difficulty of measuring the Frequency Response of the internal low-pass filter, the Frequency Response of All Modulation States is performed to show the roll-off at 3 KHz in comparison with the recommended audio filter attenuation.



25 KHz Channel Spacing, F3E, Frequency of All Modulation States

Frequency (KHz)	Audio In (dBV)	Audio Out (dBV)	Attenuation (Out - In) (dB)	Attenuation Rel. to 1 KHz (dB)	Recommended Attenuation (dB)
0.1	-35.86	-34.42	1.4	-41.2	--
0.2	-35.86	-16.91	19.0	-23.6	--
0.4	-35.86	-3.19	32.7	-9.9	--
0.6	-35.86	1.51	37.4	-5.2	--
0.8	-35.86	4.51	40.4	-2.2	--
1.0	-35.86	6.73	42.6	0.0	--
1.5	-35.86	7.75	43.6	1.0	--
2.0	-35.86	7.67	43.5	0.9	--
2.5	-35.86	7.34	43.2	0.6	--
3.0	-35.86	6.71	42.6	0.0	0
3.5	-35.86	-1.85	34.0	-8.6	-4
4.0	-35.86	-17.62	18.2	-24.4	-7
4.5	-35.86	-31.44	4.4	-38.2	-11
5.0	-35.86	-46.74	-10.9	-53.5	-13
6.0	-35.86	-60.58	-24.7	-67.3	-18
7.0	-35.86	-64.37	-28.5	-71.1	-22
8.0	-35.86	-70.00	-34.1	-76.7	-26
9.0	-35.86	-70.00	-34.1	-76.7	-29
10.0	-35.86	-70.00	-34.1	-76.7	-31
12.0	-35.86	-70.00	-34.1	-76.7	-36
14.0	-35.86	-70.00	-34.1	-76.7	-40
16.0	-35.86	-70.00	-34.1	-76.7	-44
18.0	-35.86	-70.00	-34.1	-76.7	-47
20.0	-35.86	-70.00	-34.1	-76.7	-50
25.0	-35.86	-70.00	-34.1	-76.7	-50
30.0	-35.86	-70.00	-34.1	-76.7	-50
35.0	-35.86	-70.00	-34.1	-76.7	-50
40.0	-35.86	-70.00	-34.1	-76.7	-50
45.0	-35.86	-70.00	-34.1	-76.7	-50
50.0	-35.86	-70.00	-34.1	-76.7	-50

Note: Due to the difficulty of measuring the Frequency Response of the internal low-pass filter, the Frequency Response of All Modulation States is performed to show the roll-off at 3 KHz in comparison with the recommended audio filter attenuation.




APPENDIX I

PHOTOGRAPHS OF SETUP

CONDUCTED EMISSION TEST SETUP



RADIATED TEST SETUP



APPENDIX II

EXTERNAL VIEW OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



FRONT VIEW OF EUT




BACK VIEW OF EUT




ALL VIEW




INTERNAL VIEW OF EUT - 1



INTERNAL VIEW OF EUT - 2



Picture to show the antenna connector—1



Picture to show the antenna connector—2



Picture to show the circuit board placement in the EUT—1



Picture to show the circuit board placement in the EUT—2



----END OF REPORT----