



FCC PART 22 and 90 TEST REPORT

For

SHENZHEN COVALUE COMMUNICATIONS CO.,LTD.

2/F., Bldg. 24, XiLi Industrial Park, No.119 Xinguang Rd, Xili, Nanshan, Shenzhen, China

FCC ID: Y4GDM6000-2

Report Type: Original Report	Product Type: Mobile Radio
Test Engineer: <u>Dean Liu</u>	<i>Dean Liu</i>
Report Number: <u>RDG150505001-00</u>	
Report Date: <u>2015-05-25</u>	
Reviewed By: <u>Sula Huang RF Leader</u>	<i>Sula Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	8
APPLICABLE STANDARD	8
FCC §2.1046 & § 22.727 & §90.205- RF OUTPUT POWER	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA	10
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC.....	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA	12
FCC §2.1049& §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	16
APPLICABLE STANDARD	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
TEST DATA	17
FCC §2.1051& §22.861 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS.....	25
TEST PROCEDURE	26
TEST DATA	26
FCC §2.1053 & §22.861 & §90.210 - RADIATED SPURIOUS EMISSIONS.....	31
APPLICABLE STANDARD	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST PROCEDURE	31
TEST DATA	32
FCC §2.1055 & § 22.355 & §90.213- FREQUENCY STABILITY	34
APPLICABLE STANDARD	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST PROCEDURE	34

TEST DATA34

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....36

 APPLICABLE STANDARD36

 TEST EQUIPMENT LIST AND DETAILS.....36

 TEST PROCEDURE36

 TEST DATA37

DECLARATION LETTER.....39

FEMVAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHENZHEN COVALUE COMMUNICATIONS CO.,LTD.*'s product, model: *DM6000-2* (FCC ID: *Y4GDM6000-2*) (the "EUT") in this report is a *Mobile Radio*, which was measured approximately: 16.1cm (H) x 17.5cm (W) x 4.5 cm (D), rated input voltage: 13.8VDC.

Note: The series product, model DM6000-2, DM6100-2 are electrically identical, the difference between them are just the model name, horn dimension and screenprint font on the keypad, we selected DM6000-2 for fully testing, the details was explained in the attached declaration letter.

** All measurement and test data in this report was gathered from production sample serial number: 150505001 (assigned by BACL, Dongguan). The EUT was received on 2015-05-05.*

Objective

This test report is prepared on behalf of *SHENZHEN COVALUE COMMUNICATIONS CO.,LTD.* in accordance with Part 2, Part 22 and Part 90 of the Federal Communications Commission rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service
Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA 603-D and ANSI 63.4-2003.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.


EUT Specification:

Operating Frequency Band	400-470 MHz
Modulation Mode	FM/4FSK
Channel Separation	12.5 kHz
Rated Output Power	High power level: 45 W Low power level: 25 W

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Pro instrument	DC Power Supply	pps3300	/
COVALUE	Microphone	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§2.1091	Maximum Permissible Exposure	Compliant
§2.1046; § 22.727;§90.205	RF Output Power	Compliant
§2.1047;§90.207	Modulation Characteristic	Compliant
§2.1049;§22.357;§ 22.731;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051; §22.861;§90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053; §22.861;§90.210	Spurious Radiated Emissions	Compliant
§2.1055; § 22.355;§90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

FCC §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Maximum Permissible Exposure (MPE)

Limits for Occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E , H or S (minutes)
0.3- 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6

f = frequency in MHz;

* = Plane-wave equivalent power density;

MPE Calculation

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:


Frequency	The Max Target Conducted Output Power		Antenna Cable Loss	Typical Antenna Gain		Distance	Power Density	Limit
	MHz	mW	dBm	dB	dBi			
435	45200	46.55	2.0	0	1.0	80	0.355	1.45

Note: The manufacturer does not specify an antenna to be used with this device , but a typical installation has a gain up to 0dBi.

Radio Exposure Statement:

To comply with RF exposure requirements, a minimum separation distance of 80cm and with a 2dB cable loss is required between antenna and all public persons.

Result: Compliant.



FCC §2.1046 & § 22.727 & §90.205- RF OUTPUT POWER

Applicable Standard

FCC §2.1046, § 22.727 and §90.205.

Test Procedure

Conducted RF Output Power:

TIA-603-D section 2.2.1

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer setting:

RBW	VBW
100 kHz	300 kHz

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8 °C
Relative Humidity:	53 %
ATM Pressure:	100.2 kPa

The testing was performed by Dean Liu on 2015-05-11.

Test Result: Compliant. Please refer to following tables.

FCC Part 90:

Modulation	Channel Separation (kHz)	f _c (MHz)	Conducted Output Power (W)		Note
			High	Low	
FM	12.5	400.0125	45.01	24.98	Not for FCC Review
		435	45.02	24.98	/
		469.9875	45.03	25.00	Not for FCC Review
4FSK		400.0125	44.99	24.98	Not for FCC Review
		435	45.01	24.97	/
		469.9875	45.01	24.98	Not for FCC Review

FCC Part 22:

Modulation	Channel Separation (kHz)	f _c (MHz)	Conducted Output Power (W)		Note
			High	Low	
FM	12.5	458	45.01	24.99	/
4FSK		458	44.99	24.97	/

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047 & §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA/EIA-603 2.2.3

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
HP	RF Communications Test Set	8920A	00 235	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8 °C
Relative Humidity:	53 %
ATM Pressure:	100.2 kPa


The testing was performed by Dean Liu on 2015-05-11

Test Result: Compliant. Please refer to following plots.

MODULATION LIMITING

Carrier Frequency: 435MHz, Channel Separation = 12.5 kHz, high power level

AUDIO INPUT LEVEL	DEVIATION (@300Hz)	DEVIATION (@ 1kHz)	DEVIATION (@ 3kHz)	Limit
dB	kHz	kHz	kHz	kHz
20.0	2.457	2.424	2.092	2.5
15.0	1.502	2.336	2.012	2.5
10.0	0.937	2.332	1.917	2.5
5.0	0.548	2.268	1.913	2.5
0.0	0.334	1.500	1.588	2.5
-5.0	0.250	0.856	1.097	2.5
-10.0	0.216	0.553	0.668	2.5
-15.0	0.188	0.370	0.424	2.5
-20.0	0.145	0.279	0.303	2.5



Audio Frequency Response

Carrier Frequency: 435 MHz, Channel Separation = 12.5 kHz, high power level


Audio Frequency Hz	Response Attenuation dB
300	-12.78
400	-10.07
500	-7.35
600	-5.33
700	-3.74
800	-2.32
900	-1.16
1000	0.00
1200	1.89
1400	3.25
1600	4.50
1800	5.44
2000	6.18
2200	6.60
2400	6.57
2600	6.04
2800	5.85
3000	5.71



Audio Frequency Low Pass Filter Response

Carrier Frequency: 435 MHz, Channel Separation = 12.5 kHz, high power level

Audio Frequency	Response Attenuation	Limit
kHz	dB	dB
3.0	-2.1	0.0
3.5	-9.0	-6.7
4.0	-14.5	-12.5
5.0	-25.5	-22.2
7.0	-39.5	-36.8
10.0	-55.3	-52.3
15.0	-74.1	-69.9
20.0	-85.2	-82.5
30.0	-85.8	-82.5
50.0	-86.2	-82.5
70.0	-85.7	-82.5



FCC §2.1049 & §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049, §22.357, § 22.731, §90.209 and §90.210

Applicable Emission Masks

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	B	C
72-76	B	C
150-174	B, D, or E	C, D or E
150 paging only	B	C
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	B	G
806-809/851-854	B	H
809-824/854-869	B	G
896-901/935-940	I	J
902-928	K	K
929-930	B	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	B	C

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(fd - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

§22.357 Emission types.

Any authorized station in the Public Mobile Services may transmit emissions of any type(s) that comply with the applicable emission rule, i.e. §22.359, §22.861 or §22.917

§22.731 Emission limitations.

Upon application for multichannel operation, the FCC may authorize emission bandwidths wider than those specified in §22.357, provided that spectrum utilization is equal to or better than that achieved by single channel operation.

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09
	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
HP	RF Communications Test Set	8920A	00 235	2014-05-09	2015-05-09
	RF Communications Test Set	8920A	00 235	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Test Data

Environmental Conditions

Temperature:	26.7~28.4 °C
Relative Humidity:	54~65 %
ATM Pressure:	99.8~100.6 kPa

The testing was performed by Dean Liu from 2015-05-07 to 2015-05-21.

Test Result: Compliant. Please refer to the following tables and plots.

FCC Part 90:


Modulation Mode	Channel Separation	f_c	26 dB Bandwidth	Power Level
	kHz	MHz	kHz	
FM	12.5	435	10.48	High
4FSK			9.69	
FM			10.37	Low
4FSK			9.59	

FCC Part 22:


Modulation Mode	Channel Separation	f_c	26 dB Bandwidth	Power Level
	kHz	MHz	kHz	
FM	12.5	458	10.37	High
4FSK			9.59	
FM			10.36	Low
4FSK			9.46	

Part 90:


Occupied Bandwidth – FM, 435 MHz, High Power Level




Emission Mask - Type D




Occupied Bandwidth – FM, 435 MHz, Low Power Level




Emission Mask - Type D




Occupied Bandwidth –4FSK, 435 MHz, High Power Level




Emission Mask - Type D



Occupied Bandwidth – 4FSK, 435 MHz, Low Power Level




Emission Mask - Type D




Part 22:

Occupied Bandwidth – FM, 458 MHz, High Power Level




Date: 09.MAY 2015 12:08:36

Occupied Bandwidth – FM, 458 MHz, Low Power Level




Date: 09.MAY 2015 12:05:18

Occupied Bandwidth – 4FSK, 458 MHz, High Power Level



Occupied Bandwidth – 4FSK, 458 MHz, Low Power Level



FCC §2.1051 & §22.861 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

§22.861 Emission limitations.

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
HP	RF Communications Test Set	8920A	00 235	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Adjust the spectrum analyzer for the following settings:

- 1) Resolution Bandwidth = 100 kHz for spurious emissions below 1 GHz, and 1 MHz for spurious emissions above 1 GHz.
- 2) Video Bandwidth = 3 times the resolution bandwidth.
- 3) Sweep Speed = 2000 Hz per second.
- 4) Detector Mode = mean or average power.

Test Data**Environmental Conditions**


Temperature:	55~62 °C
Relative Humidity:	26.7~28.4 %
ATM Pressure:	99.8~100.6 kPa

The testing was performed by Dean Liu on 2015-05-09 & 2015-05-23


**FCC PART 90
435 MHz – FM Mode, High Power**

Marker 1 [T1] RBW 100 kHz RF Att 20 dB
 Ref Lvl -35.02 dBm VBW 300 kHz
 51 dBm 870.73146293 MHz SWT 245 ms Unit dBm


Fundamental test with Band Reject Filter



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
 Ref Lvl -24.57 dBm VBW 3 MHz
 51 dBm 1.46492986 GHz SWT 10 ms Unit dBm




FCC PART 90 435 MHz -4FSK Mode, High Power



Fundamental test
with Band Reject
Filter




FCC PART 22 458 MHz –FM Mode,High Power




Fundamental test
with Band Reject
Filter

Date: 23.MAY.2015 14:17:27




Date: 23.MAY.2015 14:17:48

FCC PART 22 458 MHz -4FSK Mode,High Power



Fundamental test
with Band Reject
Filter



FCC §2.1053 & §22.861 & §90.210 - RADIATED SPURIOUS EMISSIONS**Applicable Standard**

FCC §2.1053 and §22.861 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
HP	Signal Generator	8648A	3426A00831	2014-11-06	2015-11-06
Sunol Sciences	Antenna	JB3	A060611-1	2014-09-06	2017-09-05
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
HP	Amplifier	8447E	2434A02181	2014-09-06	2015-09-06
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Agilent	Signal Generator	E8247C	MY43321350	2014-10-15	2015-10-15
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
TDK RF	Horn Antenna	HRN-0118	130 084	2012-09-06	2015-09-06
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

For part 90:

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = 50 + 10 Log₁₀ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

For part 22:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Test Data

Environmental Conditions

Temperature:	25.4°C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa

The testing was performed by Dean Liu on 2015-05-21.

Test Mode: Transmitting (FM mode, high power level)

Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dBμV	dBm	dBd/dBi	dB	dBm	dBm	dB
Frequency:435MHz, for FCC PART 90								
870.000	H	35.75	-38.9	0.0	1	-39.9	-20.0	19.9
870.000	V	34.74	-36.7	0.0	1	-37.7	-20.0	17.7
1305.000	H	38.25	-33.9	8.3	1.1	-26.7	-20.0	6.7
1305.000	V	37.21	-35.7	8.3	1.1	-28.5	-20.0	8.5
1740.000	H	33.58	-39.4	10.9	1.5	-30.0	-20.0	10.0
1740.000	V	35.58	-37.7	10.9	1.5	-28.3	-20.0	8.3
2175.000	H	32.69	-35.8	10.9	1.5	-26.4	-20.0	6.4
2175.000	V	32.23	-35.9	10.9	1.5	-26.5	-20.0	6.5
Frequency:458MHz, for FCC PART 22								
916.000	H	32.58	-41.4	0.0	1	-42.4	-13.0	29.4
916.000	V	32.23	-38.5	0.0	1	-39.5	-13.0	26.5
1374.000	H	30.56	-42.1	8.8	1.2	-34.5	-13.0	21.5
1374.000	V	32.37	-40.3	8.8	1.2	-32.7	-13.0	19.7
1832.000	H	29.54	-42.5	11.3	1.4	-32.6	-13.0	19.6
1832.000	V	31.54	-40.7	11.3	1.4	-30.8	-13.0	17.8
2290.000	H	30.30	-38.6	11.2	1.8	-29.2	-13.0	16.2
2290.000	V	31.38	-36.9	11.2	1.8	-27.5	-13.0	14.5

Test Mode: Transmitting (4FSK mode, high power level)

Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dB μ V	dBm	dBd/dBi	dB	dBm	dBm	dB
Frequency:435MHz, for FCC PART 90								
870.000	H	46.93	-27.7	0.0	1	-28.7	-20.0	8.7
870.000	V	46.76	-24.7	0.0	1	-25.7	-20.0	5.7
1305.000	H	36.42	-35.7	8.3	1.1	-28.5	-20.0	8.5
1305.000	V	39.72	-33.2	8.3	1.1	-26.0	-20.0	6.0
1740.000	H	37.35	-35.6	10.9	1.5	-26.2	-20.0	6.2
1740.000	V	39.90	-33.4	10.9	1.5	-24.0	-20.0	4.0
2175.000	H	32.36	-36.1	10.9	1.5	-26.7	-20.0	6.7
2175.000	V	33.01	-35.2	10.9	1.5	-25.8	-20.0	5.8
Frequency:458MHz, for FCC PART 22								
916.000	H	45.28	-28.7	0.0	1	-29.7	-13.0	16.7
916.000	V	44.42	-26.3	0.0	1	-27.3	-13.0	14.3
1374.000	H	37.21	-35.5	8.8	1.2	-27.9	-13.0	14.9
1374.000	V	39.21	-33.5	8.8	1.2	-25.9	-13.0	12.9
1832.000	H	33.46	-38.6	11.3	1.4	-28.7	-13.0	15.7
1832.000	V	35.67	-36.6	11.3	1.4	-26.7	-13.0	13.7
2290.000	H	31.58	-37.3	11.2	1.8	-27.9	-13.0	14.9
2290.000	V	33.34	-35	11.2	1.8	-25.6	-13.0	12.6

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §2.1055 & § 22.355 & §90.213- FREQUENCY STABILITY**Applicable Standard**

FCC §2.1055, § 22.355, §90.213

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-3	2014-08-01	2015-08-01
UNI-T	Multimeter	UT39A	M130199938	2015-04-10	2016-04-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The power leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

Test Data**Environmental Conditions**

Temperature:	25.4 °C
Relative Humidity:	57 %
ATM Pressure:	100.2 kPa

The testing was performed by Dean Liu on 2015-05-21.

Test Mode: Transmitting

FCC PART 90:

Reference Frequency: 435 MHz, Limit: 2.5 ppm			
Temperature	Voltage	Reading	Frequency Error
	V _{DC}	MHz	ppm
-30	13.8	435.000129	0.30
-20	13.8	435.000152	0.35
-10	13.8	435.000124	0.29
0	13.8	435.000141	0.32
10	13.8	435.000117	0.27
20	13.8	435.000110	0.25
30	13.8	435.000111	0.26
40	13.8	435.000115	0.26
50	13.8	435.000122	0.28
20	15.9	435.000145	0.33
	11.0	435.000185	0.43

FCC PART 22:

Reference Frequency: 458 MHz, Limit: 5.0 ppm			
Temperature	Voltage	Reading	Frequency Error
	V _{DC}	MHz	ppm
-30	13.8	458.000189	0.41
-20	13.8	458.000195	0.43
-10	13.8	458.000231	0.50
0	13.8	458.000214	0.47
10	13.8	458.000192	0.42
20	13.8	458.000170	0.37
30	13.8	458.000171	0.37
40	13.8	458.000183	0.40
50	13.8	458.000175	0.38
20	15.9	458.000192	0.42
	11.0	458.000208	0.45

Note: The operation end point is 11.0V which is specified by the manufacturer.

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3


Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
HP	Signal Generator	8648A	3426A00831	2014-11-06	2015-11-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "trigger offset" to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .
- k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .



Test Data**Environmental Conditions**


Temperature:	25.3 °C
Relative Humidity:	58 %
ATM Pressure:	100.2kPa

The testing was performed by Dean Liu on 2015-05-09.


Channel Separation (kHz)	Transient Period (ms)	Maximum frequency difference	Result
12.5	< 10(t_1)	± 12.5 kHz	Pass
	< 25(t_2)	± 6.25 kHz	
	< 10(t_3)	± 12.5 kHz	

Please refer to the following plots.

Turn on – 435 MHz, High power level



Turn off – 435 MHz, High power level



DECLARATION LETTER

COVALUE

SHENZHEN COVALUE COMMUNICATIONS CO., LTD.

Add: 2/F., Bldg. 24, XiLi Industrial Park, No.119 Xinguang Rd, Xili, Nanshan, Shenzhen, China

Tel: 0755-86345789

Fax: 0755-86345790

DECLARATION OF SIMILARITY

2015-05-13

To:

Dear Sir or Madam:

We, SHENZHEN COVALUE COMMUNICATIONS CO., LTD., hereby declare that product: Mobile Radio, Model numbers: DM6000-2, DM6100-2 are electrically identical with the same electromagnetic emissions and electromagnetic compatibility characteristics. Model Number: is DM6100-2 electrically identical with the Model Number: DM6000-2 that was certified by BACL. Their difference is as following:

1. The horn dimension is different;
2. The screenprint font on the keypad is different.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Shu, Chengtao

Research &Development Department Manager



***** END OF REPORT *****