



To: Federal Communications Commission  
7435 Oakland Mills Road  
Columbia, MD

FCC ID: Y4H-GP200WT

To Whom It May Concern:

This letter is to ascertain that Green Power Electronics Co.,Ltd. Product Wireless Charging Transmitter Y4H-GP200WT, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 Clause 5(2) all 6 conditions as stated below hence PBA is not required.

1	Power transfer frequency is less than 1 MHz → The power transfer frequency of DUT(Device Under Test) is between 110kHz and 205kHz.
2	Output power from each primary coil is less than 5 watts → Output power from each coils are Max. 5 watts.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils → The DUT are consist of one charging coil use. So the DUT can detect and allow coupling only between TX and RX Coil.
4	Client device is inserted in or placed directly in contact with the transmitter → When the client device is placed directly in contact with transmitter, then charging is able to start.
5	The maximum coupling surface area of the transmit (charging) device is between 60 cm <sup>2</sup> and 400 cm <sup>2</sup> . → The Maximum coupling surface area of the charging transmit is 91.49Cm <sup>2</sup> . Maximum coupling surface area (13.07 Cm X 7 Cm)
6	Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit. → The highest leakage filed is less than 30 % of the MPE limit.

If you have any question or concerns, pls. contact us.

Sincerely,

Client's signature

**Name:** Green Power Electronics Co.,Ltd

**Address:** Rm 811, STX V-Tower, 128, Gasan-Digital 1-ro, Geumcheon-gu,  
Seoul 153-795, Korea



Seung-Man. LEE