

Nedre Vats, 2012.03.26

FCC ID: Y62-RobR-915-2.

Section 15.212 Modular Transmitters.

Request for Limited Single-Modular approval.

| SL. No. | Requirements | EUT Conditions | Comply |
|---------|--|--|--------|
| 1 | The radio elements must have the radio frequency circuitry shielded. | The RF part of the module has its own RF shieldings on both sides of the board. | Y |
| 2 | The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal | Modulation and data input are buffered. | Y |
| 3 | The module must contain power supply regulation on the module | The RF part of the board has its own power supply regulation on the board. The CPU does not. The module is intended to be installed into a host that has power supply regulation for this units CPU. | N |
| 4 | The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b); | The module has an antenna attached to a unique antenna connector and will be marketed and operated only with specified antenna. | Y |
| 5 | The module must demonstrate compliance in a stand-alone configuration | See test setup photos. | Y |
| 6 | The module must be labelled with its permanently affixed FCC ID label, or use an electronic display. | The module is labeled with its FCC ID. | Y |

| | | | |
|---|--|---|---|
| 7 | The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee. | The module is compliant with all applicable FCC rules. | Y |
| 8 | The module must comply with RF exposure requirements | The module is compliant with all applicable RF exposure requirements. | Y |