

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to TCB Exclusions list, no SAR required if power is lower than the flowing threshold:

Bluetooth

Frequency Range		Center frequency (MHz)	60/f SAR Limitation (mW)
Low Frequency (MHz)	High Frequency(MHz)		
2402	2480	2441	25

WLAN

Frequency Range		Center frequency (MHz)	60/f SAR Limitation (mW)
Low Frequency (MHz)	High Frequency(MHz)		
2412	2462	2437	25

Bluetooth Maximum measured transmitter power:

Conducted Power (mW)	Max Antenna Gain (dBi)	EIRP (mW)
0.882	5	2.789

WLAN Maximum measured transmitter power:

Conducted Power (mW)	Max Antenna Gain (dBi)	EIRP (mW)
2.075	5	6.561

Threshold at which no SAR required is 25 mW.

Maximum Tx power is 6.561 mW EIRP.

Conclusion: No SAR is required.

Simultaneous transmission occurs between BT and WLAN. Per FCC KDB 447498 D01 Mobile Portable RF Exposure, 3) (c) requirement, if the output power is $\leq 60/f(\text{GHz})$ mW for any simultaneous transmitting antenna(s) for which stand-alone SAR evaluation is not required. So since both the output power of BT and WLAN are $\leq 60/f(\text{GHz})$ mW, then the SAR for simultaneous transmission is not required.