




SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Celeno Wireless Communication
Applicant Address	26 Zarhin St. P.O. Box 4093 Ra'anana 43665 Israel
FCC ID	Y7E-VXT1836000001
Manufacturer's company	ZINWELL CORPORATION
Manufacturer Address	2, Wen-Hua Road, Hsinchu Industrial Park Hsinchu Hsien 303,Taiwan

Product Name	Single Band 5GHz WiFi HD Video Extender
Brand Name	VXT1836
Model Name	VXT1836
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	5725 ~ 5850MHz
Received Date	Jun. 14, 2012
Final Test Date	Dec. 25, 2012
Submission Type	Original Equipment



Statement

Test result included is only for the IEEE 802.11n (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v02 and KDB 662911 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Testing Laboratory
1190

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting	8
3.9. Test Configurations	9
4. TEST RESULT	12
4.1. AC Power Line Conducted Emissions Measurement.....	12
4.2. Maximum Conducted Output Power Measurement.....	16
4.3. Power Spectral Density Measurement	18
4.4. 6dB Spectrum Bandwidth Measurement	22
4.5. Radiated Emissions Measurement	25
4.6. Emissions Measurement	36
4.7. Antenna Requirements	42
5. LIST OF MEASURING EQUIPMENTS	43
6. TEST LOCATION.....	45
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR261473AA	Rev. 01	Initial issue of report	Jan. 08, 2013
FR261473AA	Rev. 02	Changed the brand name	Jan. 25, 2013
FR261473AA	Rev. 03	Revised the applicant's company name and applicant address.	May 10, 2013



1. CERTIFICATE OF COMPLIANCE

Product Name : Single Band 5GHz WIFI HD Video Extender
Brand Name : VXT1836
Model Name : VXT1836
Applicant : Celeno Wireless Communication
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jun. 14, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao' is written over a horizontal line.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	5.15 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	2.31 dB
4.3	15.247(e)	Power Spectral Density	Complies	10.26 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.96dB
4.6	15.247(d)	Band Edge Emissions	Complies	-
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	5725 ~ 5850MHz
Channel Number	5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 23.04 MHz ; MCS0 (40MHz): 36.48 MHz
Maximum Conducted Output Power	MCS0 (20MHz): 26.62 dBm ; MCS0 (40MHz): 26.11 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3
The product has beam-forming function.	

Antenna & Band width

Antenna	Three (TX)	
	20 MHz	40 MHz
IEEE 802.11n	V	V

IEEE 802.11n spec

MCS	Spatial	Modulation	Coding	Data rate (Mbit/s)			
Index	Streams	Type	Rate	20 MHz channel		40 MHz channel	
				800 ns GI	400 ns GI	800 ns GI	400 ns GI
0	1	BPSK	1/2	6.5	7.2	13.5	15
1	1	QPSK	1/2	13	14.4	27	30
2	1	QPSK	3/4	19.5	21.7	40.5	45
3	1	16-QAM	1/2	26	28.9	54	60
4	1	16-QAM	3/4	39	43.3	81	90
5	1	64-QAM	2/3	52	57.8	108	120
6	1	64-QAM	3/4	58.5	65	121.5	135
7	1	64-QAM	5/6	65	72.2	135	150
8	2	BPSK	1/2	13	14.4	27	30
9	2	QPSK	1/2	26	28.9	54	60
10	2	QPSK	3/4	39	43.3	81	90
11	2	16-QAM	1/2	52	57.8	108	120
12	2	16-QAM	3/4	78	86.7	162	180
13	2	64-QAM	2/3	104	115.6	216	240
14	2	64-QAM	3/4	117	130	243	270
15	2	64-QAM	5/6	130	144.4	270	300
16	3	BPSK	1/2	19.5	21.7	40.5	45
17	3	QPSK	1/2	39	43.3	81	90
18	3	QPSK	3/4	58.5	65	121.5	135
19	3	16-QAM	1/2	78	86.7	162	180
20	3	16-QAM	3/4	117	130	243	270
21	3	64-QAM	2/3	156	173.3	324	360
22	3	64-QAM	3/4	175.5	195	364.5	405
23	3	64-QAM	5/6	195	216.7	405	450

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories


Power	Brand Holder	Model	Rating
Adapter	Asian Power Devices Inc.	WA-12M12FU	Input: 100-240V~50-60Hz, 0.5A Max. Output: 12V, 1A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Antenna Gain (dBi)		Remark
					5GHz Band 1	5GHz Band 4	
1	Celero	OPTIMIZAIR™ SMART PRINTED ANTENNA	PCB Antenna	NA	0.9	2.3	TX, RX
2	Celero	OPTIMIZAIR™ SMART PRINTED ANTENNA	PCB Antenna	NA	0.9	2.3	TX, RX
3	Celero	OPTIMIZAIR™ SMART PRINTED ANTENNA	PCB Antenna	NA	0.9	2.3	TX, RX

Note: The EUT has three antennas.

Ant. 1, Ant. 2, Ant. 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Conducted Output Power	MCS0/20MHz	6.5 Mbps	149/157/165	1/2/3/1+2+3
	MCS0/40MHz	13.5 Mbps	151/159	1/2/3/1+2+3
Power Spectral Density	MCS0/20MHz	6.5 Mbps	149/157/165	1/2/3
	MCS0/40MHz	13.5 Mbps	151/159	1/2/3
6dB Spectrum Bandwidth	MCS0/20MHz	6.5 Mbps	149/157/165	1+2+3
	MCS0/40MHz	13.5 Mbps	151/159	1+2+3
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	MCS0/20MHz	6.5 Mbps	149/157/165	1+2+3
	MCS0/40MHz	13.5 Mbps	151/159	1+2+3
Band Edge Emissions	MCS0/20MHz	6.5 Mbps	149/157/165	1+2+3
	MCS0/40MHz	13.5 Mbps	151/159	1+2+3

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. AP Mode

Mode 2. Client Mode

Mode 1 generated the worst test result, so it was recorded in the report.

For Radiated Emission Below 1GHz test:

Mode 1. AP Mode

Mode 2. Client Mode

Mode 2 generated the worst test result, so it was recorded in the report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
---------------	---------------	----------	--------------	-------------

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6250	E2K4965AGNM
Notebook	DELL	E6220	E2K4965AGNM
Wireless AP	Planex	GW-AP54SGX	N/A
Notebook	DELL	M1330	E2KWM3945ABG

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)

Test Software Version	Ranlink QA Test program for RT3883		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	1B/19/1F	1B/19/1F	1C/19/1F

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)


Test Software Version	Ranlink QA Test program for RT3883	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	1B/19/1F	1C/19/1F

During the test, "Ranlink QA Test program for RT3883" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations


3.9.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz / Test Mode: Mode 2. Client Mode



Item	Connection	Shield	Length
1	Power Cable	No	1.5m
2	RJ-45 Cable	No	10m
3	RJ-45 Cable	No	1.5m


Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power Cable	No	1.5m
2	RJ-45 Cable	No	10m

3.9.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1. AP Mode



Item	Connection	Shield	Length
1	Power Cable	No	1.50m
2	RJ45 Cable	No	10m
3	RJ45 Cable	No	1.5m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	60%
Test Engineer	Sollo Luo	Phase	Line
Test Mode	Mode 1. AP Mode	Configuration	Normal Link



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17215	48.16	-16.70	64.86	47.81	0.16	0.19	LINE	QP
2	0.17215	40.60	-14.26	54.86	40.25	0.16	0.19	LINE	AVERAGE
3	0.22556	36.45	-26.16	62.61	36.10	0.15	0.20	LINE	QP
4	0.22556	19.09	-33.52	52.61	18.74	0.15	0.20	LINE	AVERAGE
5	0.37314	47.45	-10.98	58.43	47.10	0.15	0.20	LINE	QP
6	0.37314	43.28	-5.15	48.43	42.93	0.15	0.20	LINE	AVERAGE
7	0.64740	35.51	-20.49	56.00	35.15	0.16	0.20	LINE	QP
8	0.64740	29.62	-16.38	46.00	29.26	0.16	0.20	LINE	AVERAGE
9	1.396	23.70	-22.30	46.00	23.31	0.18	0.21	LINE	AVERAGE
10	1.396	32.83	-23.17	56.00	32.44	0.18	0.21	LINE	QP
11	4.632	36.11	-9.89	46.00	35.56	0.23	0.31	LINE	AVERAGE
12	4.632	40.27	-15.73	56.00	39.72	0.23	0.31	LINE	QP

Temperature	25°C	Humidity	60%
Test Engineer	Sollo Luo	Phase	Neutral
Test Mode	Mode 1. AP Mode	Configuration	Normal Link



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17307	46.36	-18.45	64.81	46.09	0.08	0.19	NEUTRAL	QP
2	0.17307	37.03	-17.78	54.81	36.76	0.08	0.19	NEUTRAL	AVERAGE
3	0.37787	46.01	-12.32	58.33	45.73	0.08	0.20	NEUTRAL	QP
4	0.37787	40.15	-8.18	48.33	39.87	0.08	0.20	NEUTRAL	AVERAGE
5	0.68263	23.98	-22.02	46.00	23.70	0.08	0.20	NEUTRAL	AVERAGE
6	0.68263	32.46	-23.54	56.00	32.18	0.08	0.20	NEUTRAL	QP
7	1.210	30.44	-25.56	56.00	30.14	0.09	0.21	NEUTRAL	QP
8	1.210	21.43	-24.57	46.00	21.13	0.09	0.21	NEUTRAL	AVERAGE
9	2.581	23.53	-22.47	46.00	23.17	0.12	0.24	NEUTRAL	AVERAGE
10	2.581	31.52	-24.48	56.00	31.16	0.12	0.24	NEUTRAL	QP
11	4.121	31.74	-14.26	46.00	31.31	0.13	0.30	NEUTRAL	AVERAGE
12	4.121	36.47	-19.53	56.00	36.04	0.13	0.30	NEUTRAL	QP

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 5725-5850MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 8.2.3 option 3.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	20°C	Humidity	61%
Test Engineer	Denis Su	Configurations	IEEE 802.11n
Test Date	Dec. 24, 2012		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
149	5745 MHz	21.98	22.12	21.40	26.62	28.93	Complies
157	5785 MHz	21.14	21.88	20.81	26.07	28.93	Complies
165	5825 MHz	20.86	21.18	20.76	25.71	28.93	Complies

Note: Directional gain= $G_{ant} + 10 \cdot \log(N_{ant}/N_{ss}) = 7.07\text{dBi} > 6\text{dBi}$, so Limit = $30 - (7.07 - 6) = 28.93\text{dBm}$.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
151	5755 MHz	21.56	21.68	20.70	26.11	28.93	Complies
159	5795 MHz	21.33	21.38	20.41	25.83	28.93	Complies

Note: Directional gain= $G_{ant} + 10 \cdot \log(N_{ant}/N_{ss}) = 7.07\text{dBi} > 6\text{dBi}$, so Limit = $30 - (7.07 - 6) = 28.93\text{dBm}$.

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 9.1 option 1
2. Spectrum analyzer must be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW in order to ensure bin-to-bin spacing of $\leq RBW/2$ so that narrowband signals are not lost between frequency bins.
3. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
4. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
5. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where: $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$.
7. The resulting PSD level must be $\leq 8 \text{ dBm}$.
8. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	20°C	Humidity	61%
Test Engineer	Denis Su	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)

Frequency	Power Density (dBm/100kHz)			BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
	Ant. 1	Ant. 2	Ant. 3		Ant. 1	Ant. 2	Ant. 3		
5745 MHz	7.64	8.05	7.70	-15.23	-7.59	-7.18	-7.53	3.23	Complies
5785 MHz	7.17	8.20	7.26	-15.23	-8.06	-7.03	-7.97	3.23	Complies
5825 MHz	6.46	7.84	7.14	-15.23	-8.77	-7.39	-8.09	3.23	Complies

Note: Limit = $8\text{dBm}/3\text{KHz} - (10\log(3)) = 8\text{dBm}/3\text{KHz} - 4.77\text{dB} = 3.23\text{dBm}/3\text{KHz}$.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)


Frequency	Power Density (dBm/100kHz)			BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
	Ant. 1	Ant. 2	Ant. 3		Ant. 1	Ant. 2	Ant. 3		
5755 MHz	3.38	4.52	4.06	-15.23	-11.85	-10.71	-11.17	3.23	Complies
5795 MHz	4.03	4.75	3.13	-15.23	-11.20	-10.48	-12.10	3.23	Complies

Note: Limit = $8\text{dBm}/3\text{KHz} - (10\log(3)) = 8\text{dBm}/3\text{KHz} - 4.77\text{dB} = 3.23\text{dBm}/3\text{KHz}$.

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 5785 MHz / Ant. 2 (3TX)



Date: 24.DEC.2012 11:16:04

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 2 (3TX)



Date: 24.DEC.2012 11:23:05

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	1-5 % or DTS BW, not exceed 100KHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 5.1.1 EBW Measurement Procedure
3. Multiple antenna system was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	20°C	Humidity	61%
Test Engineer	Denis Su	Configurations	IEEE 802.11n


Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	14.72	23.04	500	Complies
157	5785 MHz	15.04	17.60	500	Complies
165	5825 MHz	14.16	18.16	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+Ant. 2+Ant. 3 (3TX)


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	33.44	36.16	500	Complies
159	5795 MHz	32.96	36.48	500	Complies

**6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 5785 MHz
/ Ant. 1+Ant. 2+Ant. 3 (3TX)**



Date: 25.DEC.2012 06:22:16

**6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 5755 MHz
/ Ant. 1+Ant. 2+Ant. 3 (3TX)**



Date: 25.DEC.2012 06:25:18

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	Normal Link
Test Date	Nov. 12, 2012		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	Normal Link
Test Mode	Mode 2. Client Mode		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	166.77	36.04	43.50	-7.46	49.24	1.53	27.27	12.54	0	400	Peak	HORIZONTAL
2	363.68	30.38	46.00	-15.62	40.41	2.23	27.35	15.09	0	400	Peak	HORIZONTAL
3	454.86	33.75	46.00	-12.25	42.09	2.61	27.87	16.92	0	400	Peak	HORIZONTAL
4	500.45	37.44	46.00	-8.56	45.21	2.70	28.10	17.63	0	400	Peak	HORIZONTAL
5	576.11	32.96	46.00	-13.04	39.72	2.85	28.10	18.49	0	400	Peak	HORIZONTAL
6 p	896.21	41.34	46.00	-4.66	44.67	3.58	27.41	20.50	0	400	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	48.43	32.56	40.00	-7.44	50.53	0.70	27.80	9.13	0	400	Peak	VERTICAL
2	75.59	31.05	40.00	-8.95	50.89	0.93	27.70	6.93	0	400	Peak	VERTICAL
3	125.06	33.02	43.50	-10.48	47.04	1.25	27.48	12.21	0	400	Peak	VERTICAL
4	166.77	39.54	43.50	-3.96	52.74	1.53	27.27	12.54	0	400	Peak	VERTICAL
5	174.53	36.70	43.50	-6.80	49.24	1.57	27.23	13.12	0	400	Peak	VERTICAL
6	250.19	32.73	46.00	-13.27	45.06	1.90	27.00	12.77	0	400	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	20°C	Humidity	63%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Ant. 1+Ant. 2+Ant. 3 (3TX)
Test Date	Nov. 20, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11482.60	55.98	69.23	-13.25	45.56	6.74	34.82	38.50	Peak	9	155	HORIZONTAL
2 a	11482.70	42.85	49.23	-6.38	32.43	6.74	34.82	38.50	Average	9	155	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11486.40	60.92	69.23	-8.31	50.50	6.74	34.82	38.50	Peak	82	105	VERTICAL
2 a	11486.50	47.07	49.23	-2.16	36.65	6.74	34.82	38.50	Average	82	105	VERTICAL

Note:

The product has beam-forming function.

So average limit = $54\text{dBuV/m} - (10\log(N)) = 54\text{dBuV/m} - 4.77\text{dB} = 49.23\text{dBuV/m}$.

Peak limit = $74\text{dBuV/m} - (10\log(N)) = 74\text{dBuV/m} - 4.77\text{dB} = 69.23\text{dBuV/m}$.

Temperature	20°C	Humidity	63%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Ant. 1+Ant. 2+Ant. 3 (3TX)
Test Date	Nov. 20, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11567.80	55.75	69.23	-13.48	45.32	6.77	34.84	38.50	Peak	140	100	HORIZONTAL
2 a	11568.10	42.28	49.23	-6.95	31.85	6.77	34.84	38.50	Average	140	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11567.80	61.96	69.23	-7.27	51.53	6.77	34.84	38.50	Peak	75	109	VERTICAL
2 a	11568.10	47.46	49.23	-1.77	37.03	6.77	34.84	38.50	Average	75	109	VERTICAL

Note:

The product has beam-forming function.

So average limit = $54\text{dBuV/m} - (10\log(N)) = 54\text{dBuV/m} - 4.77\text{dB} = 49.23\text{dBuV/m}$.

Peak limit = $74\text{dBuV/m} - (10\log(N)) = 74\text{dBuV/m} - 4.77\text{dB} = 69.23\text{dBuV/m}$.

Temperature	20°C	Humidity	63%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 165 / Ant. 1+Ant. 2+Ant. 3 (3TX)
Test Date	Nov. 20, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11640.80	56.76	69.23	-12.47	46.32	6.80	34.86	38.50	Peak	17	151	HORIZONTAL
2 a	11641.10	43.04	49.23	-6.19	32.60	6.80	34.86	38.50	Average	17	151	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11644.10	61.27	69.23	-7.96	50.83	6.80	34.86	38.50	Peak	85	115	VERTICAL
2 a	11645.00	47.00	49.23	-2.23	36.56	6.80	34.86	38.50	Average	85	115	VERTICAL

Note:

The product has beam-forming function.

So average limit = $54\text{dBuV/m} - (10\log(N)) = 54\text{dBuV/m} - 4.77\text{dB} = 49.23\text{dBuV/m}$.

Peak limit = $74\text{dBuV/m} - (10\log(N)) = 74\text{dBuV/m} - 4.77\text{dB} = 69.23\text{dBuV/m}$.

Temperature	20°C	Humidity	63%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Ant. 1+Ant. 2+Ant. 3 (3TX)
Test Date	Nov. 20, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		deg	cm	
1 p	11509.20	53.39	69.23	-15.84	42.96	6.75	34.82	38.50	Peak	140	100	HORIZONTAL
2 a	11509.90	40.73	49.23	-8.50	30.30	6.75	34.82	38.50	Average	140	100	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		deg	cm	
1 a	11504.20	45.71	49.23	-3.52	35.28	6.75	34.82	38.50	Average	85	104	VERTICAL
2 p	11504.30	58.42	69.23	-10.81	47.99	6.75	34.82	38.50	Peak	85	104	VERTICAL

Note:

The product has beam-forming function.

So average limit = $54\text{dBuV/m} - (10\log(N)) = 54\text{dBuV/m} - 4.77\text{dB} = 49.23\text{dBuV/m}$.

Peak limit = $74\text{dBuV/m} - (10\log(N)) = 74\text{dBuV/m} - 4.77\text{dB} = 69.23\text{dBuV/m}$.

Temperature	20°C	Humidity	63%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Ant. 1+Ant. 2+Ant. 3 (3TX)
Test Date	Nov. 20, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11588.50	52.91	69.23	-16.32	42.48	6.78	34.85	38.50	Peak	142	100	HORIZONTAL
2 a	11590.30	41.44	49.23	-7.79	31.01	6.78	34.85	38.50	Average	142	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11589.40	55.34	69.23	-13.89	44.91	6.78	34.85	38.50	Peak	75	100	VERTICAL
2 a	11589.40	43.53	49.23	-5.70	33.10	6.78	34.85	38.50	Average	75	100	VERTICAL

Note:

- The product has beam-forming function.

So average limit = $54\text{dBuV/m} - (10\log(N)) = 54\text{dBuV/m} - 4.77\text{dB} = 49.23\text{dBuV/m}$.

Peak limit = $74\text{dBuV/m} - (10\log(N)) = 74\text{dBuV/m} - 4.77\text{dB} = 69.23\text{dBuV/m}$.

- The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = $20 \log$ Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz / 300 KHz for Peak

4.6.3. Test Procedures

For Radiated Bandedge Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

For Conducted Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 v02 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
- The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit. Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated Bandedge Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.6.5. Test Deviation


There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 24.DEC.2012 11:16:04

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 (down 30dBc)




Date: 24.DEC.2012 12:02:16

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 157 (down 30dBc)




Date: 24.DEC.2012 12:03:30

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 (down 30dBc)




Date: 24.DEC.2012 12:04:54

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 24.DEC.2012 11:23:05

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 (down 30dBc)



Date: 24.DEC.2012 11:42:04

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 (down 30dBc)



Date: 24.DEC.2012 11:43:32

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov.26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Coupling and Decoupling Network	TESEQ	ISN PLC 25-25	26476	0.15MHz~30MHz	Feb. 09, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-----	-----	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2011	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2011	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085