

RE-21-E382-SCH-1-A Ed. 0

MPE test report

According to the standard:
CFR 47 FCC PART 15

Equipment under test:
XZBWE112A24
Wireless transmitter


FCC ID: Y7HXZBWE

Company:
Schneider Electric Industries France L'Isle d'Espagnac

Distribution: Mr LAIDET

(Company: Schneider Electric Industries France L'Isle d'Espagnac)

Number of pages: 5

Ed.	Date	Modified Page(s)	Technical Verification and Quality Approval	
			Name and Function	Visa
0	11-Oct-21	Creation	S. LOUIS, Radio Technician	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above. This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample. Information in italics are declared by the manufacturer/customer and are under his responsibility



DESIGNATION OF PRODUCT: XZBWE112A24

Serial number (S/N): 03056594

Reference / model (P/N): XZBWE112A24

Software version: 1.2

MANUFACTURER: Schneider Electric Industries France L'Isle d'Espagnac

COMPANY SUBMITTING THE PRODUCT:

Company: Schneider Electric Industries France L'Isle d'Espagnac

Address: BP 660 - ZI No.3 L'ISLE D'ESPAGNAC France 16340

Responsible: Mr LAIDET

DATES OF TEST: 13-Sep-21

TESTING LOCATION: EMITECH ANGERS laboratory at JUIGNE SUR LOIRE (49) FRANCE
FCC Accredited under US-EU MRA Designation Number: FR0009
Test Firm Registration Number: 873677

TESTED BY: T. LEDRESSEUR

VISA:



WRITTEN BY: T. LEDRESSEUR

CONTENTS

	TITLE	PAGE
1.	INTRODUCTION	4
2.	PRODUCT DESCRIPTION	4
3.	NORMATIVE REFERENCE	4
4.	RF EXPOSURE.....	5

REVISIONS HISTORY

Revision	Date	Modified pages	Modifications
0	22-Sep-21	/	Creation

1. INTRODUCTION

This report presents the results of radio test carried out on the following radio equipment: **XZBWE112A24**, in accordance with normative reference.

The product integrates a Zigbee function

2. PRODUCT DESCRIPTION

Class:	B
Utilization:	Wireless transmitter
Antenna type and gain:	0 dBi / integral PCB antenna
Operating frequency range:	2405 MHz
Number of channels:	1
Channel spacing:	Not concerned
Modulation:	OQPSK
Power source:	24Vdc

Power level, frequency range and channels characteristics are not user adjustable.
The details pictures of the product and the circuit boards are joined with this file.

3. RF EXPOSURE

Maximum measured power = 92.5 dB μ V/m = 0.00053 W at 2405 MHz

with $P = (E \times d)^2 / (30 \times G_p)$ with $d = 3$ m and $G_p = 1$

In accordance with KDB 447498 D01 General RF Exposure Guidance v06:

PSD = EIRP / (4 * π * R²)

0.53 / (4 * π * (20 cm)²) = 0.00011 mW/cm² (limit = 1 mW/cm² si $f > 1500$ MHz)

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.