




Report No. 2-311535

## Test Report

<b>Product</b>	Radio Frequency Identification (RFID) module
<b>Name and address of the applicant</b>	ASSA ABLOY Hospitality AS Anolitveien 1-3, 1400 Ski, Norway
<b>Name and address of the manufacturer</b>	ASSA ABLOY Hospitality AS Anolitveien 1-3, 1400 Ski, Norway
<b>Model</b>	4827610CC1
<b>Rating</b>	4.5Vdc
<b>Trademark</b>	ASSA ABLOY
<b>Serial number</b>	/
<b>Additional information</b>	Radio Frequency Identification (RFID) -13.56MHz. This product contains BLE transceiver also with same FCC/IC ID. But never transmits simultaneously.
<b>Tested according to</b>	<b>FCC Part 15.225</b> Low Power Transmitter <b>13.110 - 14.010 MHz Band</b> <b>Industry Canada RSS-210, Issue 9</b> Low Power Licence-Exempt Radiocommunications Devices
<b>Order number</b>	311535
<b>Tested in period</b>	2016.06.27 - 2016.07.01
<b>Issue date</b>	2017.02.08
<b>Name and address of the testing laboratory</b>	 Instituttveien 6 Kjeller, Norway
	FCC No: 994405 IC OATS: 2040D-1 TEL: +47 22 96 03 30 FAX: +47 22 96 05 50
 Prepared by [G. Suhanthakumar]	
 Approved by [Frode Sveinsen]	
<p>This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.</p>	

Template version: B

**Nemko Norway**

Nemko AS, Instituttveien 6, P.O. Box 96 Kjeller, 2027 Kjeller, Norway

TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532

[nemko.com/no](http://nemko.com/no)

## CONTENTS

<b>1</b>	<b>INFORMATION .....</b>	<b>3</b>
1.1	Test Item.....	3
1.2	Test Environment.....	4
1.2.1	Normal test condition .....	4
1.3	Test Engineer(s) .....	4
1.4	Test Equipment.....	4
<b>2</b>	<b>TEST REPORT SUMMARY .....</b>	<b>5</b>
2.1	General.....	5
2.2	Test Summary .....	6
2.3	Description of modification for Modification Filing .....	6
2.4	Comments .....	6
2.5	Family List Rational .....	6
<b>3</b>	<b>TEST RESULTS.....</b>	<b>7</b>
3.1	Occupied Bandwidth.....	7
3.2	Peak power output.....	Error! Bookmark not defined.
3.3	Spurious emissions (radiated) .....	11
3.4	Transmitter Frequency Stability .....	19
<b>4</b>	<b>Measurement Uncertainty .....</b>	<b>20</b>
<b>5</b>	<b>LIST OF TEST EQUIPMENT.....</b>	<b>21</b>
<b>6</b>	<b>BLOCK DIAGRAM.....</b>	<b>22</b>
6.1	System set up for radiated measurements .....	22
6.2	Test Site Radiated Emission.....	23

## 1 INFORMATION

### 1.1 Test Item

<b>Name :</b>	ASSA ABLOY
<b>FCC ID :</b>	Y7V-4827610CC1
<b>Industry Canada ID :</b>	9514A-4827610CC1
<b>Model/version :</b>	4827610CC1
<b>Serial number :</b>	/
<b>Hardware identity and/or version:</b>	4827610-B
<b>Software identity and/or version :</b>	C3GNemko.hcc
<b>Frequency Range :</b>	13.553-13.567 MHz
<b>Tunable Bands :</b>	None
<b>Number of Channels :</b>	1
<b>Operating Modes :</b>	Transmitter
<b>Type of Modulation :</b>	FSK
<b>User Frequency Adjustment :</b>	None
<b>Type of Power Supply :</b>	Primary batteries (AA) 3x 1.5Vdc(4.5Vdc)
<b>Antenna Connector :</b>	Integral loop antenna
<b>Antenna Diversity Supported :</b>	None
<b>Desktop Charger :</b>	None

#### Description of Test Item

The RFID transceiver module is located on PCB 1102, and is controlled by the main microcontroller located on PCB 1101, both located inside the LCU 5350.

It will communicate with a RFID card if the RFID card is held right in front of the RFID antenna (1103), that is also located inside the LCU 5350.

#### Theory of Operation

The RFID transceiver module supports several RFID standards, ISO 14443-A, ISO 14443-B and ISO 15693, working on 13.56MHz

On a higher level it supports MIFARE communication and encryption. The transceiver's oscillator is controlled by a 27.12MHz crystal.

## 1.2 Test Environment

### 1.2.1 *Normal test condition*

Temperature: 20 - 24 °C  
Relative humidity: 20 - 50 %  
Normal test voltage: 4.5Vdc (Primary batteries 3x 1.5Vdc)

The values are the limit registered during the test period.

## 1.3 Test Engineer(s)

G. Suhanthakumar

## 1.4 Test Equipment

See list of test equipment in clause 5.

## 2 TEST REPORT SUMMARY

### 2.1 General

All measurements are traceable to national standards.

The tests were conducted for the purpose of demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.225 and Industry Canada RSS-210 Issue 9.

Tests were performed in accordance with ANSI C63.4-2014 and ANSI C63.10-2013.

Radiated tests were made in a semi-anechoic chamber at measuring distances of 3m and 10m.

A description of the test facility is on file with the FCC and Industry Canada.

New Submission

Production Unit

Class II Permissive Change

Pre-production Unit

**DXX** Equipment Code

Family Listing



#### **THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.**

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

## 2.2 Test Summary

Name of test	FCC Part 15 reference	RSS-210 Issue 9 & RSS-GEN Issue 4	Result
Supply Voltage Variations	15.31(e)	N/A	Complies <sup>1</sup>
Antenna Requirement	15.203	7.1.4 (RSS-GEN)	NA <sup>2</sup>
Power-line Conducted Emission	15.207(c)	7.2.2 (RSS-GEN)	N/A <sup>1</sup>
Occupied Bandwidth	N/A	4.6.1 (RSS-GEN)	-
Fundamental Field strength	15.225(a)	B.6(a)	Complies
Band Emissions	15.225(b)(c)	B.6(b)(c)	Complies
Spurious Emissions (Radiated)	15.225 (d) 15.209	B.6(d) 4.9 (RSS-GEN)	Complies
Frequency stability	15.225(e)	B.6	Complies

<sup>1</sup> EUT is battery powered.

<sup>2</sup> Integral loop antenna

RSS Gen issue 4 covers section 7 & 6

RSS 210 issue 9 covers section B.6

## 2.3 Description of modification for Modification Filing

Not applicable.

## 2.4 Comments

And the output level is set to maximum in the software.

The radiated measurements are tested on three axis.

Two fully charged primary batteries are used.

All ports were populated during spurious emission measurements.

## 2.5 Family List Rational

Not Applicable.



### 3 TEST RESULTS

#### 3.1 Occupied Bandwidth

Para. No.: RSS-Gen

Test Performed By: G.Suhanthakumar

Date of Test: 2016-06-30

Test Results: Complies

Measurement Data:


6 dB BW (kHz)

13.56MHz

14.76

Requirements:

For information only



Date: 30.JUN.2016 07:24:56

**13.56MHz – 6dB BW– 14.76kHz**

### 3.2 Fundamental Field Strength

Para. No.: 15.225 (a) / B.6 (a)

Test Performed By: G.Suhanthakumar

Date of Test: 2016-06-27

**Test Results: Complies**

**Measurement data:**

**Maximum field strength**

RF channel	Measured PK value (dB $\mu$ V/m) @ 10m	Distance Correction factor dB	Converted Limit @10m (dB $\mu$ V/m)
13.56MHz	41.10	-19.5	103.5

The limit line given in the graph is corrected to 10m distance.

Radiated measurements are performed at 10 m distance.

Detachable antenna?

Yes  No

If detachable, is the antenna connector non-standard?

Yes  No

Integral loop antenna

New batteries were used.

**Requirements:**

The maximum field strength within band 13.553 – 13.567MHz at 30 meters shall be  $\leq$  84.0 dB $\mu$ V/m (at 10 meters  $\leq$  103.5 dB $\mu$ V/m)



(b) 334 microvolts/m (50.5 dB $\mu$ V/m) at 30 m, within the bands 13.410-13.553 MHz and 13.567-13.710 MHz. (at 10 meters  $\leq$  70.0 dB $\mu$ V/m)

(c) 106 microvolts/m (40.5 dB $\mu$ V/m) at 30 m, within the bands 13.110-13.410 MHz and 13.710-14.010 MHz. (at 10 meters  $\leq$  60.0 dB $\mu$ V/m)

RS

Att 0 dB

RBW 9 kHz  
 MT 1 s  
 PREAMP OFF



Date: 27.JUN.2016 17:50:32

Field strength at longitudinal polarization – 13.56MHz

### 3.3 Spurious emissions (radiated)

Para. No.: 15.209 / 15.225 (b,c,d) / B.6(b,c,d)

Test Performed By: G.Suhanthakumar

Date of Test: 2016-06-27

**Test Results: Complies**

**Measurement Data:**

#### Radiated Emissions with loop antenna, 9kHz – 30MHz

measured at a distance of 10m.

**Measured with Peak Detector:**

Frequency	Dist. corr. factor	Measured Field strength, Peak @ 10m	Duty cycle corr. factor	Calculated Field strength, Average @ 300m	Limit @ 300m	Margin
kHz	dB	dB $\mu$ V/m	dB	dB $\mu$ V/m	dB $\mu$ V/m	dB
/	/	/	/	/	/	> 30

**The limit line given in the graph is corrected to 10m distance.**

The above detected frequencies are within the band 9 – 90 kHz. The emission limit in this band is based on average detector.

The maximum is observed in longitudinal polarization

Antenna factor, amplifier gain and cable loss are included in spectrum analyzer “Transducer factor”.

#### Duty Cycle Correction Factor Calculation:

RF duty cycle: Calculation according to RF burst Para 15.35 (c)

minimum DC Correction factor =  $-20 \times \log((124.1 \text{ ms}) / 374.53\text{ms}) = -10.6 \text{ dB}$

**Maximum Duty Cycle Correction Factor according to Para 15.35 (b): 20 dB**


#### Requirement:

(d) The field strength of any emissions appearing outside of the 13.110 – 14.010 MHz band shall not exceed the general radiated emission limits in §15.209.


**Radiated emissions 9kHz – 30 MHz.**

Detector: Peak

Measuring distance 10 m. The limit is corrected to 10m distance.



Date: 27.JUN.2016 17:49:39




Date: 30.JUN.2016 07:31:43

Pulse train period during card waiting (duty cycle: 29.4%)

First burst ON OFF time during card waiting(Duty cycle: 94.2%)

Second burst ON OFF time during card waiting (Duty cycle: 89.1%)

Third burst ON/OFF time during card waiting (Duty cycle: 6.9%)



Date: 30.JUN.2016 07:37:16


Car reading mode.

**Radiated emissions 30 – 1000 MHz.**

Detector: PK


Measuring distance 3 m.

The graph shows peak scan and highest values.




Date: 27.JUN.2016 16:35:28

Card waiting mode: VP, 30 - 200MHz (PK scan)




Date: 27.JUN.2016 16:37:55

Card waiting mode: HP, 30 - 200MHz (PK scan)



Date: 27.JUN.2016 16:43:11

Card waiting mode: VP, 200 1000MHz (PK scan)



Date: 27.JUN.2016 16:45:19

Card waiting mode: HP, 200 1000MHz (PK scan)

### 3.4 Transmitter Frequency Stability

Para. No.: 15.225(e)/B.6

Test Performed By: G.Suhanthakumar	Date of Test: 2016-06-30
------------------------------------	--------------------------

#### Measurement Data:

Temperature	Given Frequency (MHz)	Measured value (MHz)	Deviation (%)
+50 ° C	13.56	13.56020288	-0.00000347
+40 ° C	13.56	13.56020286	-0.00000361
+30 ° C	13.56	13.56020285	-0.00000383
+20 ° C	13.56	13.56020335	<b>0.00000000</b>
+10 ° C	13.56	13.56020285	-0.00000369
+0 ° C	13.56	13.56020337	0.00000015
-10 ° C	13.56	13.56020338	0.00000022
-20 ° C	13.56	13.56020289	-0.00000339

Supply voltage: 4.5Vdc (fully charged battery)

#### Requirement:

(e) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  ( $\pm 100\%$ ) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage.

## 4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2


## 5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1.	ESU40	EMI Receiver	Rohde & Schwarz	LR1639	2015.11	2016.11
2.	6810.17A	Attenuator	Suhner	LR 1137	2015.03.26	2017.03.26
3.	87V	Multimeter, Digital	Fluke	N4672	2015.09.17	2016.09.17
4.	HFH2-Z2	Antenna, Loop	Rohde & Schwarz	LR1660	2015.10	2016.10
5.	HL223	Antenna log.per	Rohde & Schwarz	LR 1261	2013.12.05	2016.12.05
6.	HK116	Antenna biconic	Rohde & Schwarz	LR 1260	2013.12.05	2016.12.05
7.	310N	Amplifier, low noise	Sonoma	LR11686	2016.05	2017.05
8.	ESR	Spectrum analyser	R &S	LR 11675	2015.12	2017.12
9.	VC4060	Climatic chamber Temp	Vøtsch	LR 1435	2016.03	2017.03.
10.	A 10-B	Rubidium	Quartzlock	LR 1386	2016.02	2017.02
11.	FA210A1010 003030	Microwave cable	Rosenberger	LR1566	Cal b4 use	
12.	3115	Antenna horn	EMCO	LR 1226	2013.10	2018.10
13.	017	Power Supply	Oltronix	B300	Cal b4 use	
14.	HFH2-Z4	Antenna Inductive Probe	R & S	LR 1100	Cal b4 use	


## 6 BLOCK DIAGRAM

### 6.1 System set up for radiated measurements



Test equipment: 1,3,4,5,6

## 6.2 Test Site Radiated Emission





## Revision history

Revision #	Date	Order #	Comment	Sign
00	2016.09.13	311535	First version	GNS
01	2016.11.10	311535	Corrected IDs and model no.	FS
02	2017.02.08	311535	Corrected RSS210 references & frequency stability	GNS