

FCC ID: Y7ZDL2101T

RF exposure evaluation

§ 2.1093 Radiofrequency radiation exposure evaluation: Portable Devices.

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

TEST RESULTS

Main Power: $71.49\text{dB}\mu\text{V}/\text{m}=71.49-95.2=-23.71\text{dBm}$

30MHz-1G: $-23.71+4.7=-19.01\text{dBm}$

Modulation	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
ASK	0.304	-19.01	-20±1	-19	0.0126	5	0.0014	3.0

Conclusion:

For the max result : $0.79\text{W}/\text{Kg} \leq \text{FCC Limit } 3.0$ for 1g SAR.

The Product unsupported at the same time to Transmitting.