



FCC PART 15C
IC RSS-210, ISSUE 8, DECEMBER 2010
TEST AND MEASUREMENT REPORT

For

Sensys Networks, Inc.

2560 9th Street, Suite 219 & 217,
Berkeley, CA 94710, USA

FCC ID: Y8XAPCCSPP
IC: 9498A-APCCSPP

Report Type: Original Report	Product Type: 2.4 GHz Transceiver
Test Engineer: <u>Dennis Huang</u> 	
Report Number: <u>R1012208-247A</u>	
Report Date: <u>2011-05-23</u>	
Reviewed By: <u>RF Lead Engineer</u>  Victor Zhang	
Prepared By: <u>Bay Area Compliance Laboratories Corp.</u> (84) 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev. 2)

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	5
1.1	PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
1.2	MECHANICAL DESCRIPTION OF EUT	5
1.3	OBJECTIVE.....	5
1.4	RELATED SUBMITTAL(S)/GRANT(S)	5
1.5	TEST METHODOLOGY	5
1.6	MEASUREMENT UNCERTAINTY	6
1.7	TEST FACILITY	6
2	SYSTEM TEST CONFIGURATION.....	7
2.1	JUSTIFICATION	7
2.2	EUT EXERCISE SOFTWARE.....	7
2.3	SPECIAL ACCESSORIES	7
2.4	EQUIPMENT MODIFICATIONS	7
2.5	LOCAL SUPPORT EQUIPMENT	7
2.6	EUT INTERNAL CONFIGURATION AND DETAILS	7
2.7	INTERFACE PORTS AND CABLING	7
3	SUMMARY OF TEST RESULTS.....	8
4	FCC §15.203 & IC RSS-GEN §7.1.4 - ANTENNA REQUIREMENT.....	9
4.1	APPLICABLE STANDARD	9
4.2	RESULTS	9
5	FCC §15.207 & IC RSS-GEN §7.2.2 – AC LINE CONDUCTED EMISSIONS	10
5.1	APPLICABLE STANDARD	10
5.2	TEST RESULTS	10
6	FCC §15.247(A)(2) & IC RSS-210 §A8.2 (A) – 6 DB OCCUPIED BANDWIDTH	11
6.1	APPLICABLE STANDARD	11
6.2	MEASUREMENT PROCEDURE	11
6.3	TEST SETUP BLOCK DIAGRAM.....	11
6.4	TEST EQUIPMENT LIST AND DETAILS	11
6.5	TEST ENVIRONMENTAL CONDITIONS.....	11
6.6	TEST RESULTS	12
7	FCC §15.247(B) & IC RSS-210 §A8.4 - PEAK OUTPUT POWER.....	14
7.1	APPLICABLE STANDARD	14
7.2	MEASUREMENT PROCEDURE	14
7.3	TEST SETUP BLOCK DIAGRAM.....	14
7.4	TEST EQUIPMENT LIST AND DETAILS	14
7.5	TEST ENVIRONMENTAL CONDITIONS.....	14
7.6	TEST RESULTS	14
8	FCC §15.247(D) & IC RSS-210 §A8.5 – OUT OF BAND EMISSIONS	15
8.1	APPLICABLE STANDARD	15
8.2	MEASUREMENT PROCEDURE	15
8.3	TEST EQUIPMENT LIST AND DETAILS	15
8.4	TEST ENVIRONMENTAL CONDITIONS.....	15
9	FCC §15.247(E) & IC RSS-210 §A8.2 (B) - POWER SPECTRAL DENSITY	20

9.1	APPLICABLE STANDARD	20
9.2	MEASUREMENT PROCEDURE	20
9.3	TEST SETUP BLOCK DIAGRAM.....	20
9.4	TEST EQUIPMENT LIST AND DETAILS	20
9.5	TEST ENVIRONMENTAL CONDITIONS.....	21
9.6	TEST RESULTS	21
10	FCC §15.205, §15.209, §15.247(C) & IC RSS-GEN §4.9 - SPURIOUS RADIATED EMISSIONS.....	23
10.1	APPLICABLE STANDARD	23
10.2	TEST SETUP AND BLOCK DIAGRAMS	24
10.3	TEST PROCEDURE	25
10.4	CORRECTED AMPLITUDE & MARGIN CALCULATION	25
10.5	TEST EQUIPMENT LIST AND DETAILS	25
10.6	TEST ENVIRONMENTAL CONDITIONS.....	26
10.7	TEST RESULTS	26
11	IC RSS-210 §2.6 - RECEIVER SPURIOUS EMISSIONS	28
11.1	APPLICABLE STANDARD	28
11.2	TEST PROCEDURE	28
11.3	CORRECTED AMPLITUDE & MARGIN CALCULATION	29
11.4	TEST SETUP & BLOCK DIAGRAMS	29
11.5	TEST ENVIRONMENTAL CONDITIONS.....	29
11.6	TEST EQUIPMENT LIST AND DETAILS	30
11.7	TEST RESULTS	30
12	FCC §15.247 (I), §2.1091 & IC RSS-102 - RF EXPOSURE INFORMATION.....	31
12.1	APPLICABLE STANDARD	31
12.2	MPE PREDICTION	32
12.3	TEST RESULT	32
13	EXHIBIT A – FCC & IC EQUIPMENT LABELING REQUIREMENTS.....	33
13.1	FCC ID LABEL REQUIREMENTS	33
13.2	IC LABEL REQUIREMENTS	33
13.3	FCC ID & IC LABEL CONTENTS.....	34
13.4	FCC ID AND IC LABEL LOCATION	34
14	EXHIBIT B - TEST SETUP PHOTOGRAPHS.....	35
14.1	RADIATED EMISSION 30 MHZ-1 GHZ – FRONT VIEW	35
14.2	RADIATED EMISSION 30 MHZ-1 GHZ – REAR VIEW	35
14.3	RADIATED EMISSION ABOVE 1 GHZ – FRONT VIEW	36
14.4	RADIATED EMISSION ABOVE 1 GHZ – REAR VIEW	36
15	EXHIBIT C- EUT PHOTOS.....	37
15.1	EUT – TOP VIEW	37
15.2	EUT – BOTTOM VIEW	37
15.3	EUT – FRONT VIEW	38
15.4	EUT – REAR VIEW	38
15.5	EUT – SIDE VIEW	39
15.6	SUPPORTING EQUIPMENTS	39
15.7	EUT – CASE OPENED TOP VIEW	40
15.8	EUT – PCB ASSEMBLY TOP VIEW	40
15.9	EUT – PCB ASSEMBLY BOTTOM VIEW	41

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R1012208-247	Original Report	2011-05-02
1	R1012208-247A	Updated FCC ID	2011-05-23

1 General Information

1.1 Product Description for Equipment under Test (EUT)

This test and measurement report was prepared on behalf of *Sensys Networks, Inc.* product, *Model: APCC-SPP*, *FCC ID: Y8XAPCCSPP*, *IC: 9498A-APCCSPP* or the “EUT” as referred to this report. The EUT is Zigbee 2.4GHz transmitter. Its operating frequency is from 2.4GHz to 2.4835GHz.

1.2 Mechanical Description of EUT

The *EUT* measures approximately 115 mm (**L**) x 85 mm (**W**) x 115 mm (**H**), weighing approximately 30 g.

The data gathered are from a production sample provided by the manufacturer. Serial number: R1012208-1 assigned by BACL.

1.3 Objective

This report is prepared on behalf of *Sensys Networks, Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules and Industry Canada RSS-210 Issue 8, December 2010.

The objective is to determine compliance with FCC and IC standards, rules and limits for this device including:

- RF Exposure
- Antenna Requirement
- Conducted Emissions
- Spurious Emissions at Antenna Port
- Radiated Spurious Emissions
- Restricted Band
- Receiver Spurious Emissions
- 6 dB Bandwidth & 99% Bandwidth
- Maximum Peak Output Power
- 100 kHz Bandwidth of Frequency Band Edge
- Power Spectral Density

1.4 Related Submittal(s)/Grant(s)

No related submittals.

1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the values range from ± 2.0 for Conducted Emissions tests and ± 4.0 dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL.

Detailed instrumentation measurement uncertainties can be found in BACL report QAP-018.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

1.7 Test Facility

The test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at its facility in Sunnyvale, California, USA.

The test sites at BACL have been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission, Industry Canada, and Voluntary Control Council for Interference has the reports on file and is listed under FCC registration number: 90464, IC registration number: 3062A, and VCCI Registration Number: C-2463 and R-2698. The test site has been approved by the FCC, IC, and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2001670.htm>

2 System Test Configuration

2.1 Justification

The host system was configured for testing according to ANSI C63.4-2003.

The EUT was tested in the testing mode to represent *worst*-case results during the final qualification test.

2.2 EUT Exercise Software

N/A

2.3 Special Accessories

There were no special accessories were required, included, or intended for use with EUT during these tests.

2.4 Equipment Modifications

No modifications were made to the EUT.

2.5 Local Support Equipment

Manufacturers	Descriptions	Models	Serial Numbers
Lenovo	Laptop	T400S	60Y4172 JS
Sensys Networks, Inc	APPC Controller Card	-	-
Sensys Networks, Inc	APPC Isolator	-	-

2.6 EUT Internal Configuration and Details

Manufacturers	Descriptions	Models	Serial Numbers
Sensys Network, Inc.	PCB Board	APCC Radio Rev E	600 240-030-009

2.7 Interface Ports and Cabling

Cable Descriptions	Length (m)	From	To
Ethernet Cable	2 m	Laptop	Controller Card
Ethernet Cable	1 m	Isolator	Controller Card
Ethernet Cable	1 m	Isolator	EUT

3 Summary of Test Results

Results reported relate only to the product tested.

FCC & IC Rules	Description of Test	Result
FCC §15.203 IC RSS-Gen §7.1.4	Antenna Requirement	Compliant
FCC § 15.207 (a) IC RSS-Gen §7.2.2	AC Line Conducted Emissions	N/A ¹
FCC §15.247 (a)(2) IC RSS-210 §A8.2 (a)	6 dB Bandwidth & 99% Bandwidth	Compliant
FCC §15.247 (b)(3) IC RSS-210 § A8.4	Maximum Peak Output Power	Compliant
FCC § 15.247 (d) IC RSS-210 § A8.5	Band Edge/Out of Band Emissions	Compliant
FCC §15.247 (e) IC RSS-210 §A8.2 (b)	Power Spectral Density	Compliant
FCC §15.205, §15.209 & §15.247(c) IC RSS-Gen §4.9	Radiated Spurious Emissions	Compliant
FCC §15.205 IC RSS-210 § 2.6	Restricted Band	Compliant
IC RSS-210 §2.6 IC RSS-Gen §6	Receiver Spurious Emissions	Compliant
FCC§15.247 (i), §2.1091 IC RSS-102	RF Exposure Information	Compliant

Note¹: Not applicable, EUT is powered by DC.

4 FCC §15.203 & IC RSS-GEN §7.1.4 - Antenna Requirement

4.1 Applicable Standard


For intentional device, according to FCC Part §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Per IC RSS-Gen §7.1.4, A transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in IC RSS-210 or RSS-310 for devices of RF output powers of 10 milliwatts or less. For devices of output powers greater than 10 milliwatts, except devices subject to IC RSS-210 Annex 8 or RSS-210 Annex 9, the total antenna gain shall be added to the measured RF output power before using the specified power limits. For devices subject to IC RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

4.2 Results

The EUT supports a permanent attached antenna with a maximum gain of 5 dBi, which in accordance to sections FCC Part 15.203 and IC RSS-Gen §7.1.4 is considered sufficient to comply with the provisions of these sections.



Antenna

5 FCC §15.207 & IC RSS-GEN §7.2.2 – AC Line Conducted Emissions

5.1 Applicable Standard

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ⁽¹⁾	56 to 46 ⁽¹⁾
0.5-5	56	46
5-30	60	50

Note¹: Decreases with the logarithm of the frequency.

5.2 Test Results

This test is not applicable (N/A) as the device is DC powered.

6 FCC §15.247(a)(2) & IC RSS-210 §A8.2 (a) – 6 dB Occupied Bandwidth


6.1 Applicable Standard

According to §15.247(a)(2) and RSS-210 A8.2(a), systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

6.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emissions bandwidth. (6 dB bandwidth for DTS)
4. Repeat above procedures until all frequencies measured were complete.

6.3 Test Setup Block Diagram



6.4 Test Equipment List and Details

Manufacturers	Description	Models	Serial Numbers	Calibration Dates
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

6.5 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	57 %~59 %
ATM Pressure:	101.1~101.4kPa

The testing was performed by Dennis Huang on 2010-12-23 at RF site.

6.6 Test Results


Channel	Frequency (MHz)	6 dB OBW (MHz)	99% OBW (MHz)	Limit (MHz)
Low	2405	1.446	2.308	> 0.500
Middle	2440	1.481	2.355	> 0.500
High	2480	1.469	2.389	> 0.500

Please refer to the following plots for detailed test results


Low Channel – 2405 MHz



Middle Channel – 2440 MHz



High Channel – 2480 MHz



7 FCC §15.247(b) & IC RSS-210 §A8.4 - Peak Output Power


7.1 Applicable Standard

According to FCC §15.247(b) (3) and IC RSS-210 §A8.4 (4) for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

7.2 Measurement Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum analyzer.

7.3 Test Setup Block Diagram



7.4 Test Equipment List and Details

Manufacturers	Description	Models	Serial Numbers	Calibration Dates
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

7.5 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	57 %~59 %
ATM Pressure:	101.1~101.4kPa

The testing was performed by Dennis Huang on 2010-12-23 at RF site.

7.6 Test Results

Channel	Frequency (MHz)	Max Power		Limit (mW)	Result
		(dBm)	(mW)		
Low	2405	5.23	3.33	1000	Compliant
Middle	2440	5.08	3.22	1000	Compliant
High	2480	4.84	3.05	1000	Compliant

8 FCC §15.247(d) & IC RSS-210 §A8.5 – Out of Band Emissions

8.1 Applicable Standard

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c)).

IC RSS-210 §A8.5: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emissions limits specified in Tables 2 and 3.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 Test Equipment List and Details

Manufacturers	Description	Models	Serial Numbers	Calibration Dates
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.


8.4 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	57 %~59 %
ATM Pressure:	101.1~101.4kPa


The testing was performed by Dennis Huang on 2010-12-23 at RF site.

Plots of 100 kHz Band Edge:

Lowest Channel




Highest Channel




Plots of Spurious Emission at Antenna Port:

Low Channel – 2405 MHz




Plot 1: 30 MHz~3 GHz




Plot 2: 3 ~26 GHz

Middle Channel -2440 MHz




Plot 1: 30 MHz~3 GHz




Plot 2: 3 ~ 26 GHz

High Channel – 2480 MHz



Plot 1: 30 MHz~3 GHz



Plot 2: 3 ~ 26 GHz

9 FCC §15.247(e) & IC RSS-210 §A8.2 (b) - Power Spectral Density

9.1 Applicable Standard


According to FCC §15.247 (e) and IC RSS-210 §A8.2 (b), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Measure the power spectral density as follows:
 - A. Tune the analyzer to the highest point of the maximized fundamental emission. Reset the analyzer to a RBW = 3 kHz, VBW > RBW, span = 99% OBW, sweep = (span/3kHz) second.
 - B. From the peak level obtained in (A), derive the field strength, E, by applying the appropriate antenna factor, cable loss, pre-amp gain, etc.
4. $P = (E \times d)^2 / (30 \times G)$

G = the numeric gain of the transmitting antenna over an isotropic radiator.
 d = the distance in meters from which the field strength was measured.
 P = the power in watts for which you are solving:
5. Using the equation listed in (4), calculate a power level for comparison to the + 8 dBm limit.

9.3 Test Setup Block Diagram



9.4 Test Equipment List and Details

Manufacturers	Description	Models	Serial Numbers	Calibration Dates
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09

Statement of Traceability: BACL Corp. attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

9.5 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	57 %~59 %
ATM Pressure:	101.1~101.4kPa


The testing was performed by Dennis Huang on 2010-12-23 at RF site.

9.6 Test Results


Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
2405	-7.88	8	Compliant
2440	-8.07	8	Compliant
2480	-7.93	8	Compliant

Please refer to the following plots for detailed test results


Low Channel – 2405 MHz



Middle Channel – 2440 MHz



High Channel – 2480 MHz



10 FCC §15.205, §15.209, §15.247(c) & IC RSS-Gen §4.9 - Spurious Radiated Emissions

10.1 Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100 ⁽¹⁾	3
88 - 216	150 ⁽¹⁾	3
216 - 960	200 ⁽¹⁾	3
Above 960	500	3

⁽¹⁾ Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3332 – 3339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3345.8 – 3358	23.6 – 24.0
12.29 – 12.293	240 – 285	3600 – 4400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

IC RSS-Gen §4.9 the measurement method shall be described in the test report. The same parameter, peak power or average power, used for the transmitter output power measurement shall be used for unwanted emission measurements. The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate or carrier frequency), or from 30 MHz, whichever is the lower, to the 5th harmonic of the highest frequency generated without exceeding 40 GHz.


10.2 Test Setup and Block Diagrams

The radiated emissions tests were performed in the 3-meter open area test site, using the setup in accordance with ANSI C63.4-2003. The specification used was the FCC 15 Subpart C and RSS-210 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

Radiated Emission



10.3 Test Procedure

For the radiated emissions test, the EUT was connected to the DC power source, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meters away from the testing antenna, which is varied from 1-4 meters, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto
- (2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

10.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit.

The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

10.5 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100337	2010-03-24
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09
Sunol Science Corp	System Controller	SC99V	122303-1	N/R
Sunol Science Corp	Combination Antenna	JB3	A0020106-3	2010-06-16
Hewlett Packard	Pre amplifier	8447D	2944A06639	2010-06-18
A.R.A Inc	Horn antenna	DRG-1181A	1132	2010-11-29
Mini-Circuits	Pre Amplifier	ZVA-183-S	570400946	2010-05-0

Statement of Traceability: BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

10.6 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	50 %~52 %
ATM Pressure:	101.1~101.4kPa

The testing was performed by Dennis Huang on 2010-12-20 in 5m chamber 3

10.7 Test Results

1) 30-1000 MHz measured at 3 meters:

Frequency (MHz)	Corrected Quasi-Peak (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)
-	-	-	-	-	-	-

Note: No emissions were on the restricted band related to the transmitter. All other emissions were testified in another standard.

2) Above 1000 MHz measured at 3 meters:

Freq. (MHz)	S.A. Reading (dBμV)	Azimuth Degrees	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC & IC Limit (dBμV/m)	Margin (dB)	Comments
			Height (m)	Polar. (H/V)	Factor (dB)						
Low Channel: 2405 MHz											
4810	-	-	-	H	-	-	-	-	74	-	Peak
4810	-	-	-	V	-	-	-	-	74	-	Peak
4810	-	-	-	H	-	-	-	-	54	-	Average
4810	-	-	-	V	-	-	-	-	54	-	Average
Middle Channel: 2440 MHz											
4880	-	-	-	H	-	-	-	-	74	-	Peak
4880	-	-	-	V	-	-	-	-	74	-	Peak
4880	-	-	-	H	-	-	-	-	54	-	Average
4880	-	-	-	V	-	-	-	-	54	-	Average
High Channel: 2480 MHz											
4960	-	-	-	H	-	-	-	-	74	-	Peak
4960	-	-	-	V	-	-	-	-	74	-	Peak
4960	-	-	-	H	-	-	-	-	54	-	Average
4960	-	-	-	V	-	-	-	-	54	-	Average

Note: All Harmonics and restrict band emissions were on the noise floor level or 20dB below the limit.

Restricted Band:

Freq. (MHz)	S.A. Reading (dBμV)	Turntable Azimuth Degrees	Test Antenna			Cable Loss (dB)	Pre- Amp. (dB)	Cord. Reading (dBμV/m)	FCC & IC Limit (dBμV/m)	Margin (dB)	Comments
			Height (m)	Polar. (H/V)	Factor (dB)						
Lowest Channel											
2390	37.15	117	100	V	27.8	3.12	27.8	40.27	74	-33.73	Peak
2390	38.55	360	100	H	27.8	3.12	27.8	41.67	74	-32.33	Peak
2390	24.33	181	100	V	27.8	3.12	27.8	27.45	54	-26.55	Average
2390	25.21	360	100	H	27.8	3.12	27.8	28.33	54	-25.67	Average
Highest Channel											
2483.5	36.78	231	100	V	28.5	3.25	27.8	40.73	74	-33.27	Peak
2483.5	35	170	159	H	28.5	3.25	27.8	38.95	74	-35.05	Peak
2483.5	25.75	231	100	V	28.5	3.25	27.8	29.7	54	-24.3	Average
2483.5	26.58	170	159	H	28.5	3.25	27.8	30.53	54	-23.47	Average

11 IC RSS-210 §2.6 - Receiver Spurious Emissions

11.1 Applicable Standard

As per IC RSS-210 §2.6

Tables 2 and 3 show the general field strength limits of unwanted emissions, where applicable, for transmitters and receivers operating in accordance with the provisions specified in this RSS. Transmitters whose wanted emissions are also within the limits shown in Tables 2 and 3 may operate in any of the frequency bands of Tables 2 and 3, other than the restricted bands of Table 1 and the TV bands, and shall be certified under RSS-210. (Note: Devices operating below 490 kHz all of whose emissions are at least 40 dB below the limit given in Table 3 are Category II devices subject to RSS-310.) Unwanted emissions of transmitters and receivers are permitted to fall into Table 1 and TV frequencies but intentional emissions are prohibited. See the note of Table 2 for further details.

Table 2: General Field Strength Limits for Transmitters and Receivers at Frequencies above 30 MHz ^(Note)

Frequency (MHz)	Field Strength Microvolts/m at 3 meters (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Note: Transmitting devices are not permitted in Table 1 bands or in TV bands (54-72 MHz, 76-88 MHz, 174-216 MHz, 470-608 MHz, and 614-806 MHz). Prohibition of operation in TV bands does not apply to momentary devices, or to medical telemetry devices in the band 174-216 MHz, and to perimeter protection systems in the bands 54-72 and 76-88 MHz. The perimeter protection devices are to meet Table 3 field strengths limits.

Table 3: General Field Strength Limits for Transmitters at Frequencies below 30 MHz (Transmit)

Frequency (fundamental or spurious)	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/377F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/377F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Note: The emission limits for the bands 9-90 kHz and 110-490 kHz are based on measurements employing an average detector.

11.2 Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations.

All data were recorded in the peak detection mode. Quasi-peak readings was performed only when an emissions was found to be marginal (within -4 dB of specification limits), and are distinguished with a "QP" in the data table.

11.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$


The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

11.4 Test Setup & Block Diagrams

The radiated emissions tests were performed in the 3 meter chamber, using the setup in accordance with ANSI C63.4-2003.

Radiated Emission



11.5 Test Environmental Conditions

Temperature:	22°C~25°C
Relative Humidity:	50 %~52 %
ATM Pressure:	101.1~101.4kPa

The testing was performed by Dennis Huang on 2010-12-20 in 5m chamber 3

11.6 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100337	2010-03-24
Agilent	Spectrum Analyzer	E4440A	US45303156	2010-08-09
Sunol Science Corp	System Controller	SC99V	122303-1	N/R
Sunol Science Corp	Combination Antenna	JB3	A0020106-3	2010-06-16
Hewlett Packard	Pre amplifier	8447D	2944A06639	2010-06-18
A.R.A Inc	Horn antenna	DRG-1181A	1132	2010-11-29
Mini-Circuits	Pre Amplifier	ZVA-183-S	570400946	2010-05-10

Statement of Traceability: BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

11.7 Test Results

1) 30-1000 MHz measured at 3 meters:

Frequency (MHz)	Corrected Quasi-Peak (dBμV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)
-	-	-	-	-	-	-

Note: All digital emissions were testified in another standard.

2) Above 1000 MHz measured at 3 meters:

Freq. (MHz)	S.A. Reading (dBuV)	Detector (Average)	Table Azimuth (Degree)	Test Antenna			Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBuV/m)	IC	
				Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBuV/m)	Margin (dB)
1418	50.21	Peak	346	100	V	25	2.35	27.4	50.16	74	-23.84
1418	50.61	Peak	140	224	H	25	2.35	27.4	50.56	74	-23.44
1418	43.7	Ave	346	100	V	25	2.35	27.4	43.65	54	-10.35
1418	45.68	Ave	140	224	H	25	2.35	27.4	45.63	54	-8.37

12 FCC §15.247 (i), §2.1091 & IC RSS-102 - RF Exposure Information

12.1 Applicable Standard

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to FCC §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of RSS-102 must be followed concerning the exposure of humans to RF fields.

According to IC RSS-102 Issue 2 section 4.1, RF limits used for general public will be applied to the EUT.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Time Averaging (min)
0.003 - 1	280	2.19	-	6
1 - 10	280 / f	2.19 / f	-	6
10 - 30	28	2.19 / f	-	6
30 - 300	28	0.073	2*	6
300 - 1 500	1.585 f ^{0.5}	0.0042 f ^{0.5}	f / 150	6
1 500 - 15 000	61.4	0.163	10	6
15 000 - 150 000	61.4	0.163	10	616000 / f ^{1.2}
150 000- 300 000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000 / f ^{1.2}

Note: f is frequency in MHz

* Power density limit is applicable at frequencies greater than 100 MHz

12.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>5.23</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>3.33</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2405</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>5.0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>3.16</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.00209</u>
<u>Power density of prediction frequency at 20.0 cm (W/m²):</u>	<u>0.0209</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (W/m²):</u>	<u>10</u>

12.3 Test Result

FCC: The power density level at 20 cm distance is 0.00209mW/cm², which is below the uncontrolled exposure limit of 1.0 mW/cm².

IC: The power density level at 20 cm distance is 0.0209W/m², which is below the uncontrolled exposure limit of 10 W/m².