

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

IAdea Corporation

Room Booking Panel

Model No.: IAD-18010A; IAD-18010L

FCC ID: Y9E-IAD-18010A

Prepared for : IAdea Corporation
3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114
Taiwan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology Park,
Nanshan District , Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F23029-1
Date of Test : Jan.11~Feb.28, 2023
Date of Report : Oct.25, 2023

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. SUMMARY OF STANDARDS AND RESULTS.....	5
1.1. Description of Standards and Results	5
2. GENERAL INFORMATION.....	6
2.1. Description of Equipment Under Test	6
2.2. Tested Supporting System Details	7
2.3. Block diagram of connection between the EUT and simulators	7
2.4. Test Facility.....	7
2.5. Measurement Uncertainty (95% confidence levels, k=2).....	8
3. POWER LINE CONDUCTED EMISSION TEST	9
3.1. Test Equipments.....	9
3.2. Block Diagram of Test Setup	9
3.3. Power Line Conducted Emission Test Limits.....	9
3.4. Configuration of EUT on Test	9
3.5. Operating Condition of EUT.....	10
3.6. Test Procedure.....	10
3.7. Power Line Conducted Emission Test Results	10
4. RADIATED EMISSION TEST	13
4.1. Test Equipments.....	13
4.2. Block Diagram of Test Setup	14
4.3. Radiated Emission Limits	15
4.4. 15.205 Restricted bands of operation.....	15
4.5. EUT Configuration on Test.....	15
4.6. Operating Condition of EUT.....	16
4.7. Test Procedure.....	16
4.8. Radiated Emission Test Results	16
5. FREQUENCY STABILITY TEST.....	21
5.1. Test Equipments.....	21
5.2. Limits	21
5.3. Test Procedure.....	21
5.4. Test result	22
6. 20 DB BANDWIDTH TEST.....	23
6.1. Test Equipments.....	23
6.2. Limit	23
6.3. Test Results	23
7. DEVIATION TO TEST SPECIFICATIONS	24

Appendix A. Photograph of Test

Appendix B. Photo of the EUT

TEST REPORT

Applicant : IAdesa Corporation
Manufacture : IAdesa Corporation
EUT Description : Room Booking Panel
FCC ID : Y9E-IAD-18010A
(A) Model No. : IAD-18010A; IAD-18010L
(B) Test Voltage : AC 120V/60Hz

Tested for comply with:
FCC CFR 47 Part 15 Subpart C

Test procedure used:
ANSI C63.10:2020

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to confirm comply with all the FCC Part 15 Subpart C requirements.

The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to single evaluation of one sample of above mentioned product and shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

Date of Test : Jan.11~Feb.28, 2023 Report of date: Oct.25, 2023

Prepared by : Mia Zhao Reviewer by : Thomas Chen
Mia Zhao / Assistant Thomas Chen / Assistant Manager



信華科技(深圳)有限公司
Audix Technology (Shenzhen) Co., Ltd.
EMC 部門報告專用章
Stamp only for EMC Dept. Report
Signature: Sunny Lu
Sunny Lu / Manager

Approved & Authorized Signer : Sunny Lu

Modified History

Edition No.	Revision	Issue Date	Report No.
Original	Initial issue of report	Mar.16, 2023	ACS-F23029
Rev.01	Add Panel	Oct.25, 2023	ACS-F23029-1

- Note:
1. This report is based on report of ACS-F23029.
 2. This report is an additional version with original report number ACS-F23029. The differences with original report please see the above table of Rev.01.
 3. Through evaluation of the above difference, there is no effect on the test results of all the test items, so there is no need to re-test.

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10:2020	PASS
Radiated Emission Test	FCC Part 15: 15.205, 15.209 FCC Part 15: 15.225(a)(b)(c)(d) ANSI C63.10:2020	PASS
Frequency Stability Test	FCC Part 15: 15.225(e)	PASS
20dB Bandwidth Test	FCC Part 15: 15.215	PASS

Note: Measurement uncertainty affection to the result is considered, the EUT is technically compliant with standard requirements.

2. GENERAL INFORMATION


2.1. Description of Equipment Under Test

Applicant	IAddea Corporation
Applicant Address	3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114 Taiwan
Manufacturer	IAddea Corporation
Manufacturer Address	3F, No.21, Lane 168, Xingshan Road, Neihu Dist. Taipei, 114 Taiwan
Product	Room Booking Panel
Model No.	IAD-18010A; IAD-18010L
FCC ID	Y9E-IAD-18010A
Radio	NFC
Operation Frequency	13.56MHz
Type of Modulation	ASK
AC Adapter	Manufacturer: Asian Power Devices Inc. Model No.: WB-24J12R Input: 100-240V~50-60Hz, 0.7A Max Output: DC 12V, 2.0A, 24W DC Cable: Unshielded, Undetachable, 1.8m(with one core)
Sample Type	Prototype production
Date of Receipt	Jan.05,2023 & Sep.12, 2023
Date of Test	Jan.11~Feb.28, 2023

2.2. Tested Supporting System Details

N/A

2.3. Block diagram of connection between the EUT and simulators



(EUT: Room Booking Panel)

2.4. Test Facility

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology
Park, Nanshan District , Shenzhen, Guangdong,
China

EMC Lab. : Certificated by ISED, Canada
Company Number: 5183A
CAB identifier: CN0034
Valid Date: Mar.31, 2024

Accredited by NVLAP, USA
NVLAP Code: 200372-0
Valid Date: Mar.31, 2024

Certificated by FCC, USA
Designation No: CN5022
Valid Date: Mar.31, 2024

2.5. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	$\pm 2.6\text{dB}(150\text{KHz to } 30\text{MHz})$
Uncertainty for Radiation Emission test in 3m chamber	$\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: H})$
	$\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: V})$
	$\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: H})$
	$\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: V})$
Uncertainty for radiated spurious emission at frequency below 30MHz	$\pm 2.6\text{dB}(9\text{kHz}\sim 30\text{MHz})$
Uncertainty for Frequency range test	$\pm 2.0 \times 10^{-7}$
Uncertainty for Bandwidth test	$\pm 4.6\%$
Uncertainty for DC power test	$\pm 0.1\%$
Uncertainty for test site temperature and humidity	$\pm 0.6^{\circ}\text{C}$
	$\pm 3\%$


3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Sep.16,22	5 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.07,22	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ENV216	102160	Oct.08,22	1 Year
4.	L.I.S.N.#2	Kyoritsu	KNW-407	8-1628-5	Apr.06,22	1 Year
5.	RF Cable	Eastsheep	RG223	190424	Oct.08,22	1 Year
6.	Terminator	Hubersuhner	50Ω	No.1	Apr.06,22	1 Year
7.	Test Software	AUDIX	e3	210616	N/A	N/A

Note: N/A means Not applicable.

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes: 1. * Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.
 3. Emission Level (dBμV) = Factor (L.I.S.N.) (dB) + Cable Loss (dB)+Reading (Receiver) (dBμV)

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Room Booking Panel (EUT)

Model No. : IAD-18010A
 Serial No. : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turn on the power of all equipments.
- 3.5.3. PC run test software to control EUT work in Tx mode.

3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.7. Power Line Conducted Emission Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)


Data: 9 File: E:\1#CE\2023 Report Data\TPVA\1Z2301002-RF.EM6 (10) Date: 2023-02-28



Site no :1# CE Data No :9
 Dis./Lisn :2022 ENV216-L
 Limit :FCC PART 15 C
 Env./Ins. :22.3°C/45% Engineer :Sucy
 EUT :
 Power Rating :
 Test Mode :NFC TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	9.60	0.01	25.40	35.01	55.57	20.56	Average
2	0.158	9.60	0.01	44.30	53.91	65.57	11.66	QP
3	0.167	9.60	0.01	25.60	35.21	55.11	19.90	Average
4	0.167	9.60	0.01	40.28	49.89	65.11	15.22	QP
5	0.178	9.60	0.01	16.80	26.41	54.58	28.17	Average
6	0.178	9.60	0.01	38.00	47.61	64.58	16.97	QP
7	0.187	9.60	0.01	21.40	31.01	54.17	23.16	Average
8	0.187	9.60	0.01	36.39	46.00	64.17	18.17	QP
9	0.246	9.60	0.01	19.90	29.51	51.89	22.38	Average
10	0.246	9.60	0.01	30.30	39.91	61.89	21.98	QP
11	0.318	9.60	0.01	27.60	37.21	49.76	12.55	Average
12	0.318	9.60	0.01	31.60	41.21	59.76	18.55	QP
13	13.551	9.20	0.07	-1.09	8.18	50.00	41.82	Average
14	13.551	9.20	0.07	16.91	26.18	60.00	33.82	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1# CE Data No :10
 Dis./Lisn :2022 ENV216-M
 Limit :FCC PART 15 C
 Env./Ins. :22.3*C/45% Engineer :Sucy
 EUT :
 Power Rating :
 Test Mode :NFC TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	9.60	0.01	26.30	35.91	56.00	20.09	Average
2	0.150	9.60	0.01	44.20	53.81	66.00	12.19	QP
3	0.158	9.60	0.01	26.40	36.01	55.57	19.56	Average
4	0.158	9.60	0.01	45.50	55.11	65.57	10.46	QP
5	0.178	9.60	0.01	18.10	27.71	54.58	26.87	Average
6	0.178	9.60	0.01	35.30	44.91	64.58	19.67	QP
7	0.186	9.60	0.01	22.30	31.91	54.21	22.30	Average
8	0.186	9.60	0.01	39.00	48.61	64.21	15.60	QP
9	0.210	9.60	0.01	17.00	26.61	53.21	26.60	Average
10	0.210	9.60	0.01	33.10	42.71	63.21	20.50	QP
11	0.246	9.60	0.01	15.50	25.11	51.89	26.78	Average
12	0.246	9.60	0.01	29.30	38.91	61.89	22.98	QP
13	13.551	9.40	0.07	16.20	25.67	50.00	24.33	Average
14	13.551	9.40	0.07	28.20	37.67	60.00	22.33	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION TEST

4.1. Test Equipments

Frequency Range: 30-1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber(NSA)	AUDIX	N/A	N/A	Aug.11,22	5 Year
2.	3#Chamber(SE)	AUDIX	N/A	N/A	Sep.16,22	5 Year
3.	Signal Analyzer	Rohde & Schwarz	FSV30	104050	Apr.06,22	1 Year
4.	Tri-log-Broadband Antenna	SCHWARZBECK	VULB 9168	01317	Oct.28,22	1 Year
5.	NSA Cable	HUBER+SUHNER	CFD400NL-LW	No.3	Oct.09,22	1 Year
6.	Coaxial Switch	Anritsu	MP59B	6201397223	Apr.06,22	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESR7	101547	Apr.06,22	1 Year
8.	Amplifier	HP	8447D	2944A11159	Apr.06,22	1 Year
9.	Test Software	AUDIX	e3	6.100913a	N/A	N/A

Note: N/A means Not applicable.


Frequency Range: 1.705-30MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	10m Chamber(NSA)	AUDIX	N/A	N/A	Aug.12,22	5 Year
2.	10m Chamber(SE)	AUDIX	N/A	N/A	Sep.16,22	5 Year
3.	Loop Antenna	Schwarzbeck	FMZB 1519B	00075	Apr.17,21	2 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR3	102891	Oct.10,22	1 Year
5.	RF Cable	SPUMA	CFD400NL-LW	NO.4	Apr.06,22	1 Year
6.	Amplifier	EMCI	EMC9135	980348	Mar.02,22	1 Year
7.	Signal Analyzer	Rohde & Schwarz	FSV30	103669	Oct.09,22	1 Year
8.	Test Software	AUDIX	e3	210616	N/A	N/A


Note: N/A means Not applicable.

4.2. Block Diagram of Test Setup

Frequency Range: 30-1000MHz



Frequency Range: 1.705-30MHz



4.3. Radiated Emission Limits

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

- Remark : (1) Emission level dB μ V = 20 log Emission level μ V/m
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.4. 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.5. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.6. Operating Condition of EUT

4.6.1. Setup the EUT as shown in Section 4.2.

4.6.2. Turn on the power of all equipments.

4.6.3. Let the EUT worked in test mode (Tx Mode) and tested it.

4.7. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

For frequency range below 30MHz the Loop antenna was used at 10m measurement distance with antenna heights of 1m and antenna loop front and side faced to the EUT.

The axis of the antenna was rotated to maximize the emission. A CISPR quasi-peak detector is used for measurements below 30MHz and RBW/VBW is 9kHz/30kHz.

The limit 1.705MHz to 30MHz in clause 4.3 are specified at 30 meters, and measurements were made at 10 meters, the limit is translated to 10 meters by using a formula as follows:

$$\text{Limit}_{30\text{m}} = \text{Limit}_{10\text{m}} + 40\log(30\text{m}/10)$$

4.8. Radiated Emission Test Results

PASS.

The frequency range from 30MHz to 1000MHz and 1.705MHz to 30MHz is investigated. Please see the following pages.


Note: According to exploratory test, 9kHz to 1.705MHz no obvious signal can be detected.

Frequency Range: 30-1000MHz

Data: 3

File: E:\2023 Report Data\T\TPV\20230228-rf.EM6 (4)


Date: 2023-02-16



Site no.	: 3m Chamber	Data no.	: 3
Dis. / Ant.	: 3m 2022 VULB 9168-01317	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15 B (3M)		
Env. / Ins.	: 23.4°C/51%	Engineer	: Abel
Test Mode	: NFC TX Mode		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	189.080	16.70	1.38	14.49	32.57	43.50	10.93	QP
2	243.400	17.67	1.57	11.15	30.39	46.00	15.61	QP
3	324.880	20.20	1.86	12.06	34.12	46.00	11.88	QP
4	338.460	20.20	1.89	12.41	34.50	46.00	11.50	QP
5	352.040	20.24	1.93	13.87	36.04	46.00	9.96	QP
6	395.690	21.42	2.05	11.92	35.39	46.00	10.61	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 1
 Dis. / Ant. : 3m 2022 VULB 9168-01317 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B (3M)
 Env. / Ins. : 23.4°C/51% Engineer : Abel
 Test Mode : NFC TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	35.820	18.90	0.60	13.20	32.70	40.00	7.30	QP
2	161.920	19.20	1.27	7.09	27.56	43.50	15.94	QP
3	189.080	16.70	1.38	13.94	32.02	43.50	11.48	QP
4	243.400	17.67	1.57	11.11	30.35	46.00	15.65	QP
5	352.040	20.24	1.93	8.24	30.41	46.00	15.59	QP
6	625.580	26.08	2.71	5.08	33.87	46.00	12.13	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency Range: Below 30MHz

Data: 12

File: F:\2023 Report\TPV\20230214NFC.EM6 (12)


Date: 2023-02-14



Site no. : 10m Chamber Data no. : 12
 Dis. / Ant. : 10m 2021 LOOPANTENNA FMZ Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C 13.56
 Env. / Ins. : 23.5*C/46% Engineer : Gavin
 Test Mode : NFC TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	13.56	20.31	0.57	63.78	37.42	47.24	103.42	56.18	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 10m Chamber Data no. : 11
 Dis. / Ant. : 10m 2021 LOOPANTENNA FMZ Ant. pol. : VERTICAL
 Limit : FCC PART 15C 13.56
 Env. / Ins. : 23.5°C/46% Engineer : Gavin
 Test Mode : NFC TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	13.56	20.31	0.57	62.33	37.42	45.79	103.42	57.63	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

5. FREQUENCY STABILITY TEST

5.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.07,22	1 Year
2.	RF Cable	eastsheep	141-SMA-JJ-1000	NO.7	Jul.01,22	1 Year

5.2. Limits

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.3. Test Procedure

The EUT was placed in an environmental test chamber and powered such that control element received normal voltage and the transmitter provided maximum RF output.

5.4. Test result

EUT: Room Booking Panel		
M/N: IAD-18010A		
Test date: 2023-01-11	Pressure: 102.5±1.0 kpa	Humidity: 53.6±3.0%
Tested by: Carl	Test site: RF site	Temperature: 24.4±0.6°C

Frequency stability VS Voltage (Temperature:25°C)					
Test Voltage	Temperature	Frequency (MHz)	Max. Reading (MHz)	Result (%)	Limit (%)
AC 96V	25°C	13.56	13.56013	0.01	±0.01
AC 120V	25°C	13.56	13.56022	0.01	±0.01
AC 138V	25°C	13.56	13.56024	0.01	±0.01
Frequency stability VS Voltage (Supply voltage AC 230V)					
AC 120V	0°C	13.56	13.56010	0.01	±0.01
AC 120V	10°C	13.56	13.56011	0.01	±0.01
AC 120V	20°C	13.56	13.56014	0.01	±0.01
AC 120V	30°C	13.56	13.56013	0.01	±0.01
AC 120V	40°C	13.56	13.56009	0.01	±0.01
AC 120V	50°C	13.56	13.56011	0.01	±0.01
Conclusion: PASS					

6. 20 DB BANDWIDTH TEST

6.1. Test Equipments


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.07,22	1 Year
2.	RF Cable	eastsheep	141-SMA-JJ-1000	NO.7	Jul.01,22	1 Year

6.2.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

6.3. Test Results

EUT: Room Booking Panel		
M/N: IAD-18010A		
Test date: 2023-02-28	Pressure: 102.1±1.0 kpa	Humidity: 53.2±3.0%
Tested by: Carl	Test site: RF site	Temperature: 22.3±0.6°C
Frequency	20dB bandwidth (KHz)	Limit (KHz)
13.56MHz	463.28	N/A
Conclusion : PASS		



7. DEVIATION TO TEST SPECIFICATIONS

[NONE]

..... THE END