



# PRIMA

RICERCA & SVILUPPO

## RAPPORTO DI PROVA / TEST REPORT

Rif./Ref.No. MPETR_141238-1	Data / Date:24/04/2015	Pagine / Pages : 7
Scopo delle prove / Test object :	Prove di tipo in accordo a / Type test according to <b>FCC Cfr 47 part 2 - §2.1091, part 1 - §1.1310</b> <b>IC RSS-102 Issue 5</b>	
Richiedente / Applicant :	RADIO ACTIVITY S.R.L. Via G. De Notaris, 50 – 20128 Milano – MI – ITALY Tel. +39 02 36514205	
Persona di riferimento / Applicant's referee :	Mr. Campidoglio (m.campidoglio@radioactivity-tlc.it)	
Marchio commerciale / Trade mark :		
Fabbricante / Manufacturer :	RADIO ACTIVITY S.R.L.	
Prodotto / Product :	<b>Base station / Repeater</b>	
Modello / Model :	<b>KA-80</b>	
Data ricevimento campioni / Date of test samples receipt.	22/10/2014	
Campioni verificati / No. of tested samples	1	
Data verifiche / Testing date :	22-23-24/10/2014	
Sito di prova / Testing site :	Prima Ricerca & Sviluppo Via Campagna - 92 I - 22020 FALOPPIO CO	
Esito delle valutazioni / Assessment results :	<b>CONFORME / COMPLIANT</b>	
Verifiche effettuate da / Verifications carried out by :	Giacomo ARMELLINI Responsabile Laboratorio EMC e RADIO/ EMC and RADIO Laboratory Manager	
Approvato / Approved by :	Vincenzo LA FRAGOLA Direttore generale / Managing director	

I risultati delle prove riportati nel presente rapporto di prova si riferiscono solo ai campioni esaminati./  
The test results reported in this test report shall refer only to the samples tested

Questo Report non può essere riprodotto in modo parziale, salvo espresso autorizzazione scritta da parte del Laboratorio /  
This report may not be partially reproduced, except with the prior written permission of the issuing Laboratory

**PRIMARICERCA & SVILUPPO S.r.l.**

Sede operativa e Laboratori di prova / Headquarter and Testing lab: Via Campagna, 92 – I-22020 FALOPPIO (CO)

Tel. +39 031 3500011 – Fax +39 031 991309 – [info@primaricerca.it](mailto:info@primaricerca.it) – [www.primaricerca.it](http://www.primaricerca.it)

## **CONTENUTO / TABLE OF CONTENTS**


<b>0</b>	<b>RELEASE CONTROL RECORD.....</b>	<b>2</b>
<b>1</b>	<b>TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>3</b>
1.1	EUT Identification .....	3
1.2	EUT Technical Data .....	3
1.3	EUT modification.....	4
1.4	Auxiliary equipment .....	4
<b>2</b>	<b>REFERENCE STANDARDS .....</b>	<b>4</b>
<b>3</b>	<b>MEASUREMENTS AND CALCULATION RESULTS .....</b>	<b>5</b>
3.1	Calculation Method .....	5
3.2	Limits.....	6
3.3	Measurements and Calculation Results.....	7

### **0 RELEASE CONTROL RECORD**

TEST REPORT NUMBER	REASON OF CHANGE	DATE OF ISSUE
MPETR_141238-0	Original Release	12/03/2015
MPETR_141238-1	Editorial Change	24/04/2015

## 1 TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT)

### 1.1 EUT Identification

<b>DESCRIPTION</b>	Base station / Repeater
<b>MODEL NAME OR NO.</b>	KA-80
<b>PART NUMBER / SERIAL NO.</b>	Not present (prototype)
<b>BRAND NAME</b>	
<b>MANUFACTURER</b>	RADIO ACTIVITY S.R.L.
<b>SINGLE UNIT OR SYSTEM</b>	Single unit
<b>COUNTRY OF MANUFACTURER</b>	Italy

### 1.2 EUT Technical Data

<b>Power source</b>	External Power Supply		
<b>Power supply nominal voltage</b>	<i>Min.</i>	<i>Typ.</i>	<i>Max.</i>
	11Vdc	13.8Vdc	15Vdc
<b>Nominal power or absorbing current</b>	TX: 60 W @25W RF / RX: 5 W @Main+Div enabled		
<b>Dimensions</b>	160x200x45mm / 3.2kg		
<b>Typical usage :</b>	Radio equipment		
<b>Type:</b>	Private Land Mobile Radio Services		
<b>Frequency range of Operation</b>	72-76MHz		
<b>Output Power</b>	1-25 W / 100% duty cycle / selectable per channel		
<b>Channelization</b>	12,5KHz		
<b>Frequency stability</b>	0,5 p.p.m. (without GPS)		
<b>Data rate</b>	9600 bps		
<b>Type of antenna</b>	Not provided by the customer		

### 1.3 EUT modification

---

- None

### 1.4 Auxiliary equipment

---

- None

## 2 REFERENCE STANDARDS

---

CODE OF FEDERAL REGULATIONS	
Title 47 Part 1 Subpart I § 1.1310	Procedures Implementing the National Environmental Policy Act of 1969. Radiofrequency radiation exposure limits.
Title 47 Part 2 Subpart J § 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
ANSI C63.4	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
IC RSS-102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

## 3 MEASUREMENTS AND CALCULATION RESULTS

### 3.1 Calculation Method

#### Far Field Power flux Calculation model.

This model is applicable in the far-field region and over-estimates in the radiating near-field region. The far-field calculations are accurate when the distance,  $r$ , from an antenna of length  $D$  to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

The Power Flux is

$$S = \frac{PG}{4\pi r^2} \quad \text{or equivalent} \quad S = \frac{EIRP}{4\pi r^2}$$

where

P = input power of the antenna

G = antenna gain relative to an isotropic antenna

r = distance from the antenna to the point of investigation.

EIRP = Effective Isotropic Radiated Power

### 3.2 Limits

Tab. 1 of CFR Title 47 Part 1 Subpart I § 1.1310

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**Note to Table 1:** General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

#### IC – RSS-102 Issue 5 par. 4 RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (W/m <sup>2</sup> )	Averaging time (minutes)
0.003-10	83	90	-	Instantaneous
0.1-10	-	0.73/ f	-	6
1.1-10	87/ f <sup>0.5</sup>	-	-	6
10-20	27.46	0.0728	-2	6
20-48	58.07/ f <sup>0.25</sup>	0.1540/ f <sup>0.25</sup>	8.944/ f <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

**Note:** f is frequency in MHz.

\* Power density limit is applicable at frequencies greater than 100 MHz

### 3.3 Measurements and Calculation Results

#### WORST CASE MEASUREMENT:

DMR REPEATER ANALOGIC, MODULATION: FM, BANDWIDTH: 11kHz

Ch freq: 72MHz

Measured Peak power at antenna connector: 43.69dBm (23.39W)

Maximum possible power at antenna connector: 25W

The calculation has been performed using the maximum possible power at antenna connector 25W as worst case

TX Frequency (MHz)	Peak Power at Antenna Connector (dBm)	Duty Cycle correction (dB)	Average Power at Antenna Connector (dBm)	Average Power at Antenna Connector (W)	Antenna Gain (dBi)
72	44	-	44	25	NA <sup>(1)</sup>
<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b>					
<b>Evaluation Distance (m)</b>			2 <sup>(2)</sup>		
<b>Power density at evaluation distance (W/m<sup>2</sup>)</b>			DEPENDS ON ANTENNA ASSEMBLY GAIN <sup>(1)</sup>		
<b>Power density Limit (W/m<sup>2</sup>)</b>			2 (acc to CFR Title 47 Part 1 Subpart I § 1.1310) 1.291 (acc to RSS-102 Issue 5 par. 4)		
<b>Antenna Assembly Gain <sup>(1)</sup> (dBm)</b>		<b>Power density at evaluation distance (W/m<sup>2</sup>)</b>		<b>Power density Limit (W/m<sup>2</sup>)</b>	
0dBm		0.497		1.291 (worst case)	
<b>RESULT: WITHIN THE LIMITS</b>					
<b>Antenna Assembly Gain <sup>(1)</sup> (dBm)</b>		<b>Minimum safe distance (m)</b>		---	
0dBm		1.24		---	

<sup>(1)</sup> External Antenna is not provided by the manufacturer.

<sup>(2)</sup> Minimum installation distance from human body declared by the manufacturer