

# RADIO TEST REPORT

REP050047

Date of issue:

July 11, 2024

Applicant:

Radio Activity Srl

Via Privata Cascia, 11 – 20128 Milano (MI) – Italy

Product:

PMR digital transceiver/repeater

Model:

KA-080e

FCC ID:

Y9M-KA080E

Specifications:

- ◆ FCC 47 CFR Part 22, Subpart C and E
- ◆ FCC 47 CFR Part 90, Subpart I



ACCREDIA  
L'ENTE ITALIANO DI ACCREDITAMENTO  
ITALY

LAB N° 1244 L

#### Test location

Company name	Nemko S.p.A.
Address	Via Del Carroccio, 4
City	Biassono
Province	MB
Postal code	20853
Country	Italy
Telephone	+39 039 220 12 01
Facsimile	+39 039 220 12 21
Website	www.nemko.com
Site number	FCC: 682159; IC: 9109A

Tested by	O. Frau
Test engineer signature	
Reviewed by	D. Guarnone
Reviewer signature	

#### Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko S.p.A. ISO/IEC 17025 accreditation.

#### Copyright notification

Nemko S.p.A. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko S.p.A. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## Table of Contents

<b>Table of Contents .....</b>	<b>3</b>
<b>Section 1      Report summary .....</b>	<b>4</b>
1.1   Test specifications .....	4
1.2   Test methods .....	4
1.3   Exclusions .....	4
1.4   Statement of compliance .....	4
1.5   Test report revision history .....	4
<b>Section 2      Engineering considerations .....</b>	<b>5</b>
2.1   Modifications incorporated in the EUT for compliance .....	5
2.2   Technical judgment .....	5
2.3   Deviations from laboratory tests procedures .....	5
<b>Section 3      Test conditions .....</b>	<b>6</b>
3.1   Atmospheric conditions .....	6
3.2   Power supply range .....	6
<b>Section 4      Measurement uncertainty .....</b>	<b>7</b>
4.1   Uncertainty of measurement .....	7
<b>Section 5      Information provided by the applicant .....</b>	<b>8</b>
5.1   Disclaimer .....	8
5.2   Applicant/Manufacture .....	8
5.3   EUT information .....	8
5.4   Technical information .....	9
5.5   EUT setup details .....	10
<b>Section 6      Summary of test results .....</b>	<b>14</b>
6.1   Testing location .....	14
6.2   Testing period .....	14
6.3   Sample information .....	14
6.4   FCC Part 2 and 90 Subpart I test requirements results .....	14
6.5   FCC Part 22 Subpart C and E test requirements results .....	14
<b>Section 7      Testing data .....</b>	<b>15</b>
7.1   Number of frequencies .....	15
7.2   Modulation characteristic .....	16
7.3   Transmitter Output Power .....	22
7.4   Bandwidth limitations .....	25
7.5   Spectrum mask and spurious emissions .....	35
7.6   Transmitter frequency stability .....	62
<b>Section 8      Photos .....</b>	<b>64</b>
8.1   Photos of the test set-up .....	64
8.2   Photos of the EUT .....	65

## Section 1 Report summary

---

### 1.1 Test specifications

---

FCC 47 CFR Part 90, Subpart I  
FCC 47 CFR Part 22, Subpart C  
FCC 47 CFR Part 22, Subpart E

Private land mobile radio services. General technical standards  
Public Mobile Services. Operational and Technical Requirements  
Public Mobile Services. Paging and Radiotelephone Service

### 1.2 Test methods

---

ANSI C63.26-2015  
FCC 47 CFR Part 2, Subpart J

American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services  
Equipment authorization procedures

### 1.3 Exclusions

---

None

### 1.4 Statement of compliance

---

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.3 above. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

### 1.5 Test report revision history

---

Table 1.5-1: Test report revision history

Revision #	Date of issue	Details of changes made to test report
REP050047	2024-07-11	Original report issued

## Section 2 Engineering considerations

---

---

### 2.1 Modifications incorporated in the EUT for compliance

---

There were no modifications performed to the EUT during this assessment.

### 2.2 Technical judgment

---

None

### 2.3 Deviations from laboratory tests procedures

---

No deviations were made from laboratory procedures.

## Section 3 Test conditions

---

### 3.1 Atmospheric conditions

---

In the laboratory, the following ambient conditions are respected for each test reported below:

Ambient temperature: 18 ÷ 33 °C<sup>(1)</sup>

Relative Humidity: 25 ÷ 70 %<sup>(2)</sup>

Atmospheric pressure: 860 ÷ 1060 hPa

The following instruments are used to monitor the environmental conditions:

Equipment	Manufacturer	Model	Serial N°
Thermo-hygrometer data loggers	Testo	175-H2	20012380/305
Thermo-hygrometer data loggers	Testo	175-H2	38203337/703
Barometer	Castle	GPB 3300	072015

### 3.2 Power supply range

---

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages  $\pm 5\%$ , for which the equipment was designed.

## Section 4 Measurement uncertainty

### 4.1 Uncertainty of measurement

The measurement uncertainty was calculated for each test and quantity listed in this test report, according to CISPR 16-4-2, ETSI TR 100 028-1, ETSI TR 100 028-2 and other specific test standards and is documented in Nemko Spa working manuals WML1002 and WML0078.

The assessment of conformity for each test performed on the equipment is performed not taking into account the measurement uncertainty. The two following possible verdicts are stated in the report:

P (Pass) - The measured values of the equipment respect the specification limit at the points tested. The specific risk of false accept is up to 50% when the measured result is close to the limit.

F (Fail) - One or more measured values of the equipment do not respect the specification limit at the points tested. The specific risk of false reject is up to 50% when the measured result is close to the limit.

Hereafter Nemko's measurement uncertainties are reported:

EUT	Type	Test	Range	Measurement Uncertainty	Notes
Transmitter	Conducted	Frequency error	0.001 MHz ÷ 40 GHz	0.08 ppm	(1)
		Carrier power RF Output Power	0.009 MHz ÷ 30 MHz 30 MHz ÷ 18 GHz 18 MHz ÷ 40 GHz 40 MHz ÷ 140 GHz	1.1 dB 1.5 dB 3.0 dB 5.0 dB	(1) (1) (1) (1)
		Adjacent channel power	1 MHz ÷ 18 GHz	1.4 dB	(1)
		Conducted spurious emissions	0.009 MHz ÷ 18 GHz 18 GHz ÷ 40 GHz 40 GHz ÷ 220 GHz	3.0 dB 4.2 dB 6.0 dB	(1) (1) (1)
		Intermodulation attenuation	1 MHz ÷ 18 GHz	2.2 dB	(1)
		Attack time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Attack time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Release time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Release time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Transient behaviour of the transmitter – Transient frequency behaviour	1 MHz ÷ 18 GHz	0.2 kHz	(1)
		Transient behaviour of the transmitter – Power level slope	1 MHz ÷ 18 GHz	9%	(1)
		Frequency deviation - Maximum permissible frequency deviation	0.001 MHz ÷ 18 GHz	1.3%	(1)
		Frequency deviation - Response of the transmitter to modulation frequencies above 3 kHz	0.001 MHz ÷ 18 GHz	0.5 dB	(1)
		Dwell time	-	3%	(1)
		Hopping Frequency Separation	0.01 MHz ÷ 18 GHz	1%	(1)
		Occupied Channel Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
		Modulation Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)
	Radiated	Radiated spurious emissions	0.009 MHz ÷ 26.5 GHz 26.5 GHz ÷ 66 GHz 66 GHz ÷ 220 GHz	6.0 dB 8.0 dB 10 dB	(1) (1) (1)
		Effective radiated power transmitter	10 kHz ÷ 26.5 GHz 26.5 GHz ÷ 66 GHz 66 GHz ÷ 220 GHz	6.0 dB 8.0 dB 10 dB	(1) (1) (1)

NOTES:

(1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k = 2$ , which for a normal distribution corresponds to a coverage probability of approximately 95 %

## Section 5 Information provided by the applicant

---

### 5.1 Disclaimer

---

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

### 5.2 Applicant/Manufacture

---

Applicant name	Radio Activity Srl
Applicant address	Via Privata Cascia, 11 – 20128 Milano (MI) – Italy
Manufacture name	Same as applicant
Manufacture address	Same as applicant

### 5.3 EUT information

---

Product name	PMR digital transceiver/repeater
Model	KA-080e
Model variant(s)	--
Serial number	PRJ00527000003 (Assigned by Nemko S.p.A.)
Part number	--
Power supply requirements	13.6 V DC, 10 A max
Product description and theory of operation	The EUT is a radio base station for fixed installation
Software version	--



## 5.4 Technical information

System type	<input type="checkbox"/> Mobile system <input checked="" type="checkbox"/> Base/Fixed point-to-point system	
Frequency band	72 – 76 MHz	
Frequency Min (MHz)	72.1 MHz	
Frequency Max (MHz)	75.9 MHz	
RF power Max (W), Conducted	58.5 (47.67 dBm)	
Field strength, dB $\mu$ V/m @ 3 m	N/A	
Measured BW (kHz), 99% OBW	8.16	
Emission designators	Analog FM 11K0F3E / 14K0F3E / 16K0F3E (12.5 / 20 / 25 kHz) Analog PM 11K0G3E / 14K0G3E / 16K0G3E (12.5 / 20 / 25 kHz) DMR 4FSK Voice & Data 7K79FXE DMR 4FSK Data 7K79FXD P25 C4FM Voice & Data 8K10F1E P25 C4FM Data 8K10F1D	
Transmitter spurious, dBm @ 3 m	-41.78 @216.32 MHz	
Antenna information	External antenna not provided	

## 5.5 EUT setup details

### 5.5.1 Radio exercise details

The following software has been used to set the EUT.

### 5.5.2 EUT sub assemblies

--

### 5.5.3 EUT interface ports

Port	Name	Type <sup>1</sup>	Cable Max. >3m	Cable Shielded	Description
0	Enclosure	N/E	—	—	—
1	13.6 Vdc input	DC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Two wires cable
2	LAN	TP	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard cable with RJ45 connector
3	RF TX antenna	ANT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Coaxial cable with SMA connector
4	RF RX main antenna	ANT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Coaxial cable with SMA connector
5	RF RX diversity antenna	ANT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Coaxial cable with SMA connector
6	Main GPS antenna	ANT	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Coaxial cable with SMA connector
7	USB type A	I/O	—	—	Normally not used
8	15 pole HD	I/O	<input type="checkbox"/>	<input type="checkbox"/>	Multi wires cable


Notes:

<sup>1</sup> Port type:  
 AC = AC Power Port      DC = DC Power Port      N/E = Non-Electrical      ANT = Antenna Port  
 I/O = Signal/Control Input or Output Port      TP = Wired network or telecommunication Port


### 5.5.4 Support equipment

Product Type	Manufacturer	Model	Comments
Notebook	DELL	Latitude	—


## 5.5.5 Radiated testing block diagram (below 1 GHz)



## 5.5.6 Radiated testing block diagram (above 1 GHz)



## 5.5.7 Antenna port testing block diagram



## Section 6 Summary of test results

---

### 6.1 Testing location

---

Test location (s)	Nemko Spa

### 6.2 Testing period

---

Test start date	July 05, 2024	Test end date	July 10, 2024

### 6.3 Sample information

---

Receipt date	July 04, 2024	Nemko sample ID number(s)	PRJ00572000003 (Assigned by Nemko S.p.A.)

### 6.4 FCC Part 2 and 90 Subpart I test requirements results

---

Table 6.4-1: FCC requirements results

Part	Test description	Verdict
§2.1047	Modulation characteristics	Pass
§90.205(c)	Transmitter output power	Pass
§90.209(b)	Bandwidth limitations	Pass
§90.210	Spectrum mask and spurious emissions	Pass
§90.213(a)	Transmitter frequency stability	Pass

Notes: --

### 6.5 FCC Part 22 Subpart C and E test requirements results

---

Table 6.4-1: FCC requirements results

Part	Test description	Verdict
§22.593	Effective radiated power limits	Pass
§22.591	Bandwidth limitations	Pass
§22.359	Spectrum mask and spurious emissions	Pass
§22.355	Transmitter frequency stability	Pass

Notes: --

## Section 7 Testing data

---

### 7.1 Number of frequencies

---

#### 7.1.1 References, definitions and limits

---

**ANSI C63.26, Clause 5.1.2:**

Measurements of transmitters shall be performed and, if required, reported for each frequency band in which the EUT can be operated with the device transmitting at the number of frequencies in each band specified in table below.

*Table 7.1-1: Frequency Range of Operation*

Frequency range over which the device operates (in each band)	Number of test frequencies required	Location of measurement frequency inside the operating frequency range
1 MHz or less	1	Center (middle of the band)
1–10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near center and 1 near low end

Notes: "near" means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

#### 7.1.2 Test summary

---

Verdict	Pass		
Tested by	O. Frau	Test date	July 05, 2024

#### 7.1.3 Observations, settings and special notes

---

None

#### 7.1.4 Test data

---

*Table 7.1-2: Test channels selection*

Start of Frequency range, MHz	End of Frequency range, MHz	Frequency range bandwidth, MHz	Low channel, MHz	Mid channel, MHz	High channel, MHz
72.0	76.0	4	72.1	--	75.9

## 7.2 Modulation characteristic

---

### 7.2.1 References, definitions and limits

---

#### FCC §2.1047:

- (a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.
- (b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed

### 7.2.2 Test summary

---

Verdict	Pass
Tested by	O. Frau

Test date

July 05, 2024

### 7.2.3 Observations, settings and special notes

---

Per ANSI C63.26 Subclause 5.3.1: The audio frequency response is the degree of closeness to which the frequency deviation of the transmitter follows a prescribed characteristic.

Spectrum analyser settings:

Receiver mode	RMS deviation
Audio frequency generator tone	100 Hz and 5000 Hz

Reference voltage measurement: Apply a 1000 Hz tone and adjust the audio frequency generator to produce 20% of the rated system deviation. Record the DMM reading as  $V_{REF}$ .

Calculation of the audio frequency response at the present frequency:  $20 \times \log_{10} (V_{FREQ} / V_{REF})$

Per ANSI C63.26 Subclause 5.3.2: Modulation limiting is the ability of a transmitter circuit to limit the transmitter from producing deviations in excess of a rated system deviation.

Spectrum analyser settings:

Receiver mode	Peak positive and negative deviation
Audio frequency generator tone	300 Hz, 2500 Hz and 3000 Hz


Reference voltage measurement: Apply a 1000 Hz tone and adjust the audio frequency generator to produce 60% of the rated system deviation. This is the 0 dB reference level. Plot the data set as a percentage of deviation relative to the 0 dB reference point versus input voltage.

## 7.2.4 Test equipment list


Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Spectrum Analyzer	Rohde & Schwarz	FSW43	101767	2023-09	2024-09
Shielded room	Siemens	10m control room	1947	NCR	NCR
Radiocommunication Tester	R&S	CMT	883152/001	2024-01	2027-01
Audio Generator	Rohde & Schwarz	APN04	860 093/017	2023-12	2025-12
Cable set	Rosenberger	ST.ALO-02	1.650	2023-10	2024-10

Note: NCR - no calibration required, VOU - verify on use

## 7.2.5 Test data




Test data, continued




Test data, continued

---



Audio frequency response at 74.0 MHz (12.5 kHz)

Test data, continued



Audio frequency response at 74.0 MHz (25 kHz)

## 7.3 Transmitter Output Power

### 7.3.1 References, definitions and limits

#### FCC §22.593:

The effective radiated power of fixed stations operating on the channels listed in § 22.591 must not exceed 150 Watts. The equivalent isotropically radiated power of existing fixed microwave stations (2110-2130 and 2160-2180 MHz) licensed under this part (pursuant to former rules) must not exceed the applicable limits set forth in § 101.113 of this chapter.

#### FCC §90.205:

(c) 72-76 MHz.

The maximum effective radiated power (ERP) for stations operating on fixed frequencies is 300 watts. Stations operating on mobile-only frequencies are limited to one watt transmitter output power

(r) All other frequency bands. Requested transmitter power will be considered and authorized on a case by case basis.

(s) The output power shall not exceed by more than 20 percent either the output power shown in the Radio Equipment List [available in accordance with § 90.203(a)(1)] for transmitters included in this list or when not so listed, the manufacturer's rated output power for the particular transmitter specifically listed on the authorization.

### 7.3.2 Test summary

Verdict	Pass
Tested by	O. Frau

Test date

July 05, 2024

### 7.3.3 Observations, settings and special notes

Manufacturer's rated output power is 50 W or 47 dBm. 20% of the output power is 47.8 dBm

Measurement of peak power was performed per ANSI C63.26 subclause 5.2.3.3. Spectrum analyser settings:

Resolution bandwidth	≥ OBW
Video bandwidth	≥ 3 × RBW
Frequency span	≥ 2 × OBW
Detector mode	Peak
Trace mode	Max Hold
Sweep time	≥ 10 × (number of points in sweep) × (transmission symbol period)

### 7.3.4 Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Spectrum Analyzer	Rohde & Schwarz	FSW43	101767	2024-01	2025-01
Shielded room	Siemens	10m control room	1947	NCR	NCR
Cable set	Rosenberger	ST.ALO-02	1.650	2023-10	2024-10

Note: NCR - no calibration required, VOU - verify on use

## 7.3.5 Test data


Table 7.3-1: **Transmitter power results**

Modulation	Frequency, MHz	Output power, dBm	Max Antenna gain, dB	ERP limit, dBm
FM 12.5 kHz	72.1	47.62	4.14	51.76
FM 25.0 kHz	72.1	47.62	4.14	51.76
DMR 4FSK	72.1	47.64	4.12	51.76
P25 C4FM	72.1	47.63	4.13	51.76
FM 12.5 kHz	75.9	47.67	4.09	51.76
FM 25.0 kHz	75.9	47.66	4.10	51.76
DMR 4FSK	75.9	47.66	4.10	51.76
P25 C4FM	75.9	47.65	4.11	51.76

Table 7.3-2: **Rated vs measured power**

Modulation	Frequency, MHz	Rated output power, dBm	Measured output power, dBm	Difference, dB	Difference limit, dB	Margin, dB
FM 12.5 kHz	72.1	47	47.62	0.62	+0.8	0.18
FM 25.0 kHz	72.1	47	47.62	0.62	+0.8	0.18
DMR 4FSK	72.1	47	47.64	0.64	+0.8	0.16
P25 C4FM	72.1	47	47.63	0.63	+0.8	0.17
FM 12.5 kHz	75.9	47	47.67	0.67	+0.8	0.13
FM 25.0 kHz	75.9	47	47.66	0.66	+0.8	0.14
DMR 4FSK	75.9	47	47.66	0.66	+0.8	0.14
P25 C4FM	75.9	47	47.65	0.65	+0.8	0.15

## Test data, continued



## 7.4 Bandwidth limitations

---

### 7.4.1 References, definitions and limits

---

**FCC §22.591:**

The following channels are allocated for assignment to fixed transmitters that support other transmitters that provide public mobile service. Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

(a) The 72-76 MHz channels may be used in point-to-multipoint configurations. The 72-76 MHz channels are also allocated for assignment in the Private Radio Services (see part 90 of this chapter).

**FCC §90.209:**

(b) The maximum authorized single channel bandwidth of emission corresponding to the type of emission specified in §90.207 is as follows:  
(5) Unless specified elsewhere, channel spacings and bandwidths that will be authorized in the following frequency bands are given in the following table.

*Table 7.4-1: Standard Channel Spacing/Bandwidth*

Frequency band, MHz	Channel spacing, kHz	Authorized bandwidth <sup>1</sup> , kHz
72-76	20.0	20.0

Note: <sup>1</sup>Operations using equipment designed to operate with a 25 kHz channel bandwidth will be authorized a 20 kHz bandwidth. Operations using equipment designed to operate with a 12.5 kHz channel bandwidth will be authorized a 11.25 kHz bandwidth. Operations using equipment designed to operate with a 6.25 kHz channel bandwidth will be authorized a 6 kHz bandwidth. All stations must operate on channels with a bandwidth of 12.5 kHz or less beginning January 1, 2013

#### 7.4.2 Test summary

Verdict	Pass
Tested by	O. Frau

#### 7.4.3 Observations, settings and special notes

The test was performed as per ANSI C63.26, subclause 5.4.4.

Spectrum analyser settings:

Resolution bandwidth	1–5% of OBW
Video bandwidth	$\geq 3 \times$ RBW
Frequency span	1.5 $\times$ OBW
Detector mode	Peak
Trace mode	Max Hold

#### 7.4.4 Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Spectrum Analyzer	Rohde & Schwarz	FSW43	101767	2023-09	2024-09
Shielded room	Siemens	10m control room	1947	NCR	NCR
Cable set	Rosenberger	ST.ALO-02	1.650	2023-10	2024-10


Note: NCR - no calibration required, VOU - verify on use

#### 7.4.5 Test data

Table 7.4-2: 99% occupied bandwidth results


Modulation	Frequency, MHz	99% occupied bandwidth, kHz	Limit, kHz	Margin, kHz
FM 12.5 kHz	72.1	4.32	20.00	-15.68
FM 25.0 kHz	72.1	8.14	20.00	-11.86
DMR 4FSK	72.1	7.55	20.00	-12.45
P25 C4FM	72.1	5.66	20.00	-14.34
FM 12.5 kHz	75.9	4.35	20.00	-15.65
FM 25.0 kHz	75.9	8.16	20.00	-11.84
DMR 4FSK	75.9	7.79	20.00	-12.21
P25 C4FM	75.9	5.90	20.00	-14.10

Test data, continued




99% occupied bandwidth with modulation FM 12.5 kHz at 72.1 MHz

Test data, continued



99% occupied bandwidth with modulation FM 25 kHz at 72.1 MHz

Test data, continued




99% occupied bandwidth with modulation DMR 4FSK at 72.1 MHz

Test data, continued




99% occupied bandwidth with modulation P25 C4FM at 72.1 MHz

## 7.4.1 Test data, continued



99% occupied bandwidth with modulation FM 12.5 kHz at 75.9 MHz

## 7.4.2 Test data, continued




99% occupied bandwidth with modulation FM 25 kHz at 75.9 MHz

## 7.4.3 Test data, continued



99% occupied bandwidth with modulation DMR 4FSK at 75.9 MHz

## 7.4.4 Test data, continued



99% occupied bandwidth with modulation P25 C4FM at 75.9 MHz

## 7.5 Spectrum mask and spurious emissions

### 7.5.1 References, definitions and limits

#### FCC §22.359:

The rules in this section govern the spectral characteristics of emissions in the Public Mobile Services, except for the Air-Ground Radiotelephone Service (see § 22.861, instead) and the Cellular Radiotelephone Service (see § 22.917, instead).

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.
- (b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 30 kHz or more. In the 60 kHz bands immediately outside and adjacent to the authorized frequency range or channel, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e., 30 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (c) Alternative out of band emission limit. Licensees in the Public Mobile Services may establish an alternative out of band emission limit to be used at specified frequencies (band edges) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.
- (d) Interference caused by out of band emissions. If any emission from a transmitter operating in any of the Public Mobile Services results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

#### FCC §90.210:

Except as indicated elsewhere in this part, transmitters used in the radio services governed by this part must comply with the emission masks outlined in this section. Unless otherwise stated, per paragraphs (d)(4), (e)(4), and (o) of this section, measurements of emission power can be expressed in either peak or average values provided that emission powers are expressed with the same parameters used to specify the unmodulated transmitter carrier power. For transmitters that do not produce a full power unmodulated carrier, reference to the unmodulated transmitter carrier power refers to the total power contained in the channel bandwidth. Unless indicated elsewhere in this part, the table in this section specifies the emission masks for equipment operating under this part.

Table 7.5-1: Applicable Emission Masks

Frequency band, MHz	Mask for equipment with audio low pass filter	Mask for equipment with audio low pass filter
150–174 <sup>1,2</sup>	B, D, or E	C, D, or E
All other bands	B	C

Notes: <sup>1</sup>Equipment designed to operate with a 25 kHz channel bandwidth must meet the requirements of Emission Mask B or C, as applicable. Equipment designed to operate with a 12.5 kHz channel bandwidth must meet the requirements of Emission Mask D, and equipment designed to operate with a 6.25 kHz channel bandwidth must meet the requirements of Emission Mask E.

<sup>2</sup>Equipment designed to operate on 25 kilohertz bandwidth channels must meet the requirements of either Emission Mask B or G, whichever is applicable, while equipment designed to operate on 12.5 kilohertz bandwidth channels must meet the requirements of Emission Mask D. Equipment designed to operate on 25 kilohertz bandwidth channels may alternatively meet the Adjacent Channel Power limits of §90.221.

- (b) **Emission Mask B.** For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:
  - (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
  - (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
  - (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P)$  dB.

(c) **Emission Mask C.** For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier output power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5 kHz, but not more than 10 kHz: At least  $83 \log(f_d/5)$  dB;
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 10 kHz, but not more than 250 percent of the authorized bandwidth: At least  $29 \log(f_d^2/11)$  dB or 50 dB, whichever is the lesser attenuation;
- (3) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log(P)$  dB.

(d) **Emission Mask D—12.5 kHz channel bandwidth equipment.** For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth  $f_0$  to 5.625 kHz removed from  $f_0$ : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least  $7.27(f_d-2.88 \text{ kHz})$  dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 12.5 kHz: At least  $50 + 10 \log(P)$  dB or 70 dB, whichever is the lesser attenuation.

(4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

(e) **Emission Mask E—6.25 kHz or less channel bandwidth equipment.** For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth  $f_0$  to 3.0 kHz removed from  $f_0$ : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least  $30 + 16.67(f_d-3 \text{ kHz})$  or  $55 + 10 \log(P)$  or 65 dB, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least  $55 + 10 \log(P)$  or 65 dB, whichever is the lesser attenuation.

(4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

#### 7.5.2 Test summary

Verdict	Pass
Tested by	O. Frau

#### 7.5.3 Observations, settings and special notes

Spectrum analyser settings for spectrum mask:

Resolution bandwidth:	100 Hz / 300 Hz
Video bandwidth:	> RBW
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for spurious emissions:


Resolution bandwidth:	100 kHz (below 1 GHz); 1 MHz (above 1 GHz)
Video bandwidth:	> RBW
Detector mode:	Peak
Trace mode:	Max Hold

#### 7.5.4 Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
EMI Receiver	Rohde & Schwarz	ESW44	101620	2023-09	2024-09
Spectrum Analyzer	Rohde & Schwarz	FSW43	101767	2023-09	2024-09
Trilog Broadband Antenna	Schwarzbeck	VULB 9162	9162-025	2021-07	2024-07
Antenna 1 - 18 GHz	Schwarzbeck Mess-Elektronik	STLP9148	STLP 9148-152	2021-09	2024-09
Broadband Amplifier	Schwarzbeck Mess-Elektronik	BBV9718C	00121	2024-03	2025-03
Controller	Maturo	FCU3.0	10041	NCR	NCR
Tilt antenna mast	Maturo	TAM4.0-E	10042	NCR	NCR
Turntable	Maturo	TT4.0-5T	2.527	NCR	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	2023-09	2025-09
Shielded room	Siemens	10m control room	1947	NCR	NCR
3m Semi anechoic chamber	Comtest	SAC-3	1711-150	2022-09	2024-09
Software turntable and mast	Maturo	mcApp	8.1.0.5410	NCR	NCR
Cable set	Rosenberger and Huber + Suhner	RE01+RE02	1.654+1.655	2023-09	2024-09


Note: NCR - no calibration required, VOU - verify on use

## 7.5.1 Test data




Emission mask B with modulation FM 12.5 kHz at 72.1 MHz

## 7.5.2 Test data, continued




Emission mask B with modulation FM 25.0 kHz at 72.1 MHz


**7.5.3 Test data, continued**


Emission mask B with modulation DMR 4FSK at 72.1 MHz

## 7.5.4 Test data, continued




Emission mask B with modulation P25 C4FM at 72.1 MHz

**7.5.5 Test data, continued**



Emission mask B with modulation FM 12.5 kHz at 75.9 MHz

## 7.5.6 Test data, continued




Emission mask B with modulation FM 25 kHz at 75.9 MHz

## 7.5.7 Test data, continued




Emission mask B with modulation DMR 4FSK at 75.9 MHz

## 7.5.8 Test data, continued



Emission mask B with modulation P25 C4FM at 75.9 MHz


## 7.5.9 Test data, continued




Conducted spurious emissions with modulation FM 12.5 kHz at 72.1 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier

## 7.5.10 Test data, continued




## 7.5.11 Test data, continued



Conducted spurious emissions with modulation DMR 4FSK at 72.1 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.12 Test data, continued



Conducted spurious emissions with modulation P25 C4FM at 72.1 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.13 Test data, continued



Conducted spurious emissions with modulation FM 12.5 kHz at 75.9 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.14 Test data, continued



Conducted spurious emissions with modulation FM 25 kHz at 75.9 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.15 Test data, continued



Conducted spurious emissions with modulation DMR 4FSK at 75.9 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.16 Test data, continued



Conducted spurious emissions with modulation P25 C4FM at 75.9 MHz (30 MHz to 1 GHz)

Limit exceeded by the carrier


## 7.5.17 Test data, continued



Radiated spurious emissions with modulation FM 12.5 kHz at 72.1 MHz – Antenna in horizontal polarization (30 MHz to 1 GHz)  
 (worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.18 Test data, continued



Radiated spurious emissions with modulation FM 12.5 kHz at 72.1 MHz – Antenna in vertical polarization (30 MHz to 1 GHz)  
(worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.19 Test data, continued



Radiated spurious emissions with modulation FM 25.0 kHz at 72.1 MHz – Antenna in horizontal polarization (30 MHz to 1 GHz)  
(worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.20 Test data, continued



Radiated spurious emissions with modulation FM 25.0 kHz at 72.1 MHz – Antenna in vertical polarization (30 MHz to 1 GHz)  
 (worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.21 Test data, continued



Radiated spurious emissions with modulation DMR 4FSK at 72.1 MHz – Antenna in horizontal polarization (30 MHz to 1 GHz)  
 (worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.22 Test data, continued



Radiated spurious emissions with modulation DMR 4FSK at 72.1 MHz – Antenna in vertical polarization (30 MHz to 1 GHz)  
 (worst frequency case from conducted emissions)

Limit exceeded by the carrier


## 7.5.23 Test data, continued



Radiated spurious emissions with modulation P25 C4FM at 72.1 MHz – Antenna in horizontal polarization (30 MHz to 1 GHz)  
 (worst frequency case from conducted emissions)

Limit exceeded by the carrier

## 7.5.24 Test data, continued



Radiated spurious emissions with modulation P25 C4FM at 72.1 MHz – Antenna in vertical polarization (30 MHz to 1 GHz)  
(worst frequency case from conducted emissions)

Limit exceeded by the carrier

## 7.6 Transmitter frequency stability

### 7.6.1 References, definitions and limits

#### FCC §22.355:

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

*Table 7.6-1: Table C-1—Frequency Tolerance for Transmitters in the Public Mobile Services*

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
20 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

#### FCC §90.213:

(a) Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

*Table 7.6-2: Minimum frequency stability*

Frequency range (MHz)	Fixed and base stations	Mobile stations over 2 watts output power	Mobile stations 2 watts or less output power
72-76	±5 ppm	--	±50 ppm <sup>2</sup>

Notes: none

### 7.6.2 Test summary

Verdict	Pass
Tested by	O. Frau

Test date

July 09, 2024

### 7.6.3 Observations, settings and special notes

Test was performed on supply voltage variations as per client rated, no frequency deviation was observed.

## 7.6.4 Test equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
Spectrum Analyzer	Rohde & Schwarz	FSW43	101767	2023-09	2024-09
Climatic chamber	espec	ARS-1100	4100000067	2023-12	2024-12

Note: NCR - no calibration required, VOU - verify on use


## 7.6.5 Test data

Table 7.6-3: Transmitter frequency stability results


Test conditions	Frequency, Hz	Drift, Hz	Drift, ppm	Limit ±ppm	Margin, ±ppm
+50 °C, Nominal	74000012.6	-3.4	-0.046	5.0	-5.0
+40 °C, Nominal	74000013.2	-2.8	-0.038	5.0	-5.0
+30 °C, Nominal	74000012.3	-3.7	-0.050	5.0	-5.0
+20 °C, +15 %	74000016.2	0.2	0.003	5.0	-5.0
+20 °C, Nominal	74000016.0	Reference	Reference	Reference	Reference
+20 °C, -15 %	74000016.6	0.6	0.008	5.0	-5.0
+10 °C, Nominal	74000018.0	2.0	0.027	5.0	-5.0
0 °C, Nominal	74000020.0	4.0	0.054	5.0	-4.9
-10 °C, Nominal	74000023.6	7.6	0.103	5.0	-4.9
-20 °C, Nominal	74000022.0	6.0	0.081	5.0	-4.9
-30 °C, Nominal	74000023.0	7.0	0.095	5.0	-4.9

## Section 8 Photos


### 8.1 Photos of the test set-up



Set-up photo for radiated tests below 1 GHz photo



Set-up photo for antenna port tests



Set-up photo for frequency error tests

## 8.2 Photos of the EUT


---



Front side photo



Rear side photo



Bottom side photo



Top side photo



Right side photo



Left side photo



Copy of marking plate

End of the test report