




# PRIMA

RICERCA & SVILUPPO

## RAPPORTO DI PROVA / TEST REPORT

Rif./Ref.No. MPETR_141214-2	Data / Date: 09/09/2015	Pagine / Pages : 7
Scopo delle prove / Test object :	Prove di tipo in accordo a / Type test according to <b>FCC Cfr 47 part 2 - §2.1091, part 1 - §1.1310</b> <b>IC RSS-102 Issue 5</b>	
Richiedente / Applicant :	RADIO ACTIVITY S.R.L. Via G. De Notaris, 50 – 20128 Milano – MI – ITALY Tel. +39 02 36514205	
Persona di riferimento / Applicant's referee :	Mr. Campidoglio (m.campidoglio@radioactivity-tlc.it)	
Marchio commerciale / Trade mark :		
Fabbricante / Manufacturer :	RADIO ACTIVITY S.R.L.	
Prodotto / Product :	<b>Base station / Repeater</b>	
Modello / Model :	<b>KA-450</b>	
Data ricevimento campioni / Date of test samples receipt.	18/03/2015	
Campioni verificati / No. of tested samples	1	
Data verifiche / Testing date :	22/07/2015 – 28/07/2015	
Sito di prova / Testing site :	Prima Ricerca & Sviluppo Via Campagna - 92 I - 22020 FALOPPIO CO	
Esito delle valutazioni / Assessment results :	<b>CONFORME / COMPLIANT</b> (SEE PAG 7 FOR MIN SAFE DISTANCE TO BE RESPECTED)	
Verifiche effettuate da / Verifications carried out by :	Andrea Bortolotti Tecnico Laboratorio EMC e RADIO/ EMC and RADIO Laboratory technician	
Approvato / Approved by :	Giacomo ARMELLINI Responsabile Laboratorio EMC e RADIO/ EMC and RADIO Laboratory Manager	

I risultati delle prove riportati nel presente rapporto di prova si riferiscono solo ai campioni esaminati./  
The test results reported in this test report shall refer only to the samples tested  
Questo Report non può essere riprodotto in modo parziale, salvo espresso autorizzazione scritta da parte del Laboratorio /  
This report may not be partially reproduced, except with the prior written permission of the issuing Laboratory

**PRIMARICERCA & SVILUPPO**

Sede operativa e Laboratori di prova / Headquarter and Testing lab: Via Campagna, 92 – I-22020 FALOPPIO (CO)

Tel. +39 031 3500011 – Fax +39 031 991309 – [info@primaricerca.it](mailto:info@primaricerca.it) – [www.primaricerca.it](http://www.primaricerca.it)

## CONTENUTO / TABLE OF CONTENTS


<b>0</b>	<b>RELEASE CONTROL RECORD.....</b>	<b>2</b>
<b>1</b>	<b>TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>3</b>
1.1	EUT Identification .....	3
1.2	EUT Technical Data .....	3
1.3	EUT modification.....	4
1.4	Auxiliary equipment .....	4
<b>2</b>	<b>REFERENCE STANDARDS .....</b>	<b>4</b>
<b>3</b>	<b>MEASUREMENTS AND CALCULATION RESULTS .....</b>	<b>5</b>
3.1	Calculation Method .....	5
3.2	Limits.....	6
3.3	Measurements and Calculation Results.....	7

### 0 RELEASE CONTROL RECORD

TEST REPORT NUMBER	REASON OF CHANGE	DATE OF ISSUE
MPETR_141214-0	Original Release	28/07/2015
MPETR_141214-1	Editorial Change	11/08/2015
MPETR_141214-2	Editorial Change	09/09/2015

## 1 TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT)

### 1.1 EUT Identification

DESCRIPTION	Base station / Repeater
MODEL NAME OR NO.	KA-450
PART NUMBER / SERIAL NO.	Not present (prototype)
BRAND NAME	 <b>Radio Activity</b>
MANUFACTURER	RADIO ACTIVITY S.R.L.
SINGLE UNIT OR SYSTEM	Single unit
COUNTRY OF MANUFACTURER	Italy

### 1.2 EUT Technical Data

Power source	External Power Supply		
Power supply nominal voltage	<i>Min.</i>	<i>Typ.</i>	<i>Max.</i>
	11Vdc	13.8Vdc	15Vdc
Nominal power or absorbing current	TX: 60 W @25W RF / RX: 5 W @Main+Div enabled		
Dimensions	160x200x45mm / 3.2kg		
Typical usage :	Radio equipment for fixed installation or mobile station		
Type:	Private Land Mobile Radio Services		
Frequency range of Operation	406.1÷430MHz & 450÷470MHz		
Output Power	1-25 W / 100% duty cycle / selectable per channel		
Channelization	12,5kHz		
Frequency stability	0,5 p.p.m. (without GPS)		
Data rate	9600 bps		
Type of antenna	Not provided by the customer		

### 1.3 EUT modification

---

- None

### 1.4 Auxiliary equipment

---

- None

## 2 REFERENCE STANDARDS

---

FCC CFR Title 47 Part 1 Subpart I § 1.1310	Procedures Implementing the National Environmental Policy Act of 1969. Radiofrequency radiation exposure limits.
FCC CFR Title 47 Part 2 Subpart J § 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
ANSI C63.4	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
IC RSS-102 Issue 5	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

## 3 MEASUREMENTS AND CALCULATION RESULTS

### 3.1 Calculation Method

#### Far Field Power flux Calculation model.

This model is applicable in the far-field region and over-estimates in the radiating near-field region. The far-field calculations are accurate when the distance,  $r$ , from an antenna of length  $D$  to a point of investigation is greater than

$$r = \frac{2D^2}{\lambda}$$

The Power Flux is

$$S = \frac{PG}{4\pi r^2} \quad \text{or equivalent} \quad S = \frac{EIRP}{4\pi r^2}$$

where

P = input power of the antenna

G = antenna gain relative to an isotropic antenna

r = distance from the antenna to the point of investigation.

EIRP = Effective Isotropic Radiated Power

### 3.2 Limits

Tab. 1 of CFR Title 47 Part 1 Subpart I § 1.1310

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**Note to Table 1:** General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

#### IC – RSS-102 Issue 5 par. 4 RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (W/m <sup>2</sup> )	Averaging time (minutes)
0.003-10	83	90	-	Instantaneous
0.1-10	-	0.73/ f	-	6
1.1-10	87/ f <sup>0.5</sup>	-	-	6
10-20	27.46	0.0728	-2	6
20-48	58.07/ f <sup>0.25</sup>	0.1540/ f <sup>0.25</sup>	8.944/ f <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.6834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

**Note:** f is frequency in MHz.

\* Power density limit is applicable at frequencies greater than 100 MHz

### 3.3 Measurements and Calculation Results

#### WORST CASE MEASUREMENT:

DMR REPEATER ANALOGIC, MODULATION: FM, BANDWIDTH: 12.5kHz

Ch freq: 406.1MHz

Measured Peak power at antenna connector: 43.98dBm (25W)

Maximum possible power at antenna connector: 25W

The calculation has been performed using the maximum possible power at antenna connector 25W as worst case. The external antenna is not provided by the manufacturer so the evaluation of the min safe distance has been performed with different Antenna Assembly Gain

TX Frequency (MHz)	Peak Power at Antenna Connector (dBm)	Duty Cycle correction (dB)	Average Power at Antenna Connector (dBm)	Average Power at Antenna Connector (W)	Antenna Gain (dBi)
406.1	44	-	44	25	NA <sup>(1)</sup>
<b>MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b>					
<b>Power density Limit (W/m<sup>2</sup>)</b>			2.70 (acc to CFR Title 47 Part 1 Subpart I § 1.1310) 1.59 (acc to RSS-102 Issue 5 par. 4)		
Antenna Assembly Gain <sup>(1)</sup> (dBi)	EIRP (dBm)	EIRP (W)	Power density Limit (W/m <sup>2</sup> )	Minimum Safety Distance (m)	Max Antenna Length for Far Field Calculation (m)
0	44	25.12	1.59 (WORST CASE)	1.12	0.64
1	45	31.62		1.26	0.68
2	46	39.81		1.41	0.72
3	47	50.12		1.58	0.77
4	48	63.10		1.78	0.81
5	49	79.43		2.00	0.86
6	50	100.00		2.24	0.91
7	51	125.89		2.51	0.96
8	52	158.49		2.82	1.02
9.1	53.1	204.17		3.20	1.09

<sup>(1)</sup> External Antenna is not provided by the manufacturer.